



ESDU Struct 00.07.04

Issued November 1949

With Amendment A

January 1983

Primary warping constant for Z-sections with bulbs

Endorsed by
The Royal Aeronautical Society

AVA Documents
Document Sharing Hub

PRIMARY WARPING CONSTANT FOR Z-SECTIONS WITH BULBS

CONTENTS

	Page
1. NOTATION	1
2. NOTES	1
3. DERIVATION	1
4. EXAMPLE	2

ESDU Copyright material. For current status contact ESDU.

PRIMARY WARPING CONSTANT FOR Z-SECTIONS WITH BULBS

1. NOTATION

B	area of one bulb measured from centreline of flange (see sketch on Figure 1)	m^2	in^2
d	width of each flange measured between bulb centre and centreline of web (see sketch on Figure 1)	m	in
e	distance of bulb centroid from centreline of flange (see sketch on Figure 1)	m	in
F	area of each corner fillet (see sketch on Figure 1)	m^2	in^2
h	depth of web	m	in
t	thickness of web	m	in
t_1	effective thickness of web = $t + 2(F/h)$	m	in
t_2	thickness of each flange	m	in
Γ_1	primary warping constant as defined in ESDU Struct. 00.07.00	m^6	in^6

Both SI and British units are quoted but any coherent system of units may be used.

2. NOTES

The ratio $\Gamma_1/(t_1 h^3 d^2/12)$ is plotted against $d/t_2/(h/t_1)$ on Figure 1 for various values of $B/(h/t_1)$ and e/h . For intermediate values of $B/(h/t_1)$ and e/h , double linear interpolation gives good accuracy. These data may be compared with those given by ESDU 77023* which gives Γ_1 for lipped Z-sections.

3. DERIVATION

1. KAPPUS, R. Twisting failure of centrally loaded open section columns in the elastic range. NACA tech Memor. 851, 1938.
2. ARGYRIS, J.H. Work done for Structures Committee leading to the formula,
DUNNE, P.C.

$$\Gamma_1 = \frac{t_1 h^3 d^2}{12} \frac{p(2+p) + 2\beta(3+2\rho) + 24\epsilon\beta[(1+\rho) + \epsilon(1+2\rho)]}{1+2\rho+2\beta}, \quad (3.1)$$

* ESDU 77023, "Shear centre and primary warping constant for lipped and unlipped channel and Z-sections."