



FABRIC, ALTO, WARP KNIT FABRIC, UNLAMINATED

WSS-M1H1050-A

1. SCOPE

The material defined by this specification is a 3 bar 28 gauge warp knitted velour type polyester face fabric.

2. APPLICATION

This specification was released originally for material used as an interior trim fabric for use in the 2007 Model Year.

3. REQUIREMENTS

In addition to the requirements listed herein, the fabric shall meet all requirements of WSS-M8P18-A1/A2/A3/A4 as applicable.

3.1 STANDARD REQUIREMENTS FOR PRODUCTION MATERIALS

Material suppliers and part producers must conform to the Company's Standard Requirements For Production Materials (WSS-M99P1111-A).

3.2 FABRIC CONSTRUCTION

3.2.1 Fabric Count, +/- 10% tolerance
(ASTM D 3775)

Wales	144/10 cm
Courses	230/10 cm

3.2.2 Fabric Weight, +/- 10% tolerance
(FLTM BN 106-01)

319 g/m²

3.3 COMPOSITION (ASTM D 629)

Fabric	100% polyester
--------	----------------

3.4 YARN CONSTRUCTION (ASTM D 1244)

Face	dtex 105f48 (polyester, flat)
------	---------------------------------

Back	dtex 76f24 (polyester, flat)
------	-------------------------------

Date	Action	Revisions
2006 12 13	Activated	



Documents

M. Montgomery

Document Sharing Hub



3.5 METHOD OF DYEING

piece dyed or as approved by
Materials Engineering

3.6 FINISHED OPERATIONS

As approved by Materials
Engineering

4. GENERAL INFORMATION

The information given below is provided for clarification and assistance in meeting the requirements of this specification.

- 4.1** Purchase departments will ensure that both materials defined in this specification and shipped to any one assembly plant will be produced by one supplier only.