



ENGINEERING MATERIAL SPECIFICATION

OIL, ENGINE, ILSAC GF-5, INITIAL AND SERVICE FILL, SAE 5W-20
OIL, ENGINE, ILSAC GF-5, INITIAL AND SERVICE FILL, SAE 5W-30
OIL, ENGINE, ILSAC GF-5, INITIAL AND SERVICE FILL, SAE 0W-20

WSS-M2C945-A
WSS-M2C946-A
WSS-M2C947-A

1. SCOPE

These material specifications define the minimum acceptable performance requirements and physical/chemical properties of engine oils to be used by Ford Motor Company in its engine/vehicle manufacturing and service operations.

2. APPLICATION

These specifications are released for initial fill and service fill engine oils used for lubrication of spark ignition engines using gasoline. The Documentation, Performance Requirements and Quality Control subsections of the Qualification Procedure para 3.4, apply only to engine oils supplied directly to Ford Motor Company

3. REQUIREMENTS

3.1 STANDARD REQUIREMENTS FOR PRODUCTION MATERIALS

Material suppliers and part producers must conform to the Company's Standard Requirements For Production Materials (WSS-M99P1111-A).

3.2 PERFORMANCE

Shall meet all the requirements of the "ILSAC GF-5 Minimum Performance Standard for Passenger Car Engine Oils" plus the following:

All required engine tests shall be conducted in accordance with the most recently approved procedures as described in ASTM Standards and the applicable ASTM Standards Research Reports and Information Letters. All tests under surveillance by ASTM must be conducted using test equipment monitored by and calibrated to the requirements of the ASTM Test Monitoring Center.

3.3 PHYSICAL/CHEMICAL PROPERTIES

3.3.1 Physical Appearance and Odor

Shall be clear and bright with no objectionable odor.

3.3.2 Contaminants

Shall be free of carcinogens, toxins, metals not removed in refining or from previous use.

Date	Action	Revisions	Rev. 01
2013 08 23	Revised	See Summary of Revisions	C. E. Richardson, NA
2010 07 30	Activated	WSS-M2C945-A and WSS-M2C946-A	C. E. Richardson, NA



3.4 QUALIFICATION PROCEDURE

3.4.1 Documentation

Supplier must furnish to Fuels and Lubricants Engineering a completed and certified copy of the attached Supplement A, test reports demonstrating full compliance with all the requirements of this specification and a copy of the final ACC Monitoring Agency summary, if available. The need for ACC registration of tests will be determined by Fuels and Lubricants Engineering. The copy of the ACC Monitoring Agency summary should be sent directly from Registration Systems Inc. to Fuels and Lubricants Engineering.

The test reports must include results on both the candidate oil and the appropriate ASTM reference oils. The standard photographs of the test components are considered an essential part of the required test documentation. The oil sample code used for identification in each test document must be consistent. Any deviation in sample code uniformity must be explained and shown on the cover of each test report.

All tests must be certified by a qualified and authorized representative of the test facility.

The supplier shall identify all the formulation changes and modifications that occurred in the test program that coincide with the tests listed in the ACC Monitoring Agency summary. Individual formulations should be listed in Supplement A, and for ACC registered tests, identified by the line item number and the formulation code.

3.4.2 "Read Across" Guidelines

It is required that VG, VID and IIIGA or ROBO performance tests be conducted on the final formulation. However, exceptions may be permitted with supportive supplementary data on similar formulations to allow for final approval in the absence of complete testing.

3.4.3 Fleet Testing

Materials which constitute a significant departure from conventional formulations, whether in base stocks, refining processes or additive packages, must be fleet tested, in addition to the requirements outlined herein. These tests must include the type(s) of service judged to be affected by the difference in formulation technology. Fuels and Lubricants Engineering should be consulted prior to testing.

3.4.4 Verification

Fuels and Lubricants Engineering reserves the right to conduct verification testing. If the test results do not support the originally submitted data, the supplier must re-test the product in coordination with Fuels and Lubricants Engineering. This re-test must be conducted and certified by a mutually agreed upon test facility.

3.4.5 Chemical and Physical Properties

Supplier shall furnish appropriate chemical and physical properties as required on Supplement A along with the manufacturing limits that apply to the material as requested.





WSS-M2C945-A
WSS-M2C946-A
WSS-M2C947-A

3.4.6 Performance Requirements

Conformance to the engine test requirements listed in Supplement A will be determined by using Multiple Test Acceptance Criteria (MTAC) and Tiered Limit Methods (TLM) where applicable. All data and reports from the tests used for MTAC and TLM must be provided by the supplier. Identify the engine tests on Supplement A that have been used to determine the MTAC and TLM results by the corresponding line item number on the ACC Monitoring Agency summary. Fuels and Lubricants Engineering reserves the right to use all tests when averaging in place of MTAC.

3.4.7 Quality Control

Upon engineering approval supplier and Fuels and Lubricants Engineering shall establish mutually agreed upon quality control limits to be listed in Supplement B. These will be used for ongoing product verifications at mutually agreed upon frequencies. The infrared absorption spectra of the approved material shall constitute the reference standard and shall be kept on file. All samples shall produce infrared curves that correspond to the reference standard when tested under the same conditions as those specified on the master curve.

4. GENERAL INFORMATION

The information given below is provided for clarification and assistance in meeting the requirements of this specification. Contact gmfs@ford.com for questions concerning Engineering Material Specifications.

5. SUMMARY OF REVISIONS

2013 08 23 Released WSS-M2C947-A for SAE 0W-20. Minor revision/reformatting to Supplement A.