

REDUCING SOLVENTS FOR PRIMERS

9984446 9984452 9984454 9984464 9984466

9984497 9984499 9984500

1 SCOPE. This specification covers the basic physical, chemical and performance requirements of reducers for use with various primer materials used on metal and plastic parts. The reducers are covered by specification numbers specific to the primer material with which they are used, described below. These reducers are used to adjust primer application viscosity, overall solvent evaporation for proper application, and film flow after application. The reducers may be individual solvents or blends of classes of solvents such as aromatic hydrocarbons, ketones and esters. Reducers approved under each specification are not interchangeable, and must be evaluated and approved for use with each specific approved primer material before addition to the applicable approved source list.

1.1 The following primer reducers are covered by this specification:

9984446 - Reducer For 9981207 Lacquer Sealer
 9984452 - Reducer For 9984068 Primer Surfacer
 9984454 - Reducer For 9984059 In-Line Repair Primer
 9984464 - Reducer For 9984058 Final Line Repair Primer
 9984466 - Reducer For 9984816 Flexible Primer
 9984497 - Reducer For 9984820 and 9984821 Primers
 9984499 - Reducer For 9984076 Spotting Primer
 9984500 - Reducer For 9984067 Primer Surfacer

2 REFERENCED STANDARDS.

ASTM D56	9984103
ASTM D1012	9984470
ASTM D1078	9984472
ASTM D1298	9984481
9984065	9984506

3 REQUIREMENTS. Materials submitted for qualification to this specification must meet all the physical, chemical, and performance requirements.

3.1 Physical Requirements. This specification covers individual solvents or blends of solvents having a wide range of physical properties. Upon submission, therefore, the following physical properties shall be provided for each reducer and shall form the specification requirements for all subsequent lots.

3.1.1 Following data shall be provided for each approved product:

3.1.1.1 Distillation Range, C (ASTM D1078).

Initial Boiling Point (Min.)

10% Boiling Point (Min.)

50% Boiling Point (Max.)

End (Dry) Point (Max)

3.1.1.2 Flash Point, C (ASTM D56).

3.1.1.3 Specific Gravity at 25 C (ASTM D1298).

3.1.1.4 Aniline Point, C (ASTM D1012).

3.2 Chemical Requirements.

3.2.1 Identification. Gas chromatographic and infrared analysis will be used to identify, characterize and qualify new materials for approval to this specification. All subsequent lots of the approved material must be compositionally identical to the initial samples submitted for qualification.

3.2.2 Purity. Minimum 99% purity by gas chromatographic assay. The material must be free of any suspended particles, corrosion products, undissolved water, silicones or any other materials detrimental to the painting process. Product must be essentially colorless and not impart any color to coating materials.

3.2.3 Odor. The odor of the material shall be reviewed in comparison with current production materials. Any significant change in the material's characteristic odor must be evaluated in a GM approved laboratory and production trial. Any change in formulation must be reassessed for effect on odor.

3.2.4 Hazardous Materials Documentation. The supplier must provide all required safety documentation per Section 5 upon initial submission. Toxicity and flammability will be assessed by the using plant's Hazardous Materials Committee to determine conditions for use. The supplier must comply with all governmental regulations regarding proper labelling of hazardous materials.

3.2.5 Solvent Emissions Compliance. The supplier must furnish to the using plant's Plant Engineering Department all information required to assess the effect of material's use on meeting governmental restrictions on the discharge of volatile organic compounds (VOC) and disposal of hazardous waste.

3.3 Performance Requirements. The reducer shall be assessed and found satisfactory in plant trials with the intended approved primer material. Subsequently, the material must perform satisfactorily in the specified production application. Failure to do so shall constitute reason for rejection regardless of compliance with the other requirements of this specification.

4 INITIAL SOURCE APPROVAL. No shipment shall be made by any supplier until representative initial production samples have been approved by engineering as meeting the requirements of this specification.

REDUCING SOLVENTS FOR PRIMERS

9984446 9984452 9984454 9984464 9984466

9984497 9984499 9984500

4.1 Completed copies of the GM Material Safety Data Sheet, and Critical Material Register (available from the laboratory or engineering department) must be submitted with any new submissions or where a composition change has occurred.

5 SOURCE SHIPMENT RESPONSIBILITY. It will be the responsibility of the supplier to ensure that the material is not exposed to temperatures during shipment which would cause the material to fail to meet any of the requirements of this specification.

6 INSPECTION AND REJECTION. All shipments of material or parts under contract or purchase order manufactured to this specification shall be equivalent in every respect to the initial samples approved by engineering. There shall be no changes in either formulation or manufacturing processes permitted without prior notification and approval by engineering.

Lack of notification by the supplier constitutes grounds for rejection of any shipment. While samples may be taken from incoming shipments and checked for conformance to this specification, the supplier shall accept the responsibility for incoming shipments meeting this specification without dependence upon purchaser's inspection.

7 APPROVED SOURCES. Engineering qualification of an approved source is required for this specification. Only sources listed in the GM Materials File under this specification number have been qualified as meeting the requirements of this specification. Approved materials are not interchangeable and are released for use only in previously qualified combinations with other coating materials and processes.

8 GENERAL INFORMATION. These specifications were approved by the Paint-Committee in March 1990.