



Oil, Engine Assembly

1 Scope

1.1 Material Description. This specification defines an oil that is suitable for lubrication of engine components during engine assembly.

1.2 Symbols. Not applicable.

1.3 Applicability. Valve stems may be dipped in this oil prior to installation in the cylinder head.

1.4 Remarks. This oil is not intended for use as initial factory-fill oil.

2 References

Note: Only the latest approved standards are applicable unless otherwise specified.

2.1 External Standards/Specifications.

API 1509

SAE 50

SAE J300

2.2 GM Standards/Specifications.

GMW3059

2.3 Additional References.

- TMC003 Material Safety Data Sheet guidance documents (available at www.gmsupplypower.com).

3 Requirements

3.1 General Requirements

3.1.1 Service Category. The oil must meet American Petroleum Institute (API) service category "SJ" or higher as described in API 1509.

3.1.2 Viscosity Grade. The oil must conform to the SAE 50 viscosity requirement as described in SAE J300.

4 Manufacturing Process

Not applicable.

5 Rules and Regulations

5.1 Legal Regulations. All materials must satisfy applicable laws, rules, regulations and recommendations valid in the country of usage.

5.2 Language. In the event of conflict between the English and domestic language, the English language shall take precedence.

5.3 Inspection and Rejection. All shipments of material or parts under contract or purchase order manufactured to this specification shall be equivalent in every respect to the initial samples approved by Engineering. There shall be no changes in either formulation or manufacturing processes permitted without prior notification and approval by Engineering. Lack of notification by the supplier constitutes grounds for rejection of any shipment. While samples may be taken from incoming shipments and checked for conformance to this specification, the supplier shall accept the responsibility for incoming shipments meeting this specification without dependence upon purchaser's inspection.

The series of tests used to approve each batch of product along with acceptance limits will be agreed upon by the purchaser and seller. The laboratory providing the certificate of analysis must also participate in a proficiency

testing program (round robin) that is approved by the Fuels, Fluids, and Lubricants Global Subsystem Leadership Team (GSSLT) or designate. The Fuels, Fluids, and Lubricants GSSLT or designate must receive copies of the proficiency testing reports directly from the test program administrator.

5.4 Initial Source Approval. No shipment shall be made by any supplier until representative initial production samples have been approved by the Fuels, Fluids, and Lubricants Global Subsystem Leadership Team or designees meeting the requirements of this specification.

5.5 Material Safety Data Sheets/Safety Data Sheets (MSDS/SDS). For new product submissions, or when a change in chemical composition of an existing product has occurred, a complete copy of the Material Safety Data Sheet/Safety Data Sheet must be submitted in compliance with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS) requirements or other country-specific MSDS/SDS requirements. In addition, product MSDS/SDS submissions must be in compliance with specific country General Motors TMC003 Material Safety Data Sheet/Safety Data Sheet guidance documents where available.

5.6 All materials supplied to this standard must comply with the requirements of GMW3059, **Restricted and Reportable Substances for Parts.**

6 Approved Sources

Materials supplied to this specification must be approved by General Motors.

The appropriate GM Materials Engineering department(s) must confirm material as meeting the requirements of this specification. Any test data sheets of material submitted to General Motors for such confirmation (e.g., during Production Part Approval Process (PPAP)) under this material specification must list all properties and must apply corresponding test methods of this material specification.

7 Notes

7.1 Glossary.

Round Robin: A proficiency testing program.

7.2 Acronyms, Abbreviations, and Symbols.

API	American Petroleum Institute
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
GSSLT	Global Subsystem Leadership Team
MSDS	Material Safety Data Sheet
PPAP	Production Part Approval Process
SDS	Safety Data Sheet

8 Coding System

This standard shall be referenced in other documents, drawings, etc., as follows:

Material per 9985776

9 Release and Revisions

This standard was originated in September 1989. It was first published in September 1989.

Issue	Publication Date	Description (Organization)
1	SEP 1989	Initial publication.
2	JUN 1999	Replaced service category SG with SJ; added API reference. (PT Division)
3	AUG 2014	Updated template; made editorial changes. (Materials - Fuels, Fluids, and Lubricants GSSLT)