



Lubricant, Rubber (Diluted Material)

1 Scope

Note: Nothing in this standard supercedes applicable laws and regulations.

Note: In the event of conflict between the English and domestic language, the English language shall take precedence.

1.1 Purpose/Material Description. This specification describes a mixture of 0.5% wetting agent and water suitable for use as a lubricant to facilitate assembly of rubber parts.

1.2 Symbols. Not applicable.

1.3 Applicability. This material is used as a lubricant to facilitate assembly of rubber parts.

1.4 Remarks. This lubricant is not approved for fuel system assembly. Not for use where corrosion may be a concern. Dries clear.

2 References

Note: Only the latest approved standards are applicable unless otherwise specified.

2.1 External Standards/Specifications.

None

2.2 GM Standards/Specifications.

GMW3059

2.3 Additional References.

GM Part Number 9985406

3 Requirements

3.1 All materials supplied to this standard must comply with GMW3059, **Restricted and Reportable Substances**, including the requirement to obtain a GM-approved International Material Data System (IMDS) submission.

3.2 Requirements on Delivery.

3.2.1 Chemical Requirements. The lubricant shall be a uniform mixture of 0.5% wetting agent and the remainder primarily water. The wetting agent portion of the mixture shall be sodium lauryl sulfate soap. Small quantities of fungicide or other additives may be added to meet requirements of 3.2.3.

3.2.2 The rubber lubricant is to be supplied ready to use without any mixing, agitation or dilution with water.

3.2.3 Physical Requirements. Materials shall not exhibit any settling or stratification after six (6) months storage. Containers shall be free of any particulate matter or other foreign materials.

4 Manufacturing Process

Not applicable.

5 Rules and Regulations

5.1 Legal Regulations. All materials must satisfy applicable laws, rules, regulations and recommendations valid in the country of usage.

5.2 Language. In the event of conflict between the English and domestic language, the English language shall take precedence.

5.3 Inspection and Rejection. All shipments of material or parts under contract or purchase order manufactured to this specification shall be equivalent in every respect to the initial samples approved by Engineering. There shall be no changes in either formulation or manufacturing processes permitted without prior notification and approval by Engineering. Lack of notification by the supplier constitutes grounds for rejection of any shipment. While samples may be taken from incoming shipments and checked for conformance to this specification, the supplier shall accept the responsibility for incoming shipments meeting this specification without dependence upon purchaser's inspection.

The series of tests used to approve each batch of product along with acceptance limits will be agreed upon by the purchaser and seller. The laboratory providing the certificate of analysis must also participate in a proficiency testing program (round robin) that is approved by the Fuels, Fluids, and Lubricants Global Subsystem Leadership Team (GSSLT) or designate. The Fuels, Fluids, and Lubricants GSSLT or designate must receive copies of the proficiency testing reports directly from the test program administrator.

5.4 Initial Source Approval. No shipment shall be made by any supplier until representative initial production samples have been approved by the Fuels, Fluids, and Lubricants Global Subsystem Leadership Team or designees meeting the requirements of this specification.

5.5 Material Safety Data Sheets/Safety Data Sheets (MSDS/SDS). For new product submissions, or when a change in chemical composition of an existing product has occurred, a complete copy of the Material Safety Data Sheet/Safety Data Sheet must be submitted in compliance with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS) requirements or other country-specific MSDS/SDS requirements.

6 Approved Sources

Materials supplied to this specification must be approved by General Motors.

The appropriate GM Materials Engineering department(s) must confirm material as meeting the requirements of this specification. Any test data sheets of material submitted to General Motors for such confirmation (e.g., during Production Part Approval Process (PPAP)) under this material specification must list all properties and must apply corresponding test methods of this material specification.

For other GM locations, the responsible engineering group should be contacted to obtain the approved source in that individual country.

7 Notes

7.1 Glossary. Not applicable.

7.2 Acronyms, Abbreviations, and Symbols.

GHS	Globally Harmonized System of Classification and Labeling of Chemicals
GSSLT	Global Subsystem Leadership Team
IMDS	International Material Data System
MSDS	Material Safety Data Sheet
PPAP	Production Part Approval Process
SDS	Safety Data Sheet

8 Coding System

8.1 This standard shall be referenced in other documents, drawings, etc., as follows:

GMW18244-9985406