



Split Mu Evaluation

1 Introduction

Note: Nothing in this standard supercedes applicable laws and regulations.

Note: In the event of conflict between the English and domestic language, the English language shall take precedence.

1.1 Purpose. Provide a common global development and validation performance evaluation of a driveline system that utilizes traction enhancing driveline hardware, e.g., Active On Demand (AOD) All Wheel Drive (AWD) and Limited Slip Differential (LSD) with electronic controls. This procedure is also performed to evaluate the performance of driveline components after being subjected to severe loads resulting from multiple vehicle launches on "split mu" surfaces, i.e., left (or right) side of the vehicle on a small frictional coefficient (μ) surface, i.e., "low mu" surface, and the other side on a large frictional coefficient surface, i.e., "hi mu" surface.

1.2 Applicability. Passenger cars and light trucks equipped with driveline traction enhancing hardware beyond normal brake system traction control systems.

1.3 Remarks. This test is typically run by the GM Vehicle Dynamics group or the GM Driveline group and is used for development/validation of the drivetrain or traction performance. These systems may include but, are not limited to, AOD AWD and regular AWD systems, LSD, drive shafts, half shafts, axles, torque couplings, and driveline disconnects.

2 References

Note: Only the latest approved standards are applicable unless otherwise specified.

2.1 External Standards/Specifications.

None

2.2 GM Standards/Specifications.

GMW14264

2.3 Additional References.

- Subsystem Technical Specification (SSTS)
- System Technical Specification (STS)
- Vehicle Technical Specification (VTS)

3 Resources

3.1 Facilities. Testing requires a split mu surface with a minimum length of 120 m such as the ceramic tile facility located at the Milford Proving Ground Vehicle Dynamics Test Area (VDTA). Artificial low coefficient surfaces such as wet tiles or winter surfaces with natural ice are acceptable. The low coefficient surface shall have a coefficient of friction ≤ 0.2 , and the high coefficient surface shall have a coefficient of friction ≥ 0.8 . See 4.2 for "low mu" and "hi mu" surface definitions.

The facility requires sufficient area to allow the vehicle to safely decelerate from test speeds after reaching the end of test distance at 120 m. The split mu test surface shall allow for a minimum 3.5 m wide test lane straddling the "low mu" and "low mu" surfaces at the vehicle centerline. The hi-mu portion of the test surface shall have a minimum width of 3.5 m width to conduct high mu accelerations and speed measurements.

3.1.1 Calibration. The test facilities and equipment shall be in good working order and shall have a valid calibration label.

3.1.2 Alternatives. Alternative test facilities and equipment may also be used. However, all measuring variables as specified in this standard shall be determined correctly with respect to their physical definition.

3.2 Equipment.

3.2.1 Data Acquisition System (DAS). The DAS is used for recording vehicle communication bus, e.g., Controller Area Network (CAN), Local Interconnect Network (LIN), etc. channels and instrumented driveline or chassis controller channels (if requested/necessary). The vehicle communication bus shall be recorded at full bus speed, e.g., Global A CAN is 500 kbit/s, but individual modules on the bus may have slower update rates as compared to overall vehicle bus. The DAS shall have at a minimum a recording speed matching the fastest communication bus rate for all data channels.

Note: When recording digital data or external analog data it should be broadcast and recorded at a sample rate of no less than 1000 Hz. Examples of external data include accelerator pedal position and axle torque.

3.2.2 Longitudinal Speed Measurement Device and Readout. The speed transducer must be capable of reading velocity in excess of the vehicle test speed. A minimum of 150 km/h is recommended. The transducer accuracy must be within 0.5 km/h over the speed range of 5 km/h to 150 km/h.

3.2.3 Lateral Speed Measurement Device and Readout. The speed transducer must be capable of reading velocity in excess of the vehicle test speed. A minimum of 50 km/h is recommended. The transducer accuracy must be within 0.5 km/h over the speed range of ± 50 km/h.

3.2.4 Accelerometer Oriented to Measure Longitudinal Acceleration. The accelerometer must be capable of measuring a minimum of 11.75 m/s^2 (1.2G), with an accuracy of 0.1 m/s^2 (0.01G).

3.2.5 Accelerometer Oriented to Measure Lateral Acceleration. The accelerometer must be capable of measuring a minimum of 11.75 m/s^2 (1.2G), with an accuracy of 0.1 m/s^2 (0.01G).

3.2.6 Angular Rate Sensor Oriented to Measure Yaw Velocity. The angular rate transducer must be capable of measuring at ± 50 degrees/s with an accuracy of 0.01 degrees/s.

3.2.7 Accelerator Pedal Percentage/Travel. Record signal direct from pedal position sensor.

3.2.8 Time Marker (T-Marker). A reflector on the vehicle at the primary drive axle and a sensor at the end of the 120 m "split mu" test lane to indicate the end of the test run.

3.2.9 Driveline Torque Data for Each Wheel. Instrumented half shafts and/or axle shafts and associated slip rings and signal conditioning devices.

Note: Do not use wheel force transducers as wheel inertia maybe different than the Original Equipment Manufacturer (OEM) recommended wheel inertia.

3.2.10 Wheel Velocity Data for Each Wheel. The transducers must be capable of reading velocity in excess of the vehicle test speed, a minimum of 50 km/h over test velocity is recommended. The transducer accuracy must be within 0.5 km/h over the speed range of 5 km/h to 150 km/h.

3.2.11 Hydraulic Brake Pressure at Each Wheel. The transducers must be capable of reading brake pressure in excess of the rated system pressure.

Note: 3.2.9 through 3.2.11 are typically required only for driveline development testing unless requested.

Note: All instrumentation shall be calibrated as required. Record instrumentation details and date of calibration on Data Sheet A1 in Appendix A, unless information is maintained in the testing laboratory records.

3.3 Test Vehicle/Test Piece. The vehicle shall be equipped with specific driveline configuration requested. It may be possible to interchange driveline, chassis controls, tires and wheels, and powertrain hardware and software to accomplish multiple test configurations on the same vehicle.

Note: All available combinations of engine, transmission, AWD, LSD, final drive ratios, i.e., all possible propulsion systems, and tire and wheel combinations may need to be tested separately due to differences in driveline reactions and other hardware or electronic influences. Consult the Requesting Engineer for the test objectives and required combinations required to meet the test objectives.

Note: Testing shall be conducted using production intent tire and wheel combinations. For programs equipped with summer tires testing shall be conducted using the both the program intent winter surface tire and production intent summer tire.

3.4 Test Time.

Calendar time:	5 d
Test time:	24 h
Coordination time:	16 h

3.5 Test Required Information.

 Possible sources are:

- Vehicle Technical Specification (VTS)
- Subsystem Technical Specification (SSTS)
- System Technical Specification (STS)
- Traction VPO and/or Traction BFO/TIE

3.6 Personnel/Skills.

 Trained driver. Ability to conduct end of test inspection of test parts if required.

4 Procedure

4.1 Preparation.

4.1.1 Determine and record the velocity ratio targets and number of consecutive "split mu" accelerations, accelerator pedal positions, and chassis/driveline mode combinations to be tested based on requirements in 3.5 or as required by Requesting Engineer. Document the test configuration on Data Sheets A2 and A3 in Appendix A. Multiple copies of Data Sheet A3 will be required to document the various ballast conditions and test modes. Provide the following:

- Fleet Number or Vehicle Identification Number (VIN)
- Vehicle configuration
- Test surface (simulated or actual "low mu" surface) and any special temperature requirements.
- Number of consecutive "split mu" tests in each mode.
- Elapsed time between the start of consecutive runs, i.e., total cycle time of each run, which allows for returning the vehicle to start of the test surface and incidental cool down of drivetrain components. This is typically approximately (~) 30 s if not specified in the requirements in 3.5.
- Accelerator pedal positions, typically 30%, 60% and 100%, i.e., Wide Open Throttle (WOT). Positions shall be achieved within $\pm 5\%$ with no overshoot and ramped in with rapid accelerator pedal application. A accelerator application defined as Drivers Best Effort (DBE) can also be performed if requested. DBE is typically defined as maximum acceleration obtainable without significant traction control or stability control actuation.

Note: "Split mu" testing is usually performed on level ground but, may be run on normal test grades of 12%, 20% or any special grade to meet program requirements.

4.1.2 Install instrumentation for recording test data as required by Requesting Engineer. The following channels being critical to most tests:

- Vehicle bus (critical signals)
- Wheel speeds (all wheels)
- Transmission gear state (or ratio)
- Accelerator pedal position
- Measured (optional) or Estimated driveline torque signals
- Traction and Stability control active signals
- User selected modes effecting driveline/vehicle performance
- Vehicle Velocity

Note: Optional channels are defined in 3.2.8 and 3.2.10.

4.1.3 Set tire pressure to specifications.

4.1.4 Check all fluid levels. Fill as required.

4.1.5 Inspect all driveline torque carrying components with vehicle on hoist. Record any leaks or unusual conditions on Data Sheet A2 in Appendix A using the subjective scales of GMW14264.

4.1.6 Break-In. For vehicles or driveline components with < 805 km (500 mi) of usage, break in vehicle as required. Refer to the requesting engineer for appropriate break-in procedures.

4.2 Conditions. Road surface coefficients are defined in Table 1.

Table 1: Road Surface Coefficients

Road Surface	Peak Friction Coefficient (μ)	Example Road Surface
High coefficient	$\mu > 0.8$	Dry Asphalt/Dry Concrete
Medium coefficient	$0.4 < \mu < 0.7$	Wet Jennite or Wet Basalt/Packed Snow
Low coefficient	$\mu < 0.2$	Wet ice, Wet Ceramic Tile, or Wet Polished Concrete/Ice
Split coefficient	Road surface with different peak friction coefficients under left and right driven wheels, e.g., low and high or medium and high peak friction coefficient combinations only.	

4.2.1 Environmental Conditions. Dry "hi mu" surface and simulated/actual "low mu" surface, e.g., wet ceramic tiles/ice, per Table 1.

4.2.2 Test Conditions. Deviations from the requirements of this standard shall have been agreed upon. Such requirements shall be specified on component drawings, test certificates, reports, etc.

4.3 Instructions. This test procedure shall be run in all "driver selected option" modes, i.e., Traction Control (TC) "on" or "off", snow and launch control, winter, sport, off-road, etc. Consult the Requesting Engineer to determine applicable modes.

4.3.1 Perform the test as defined in 4.1.1 or complete (4) four runs per mode at 30%, 60%, 100% (WOT), and DBE accelerator pedal positions. Document modes and cycle counts on Data Sheet A3 in Appendix A.

Note: Allow the drivetrain to cool after completing each mode of this test procedure. Extended duration cool down is mandatory if automatic thermal shut down or thermal temperature limits per requirements in 3.5 are reached during any event. Thermal shut down limits indicate system thermal capacity and completion of that test mode.

4.3.2 Launch Conditions.

4.3.2.1 Manual Transmission: Launch the vehicle at the engine speed, revolutions per minute (RPM), based on requirements in 3.5 or as required by Requesting Engineer, with a rapid release of the clutch pedal (foot does not leave clutch pedal pad) and appropriate accelerator pedal application to match clutch pedal release rate (stopping at the desired accelerator pedal position).

4.3.2.2 Automatic Transmission: Determine "worst case" launch method which is either brake torqueing or simply releasing the brake pedal and rapidly applying accelerator pedal to the desired position. The method that produces maximum "low mu" wheel slip is considered "worst case".

Note: Apply the accelerator pedal with a ramp input to desired pedal position. Pedal shall be ramped to desired pedal percentage within 2 s and maintained at desired pedal percentage within $\pm 5\%$. Overshoot above the 5% tolerance is not allowed on initial pedal application. Suggested method is to use a block accelerator or electronic limiter to achieve proper accelerator pedal position.

4.3.3 Launch and Acceleration on "Split Mu" and Uniform "Hi Mu" Surfaces.

Note: For reasons of consistency in the road surface coefficients values, the same test track facility should be utilized for all parts of the test.

4.3.3.1 Move the test vehicle to the test area defined in 3.1 capable of "split mu" launches.

4.3.3.2 When testing on actual ice surfaces, run one 32 km/h check stop on the "low mu" test surface to determine if the surface coefficient is acceptable at beginning of test sequence. Document the results in on Data Sheet A3 in Appendix A.

4.3.3.3 For each run defined in 4.1.1, perform both 4.3.3.4 "Split Mu" Acceleration and 4.3.3.5 "Hi Mu" Acceleration.