



Master Index

for Complete Set:
ANSI/HI Pump Standards,
Version 3.2

Copyright Hydraulic Institute 2015



6 Campus Drive
First Floor North
Parsippany, New Jersey
07054-4405
www.hi-pumps.org

Documents

Document Sharing Hub

This page intentionally blank.

ANSI/HI Pump Standards: Version 3.2

Master Index for Complete Set

This index is not part of any standard, but is presented to help the user in considering factors beyond the standards.

Note: Bold numbers indicate the standard number, nonbold numbers indicate the page number;
an f. indicates a figure, a t. indicates a table.

- Abbreviations and definitions, **50.7**: 28
- Abrasion–corrosion, defined, **12.1-12.6**: 43
- Abrasive fluids and residual mechanical unbalance of rotating parts, **9.6.4**: 17
- Abrasive wear, defined, **12.1-12.6**: 43
- Absolute pressure, defined, **3.1-3.5**: 20, **3.6**: 3
- Accelerating Deployment of ISO 15926 project, **50.7**: 3
- Acceleration head, **6.1-6.5**: 31–34, **8.1-8.5**: 14
 - air-operated pumps, **10.1-10.5**: 9
- Acceleration pressure, , **6.1-6.5**: 31–34, **8.1-8.5**: 14
 - Air-operated pumps, **10.1-10.5**: 9-10
- Accelerometers, **9.6.5**: 12, **9.6.9**: 12
- Acceptance level
 - Level A, **3.6**: 1, 8, 16
 - Level B, **3.6**: 8, 16, 17 f.
- Accuracy and performance, defined, **7.1-7.5**: 11
- Accuracy, **9.6.5**: 36, **9.6.9**: 27
- Alarm limits defined, **9.6.9**: 5
 - leakage guidelines, **9.6.9**: 11
 - power guidelines, **9.6.9**: 6
 - rate-of-flow guidelines, **9.6.9**: 13
 - speed (rpm) guidelines, **9.6.9**: 14
 - temperature guidelines, **9.6.9**: 9
 - vibration guidelines, **9.6.9**: 13
- Acidity, of water, **2.3**: 79
- Acoustic resonance, **9.6.6**: 33
 - bulk/elastic modulus for typical materials, **9.6.6**: 34
 - bulk/elastic modulus of typical liquid, **9.6.6**: 34
 - for rigid pipe and ambient water, **9.6.6**: 34
 - half-wave resonance frequency, **9.6.6**: 33
 - in pipe, **9.6.6**: 34
 - reflection points, **9.6.6**: 34
- Acoustic sensors, in bearing wear monitoring, **9.6.5**: 21
- Acronyms, **9.6.6**: 11
- Active storage, defined, **9.8**: 48
- Actuating mechanism. See Valve gear
- Adapters, **2.3**: 64
- Added mass, defined, **9.6.8**: 58
- Adhesive wear resistance of wrought materials, **9.1-9.5**: 11 t.
- AEX XML Schema, **50.7**: 1, 2, 29
 - and construction materials and properties, **50.7**: 24
 - and W3C schema namespace declaration, **50.7**: 26
 - and XPath, **50.7**: 28
 - and XSD file names and associated namespaces, **50.7**: 27
- collection-container type, **50.7**: 25, 27f., 29
- content, **50.7**: 23
- core data type, **50.7**: 24, 27 f., 29
- core object type, **50.7**: 24, 27 f., 29
- document namespaces, **50.7**: 26
- equipment data foundation files, **50.7**: 23
- file folder structure, **50.7**: 26
- for equipment items, **50.7**: 23, 24 f.
- getting started with, **50.7**: 23
- namespaces, **50.7**: 26, 30
- prerequisites and tools, **50.7**: 23
- structural design, **50.7**: 24, 25 f.
- subject type, **50.7**: 25, 27 f., 29
- testing conformance to, **50.7**: 21
- use of namespaces, **50.7**: 26, 27f., 30
- versions and revisions system, **50.7**: 25
- where to find, **50.7**: 23
- Affinity rules, **1.3**: 69
- Air chamber, **10.1-10.5**: 2
- Air consumption defined, **10.1-10.5**: 10, **10.6**: 6
 - measurement of, **10.6**: 14
- Air core vortex, defined, **9.8**: 48
- Air distribution system, **10.1-10.5**: 2
- Air entrainment, **4.1-4.6**: 15, 22
- Air gap, defined, **4.1-4.6**: 8, **5.1-5.6**: 14
- Air release valves, **9.6.6**: 32
- Airborne sound instrumentation
 - acoustical calibration, **9.1-9.5**: 28
 - octave-band analyzer, **9.1-9.5**: 28
 - recorders, **9.1-9.5**: 28
 - sound-level meter and microphone system, **9.1-9.5**: 28
- Airborne sound level test report, **9.1-9.5**: 41 f.
- Airborne sound readings
 - averaging, **9.1-9.5**: 40
 - corrections for background noise, **9.1-9.5**: 39 t.
 - corrections, **9.1-9.5**: 39
- Air-operated bellows pumps, **10.1-10.5**: 1, 2 f.
 - bellows selection and materials, **10.1-10.5**: 13
 - features, **10.1-10.5**: 12
 - handling of harsh chemicals, **10.1-10.5**: 12
 - handling of hot liquids, **10.1-10.5**: 12
 - malfunction causes and remedies, **10.1-10.5**: 20, 22 t.
 - typical services, **10.1-10.5**: 11
- Air-operated diaphragm pumps, **10.1-10.5**: 1 f., 1

- and rate of flow, **10.1-10.5**: 13
- diaphragm selection and materials, **10.1-10.5**: 13
- features, **10.1-10.5**: 12
- handling of hazardous liquids, **10.1-10.5**: 11
- liquids and slurries handled, **10.1-10.5**: 11
- malfunction causes and remedies, **10.1-10.5**: 20, 21 t.
- pump controls, **10.1-10.5**: 13
- pumping of dry powders, **10.1-10.5**: 12
- typical applications, **10.1-10.5**: 11
- Air-operated pump tests, **10.6**: 1
- types of, **10.6**: 1
- Air-operated pumps, **10.1-10.5**: 1
- duplex, **10.1-10.5**: 2
- nomenclature, **10.1-10.5**: 2
- simplex, **10.1-10.5**: 2
- types, **10.1-10.5**: 1, 1 f.
- Alarm limit, **9.6.5**: 3
- Alkalinity, of water, **2.3**: 79
- Allowable bearing housing vibration
 - at speeds above 600 rpm, **9.6.4**: 7, 8 f., 9 f.
 - at speeds of 600 rpm and below, **9.6.4**: 10 t.
 - pump types BB1, BB2, BB3, BB4, BB5, OH1, OH2, OH3, OH4, OH5, OH7, **9.6.4**: 8 f.
 - pump types VS1, VS2, VS3, VS4, VS5, VS6, VS7, VS8, **9.6.4**: 8 f.
 - slurry pump types, **9.6.4**: 9 f.
 - solids-handling pump types, **9.6.4**: 9 f.
- Allowable imbalance, **9.6.8**: 32
- Allowable operating range, defined, **12.1-12.6**: 36
- Allowable operating region (AOR), **9.6.3**: 1
- and bearing life, **9.6.3**: 3
- and dip (in head vs. rate-of-flow curve), **9.6.3**: 6, 7 f.
- and droop (in head vs. rate-of-flow curve), **9.6.3**: 5, 6 f.
- and factory test, **9.6.3**: 2
- and hydraulic loads, **9.6.3**: 3
- and internal mechanical contact, **9.6.3**: 3
- and liquid velocity, **9.6.3**: 4
- and noise, **9.6.3**: 4
- and NPSH margin, **9.6.3**: 5, 5 f.
- and power limit, **9.6.3**: 4
- and pump size, **9.6.3**: 7
- and service life, **9.6.3**: 2
- and shaft fatigue life, **9.6.3**: 3
- and shaft seal life, **9.6.3**: 3
- and suction recirculation, **9.6.3**: 6, 8 f.
- and temperature rise, **9.6.3**: 4
- and thrust reversal, **9.6.3**: 4
- and vibration, **9.6.3**: 4
- defined, **9.6.3**: 1
- factors affecting, **9.6.3**: 2
- Allowable operating region defined, **1.1-1.2**: 71, **2.1-2.2**: 34
- Alnico magnet, defined, **5.1-5.6**: 17
- Alnico, defined, **4.1-4.6**: 9
- Aluminum, **9.1-9.5**: 21
- alloy 319, **9.1-9.5**: 21
- alloy 355, **9.1-9.5**: 21
- alloy 356, **9.1-9.5**: 21
- alloy 7075 (Al-Zn-Mg-Cu-Cr), **9.1-9.5**: 22
- alloy ASTM B211, alloy 2011, **9.1-9.5**: 22
- alloy ASTM B211, alloy 6061, **9.1-9.5**: 22
- alloy B750, **9.1-9.5**: 22
- alloy C-355-T6, **9.1-9.5**: 21
- alloy TP-220-T4, **9.1-9.5**: 21
- aluminum copper (Al/Cu) SAE AA2017, **9.1-9.5**: 22
- compatibility with other materials, **9.1-9.5**: 21
- tenzalloy, **9.1-9.5**: 22
- American Bearing Manufacturers Association (ABMA), **5.1-5.6**: 45
- American National Standards Institute (ANSI), **5.1-5.6**: 46
- American Petroleum Institute, **5.1-5.6**: 45
- American Society for Heating, Refrigerating, and Air-Conditioning Engineers (ASHRAE), **50.7**: 3
- American Society for Testing and Materials (ASTM), **5.1-5.6**: 46
- American Society of Mechanical Engineers (ASME), **5.1-5.6**: 46
- Amplification chart, **9.6.8**: 85f.
- Amplification factor, defined, **9.6.8**: 58
- Analyses beyond scope of document, **9.6.8**: 7
- Analysis complexity levels, **9.6.8**: 28t.
- Analysis level 3
 - elements, **9.6.8**: 36
 - limitations, **9.6.8**: 36
- Analysis level definitions, **9.6.8**: 33
- level 1, **9.6.8**: 33
- level 2, **9.6.8**: 34
- level 3, **9.6.8**: 36
- Analysis levels introduction, **9.6.8**: 27
- See also Levels of analysis types, **9.6.8**: 27
- Analysis reporting format, **9.6.8**: 92
- Anchors, **9.6.6**: 6, 7
- final installation, **9.6.6**: 7
- true, **9.6.6**: 23
- Angular momentum, **1.3**: 1
- Annular seal, defined, **9.6.8**: 58
- ANSI/ASME B73.1 pumps, **9.6.2**: 1
- adjustment factor basis for temperature and material, **9.6.2**: 8
- adjustment factors for temperature and material, **9.6.2**: 9, 9t., 10t.
- adjustment of tabulated maximum forces and moments load values, **9.6.2**: 4
- assessment of applied nozzle loads, **9.6.2**: 4
- definitions and coordinates, **9.6.2**: 2f., 2
- equation set 1 (individual loading), and maximum forces and moments, **9.6.2**: 4t., 5t.
- equation set 2 (nozzle stress, hold-down bolt stress, pumps slippage), and maximum forces and moments, **9.6.2**: 4t., 6t.
- equation set 3 (y-axis movement), and maximum forces and moments, **9.6.2**: 4t., 6t.

- equation set 4 (z-axis movement), and maximum forces and moments, **9.6.2:** 4t., 7t.
- equation sets for applied loads, **9.6.2:** 4t.
- example assessment of applied nozzle loads (1.5×1-8 CF8M Type 316 pump, Class 150 flanges, at 100 °F), **9.6.2:** 23
- example assessment of applied nozzle loads (3×1.5-13 Alloy 20 pump, Class 300 flanges, at 400 °F), **9.6.2:** 26
- Groups 1, 2, and 3, defined, **9.6.2:** 2
- loads for combined forces and/or moments, **9.6.2:** 4, 6t., 7t.
- loads for individual force or moment, **9.6.2:** 4, 5t.
- material specifications, **9.6.2:** 9t.
- ANSI/ASME B73.1 Specification for Horizontal End Suction Centrifugal Pumps for Chemical Process, **50.7:** 1, 3, 8
- ANSI/ASME B73.2 pumps, **9.6.2:** 1, 10
 - adjustment factor basis, **9.6.2:** 13
 - assessment of applied nozzle loads, **9.6.2:** 12, 12t.
 - criteria for loading allowances, **9.6.2:** 11
 - equation set 6 (criteria for applied loads), **9.6.2:** 12t.
 - example assessment of applied nozzle loads (4030/28 Alloy 20 pump, Class 300 flanges, at 400 °F), **9.6.2:** 32
 - example assessment of applied nozzle loads (Size 2015/17 CF8M Type 316 pump, Class 150 flanges, at 100 °F), **9.6.2:** 31
 - flange stress, **9.6.2:** 11
 - list of material specifications, **9.6.2:** 13t.
 - maximum axial force, **9.6.2:** 11
 - maximum bending moments, **9.6.2:** 11
 - maximum forces and moments to assess applied loads, **9.6.2:** 12t.
 - maximum shear force, 11 maximum torsional moments, **9.6.2:** 11
 - nomenclature, definitions, and coordinates, **9.6.2:** 10, 11f.
 - pressure, **9.6.2:** 11
 - temperature and material adjustment factors, **9.6.2:** 13, 14t.
 - temperature, **9.6.2:** 11
- ANSI/ASME B73.2 Specification for Vertical In-Line Centrifugal Pumps for Chemical Process, **50.7:** 1, 3, 8
- ANSI/ASME B73.3 pumps, **9.6.2:** 1
 - adjustment factor basis for temperature and material, **9.6.2:** 8
 - adjustment factors for temperature and material, **9.6.2:** 9, 9t., 10t.
 - assessment of applied nozzle loads, **9.6.2:** 7
 - definitions and coordinates, **9.6.2:** 2f., 2
 - Groups 1, 2, and 3, defined, **9.6.2:** 2
 - material specifications, **9.6.2:** 9t.
- ANSI/ASME B73.5M pumps, **9.6.2:** 1
- ANSI/ASME B73.5M pumps, **9.6.2:** 1
 - adjustment for mounting other than fully grouted metal baseplate with anchor bolts, **9.6.2:** 7
 - assessment of applied loads, **9.6.2:** 16, 17t.
 - assessment of applied nozzle loads, **9.6.2:** 7
 - assumed effect of nozzle loading, **9.6.2:** 16
 - Axial split case single- and two-stage pumps, **9.6.2:** 1
 - casing hold-down bolts, **9.6.2:** 16
 - criteria for loading allowances, **9.6.2:** 15
 - definitions and coordinates, **9.6.2:** 2f., 2
 - example assessment of applied nozzle loads (1.5×1-8, modulus of elasticity > 1.0 × 10⁶, at 110 °F), **9.6.2:** 28
 - Groups 1, 2, and 3, defined, **9.6.2:** 2
 - limiting factors, **9.6.2:** 15
 - maximum allowable tensile stress, **9.6.2:** 16
 - maximum forces and moments to assess applied loads based on hold-down bolts, **9.6.2:** 17t.
 - maximum forces and moments to assess applied loads based on nozzle stress, **9.6.2:** 17t.
 - nomenclature, definitions, and coordinates, **9.6.2:** 14, 15f.
 - radial movement of pump shaft at coupling hub, **9.6.2:** 15
 - scope (single-stage double suction and two-stage single suction), **9.6.2:** 14
 - ANSI/HI 1.6 Centrifugal Pump Tests, **14.6:** 1
 - ANSI/HI 11.6 Submersible Pump Tests, **14.6:** 1
 - ANSI/HI 2.6 Vertical Pump Tests, **14.6:** 1
 - ANSI/HI 4.1-4.6 Sealless, Magnetically Driven Rotary Pumps for Nomenclature, Definitions, Application, Operation, and Test, **14.6:** 1
 - ANSI/HI **9.6.7**
 - differences between 2010 and 2004 versions, **9.6.7:** 1, 2
 - ANSI/IEEE standards, **5.1-5.6:** 46
 - Anti-reverse rotation devices, **2.3:** 27
 - Anti-rotation baffles defined, **9.8:** 48
 - and rectangular wet wells, **9.8:** 32
 - and trench-type wet wells, **9.8:** 26f., 27
 - API 610 Standard for Centrifugal Pumps for Petroleum, Petrochemical and Natural Gas Industries, **50.7:** 1, 3, 8
 - additional data to support data sheet, **50.7:** 14
 - and HI-EDE implementation, **50.7:** 20
 - data sheet, **50.7:** 8, 9 f.
 - See also R/D/S/A compliance
 - API Plan 02, **12.1-12.6:** 81
 - API Plan 11, **12.1-12.6:** 81
 - API Plan 32, **12.1-12.6:** 81
 - API Plan 52, **12.1-12.6:** 82
 - API Plan 53, **12.1-12.6:** 82
 - API Plan 54, **12.1-12.6:** 82
 - API Plan 62, **12.1-12.6:** 82
 - API Standard 610 (impellers), **1.3:** 35
 - Applications, **1.3:** 113
 - booster service, **1.3:** 114
 - dry pit (nonclog) pumps, **1.3:** 117, 118f.
 - pump as turbine (PAT), **1.3:** 114, 115f., 117
 - self-priming pumps, **1.3:** 119, 120f., 121f., 123
 - transfer pumping, **1.3:** 113

- two-phase pumping (liquid and gas), **1.3**: 122, 122f., 123f., 124f., 125f.
- type OH pumps as self-priming pumps, **1.3**: 120
- Apparent viscosity, **6.1-6.5**: 34
- Apparent viscosity, defined, **3.1-3.5**: 38, **12.1-12.6**: 39
- Appeals, **40.7**: 8
- Application considerations, **4.1-4.6**: 13
 - bearings, **4.1-4.6**: 17
 - containment shell thickness and materials, **4.1-4.6**: 17
 - coupling selection, **4.1-4.6**: 13
 - entrained air or gas, **4.1-4.6**: 15
 - high viscosity, **4.1-4.6**: 14
 - liquid classification, **4.1-4.6**: 16
 - liquid properties, **4.1-4.6**: 14
 - liquid vapor pressure, **4.1-4.6**: 15
 - low viscosity, **4.1-4.6**: 15
 - lubricating liquid, **4.1-4.6**: 16
 - magnets, **4.1-4.6**: 13, 17
 - materials, **4.1-4.6**: 17
 - mechanical safety, **4.1-4.6**: 18
 - monitoring devices, **4.1-4.6**: 18
 - nonlubricating liquid, **4.1-4.6**: 16
 - off-design rating procedures, **4.1-4.6**: 16
 - particles, **4.1-4.6**: 15
 - pump, **4.1-4.6**: 17
 - safety, **4.1-4.6**: 17
 - shear sensitivity, **4.1-4.6**: 16
 - specific gravity, **4.1-4.6**: 15
 - specific heat, **4.1-4.6**: 15
 - stripping applications, **4.1-4.6**: 16
 - temperature, **4.1-4.6**: 14
 - variable viscosity, **4.1-4.6**: 15
 - viscosity, **4.1-4.6**: 14
- Application data requirements, **7.1-7.5**: 19, **8.1-8.5**: 13
- Application guidelines, **5.1-5.6**: 27–32
 - advantages of sealless pumps, **5.1-5.6**: 28
 - canned motor or magnet component temperature, **5.1-5.6**: 32
 - circulation piping plan selection, **5.1-5.6**: 28, 29
 - containment expectations, **5.1-5.6**: 28
 - limitations of sealless pumps, **5.1-5.6**: 28
 - pump selection, **5.1-5.6**: 30
 - safety considerations, **5.1-5.6**: 28
 - See also* Design
 - unit design selection, **5.1-5.6**: 28
- Applications, **12.1-12.6**: 44
 - handling of hazardous liquids, **10.1-10.5**: 11
 - handling of hot liquids, **10.1-10.5**: 12
 - liquids and slurries handled, **10.1-10.5**: 11
 - pumping of dry powders, **10.1-10.5**: 12
 - typical services, **10.1-10.5**: 11
- Approach channel, defined, **9.8**: 48
- Approach flow patterns
 - at various intakes, and effects on velocity, **9.8**: 62f.
 - for various combinations of pumps, **9.8**: 63f.
 - remedial measures for, **9.8**: 60, 62f., 63f., 64f., 65f.
 - with multiple pumps in open and partitioned sumps, **9.8**: 64f.
- Approval process
 - applicable standards, **40.7**: 3
 - application approved, **40.7**: 3
 - application for approval, **40.7**: 3
 - application rejected, **40.7**: 3
 - approval decision, **40.7**: 5
 - approval denied, **40.7**: 5
 - approval granted upon remedy of nonconformities, **40.7**: 5
 - audit flowchart, **40.7**: 17 f.
 - confidentiality, **40.7**: 4
 - demonstrations of pump testing procedures, **40.7**: 5
 - documents needed for audit, **40.7**: 16
 - general, **40.7**: 3
 - languages used, **40.7**: 4
 - on-site assessment, **40.7**: 4
 - opening meeting, **40.7**: 4
 - records review, **40.7**: 5
 - renewal of approval, **40.7**: 6
 - role of Auditor, **40.7**: 4
 - staff interviews, **40.7**: 5
- ASME B73 (baseplates), **1.3**: 101, 101f.
- ASME B73.1 (impellers), **1.3**: 35
- ASME/ANSI B73.1
- Association for Manufacturing Technology (AMT), **5.1-5.6**: 46
- ASTM standards, **5.1-5.6**: 46
- Asynchronous, defined, **9.6.8**: 58
- ATEX Certification, **1.4**: 8, **2.4**: 8
- Atmospheric head (h_{atm}), **1.1-1.2**: 70
- Audit flowchart, **40.7**: 17 f.
- Audit requirements changes to, **40.7**: 7 t.
- Auditor, defined, **40.7**: 1
- Austenitic stainless steels, **12.1-12.6**: 65
- Automatically controlled, defined, **7.1-7.5**: 8
- Auxiliary drive (steam) valve, **8.1-8.5**: 6
- Auxiliary piping, **5.1-5.6**: 26
- Average particle size (d50), **12.1-12.6**: 40 f.
 - defined, **12.1-12.6**: 39
- Axial flow (propeller) pump, defined, **9.8**: 48
- Axial flow impeller, **2.1-2.2**: 19, **2.3**: 6, 6 f., 9
- Axial flow pumps, **1.1-1.2**: 10 f., 11, 11 f.
- Axial load, **1.3**: 34, **5.1-5.6**: 14
- Axial piston pumps, **3.1-3.5**: 1 f., 3 t., 4 t., 5 f., 6 f., 15 f.
 - description, **3.1-3.5**: 7
 - fixed displacement type, **3.1-3.5**: 8
 - range chart, **3.1-3.5**: 8 f.
 - variable displacement type, **3.1-3.5**: 8
- Axial thrust
 - calculating by manufacturer's thrust factor method, **2.3**: 14
 - calculating for impellers with back rings (at BEP), **2.3**: 13
 - calculating for impellers with no back rings (at BEP), **2.3**: 11, 12 f.
 - calculating, **2.3**: 9

- calculation for axial flow pump impellers, **1.3**: 31
- calculation for enclosed impeller with plain back shroud, **1.3**: 23f., 23, 26
- calculation for impeller with back ring, **1.3**: 25f., 25, 27
- calculation for impellers, **1.3**: 21
- calculation for semi-open impellers, **1.3**: 29, 29f.
- calculation of axial force due to momentum change, **1.3**: 31
- on enclosed impellers, **1.3**: 21, 21f.
- shaft upthrust force from enclosed suction can pumps, **2.3**: 10 f., 10
- shaft upthrust force from shaft sleeves through packing or mechanical seals, **2.3**: 10, 11 f.
- shaft upthrust force from shaft sleeves through pressure breakdown bushings, **2.3**: 10, 11 f.
- static component of, **2.3**: 10
- terminology, **2.3**: 8
- versus rate of flow, **2.3**: 14, 15 f.
- Axial thrust factor (K_A), **1.3**: 22, 22f.
- Axial thrust, **2.3**: 8, 9 f.
- B parameter**
 - and preliminary selection of rotodynamic pump, **9.6.7**: 15
 - calculating based on best efficiency flow, **9.6.7**: 8
 - calculation example (metric units), **9.6.7**: 10
 - calculation example (US customary units), **9.6.7**: 13
- b_2 . See Impeller width at discharge (b_2)
- Barrier fluid, **1.3**: 63
- Back pull-out assembly, defined, **1.1-1.2**: 42, 43 f.
- Backpressure valve, **7.1-7.5**: 21
- Backwall clearance defined, **9.8**: 49
 - remedial measures for, **9.8**: 72
- Backwall splitter, defined, **9.8**: 49
- Backwall, defined, **9.8**: 48
- Baffles
 - anti-rotation baffle between end pump and backwall in performance enhancement of trench-type wet wells, **9.8**: 26f., 86f., 87
 - defined, **9.8**: 49
 - inlet baffles in performance enhancement of trench-type wet wells, **9.8**: 85, 85f.
 - See also Anti-rotation baffles
 - to improve flow pattern downstream from dual flow screen, **9.8**: 67f.
- Balance machines, **9.6.4**: 13
 - calibration, **9.6.4**: 13
 - weight rating, **9.6.4**: 14
- Balancing
 - and inherent balance, **9.6.4**: 15
 - and keys and keyways in balancing arbors, **9.6.4**: 16
 - and removal or addition of material, **9.6.4**: 17
 - and runout in balancer drive or balancing arbor, **9.6.4**: 15
 - excessive looseness between impeller hub and balancing arbor, **9.6.4**: 16
- Ball check valves, **10.1-10.5**: 4 f.
- Bare rotor
 - defined, **1.1-1.2**: 43
 - terms, **1.1-1.2**: 41
- Barometric pressure, **6.1-6.5**: 28t., 28
- Barometric pressure, **8.1-8.5**: 11
 - and altitude, **8.1-8.5**: 11, 12t.
- Barrel design. See Pump type BB4
- Barrel or can (line shaft) pumps, **2.1-2.2**: 11
- Barrel suction, defined, **9.8**: 49
- Barrier fluid flow leakage monitoring, **9.6.9**: 10, 10t.
- Barrier fluid, defined, **12.1-12.6**: 38
- Baseline measurements, **9.6.5**: 2
- Baseline, **9.6.5**: 36, **9.6.9**: 27
- Baseplates, **1.3**: 94
 - selection parameters, **1.3**: 95t.
 - alignment blocks or guides for thermal expansion of the pump case, **1.3**: 108
 - coupling alignment, **1.3**: 107
 - drip rims, **1.3**: 108
 - epoxy grouting, **1.3**: 108
 - fasteners, **1.3**: 108
 - formed polymer, **1.3**: 102, 103f.
 - freestanding, **1.3**: 99, 100f.
 - functional requirements, **1.3**: 95, 95t.
 - grout holes, **1.3**: 109
 - grouted, **1.3**: 97, 97f., 98f.
 - jacking pads and screws, **1.3**: 108
 - leveling screws, **1.3**: 108
 - lifting requirements, **1.3**: 108
 - nongrout, **1.3**: 97, 98f.
 - offshore skid type, **1.3**: 104, 105f.
 - oil pipeline skid type, **1.3**: 104, 105f.
 - pedestal, **1.3**: 103, 104f.
 - polymer, **1.3**: 102
 - pregouted, **1.3**: 98, 99f.
 - shims and fasteners, **1.3**: 108
 - slide-bearing, **1.3**: 100, 100f.
 - sloped deck plates, **1.3**: 108
 - soleplates, **1.3**: 99, 100f.
 - solid polymer concrete, **1.3**: 103, 103f.
 - standards, **1.3**: 101, 101f., 102f.
 - stress and rigidity requirements, **1.3**: 107
 - three-point mount, **1.3**: 106, 106f.
 - tolerancing, **1.3**: 107
 - types, **1.3**: 96
- Bays
 - and adequate width (rectangular intakes for clear liquids), **9.8**: 3
 - defined, **9.8**: 49
 - flow-guiding devices at entrance to, **9.8**: 65, 65f.
 - narrow widths, remedial measures for, **9.8**: 72
 - trash racks and effect on velocity distribution entering pump bay, **9.8**: 64f.
- BB1-BB5. See Pump type BB1-Pump type BB5
- Bearing arrangements, **1.3**: 31
- Bearing bushings, **2.3**: 16
 - in adapters, **2.3**: 64

- intermediate, **2.3**: 64
- losses due to viscosity, **2.3**: 50
- Bearing housing, **2.3**: 64, 73
 - and temperature monitoring, **9.6.9**: 7
 - and vibration monitoring, **9.6.9**: 12
- Bearing housing closures, **2.3**: 26
- Bearing housings
 - acceleration in vibration monitoring, **9.6.5**: 12
 - Bearing wear monitoring, **9.6.5**: 20
 - by acoustic sensors, **9.6.5**: 21
 - by contact or continuity switches, **9.6.5**: 21
 - by power monitors, **9.6.5**: 21
 - by proximity sensing devices, **9.6.5**: 20
 - by temperature probes, **9.6.5**: 21
 - by vibration sensors, **9.6.5**: 21
 - carbon bearings, **9.6.5**: 20
 - component contact detection, **9.6.5**: 20
 - control limits, **9.6.5**: 21
 - detection methods, **9.6.5**: 20
 - of plain bearings in sealless pumps, **9.6.5**: 20
 - progressive monitoring, **9.6.5**: 20
 - silicon carbide bearings, **9.6.5**: 20
 - vibration control limits, **9.6.5**: 13
 - vibration monitoring, **9.6.5**: 12, 13
- Bearing isolators, **2.3**: 26
- Bearing materials, **4.1-4.6**: 17
- Bearing whip, defined, **9.6.8**: 58
- Bearing whirl, defined, **9.6.8**: 58
- Bearing, defined, **3.1-3.5**: 18, **12.1-12.6**: 36
 - external (MDPs), **5.1-5.6**: 23
 - failure mode indicated by temperature monitoring, **9.6.9**: 7
 - failure mode indicated by vibration monitoring, **9.6.9**: 12
 - friction losses due to viscosity, **2.3**: 50
 - hydrodynamic radial, **9.6.9**: 7
 - internal, **5.1-5.6**: 22
 - liquid film, temperature monitoring, **9.6.5**: 6
 - lubrication of, **5.1-5.6**: 19, 25
 - lubrication, **2.3**: 19
 - outboard (antifriction), **2.3**: 73
 - outboard, **2.3**: 64
 - retainer, **2.3**: 64
 - rolling element bearing failure, **9.6.9**: 5, 15t.
 - rolling element defects, **9.6.9**: 12
 - rolling element temperature monitoring, **9.6.9**: 7
 - rolling element, defects in vibration monitoring, **9.6.5**: 12
 - sleeve bearing failure, **9.6.9**: 5
 - sleeve bearing temperature monitoring, **9.6.9**: 7
 - spacing, **2.3**: 19
 - thrust, **9.6.9**: 7
- Bearings, **1.3**: 43, **12.1-12.6**: 67
 - adjusted rating life, L_{na} , **1.3**: 47, 50, 50t.
 - air entrainment in lubricants, **1.3**: 56
 - and contact seals, **12.1-12.6**: 67
 - and labyrinth seals, **12.1-12.6**: 67, 68 f.
 - and lip seals, **12.1-12.6**: 67, 67 f.
 - axial adjustment of housing, **12.1-12.6**: 90
 - axial load, F_a , **1.3**: 47
 - ball bearings, **1.3**: 46f.
 - basic dynamic radial load rating, C_r , **1.3**: 47
 - basic rating life, L_{10} , **1.3**: 47, 49
 - Best efficiency point (BEP), **12.1-12.6**: 61, 62 t.
 - contamination factor, η_c , **1.3**: 51, 52t.
 - contamination prevention in lubricants, **1.3**: 56
 - cylindrical-type radial journal (sleeve) bearings, **1.3**: 45f.
 - degradation improvement in lubricants, **1.3**: 57
 - dynamic equivalent radial load, P_r , **1.3**: 47
 - factors, **1.3**: 48
 - fatigue life, **12.1-12.6**: 67, 69 t.
 - fatigue limit load, C_u , **1.3**: 51
 - grease lubrication, **1.3**: 53
 - heat and oil oxidation, **1.3**: 56
 - heat stabilization temperature, **1.3**: 53
 - high level of lubricant, **1.3**: 55
 - isolators, **12.1-12.6**: 67, 68 f.
 - life (horizontal pumps), **1.3**: 46
 - life modification factor, a_{xyz} , **1.3**: 49
 - life, **1.3**: 48
 - low level of lubricant, **1.3**: 55
 - lubrication methods, **1.3**: 43
 - lubrication, **1.3**: 53
 - material adjustment factor, a_2 , **1.3**: 48
 - minimum load, **1.3**: 46
 - modified rating life, L_{nm} , **1.3**: 48, 50
 - moisture elimination in lubricants, **1.3**: 57
 - oil lubrication, **1.3**: 54
 - operating conditions adjustment factor, a_3 , **1.3**: 48
 - particle contamination of lubricants, **1.3**: 56
 - pivot-shoe thrust bearings, **1.3**: 45, 45f.
 - product lubrication, **1.3**: 55
 - quality of lubrication, **1.3**: 55
 - quality of oil, **1.3**: 55
 - quantity improvement of lubricants, **1.3**: 56
 - radial load, F_r , **1.3**: 47
 - reliability adjustment factor, a_1 , **1.3**: 48
 - reliability, **1.3**: 47
 - roller bearings, **1.3**: 46f.
 - rolling element bearings, **1.3**: 44, 44t.
 - sleeve bearings, **1.3**: 44, 45f.
 - temperature, **1.3**: 53
 - type BB4 multistage radial split single casing pump, **1.3**: 46f.
 - water contamination of lubricants, **1.3**: 56
- Bell inlet velocity, defined, **9.8**: 40
- Bell, defined, **9.8**: 49
- Bellows assembly
 - bellows, **10.1-10.5**: 3
 - connecting rods, **10.1-10.5**: 3
 - end caps, **10.1-10.5**: 3
- Benching, defined, **9.8**: 49
- BEP rate of flow $[Q_{op}]$, defined, **1.1-1.2**: 68, **2.1-2.2**: 30

- BEP. See Best efficiency point, **9.6.3**: 1
- Best efficiency point (BEP) , **1.3**: 1, 15
- axial load for multistage pumps, **1.3**: 34
 - Defined, **1.1-1.2**: 71, **2.1-2.2**: 34, **2.3**: 41, **9.6.8**: 58, **11.6**: 5
 - operation above, **2.3**: 41
 - operation below, **2.3**: 41
- Best efficiency point (BEP), and NPSH margin, **9.6.1**: 4, 4f.
- Between-bearings (BB) type, **1.3**: 1, 33, 33f., 110, 112f.
- double suction pumps, **1.3**: 33, 34f.
 - multistage pumps, **1.3**: 34, 34f.
 - operation away from, **1.3**: 71
 - radial load for multistage pumps, **1.3**: 34
 - shaft support for multistage pumps, **1.3**: 34
- Between bearings, multistage, axially split pump, **2.1-2.2**: 31 f.
- Between bearings, multistage, radially split, double casing pump, **1.1-1.2**: 33 f.
- Between bearings, multistage, radially split, single casing pump, **1.1-1.2**: 32 f.
- Between bearings, single stage, axially split pump, **1.1-1.2**: 29 f.
- Between bearings, single stage, radially split pump, **1.1-1.2**: 30 f.
- Between-bearing impeller pumps icons, **1.1-1.2**: 78 f.–79 f.
- Between-bearing pump defined, **9.6.8**: 27
- Body, defined, **3.1-3.5**: 17
- Bolted couplings, **2.3**: 29
- Bolt-proof load, defined, **5.1-5.6**: 18
- Bowl assembly efficiency, defined, **2.1-2.2**: 37
- Bowl assembly input power, defined, **2.1-2.2**: 36
- Bowl assembly total head, defined, **2.1-2.2**: 33
- Bowl efficiency
- and losses due to viscosity, **2.3**: 50
- Brake horsepower. See Pump input power
- Breakaway torque, defined, **3.1-3.5**: 24
- Bromobutyl, **12.1-12.6**: 66
- Bubble test, **4.1-4.6**: 26
- Buffer fluid, **1.3**: 63, **12.1-12.6**: 77
- defined, **12.1-12.6**: 38
- Building services (HVAC), **9.6.1**: 11
- Bull ring packing, **6.1-6.5**: 77f., 77
- Butyl, **12.1-12.6**: 66
- Bypass valves, **9.6.9**: 8
- Calculations, submersible pump tests
- of NPSHA on dry-pit pump, **11.6**: 48
 - of NPSHA on wet-pit pump, **11.6**: 47
 - of performance based on change in pump impeller diameter, **11.6**: 46
 - of performance based on change in pump speed, **11.6**: 45
 - of performance tolerance bands for pump acceptance according to grade 1E and 2B, **11.6**: 49
- calculations, viscosity correction **9.6.7**: 3-18
- and mechanical considerations, **9.6.7**: 26
 - and pump design effects, **9.6.7**: 25
- and sealing issues, **9.6.7**: 26
- and sealless pumps, **9.6.7**: 26
- determining pump performance on viscous liquid when performance on water is known, **9.6.7**: 6f.
- establishing if procedure is applicable, **9.6.7**: 5f.
- limitations, **9.6.7**: 1, 4, 25
- overview, **9.6.7**: 5, 5f., 6f., 7f.
- selecting pump for given head, rate of flow, and viscous conditions, **9.6.7**: 7f.
- Calibration column, **7.1-7.5**: 21
- Cambell diagram for variable frequency unit, **9.6.8**: 85f.
- Campbell diagram, **9.6.8**: 30, 33
- defined, **9.6.8**: 58
 - for lateral critical speeds, **9.6.8**: 31f.
 - for torsional critical speeds, **9.6.8**: 34f.
- Can pump, defined, **9.8**: 17
- Can vertical turbine pump intakes (clear liquids), **9.8**: 17
- can pump, defined, **9.8**: 17
 - closed bottom, **9.8**: 18, 19, 21f.
 - design considerations, **9.8**: 19
 - open bottom, **9.8**: 18, 19, 20f.
- Canned motor pumps (CMPs), **5.1-5.6**: 1, 2f., 14
- and motor temperature, **5.1-5.6**: 32
 - close-coupled, in-line, **5.1-5.6**: 1, 5f.
 - defined, **5.1-5.6**: 16
 - definitions (terminology), **5.1-5.6**: 16
 - driver sizing, **5.1-5.6**: 30
 - horizontal mounting base, **5.1-5.6**: 25
 - maintenance of canned motor, **5.1-5.6**: 42
 - motor insulation temperature limits, **5.1-5.6**: 32
 - secondary leakage containment, **5.1-5.6**: 20, 21
 - separated pump and motor, **5.1-5.6**: 2, 6f.
 - submerged mounting, **5.1-5.6**: 26
 - unit location and foundation, **5.1-5.6**: 39
 - vertical submerged, **5.1-5.6**: 2, 7f.
- Cantilever shaft design sump pump (VS5), **2.1-2.2**: 10 f.
- Cantilevered wet pit, defined, **12.1-12.6**: 4
- Canvas packing, **8.1-8.5**: 20
- Capacity
- actual rate of flow (QR), defined, **7.1-7.5**: 11
 - adjustment, defined, **7.1-7.5**: 11
 - design rate of flow (QD), defined, **7.1-7.5**: 11
 - rate of flow (Q), defined, **7.1-7.5**: 11
- Carboxylated nitrile, **12.1-12.6**: 66
- Casing position, **1.1-1.2**: 44, 44 f.
- Casings, **1.3**: 1, 7, **2.3**: 65, 73, **5.1-5.6**: 21
- multistage arrangements, **1.3**: 8
 - back-to-back arrangement, **1.3**: 11, 11f.
 - circular (concentric), **1.3**: 8, 8f.
 - diffuser, **1.3**: 8, 8f.
 - double volute, **1.3**: 7, 7f.
 - single volute, **1.3**: 7, 7f.
 - stacked in-line arrangement, **1.3**: 10, 10f.
 - type BB3 between-bearings axial split volute, **1.3**: 9, 9f.
 - type BB4 between-bearings radial split single, **1.3**: 9, 9f.
 - type BB5 between-bearings radial split double

- (diffusers), **1.3**: 10
- type BB5 between-bearings radial split double (volute pumps), **1.3**: 10, 10f.
- Catch tank leakage monitoring, **9.6.9**: 10, 10t.
- Cause, defined, **9.6.5**: 36, **9.6.9**: 27
- Cavitation, **3.1-3.5**: 43
 - damage from, **9.6.1**: 10
 - defined, **9.8**: 49, **10.1-10.5**: 7, **10.6**: 6
 - in centrifugal pumps, **9.6.1**: 13
- Cavitation erosion resistance, **9.1-9.5**: 26
 - elastomers, **9.1-9.5**: 27
 - engineered plastics, **9.1-9.5**: 27
 - general ranking of common cast metals, **9.1-9.5**: 27 f.
 - general ranking of, **9.1-9.5**: 26
 - hard-faced materials, **9.1-9.5**: 27
- Cell, defined, **9.8**: 49
- Centipoises, **3.1-3.5**: 38
- Centistokes, **3.1-3.5**: 38, **9.6.7**: 31
- Ceramics, **4.1-4.6**: 9
 - defined, **5.1-5.6**: 15
 - coating application, **9.1-9.5**: 25
 - properties, **9.1-9.5**: 25
- Certificate of Approval, **40.7**: 12
 - example, **40.7**: 12 f.
- Certification section, **1.4**: 39, **2.4**: 43
 - purpose, **2.4**: 43
- Certified curve, **6.6**: 18
- CFD. See Computational fluid dynamics
- C-frame adapter, **1.1-1.2**: 46 f., 46
 - See also Overhung impeller, flexibly coupled, single stage, foot mounted ANSI B73.1 pump
- Changes to scope of approval and additional pump test laboratories, **40.7**: 6
- Character string fields, **50.7**: 12
- Check valve, defined
- Check valves, **7.1-7.5**: 10, **9.6.6**: 29, **9.8**: 49, **10.1-10.5**: 4, 4 f.
 - foot valves, **9.6.6**: 29, 29 f.
- Checklist to facilitate use of guideline, **9.6.8**: 5f.
- Chemical packings, **8.1-8.5**: 20
- Chemical process pumps, **9.6.1**: 8
- Chlorides (in water), **2.3**: 79
- Chlorobutyl, **12.1-12.6**: 66
- Choice of driver, **7.1-7.5**: 20
- Chromium-molybdenum iron, **12.1-12.6**: 65
- Chromium-nickel iron, **12.1-12.6**: 65
- CIMA. See Construction Industry Manufacturers Association
- Circular plan wet pit (solids-bearing liquids), **9.8**: 28
 - accessories, limitation of, **9.8**: 28
 - cleaning procedure and low liquid level, **9.8**: 28, 37f.
 - design, **9.8**: 28, 29f., 30f.
 - floor clearance, **9.8**: 28
- Circular pump stations (clear liquids), **9.8**: 9, 11f.
 - dimensioning recommendations, **9.8**: 12
 - duplex, **9.8**: 9
 - floor clearance, **9.8**: 12
 - inflow pipe, **9.8**: 12
 - inlet bell clearance, **9.8**: 12
 - inlet bell or volute diameter, **9.8**: 12
 - sump diameter, **9.8**: 12
 - triplex, **9.8**: 9
 - wall clearance, **9.8**: 12
- Circular well, defined, **9.8**: 49
- Circulating/cooling water pumps, **9.6.1**: 9
- Circulation piping plan selection, **5.1-5.6**: 25, 28, 29, 33f.–37f.
- Circulator pump type icons, **1.1-1.2**: 81
- Circumferential piston pumps, **3.1-3.5**: 1 f., 3 t., 4 t., 5 f., 6 f., 15 f.
 - description, **3.1-3.5**: 12
 - range chart, **3.1-3.5**: 12 f.
- Classic instability, defined, **9.6.8**: 58
- Classification by configuration
 - discharge, above- and below-floor discharge, **2.1-2.2**: 11
 - drivers, **2.1-2.2**: 11
- Classification by impeller design, **2.1-2.2**: 16
- Clean liquids, **5.1-5.6**: 29
 - circulation piping plan selection, **5.1-5.6**: 33f., 36f., 37f.
- Cleaning applications, **12.1-12.6**: 45
- Clockwise, determination of, **3.1-3.5**: 19
- Close coupled, defined, **4.1-4.6**: 6, **5.1-5.6**: 14
- Close-coupled horizontal in-line, **1.1-1.2**: 39 f.
- Close-coupled pumps, **1.1-1.2**: 1
- Close-coupled sealless with canned motor, **1.1-1.2**: 38 f.
- Close-coupled, vane-type, magnetic drive pumps, **4.1-4.6**: 1, 2 f.
- CMP. See Canned motor pump
- Coatings, **9.1-9.5**: 22
- Coercive force, defined, **4.1-4.6**: 6
- Cold spring, **9.6.6**: 7
- Colloidal liquids, defined, **10.1-10.5**: 11
- Color (in water), **2.3**: 79
- Column hydraulic loss due to viscosity, **2.3**: 50
- Column increasers and reducers losses due to viscosity, **2.3**: 50
- Columns, **2.3**: 65, 73
- Commissioning, **12.1-12.6**: 89
- Commissioning, start-up, operation, and shut-down section, **1.4**: 27, **2.4**: 29
 - across-the-line start, **2.4**: 33
 - adequate submergence, **2.4**: 30
 - anti-reverse rotation devices, **2.4**: 29
 - back-flushing to remove debris, **2.4**: 30
 - bearing temperature, **1.4**: 31, **2.4**: 36
 - closed valve warning, **2.4**: 33
 - condition monitoring, **1.4**: 30, **2.4**: 35
 - drive system settings, **1.4**: 29, **2.4**: 33
 - driver inspection, **1.4**: 29
 - guarding, **1.4**: 27, **2.4**: 30
 - hydraulic resonance in piping, **1.4**: 31, **2.4**: 36
 - hydraulic resonance in piping, solutions, **1.4**: 31,

- 2.4: 36
- lube filtration, 2.4: 33
- lubrication system settings, 1.4: 29, 2.4: 32
- lubrication, 1.4: 27, 2.4: 29
- mechanical seals, 1.4: 28, 2.4: 31
- minimum continuous flow, 1.4: 29, 2.4: 32
- minimum thermal flow, 1.4: 29, 2.4: 32
- noise in pumping machinery, 1.4: 30, 2.4: 35
- noise prevention, 1.4: 31, 2.4: 35
- noise transmittal methods, 1.4: 30, 2.4: 35
- operation at reduced flow, 2.4: 35
- packed stuffing box, 1.4: 28, 2.4: 31
- parallel and series operation, 1.4: 30, 2.4: 34
- performance testing/verification, 1.4: 31, 2.4: 36
- position of discharge valve on starting, 1.4: 29
- primary and secondary drivers, 1.4: 29, 2.4: 32
- priming and filling, 1.4: 27
- priming by ejector or exhauster, 1.4: 27, 2.4: 30
- priming by vacuum pumps, 1.4: 28, 2.4: 31
- pump bearings, 2.4: 32
- reduced flow/minimum flow discharge bypass, 1.4: 30
- reduced voltage start, 2.4: 33
- rotation, 1.4: 27, 2.4: 29
- shaft sealing settings and adjustments, 1.4: 28, 2.4: 31
- start-up considerations, 1.4: 27, 2.4: 30
- start-up, operation, and shut-down, 1.4: 29, 2.4: 32
- system flushing, 1.4: 27, 2.4: 30
- valve setting at start-up, 1.4: 29, 2.4: 34
- valve settings and operation, 1.4: 29, 2.4: 33
- vent line, 2.4: 30
- vibration (alarms and trip points), 1.4: 30, 2.4: 35
- water (hydraulic) hammer, 1.4: 30, 2.4: 34
- Common polymer materials of construction for various liquids
 - adhesives and sealants, 9.1-9.5: 26
 - carbon and graphite, 9.1-9.5: 26
 - ceramics, 9.1-9.5: 25
 - elastomeric polymers, 9.1-9.5: 24
 - fabrics, 9.1-9.5: 26
 - leather, 9.1-9.5: 26
 - other nonmetals, 9.1-9.5: 25
 - reinforced fibers, 9.1-9.5: 26
 - rigid polymers and composites, 9.1-9.5: 24
 - tensile strength and modulus of elasticity, 9.1-9.5: 24
 - thermoplastics, 9.1-9.5: 25
 - thermosetting polymers, 9.1-9.5: 24
 - types, 9.1-9.5: 24
- Compliance levels, 50.7: 1, 11, 16, 17 t.
 - R compliance, 50.7: 15, 17t.
 - R/D compliance, 50.7: 15, 17 t.
 - R/D/S compliance, 50.7: 15, 17t.
 - R/D/S/A compliance, 50.7: 16, 17t.
 - relationship among, 50.7: 16, 16f.
- Compressed gas (caution), 5.1-5.6: 49
- Compressed-air properties definitions, 10.1-10.5: 10
- Computational fluid dynamics (CFD), 9.8: 45
 - acceptable uses of, 9.8: 48
 - correlation of simulation and experimental results, 9.8: 48
 - simulation methods, 9.8: 48
- Computational fluid dynamics, defined, 9.8: 49
- Computer discs and tape, cautions regarding, 4.1-4.6: 22, 5.1-5.6: 38
- Concentration correction factor, 12.1-12.6: 51
 - defined, 12.1-12.6: 43
- Concentration of solids by mass or weight, defined, 12.1-12.6: 41
- Concentration of solids by volume, defined, 12.1-12.6: 41
- Condensate pumps, 9.6.1: 9
- Condensation, defined, 10.1-10.5: 10
- Condition monitoring, 9.6.5: 1, 9.6.9: 27
 - and severity and types of consequences, 9.6.5: 2
 - baseline measurements, 9.6.5: 2
 - bearing wear (plain bearings in sealless pumps), 9.6.5: 20
 - comparing indicators to baseline measurements, 9.6.5: 2
 - corrosion, 9.6.5: 7
 - defined, 9.6.5: 1, 36
 - design review, 9.6.5: 22
 - failure modes (with causes and indicators), 9.6.5: 1, 25t., 9.6.9: 15t.
 - frequency, 9.6.5: 2, 3t.
 - indicators (with causes and failure modes), 9.6.5: 1, 31t., 9.6.9: 23t.
 - leakage, 9.6.5: 9
 - maintenance inspection, 9.6.5: 17
 - periodic lubricant analysis, 9.6.5: 13
 - power, 9.6.5: 4
 - preinstallation hydrostatic test, 9.6.5: 21
 - pressure, 9.6.5: 11
 - pump sound, changes in, 9.6.5: 1
 - rate of flow, 9.6.5: 16
 - severity levels, 9.6.5: 2, 2t.
 - shaft position, 9.6.5: 15
 - speed (rpm), 9.6.5: 19
 - temperature, 9.6.5: 5
 - vibration, 9.6.5: 12
- Condition points, 1.1-1.2: 70, 2.1-2.2: 34, 12.1-12.6: 35
- Cone, defined, 9.8: 49
- Confidentiality, 40.7: 4
- Connecting piping, 12.1-12.6: 89
- Consequences, 9.6.5: 2
- Considerations in the specification of dynamic analysis, 9.6.8: 16
 - market influences and trends considerations, 9.6.8: 16
 - pump and system configuration proven field experience, 9.6.8: 16
- Constant-speed systems, 9.6.9: 14
- Construction characteristics, 7.1-7.5: 1
- Construction drawings, 12.1-12.6: 4, 5 f.–20 f.
- Construction Industry Manufacturers Association (CIMA), 1.3: 120

- Contact or continuity switches, **9.6.5**: 21
- Containment definitions (terminology), **5.1-5.6**: 18
- Containment device, **5.1-5.6**: 1
- Containment of liquid, **14.6**: 34
- Containment shell, **4.1-4.6**: 13, **5.1-5.6**: 14, **9.6.9**: 8
 - air in, **4.1-4.6**: 23
 - defined, **4.1-4.6**: 7, **5.1-5.6**: 18
 - design pressure ratings, **5.1-5.6**: 21
 - design, **5.1-5.6**: 20
 - draining, **4.1-4.6**: 24
 - secondary, **5.1-5.6**: 20
 - thickness and materials, **4.1-4.6**: 17
- Continuous service, **2.3**: 39
- Contractors Pump Bureau (CPB), **1.3**: 120
- Contractual agreement(s), **40.7**: 2
- Control limits, **9.6.9**: 5, 27
 - alarm limit, **9.6.5**: 3
 - defined, **9.6.5**: 36
 - shutdown limit, **9.6.5**: 3
 - See also Alarm limits; Shut-down limits
- Control methods, **7.1-7.5**: 20
- Controlled-volume metering pumps, **7.1-7.5**: 1, **7.6**: 1
 - basic elements of, **7.1-7.5**: 1, 1f.
 - defined, **7.1-7.5**: 1
 - drive and control mechanisms, **7.1-7.5**: 5
- Conversion factors, **14.6**: 68, 68 t.
- Cooling liquid flow path, defined, **4.1-4.6**: 7
- Cooling liquid flow, **4.1-4.6**: 13
- Cooling, defined, **5.1-5.6**: 15
- Cooling-loop blockage, **9.6.9**: 7
- Copper and copper alloys aluminum bronze, **9.1-9.5**: 20
 - copper-nickel alloys, **9.1-9.5**: 20
 - high copper, **9.1-9.5**: 19
 - lead nickel bronze (nickel silvers), **9.1-9.5**: 20
 - lead red brass, **9.1-9.5**: 19
 - silicon bronze, **9.1-9.5**: 19
 - tin bronze, **9.1-9.5**: 19
 - yellow brass, **9.1-9.5**: 19
- Corrective action, **40.7**: 8
- Corrosion allowance for metallic rotodynamic pumps, **1.3**: 11
- Corrosion monitoring, **9.6.5**: 7
 - alarm limits, **9.6.5**: 8
 - by electrical resistance (ER), **9.6.5**: 8
 - by linear polarization resistance (LPR), **9.6.5**: 8
 - by ultrasonic thickness measurement (UTM), **9.6.5**: 8
 - by visual/dimensional inspection, **9.6.5**: 7
 - frequency, **9.6.5**: 8
 - means of, **9.6.5**: 7
 - shutdown limits, **9.6.5**: 8
- Corrosion, **2.3**: 78, **5.1-5.6**: 24, **9.6.6**: 14
 - and aeration, **2.3**: 79
 - and materials for rotodynamic vertical pumps, **2.3**: 80
 - and protective coatings, **2.3**: 80
 - and rust coating, **2.3**: 78
 - and water quality analysis, **2.3**: 79
 - defined, **2.3**: 78, **12.1-12.6**: 43
 - failure mode indicated by temperature monitoring, **9.6.9**: 7
 - galvanic, **2.3**: 78
 - intergranular, **2.3**: 78
 - mechanism of, **2.3**: 78
 - pitting, **2.3**: 79
 - uniform, **2.3**: 78
- Corrosion/erosion/contamination, **9.1-9.5**: 11
- Cost and lead time considerations, **9.6.8**: 26
- Counterclockwise, determination of, **3.1-3.5**: 19
- Coupling selection, **4.1-4.6**: 13
- Couplings, **1.3**: 57, 58t., **2.3**: 29, **9.6.6**: 25
 - alignment, **1.3**: 59
 - condition monitoring failure modes, **9.6.9**: 19t.
 - disk, **1.3**: 59
 - driveshaft, **1.3**: 57
 - elastomeric, **1.3**: 59
 - failure indicated by power monitoring, **9.6.9**: 5
 - failure indicated by vibration monitoring, **9.6.9**: 12
 - flanged adjustable spacer, rigid style, **2.3**: 30 f.
 - flanged adjustable, rigid style, **2.3**: 30 f.
 - gear, **1.3**: 59
 - in sump pump configuration, **2.3**: 62, 63 f., 65, 71
 - limited end float, **1.3**: 58
 - magnetic, **9.6.9**: 5, 7, 8
 - maintenance inspection for failure, **9.6.5**: 17, 18
 - offset, **1.3**: 57
 - speed limitations, **1.3**: 59
- CPB. See Contractors Pump Bureau
- Cracking pressure, defined, **3.1-3.5**: 18
- Credit cards, caution regarding, **4.1-4.6**: 22, **5.1-5.6**: 38
- Critical carrying velocity, **6.1-6.5**: 34
- Critical damping ratio, defined, **9.6.8**: 58
- Critical damping, defined, **9.6.8**: 58
- Critical depth, defined, **9.8**: 49
- Critical speed, defined, **9.6.8**: 58
- Cross-coupling, defined, **9.6.8**: 58
- Cross-flow control, **9.8**: 61, 64f., 65f.
- Cross-sectional drawings section, **1.4**: 38
- Cup type pistons composition cups, **6.1-6.5**: 78, 79f.
 - installation, **6.1-6.5**: 79
 - synthetic rubber cups, **6.1-6.5**: 79, 79f.
- Curie temperature, defined, **4.1-4.6**: 7, **5.1-5.6**: 17
- Curtain walls
 - defined, **9.8**: 49
 - in remediation of surface vortices, **9.8**: 68, 69f., 71f.
- Curve shape, **20.3**: 2
- Cutwater area, **1.3**: 1
- Cycle rate defined, **10.1-10.5**: 4, **10.6**: 3
 - measurement of, **10.6**: 15
- Cycle, defined, **10.1-10.5**: 4, **10.6**: 3
- Cyclic service, **2.3**: 39
- D slide valves, **8.1-8.5**: 6, 6f.
- D. See also Pump displacement
- D. See Displacement
- D₂. See Impeller diameter
- (D₂) Discharge recirculation, **1.3**: 72

- Damped natural frequency analysis of OH or BB pumps, **9.6.8:** 47
 - analysis, **9.6.8:** 48
 - interpretation of results, **9.6.8:** 48
 - methodology, **9.6.8:** 47
 - model, **9.6.8:** 47
 - validation, **9.6.8:** 49
- Damped torsional analysis, defined, **9.6.8:** 59
- Dampening devices, **7.6:** 8
- Damping, **9.6.8:** 27
 - defined, **9.6.8:** 59
- Darcy-Weisbach method, **9.6.6:** 14, 15
- Data element groups, **50.7:** 12
- Data elements, **50.7:** 11
 - additional data to support API 610/ISO 13709 data sheet, **50.7:** 14
 - and bid, quotation, and purchasing, **50.7:** 10
 - and equipment types, **50.7:** 10, 11t.
 - and field names, **50.7:** 11, 12
 - and HI data exchange compliance levels, **50.7:** 1, 11, 15, 17t.
 - and pump technology designations, **50.7:** 11, 18, 19t.
 - and R/D/S field designations, **50.7:** 11, 12, 13, 17 t.
 - and units of measure, **50.7:** 12
 - and work processes, **50.7:** 10, 11t.
 - classes, **50.7:** 12
 - See also Pump data transaction set
- Data exchange. See Electronic data exchange
- Data field definitions, **50.7:** 13
 - Data sheets standardization of, **50.7:** 1
 - usefulness and examples of, **50.7:** 8
- Data sheet, **7.6:** 9
- Datum defined, **12.1-12.6:** 34
 - elevations for various slurry pump designs, **12.1-12.6:** 34 f.
- Datum elevation for various pump designs, **1.1-1.2:** 69 f., **14.6:** 7 f.
- Datum elevation, **2.1-2.2:** 33 f.
- Datum, defined, **3.1-3.5:** 21, **3.6:** 5, **6.6:** 5, **10.1-10.5:** 6, **10.6:** 4
- Decision matrix, **9.6.8:** 12t.
- Decontamination of returned products procedure, **9.1-9.5:** 42
- Decouple, defined, **5.1-5.6:** 17
- Decoupling torque test, **4.1-4.6:** 28
- Decoupling, defined, **4.1-4.6:** 7
- Deep-well pumps (VS1), **2.1-2.2:** 4 f.
- Default test acceptance grades, **14.6:** 17
 - based on purchaser's intended service, **14.6:** 17, 17 t.
 - defined, **12.1-12.6:** 41
- Definitions of terms, **2.1-2.2:** 28, **3.1-3.5:** 16, **6.1-6.5:** 24–35, **7.1-7.5:** 11, **7.1-7.5:** 11, **9.6.8:** 58, **10.1-10.5:** 4, **10.6:** 1, **12.1-12.6:** 31–44
- Demagnetization, defined, **4.1-4.6:** 7, **5.1-5.6:** 17
- Dephase, defined, **4.1-4.6:** 7
- Deposit velocity, **12.1-12.6:** 45
 - defined, **12.1-12.6:** 41
- Design, **4.1-4.6:** 12
 - air-operated pump, **10.1-10.5:** 11
 - and circulation piping plan selection, **5.1-5.6:** 25
 - and electrical classifications and codes, **5.1-5.6:** 20
 - and three years mean time between repairs, **5.1-5.6:** 20
 - auxiliary piping, **5.1-5.6:** 26
 - bellows pump features, **10.1-10.5:** 12
 - bellows selection and materials, **10.1-10.5:** 13
 - casing, **5.1-5.6:** 21
 - check valve selection and materials, **10.1-10.5:** 14
 - containment shells, **5.1-5.6:** 20
 - diaphragm pump features, **10.1-10.5:** 12
 - diaphragm selection and materials, **10.1-10.5:** 13
 - dynamic balance, **5.1-5.6:** 24
 - external bearings, **5.1-5.6:** 23
 - external couplings and guards (MDP), **5.1-5.6:** 25
 - gaskets, **5.1-5.6:** 21
 - instrumentation options, **5.1-5.6:** 27
 - integral motors (CDP), **5.1-5.6:** 23
 - internal bearings, **5.1-5.6:** 22
 - joint bolting, **5.1-5.6:** 21
 - magnetic couplings (MDP), **5.1-5.6:** 23
 - manufacturer's data responsibilities, **5.1-5.6:** 20
 - manufacturer's responsibility for engineering coordination, **5.1-5.6:** 20
 - materials, **5.1-5.6:** 24
 - mounting of pumps, **5.1-5.6:** 25
 - pump case materials, **10.1-10.5:** 13
 - pump controls, **10.1-10.5:** 13
 - purchaser's data responsibilities, **5.1-5.6:** 20
 - See also Application guidelines
 - specific gravity, and effect on pump performance, **10.1-10.5:** 14
 - venting and draining, **5.1-5.6:** 22
 - viscosity correction, **5.1-5.6:** 20
 - viscosity, and effect on pump performance, **10.1-10.5:** 14
 - wetted parts selection, **10.1-10.5:** 13
- Design considerations, **3.1-3.5:** 34, **9.6.6:** 6
- Design guidelines, **8.1-8.5:** 13
- Design Institute for Physical Properties (DIPPR), **50.7:** 3
- Design review, **9.6.5:** 22
 - frequency, **9.6.5:** 24
 - hydraulic applications, **9.6.5:** 23
 - installation, **9.6.5:** 23
 - mechanical applications, **9.6.5:** 22
 - operating procedures, **9.6.5:** 23
- Desired data, **50.7:** 13, 14
 - See also R/D/S field designations
- Dew point, defined, **10.1-10.5:** 10
- Diaphragm assembly diaphragm, **10.1-10.5:** 2
 - diaphragm with integral outer plate, **10.1-10.5:** 3 f., 3
 - inner and outer plates, **10.1-10.5:** 3
- Diaphragm hydraulic system, **7.1-7.5:** 10
- Diaphragms, **7.1-7.5:** 10
 - double, with leak detection systems, **7.1-7.5:** 20

- leak detection, **7.1-7.5**: 10
- multiple, **7.1-7.5**: 10
- Differential pressure (Δp), **8.1-8.5**: 11, **9.6.9**: 12
 - calculation, **3.6**: 14
 - defined, **3.1-3.5**: 23, **3.6**: 7
- Dilatant liquids, defined, **10.1-10.5**: 11
- Dimensionally interchangeable pump, **2.1-2.2**: 19
- Direct-acting (steam) pumps
 - all bronze, **9.1-9.5**: 14
 - all iron, **9.1-9.5**: 14
 - bronze fitted, **9.1-9.5**: 14
 - defined, **8.1-8.5**: 1
 - double-acting pump, **8.1-8.5**: 1
 - duplex pump, **8.1-8.5**: 2, 3f.
 - horizontal pump, **8.1-8.5**: 1
 - inspection, **8.1-8.5**: 26
 - nomenclature, **8.1-8.5**: 2
 - piston pump, **8.1-8.5**: 1, 2f.
 - simplex pump, **8.1-8.5**: 1, 3f.
 - types, **8.1-8.5**: 1, 1f.
 - typical services, **8.1-8.5**: 13
 - vertical pump, **8.1-8.5**: 1
- Direction of rotation, defined, **3.1-3.5**: 19
- Dirty liquids, **5.1-5.6**: 30
 - circulation piping plan selection, **5.1-5.6**: 34f.
- Discharge flanges, **5.1-5.6**: 21
- Discharge manifold, **10.1-10.5**: 3
- Discharge pipe or hose, **2.3**: 65, 73, **7.6**: 8
- Discharge piping, **6.1-6.5**: 49f., 56, **7.1-7.5**: 21
- Discharge port, defined, **3.1-3.5**: 17
- Discharge pressure, **8.1-8.5**: 10, **9.6.9**: 11, **10.1-10.5**: 6
 - See Outlet pressure
- Discharge pressure gauge, **7.6**: 8
- Discharge pressure pulsation. See Acoustic resonance
- Disk friction losses, **9.6.7**: 19
 - influence on viscosity correction factor for efficiency, **9.6.7**: 20f.
 - ratio to useful power, **9.6.7**: 20f.
- Displacement, defined, **3.1-3.5**: 20, **3.6**: 2, **7.1-7.5**: 11
- Displacement per stroke (D), defined, **10.1-10.5**: 6, **10.6**: 4
- Displacement, **6.1-6.5**: 24, **8.1-8.5**: 9
- Double diaphragms, with leak detection systems, **7.1-7.5**: 20
- Double suction impellers, **2.3**: 6 f., 6, **9.8**: 49
- Double-acting pump, **6.1-6.5**: 1f., 2f., 3
- Drain bosses, **5.1-5.6**: 21
- Draining, **5.1-5.6**: 22
- Drains, **8.1-8.5**: 27
- Drilling applications, **12.1-12.6**: 45
- Drive (steam) cylinder, **8.1-8.5**: 6
- Drive (steam) end, **8.1-8.5**: 4, 5f.
 - lubrication, **8.1-8.5**: 18, 27
- Drive (steam) piston, **8.1-8.5**: 6
- Drive alignment after piping installation, **7.1-7.5**: 23
- Drive and control mechanisms, **7.1-7.5**: 5
- Drive characteristics, **4.1-4.6**: 20
- Drive motor, **7.6**: 8
- Drive specifications, **3.1-3.5**: 43
- Drive train arrangements, **12.1-12.6**: 82
- Driven component liner, defined, **5.1-5.6**: 18
- Driven shaft, **5.1-5.6**: 1
- Driver power. See Total input power
- Driver sizing, **5.1-5.6**: 30
- Drivers, **1.3**: 153, **7.6**: 8
 - deceleration devices, **1.3**: 176, **2.3**: 94
 - eddy current drives, **1.3**: 176
 - functions and parameters for selection, **1.3**: 154t.
 - gears, **2.3**: 94
 - in VS4 line-shaft design sump pumps, **2.3**: 65
 - in VS5 cantilever shaft design sump pumps, **2.3**: 73
 - mounting, **3.1-3.5**: 57
 - pedestal, **2.3**: 65, 74
 - See also Electric motors; Engines; Steam turbines
 - selection, **2.3**: 81, 81 t.
 - sizing, **2.3**: 81
 - types, **2.3**: 81
 - variable-speed, **1.3**: 176, **2.3**: 94
- Dry critical speed analysis, defined, **9.6.8**: 59
- Dry pit (nonclog) pumps, **1.3**: 117, 118f.
- Dry run, **9.6.9**: 8
- Dry suction lift defined, **10.1-10.5**: 7, **10.6**: 9
 - vacuum gauge test method, **10.6**: 10
 - vacuum gauge with enclosed tank test method, **10.6**: 10
 - water lift test method, **10.6**: 10
- Dry-pit suction, defined, **9.8**: 49
- Dual flow screens, defined, **9.8**: 50
- Dual pressurized seals, **12.1-12.6**: 77, 78 f.
 - arrangements, **9.6.9**: 10, 10t.
 - defined, **12.1-12.6**: 38
- Dual seal, defined, **12.1-12.6**: 38
- Dual unpressurized seal
 - arrangements, **9.6.9**: 10, 10t.
 - defined, **12.1-12.6**: 38
- Ductile iron, **12.1-12.6**: 64
- Dunkerly equation, **9.6.8**: 40
- Duplex pump, **6.1-6.5**: 3
- Duplex stainless steels, **12.1-12.6**: 65
- Duplicate performance pump, **2.1-2.2**: 19
- Duplicate, defined, **9.6.8**: 59
- Duty cycle, **3.1-3.5**: 44
- Duty point. See Guarantee point
- Factory performance tests, **14.6**: 9
 - nonwitnessed and certified, **14.6**: 9
 - remote witnessing by purchaser's representative, **14.6**: 9
 - See also Performance test reports
 - witnessed, **14.6**: 9
- Dynamic analysis
- Dynamic analysis sample specification wording, **9.6.8**: 86
- Dynamic analysis sample specifications, **9.6.8**: 84
 - instructions for specification writers, **9.6.8**: 84
 - reduction of vibration and reliability problems, **9.6.8**: 27

- separation margin, **9.6.8**: 84
- Dynamic analysis sample specifications, motor reed
 - critical frequency, **9.6.8**: 90
 - instructions to motor purchasers, **9.6.8**: 90
 - instructions to specification writers, **9.6.8**: 90
 - sample specification, **9.6.8**: 90
- Dynamic balance, **5.1-5.6**: 24
- Dynamic balancing. See two-plane balancing
- Dynamic losses, **9.6.6**: 13
- Dynamic viscosity units, **9.6.7**: 32
 - conversion from CGS to SI, **9.6.7**: 32
 - conversion from SI to CGS, **9.6.7**: 32
 - conversion to kinematic viscosity units, **9.6.7**: 31
- Economic consequences, **9.6.5**: 2, **9.6.9**: 4, 4t.
- Eddy current defined, **4.1-4.6**: 7
 - drive, defined, **4.1-4.6**: 7, **5.1-5.6**: 17
 - losses, defined, **4.1-4.6**: 7
 - magnetic coupling, **4.1-4.6**: 12
- Eddy current losses, defined, **5.1-5.6**: 17
- Eddy currents defined, **5.1-5.6**: 16
 - induced, **5.1-5.6**: 21
- Eddy, defined, **9.8**: 50
- Effective diaphragm area (AEFF), defined, **10.1-10.5**: 4, 4 f.
- Effective diaphragm area (AEFF), definition and equation, **10.6**: 4, 4f.
- Effective particle diameter, **6.1-6.5**: 34
- Efficiency
 - calculating correction factor, **9.6.7**: 1
 - calculating correction factors (example; metric units), **9.6.7**: 11
 - calculating correction factors (example; US customary units), **9.6.7**: 13
 - calculating correction factors, and preliminary selection of rotodynamic pump, **9.6.7**: 16, 17, 18
 - characteristic curves with viscosity correction factors, **9.6.7**: 2, 3f.
 - characteristic curves, **9.6.7**: 1
 - correction factors, **9.6.7**: 9, 10f.
 - defined, **11.6**: 9
 - influence of disk friction losses on viscosity correction factor for, **9.6.7**: 20f.
 - major influences on, **20.3**: 1
 - mechanical, defined, **7.1-7.5**: 11
 - optimum normally attainable (metric units), **20.3**: 4 f.
 - optimum normally attainable (US units), **20.3**: 6 f.
 - reduction due to specific speed (metric units), **20.3**: 5 f.
 - reduction due to specific speed (US units), **20.3**: 7 f.
 - reciprocating pump, **6.1-6.5**: 29
 - rotary pump, **3.1-3.5**: 43
 - rotary vs. rotodynamic pumps, **3.1-3.5**: 44, 45 f.
 - volumetric, defined, **7.1-7.5**: 12
- Efficiency deviations
 - and desired curve shape, **20.3**: 2
 - and difference between attainable bowl and attainable pump efficiencies, **20.3**: 2
 - and high suction specific speed, **20.3**: 2
 - and impeller diameter trim, **20.3**: 2
 - and internal wear ring clearances, **20.3**: 1, 12 f., 13 f.
 - and mechanical losses, **20.3**: 1
 - and slurries, **20.3**: 1
 - and solids size, **20.3**: 1
 - and special impeller designs, **20.3**: 2
 - and surface roughness, **20.3**: 1, 10 f., 11 f.
 - and thrust balance, **20.3**: 2
 - and types of pumps, **20.3**: 1, 2 t.
 - and viscosity, **20.3**: 1
 - for multistage vertical turbine (diffuser) type pumps, **20.3**: 2
 - influences on, **20.3**: 1
 - metric units, **20.3**: 8 f.
 - US units, **20.3**: 9 f.
- Efficiency prediction
 - and variance of specific speed at which optimum efficiency occurs for different pump types, **20.3**: 14
 - charts, **20.3**: 1, 4 f.–7 f.
 - efficiency reduction due to specific speed (US units), **20.3**: 7 f.
 - of normally attainable efficiency levels at best efficiency point (example; metric units), **20.3**: 2 t., 4 f., 5 f., 8 f., 14
 - of normally attainable efficiency levels at best efficiency point (example; US units), **20.3**: 2 t., 6 f., 7 f., 9 f., 14
 - optimum normally attainable efficiency (metric units), **20.3**: 4 f.
 - optimum normally attainable efficiency (US units), **20.3**: 6 f.
- Efficiency prediction method, **1.3**: 81
- Efficiency ratio, defined, **12.1-12.6**: 42
- Efficiency reduction factor, **12.1-12.6**: 51
 - defined, **12.1-12.6**: 42
- EGL. See Energy grade line
- Elastomer shelf life, **10.1-10.5**: 20
- Elastomers, **12.1-12.6**: 64, 65
 - bonded to metals, **12.1-12.6**: 64
 - linings, storage of, **12.1-12.6**: 90
 - synthetic rubber, **12.1-12.6**: 66
- Electric motor input power, defined, **1.1-1.2**: 72, **2.1-2.2**: 36, **12.1-12.6**: 36
- Electric motors, **1.3**: 153, **2.3**: 83
 - AC polyphase, **2.3**: 83
 - AC single-phase, **2.3**: 83
 - alternating-current (AC) polyphase, **1.3**: 156
 - alternating-current (AC) single-phase, **1.3**: 155
 - and altitude, **1.3**: 163, **2.3**: 91
 - and frequency, **2.3**: 91
 - and hazardous locations and materials, **2.3**: 92
 - and shaft-mounted fans, **2.3**: 87
 - bearings, **2.3**: 87
 - Class I-III hazardous locations, **2.3**: 92
 - classified (or regulated) areas (hazardous atmospheres), **1.3**: 164
 - closed-circuit cooling, **2.3**: 87

- construction, **2.3**: 84
- cooling fluids, **2.3**: 87
- cooling in VSO-style pumps, **2.3**: 87
- cooling methods, **1.3**: 158, **2.3**: 86
- definition of first numeral in IP classification system, **2.3**: 86 t.
- definition of second numeral in IP classification system, **2.3**: 86 t.
- degree of protection, **2.3**: 85, 86 t.
- direct current (DC), **1.3**: 156
- Division 1-2 hazardous locations, **2.3**: 93
- dust-ignition proof, **2.3**: 92, 93
- dust-ignition-proof machines, **1.3**: 164
- dust-ignition-proof motor requirements, **1.3**: 166
- efficiency, **1.3**: 161, **2.3**: 90
- enclosures, **1.3**: 156, 157t., **2.3**: 84, 85 t.
- explosion-proof machines, **1.3**: 164
- explosion-proof motor requirements, **1.3**: 165
- explosion-proof, **2.3**: 92, 93
- frequency, **1.3**: 163
- Group A-D hazardous materials, **2.3**: 93
- horizontal mounting, **1.3**: 159
- industry standards, **1.3**: 168
- IP designation system (degree of protection), **1.3**: 157, 158t.
- motor bearings, **1.3**: 159
- NEMA Designs A-D, **1.3**: 161, 161f., **2.3**: 89
- open circuit cooling, **2.3**: 87
- performance characteristics, **1.3**: 160, **2.3**: 87
- power factor, **1.3**: 162, **2.3**: 90
- relationship between voltage and current, **1.3**: 160
- service factor, **1.3**: 163, **2.3**: 90
- squirrel-cage induction, **2.3**: 83
- starting torque, **1.3**: 160
- starting voltage and frequency, **2.3**: 91
- starting, **1.3**: 163, **2.3**: 92
- synchronous, **2.3**: 84
- torque vs. speed, **1.3**: 160, **2.3**: 87, 88 f.
- torque-speed curves, **1.3**: 160f.
- types, **1.3**: 155, **2.3**: 83
- variable-speed power sources, **1.3**: 166
- vertical mounting, **1.3**: 159
- voltage-current relationship, **2.3**: 87
- wound rotor induction, **2.3**: 84
- Electric power plant (non-nuclear) pumps, **9.6.1**: 9, 9t.
- Electrical current, in power monitoring, **9.6.5**: 4, **9.6.9**: 6
- Electrical resistance (ER), **9.6.5**: 8
- Electromagnetic drive (solenoid), **7.1-7.5**: 6, 6f.
- Electronic counters (in rotary speed measurement), **3.6**: 25
- Electronic counters, **9.6.9**: 14
- Electronic counters, in speed (rpm) monitoring, **9.6.5**: 19
- Electronic data dictionary, 1, 8
- Electronic data exchange (EDE), **50.7**: 1
 - additional resources, **50.7**: 30
 - and bounded set of data elements (dictionary), **50.7**: 8
 - and business leaders/managers, **50.7**: 3
 - and information technology staff and system implementation specialists, **50.7**: 4
 - and neutral data exchange files, **50.7**: 8
 - and pump specifiers and manufacturers, **50.7**: 4
 - and universal digital format (XML), **50.7**: 8
 - compliance levels for data elements, **50.7**: 1
 - defined, **50.7**: 1
 - demonstration of real usage scenarios, **50.7**: 22, 22 f.
 - in bidding and quoting transactions, **50.7**: 1
 - link to HI-EDE data dictionary, **50.7**: 31
 - standards utilizing XML schemas, **50.7**: 1
 - testing compliance with HI, **50.7**: 21
 - units of measure and conversion for transactions, **50.7**: 1
- Electronic instruments, caution regarding, **4.1-4.6**: 22
- Elevation head, **6.1-6.5**: 28, **6.6**: 5, **8.1-8.5**: 11
 - defined, **1.1-1.2**: 69, **2.1-2.2**: 32, **3.6**: 5, **10.6**: 5, **11.6**: 7, **12.1-12.6**: 34
- Elevation pressure, **6.1-6.5**: 28, **8.1-8.5**: 11
 - defined, **3.1-3.5**: 21, **6.6**: 5, **10.6**: 4
- Elevation pressure, definition and equation, **3.6**: 5
- Empirical method, **9.6.7**: 1, 2
- Encapsulation, defined, **4.1-4.6**: 7
- Enclosed impellers, **2.3**: 5, 6 f.
 - and axial thrust, **2.3**: 9 f., 9
- Enclosed line-shaft pumps, **2.3**: 16, 17 f., 18 f.
 - bearing bushings, **2.3**: 16
 - bearing lubrication, **2.3**: 20
 - bearing spacing, **2.3**: 19
- End plate, defined, **3.1-3.5**: 17
- End suction pump, defined, **9.8**: 50
- Energy conservation, **3.1-3.5**: 43
 - and variable-speed pumping, **3.1-3.5**: 43
- Energy grade line (EGL), **9.8**: 83
- Engineered plastics applications, **9.1-9.5**: 27
- Engines, **1.3**: 168, 175f.
 - types, **1.3**: 168
 - condition monitoring, **1.3**: 173
 - cooling, **1.3**: 170
 - diesel fuel grades, **1.3**: 174
 - diesel, **1.3**: 169
 - drive connections, **1.3**: 169
 - enclosures, **1.3**: 170
 - Engine Power Test Code, **1.3**: 174
 - gasoline, **1.3**: 169
 - mass elastic analysis, **1.3**: 175
 - mounting, **1.3**: 169
 - operating speeds, **1.3**: 172
 - operation, **1.3**: 172
 - package design considerations, **1.3**: 174
 - speed governing, **1.3**: 172
 - starting, **1.3**: 173
 - testing and performance, **1.3**: 174
- Entrained air or gas bubbles, **9.8**: 1
- Environment, **7.1-7.5**: 20
- Environmental consequences, **9.6.5**: 2, **9.6.9**: 4, 4t.
- Environmental considerations, **5.1-5.6**: 29

- Equipment data sheets, **12.1-12.6**: 44
 - metric units, **12.1-12.6**: 97–98
- Equipment life cycle work process, **50.7**: 4, 5 f.
- ER. See Electrical resistance
- Erosion, **2.3**: 78
 - cavitation, **2.3**: 78
 - defined, **2.3**: 78
- Erosion, defined, **12.1-12.6**: 44
- Erosion, maintenance inspection for, **9.6.5**: 17, 18
- Erosion–corrosion, **12.1-12.6**: 57
 - defined, **12.1-12.6**: 44
- Erosion–Corrosion, **2.3**: 78
- Ex rating, **1.4**: 8, **2.4**: 8
- Excessive radial thrust, **1.3**: 72
- Excitation force level, **9.6.8**: 27
- Exclusions from standard, **9.6.4**: 1
- Expansion joints, **9.6.6**: 25
 - and pressure effects, **9.6.6**: 27
 - and supports, **9.6.6**: 26
 - and tie rods, **9.6.6**: 27, 27 f.
 - double, **9.6.6**: 26 f., 26
 - elastomer, **9.6.6**: 25, 26 f.
 - metal bellows type, **9.6.6**: 26, 26 f.
 - packed, **9.6.6**: 25, 25 f.
 - slip (axial) type, **9.6.6**: 25, 25 f.
 - types of, **9.6.6**: 25
 - universal, **9.6.6**: 26 f., 26
- Explosive atmosphere, caution regarding, **4.1-4.6**: 22
- External flush fluid, defined, **12.1-12.6**: 38
- External flush, **5.1-5.6**: 30
- External gear and bearing screw pump on base plate, **3.1-3.5**: 30 f.
- External gear pumps, **3.1-3.5**: 1 f., 3 f., 4 f., 15 f.
 - and helical gears, **3.1-3.5**: 10
 - and herringbone gears, **3.1-3.5**: 10
 - and spur gears, **3.1-3.5**: 10
 - description, **3.1-3.5**: 10
 - flanged ports, **3.1-3.5**: 28 f.
 - on base plate, **3.1-3.5**: 29 f.
 - range chart, **3.1-3.5**: 10 f.
 - threaded ports, **3.1-3.5**: 28 f.
- Face-type seal. See Mechanical seal
- Factory test, **9.6.3**: 2
 - characteristics to be monitored, **9.6.3**: 2
 - Preferred operating region (POR), **9.6.3**: 1
 - related to specific speed, **9.6.3**: 1, 1 t.
- Factory tests certified, **11.6**: 2
 - nonwitnessed, **11.6**: 2
 - remote witnessing by buyer's representative, **11.6**: 3
 - witnessed, **11.6**: 3
 - witnessing by buyer's representative, **11.6**: 3
- Failure modes
 - defined, **9.6.5**: 36
 - factors in probability of, **9.6.5**: 2
 - Field alarms, default initial setting recommendations, **9.6.5**: 1
 - for sealless pumps and pumps with journal bearings, **9.6.5**: 30t.
 - list of, **9.6.5**: 1
 - with causes and indicators, **9.6.5**: 1, 25t.
- Failure modes characterization, **9.6.9**: 1
 - condition monitoring, **9.6.9**: 15t.
 - defined, **9.6.9**: 27
 - determining severity level, **9.6.9**: 4, 4t., 5t.
 - indicated by power monitoring, **9.6.9**: 5
 - indicated by temperature monitoring, **9.6.9**: 7
 - indicated by vibration monitoring, **9.6.9**: 12
- Failure, **9.6.9**: 27
- Failure, defined, **9.6.5**: 36
- FEA, defined, **9.6.8**: 59
- Ferrite, defined, **4.1-4.6**: 9
- FIATECH/AEX, **50.7**: 1, 3
 - informative content, **50.7**: 4
 - intended audience, **50.7**: 3
 - normative content, **50.7**: 4
 - overview, **50.7**: 3
 - purpose, **50.7**: 1
 - scope, **50.7**: 1
 - supported work processes and equipment types, **50.7**: 11, 11t.
- Field adjustment, **9.6.6**: 7
- Field alarm settings, **9.6.4**: 20
- Field-test pressure, **2.1-2.2**: 37
- Field-test pressure, defined, **1.1-1.2**: 73
- Fillet defined, **9.8**: 50
 - in performance enhancement of trench-type wet wells, **9.8**: 87
- Filtered high-frequency signal processing, **9.6.5**: 12, **9.6.9**: 12
- Fine-particle correction factor (Cfp), **12.1-12.6**: 51
 - defined, **12.1-12.6**: 42
- Finite element analysis method (FEA), **9.6.8**: 35
 - sources of errors, **9.6.8**: 35
- Finite element analysis, defined, **9.6.8**: 59
- First critical speed, defined, **9.6.8**: 38
- First dry critical speed of vertically suspended (VS) pumps, **9.6.8**: 46
 - analysis, **9.6.8**: 46
 - interpretation of results, **9.6.8**: 47
 - methodology, **9.6.8**: 46
 - model, **9.6.8**: 46
 - validation, **9.6.8**: 47
- First transverse (lateral) critical speed, **9.6.8**: 39
 - for a rotor with a single attached mass, **9.6.8**: 39
 - for a shaft of constant cross section, **9.6.8**: 39
 - for a shaft of negligible mass carrying several concentrated masses, **9.6.8**: 40
 - for the angular or torsional case, **9.6.8**: 41
- Fittings, **7.1-7.5**: 23, **8.1-8.5**: 16, **9.6.6**: 14
 - losses due to viscosity, **2.3**: 50
- Fixed stroke-length drives, **7.1-7.5**: 6, 7f.
- Flammability, **5.1-5.6**: 29
- Flammable liquids or vapors, **8.1-8.5**: 16
- Flanges and fittings, **5.1-5.6**: 21, **7.1-7.5**: 23, **8.1-8.5**: 16,

- 12.1-12.6:** 82
- Flap check valves, **10.1-10.5:** 4 f.
- Flexible coupling, **7.1-7.5:** 23
 - defined, **9.6.8:** 59
- Flexible foundation, defined, **9.6.8:** 59
- Flexible impeller pumps. See Flexible vane pumps
- Flexible member pumps, **3.1-3.5:** 1 f.
- Flexible rotor, defined, **9.6.8:** 59
- Flexible vane pumps, **3.1-3.5:** 1 f., 3 t., 4 t., 5 f., 6 f., 15 f.
 - description, **3.1-3.5:** 8
 - range chart, **3.1-3.5:** 8 f.
- Flexibly coupled horizontal in-line, **1.1-1.2:** 40 f.
- Flooded suction, **6.1-6.5:** 31, **8.1-8.5:** 12
 - defined, **1.1-1.2:** 71, **2.1-2.2:** 35, **10.1-10.5:** 7
- Floor clearance, defined, **9.8:** 50
- Floor cones defined, **9.8:** 50
 - in performance enhancement of trench-type wet wells, **9.8:** 85, 86f.
- Floor vanes, defined, **9.8:** 50
- Flow improvement devices, **9.6.6:** 2, 30 f., 30
- Flow rate (Q), defined, **11.6:** 6
- Flow rate monitoring, **9.6.9:** 13
- Flow rate, **6.1-6.5:** 24, **9.6.6:** 14
- Flow separation
 - in runout condition, **2.3:** 41
- Flow splitters, **9.8:** 86, 86f.
- Flow straightener, defined, **9.8:** 50
- Flowchart describing workflow, **9.6.8:** 3f.
- Flowchart referencing applicable sections of guideline, **9.6.8:** 4f.
- Flowcharts for use of standard hydraulic considerations, **9.6.6:** ix f.
 - mechanical considerations, **9.6.6:** viii f.
- Flowmeter, **6.6:** 18
- Fluid types
 - chemical process, **9.1-9.5:** 5
 - clear water, **9.1-9.5:** 5
 - NACE guidelines, **9.1-9.5:** 5
 - petroleum handling, **9.1-9.5:** 5
- Fluid viscosity, **9.6.6:** 13
- Fluid whirl, defined, **9.6.8:** 59
- Fluids
 - corrosive nature of, **3.1-3.5:** 43
 - defined, **3.1-3.5:** 17
 - dilatant, **3.1-3.5:** 39
 - lubricity of, **3.1-3.5:** 43
 - Newtonian, **3.1-3.5:** 39
 - non-Newtonian, **3.1-3.5:** 39
 - plastic, **3.1-3.5:** 40
 - pseudo-plastic, **3.1-3.5:** 40
 - rheopectic, **3.1-3.5:** 41
 - thixotropic, **3.1-3.5:** 40
 - time-independent non-Newtonian, **3.1-3.5:** 40
 - types, **3.1-3.5:** 35
 - with entrained vapor, **3.1-3.5:** 34
 - with gases or solids, **3.1-3.5:** 35
- Fluids, applicable standards, **9.1-9.5:** 5
- Flux
 - defined, **4.1-4.6:** 7
 - density, defined, **4.1-4.6:** 8
- Foot valves, **9.6.6:** 29, 29 f.
 - defined, **9.8:** 50
 - losses due to viscosity, **2.3:** 50
- Forced response analysis of vertical pump, driver baseplate structural system, **9.6.8:** 57
 - analysis, **9.6.8:** 57
 - interpretation of results, **9.6.8:** 57
 - model, **9.6.8:** 57
 - validation, **9.6.8:** 57
- Forced response analysis OH or BB pump, driver baseplate structural system, **9.6.8:** 56
 - analysis, **9.6.8:** 56
 - interpretation of results, **9.6.8:** 56
 - model, **9.6.8:** 56
 - validation, **9.6.8:** 57
- Forces and moments, **7.1-7.5:** 22
- Forebays defined, **9.8:** 50
 - flow from, **9.8:** 1
- Formed suction intakes (FSI), **9.8:** 8, 10f.
 - alternate designs, **9.8:** 9, 99, 100f., 101f., 102f.
 - defined, **9.8:** 50
 - minimum submergence (calculation), **9.8:** 9
 - recommended dimensions, **9.8:** 9, 10f.
 - shoe-box-type, **9.8:** 99, 101f., 102f.
 - stork-type, **9.8:** 99, 100f.
 - to provide uniform velocity at pump bell throat, **9.8:** 71
- Foundation rigidity
 - horizontal pump structures, **9.6.8:** 14f.
 - vertical pump structures using motor CG location, **9.6.8:** 14f.
 - vertical pump structures using top motor bearing location, **9.6.8:** 15f.
- Foundation, **2.3:** 26, **6.1-6.5:** 68, **7.1-7.5:** 22
 - bolts, 68, 68f.
- Frame assembly. See Power end
- Frame mounted, defined, **12.1-12.6:** 4
- Frame selections
 - open drip-proof, **1.1-1.2:** 84, 88 t.
 - TEFC, **1.1-1.2:** 84
- Francis vane impeller, **2.1-2.2:** 19
- Free surface flow, defined, **9.8:** 50
- Free surface vortices, **9.8:** 1
 - air-entraining, prevention of in sump, **9.8:** 1
 - and approach-flow skewness, **9.8:** 43
 - and pump inlet disturbances, **9.8:** 68, 69f., 71f.
 - and vortex suppression devices (for highly nonuniform approach flows), **9.8:** 43
 - curtain walls in remediation of, **9.8:** 68, 69f., 71f.
 - defining measure of vortex strength, **9.8:** 37f., 43
 - evaluating strength of (physical model studies), **9.8:** 36, 37f.
 - recommended submergence for minimizing (formula), **9.8:** 44
 - required minimum submergence for minimizing, **9.8:**

- 45, 46f., 47f.
required submergence for minimizing, **9.8**: 43
vortex type as function of various dimensionless parameters, **9.8**: 43
Freight, caution regarding, **4.1-4.6**: 22, **5.1-5.6**: 38
Frequencies
filtering out those outside measurement range, **9.6.4**: 2
for electric motors, **2.3**: 91
natural frequency and resonance, **9.6.4**: 17
natural, **2.3**: 26
ranges, **9.6.4**: 2
Frequency of monitoring, **9.6.5**: 3, 3t.
Frequency separation, defined, **9.6.8**: 59
Frequency-responsive devices (in rotary speed measurement), **3.6**: 25
Friction characteristic, **6.1-6.5**: 34
defined, **12.1-12.6**: 39
Friction head, defined, **1.1-1.2**: 70, **2.1-2.2**: 34, **12.1-12.6**: 35
Friction loss pressure, **6.1-6.5**: 28
defined, **10.1-10.5**: 7
Friction, **9.6.6**: 13
Froth factors, **12.1-12.6**: 53
application to pump selection, **12.1-12.6**: 54, 54 f.
defined, **12.1-12.6**: 52
or common processes, **12.1-12.6**: 53, 53 t.
Froth pumping, **12.1-12.6**: 52
Froude number
and alternative configuration for rectangular intakes when liquid source is shallow relative to required pump submergence, **9.8**: 103, 105f., 106f.
and rectangular intakes (clear liquids), **9.8**: 3
and submergence (tanks, pump suction), **9.8**: 16
and submergence (unconfined intakes for clear liquids), **9.8**: 23
and vortex type, **9.8**: 43
defined, **9.8**: 50
in physical model studies (intake structures and pump suction piping), **9.8**: 33, 35
FSI. See Formed suction intakes
Full-flow bypass pressure, defined, **3.1-3.5**: 18
Galling resistance, **9.1-9.5**: 11
Galling, defined, **9.1-9.5**: 11
Galvanic corrosion, **9.1-9.5**: 8
minimization of, **9.1-9.5**: 8
Galvanic series of metals and alloys, **9.1-9.5**: 9 f.
Galvanic series, **9.1-9.5**: 8
Gap, defined, **4.1-4.6**: 8
Gas entrainment, **4.1-4.6**: 15
Gas fraction. See Gas volume fraction
Gas oil ratio (GOR), defined, **3.1-3.5**: 25
Gas vent valves, **7.1-7.5**: 20
Gas volume fraction (GVF), **3.1-3.5**: 51
defined, **3.1-3.5**: 24
Gases
effect of dissolved gas in saturated solution on liquid rate of flow of rotary pumps, **3.1-3.5**: 37 f.
effect of entrained gas on liquid rate of flow of rotary pumps, **3.1-3.5**: 36 f.
entrained or dissolved in liquids, **3.1-3.5**: 35
Gaskets, **5.1-5.6**: 21, **7.1-7.5**: 23, **8.1-8.5**: 17
Gauge head, defined, **1.1-1.2**: 68, **2.1-2.2**: 31, **12.1-12.6**: 33
Gauge pressure, **6.1-6.5**: 28, **8.1-8.5**: 11
defined, **3.1-3.5**: 20, **3.6**: 5, **6.6**: 5, **10.6**: 4
Gauge pressure in terms of head (hg), defined, **11.6**: 7
Gauges, **9.6.9**: 6, 11
Gauss, defined, **4.1-4.6**: 8
Gear pumps, **3.1-3.5**: 1 f., 3 t., 4 t., 15 f.
description, **3.1-3.5**: 9
General industrial pumping applications, **9.6.1**: 12
General principles, **7.1-7.5**: 17
General requirements, **9.6.6**: 4
Gilbert, defined, **4.1-4.6**: 8
Gland follower. See Gland
Gland, defined, **3.1-3.5**: 19
Glossary, **9.8**: 48
GOR. See Gas oil ratio
Grades of accuracy, **14.6**: 10
acceptance tolerances, **14.6**: 10
and corresponding tolerance bands, **14.6**: 13, 13 t.
default test acceptance grades, **14.6**: 17, 17 t.
grade 1 (1B, 1E, 1U), **14.6**: 13, 13 t.
grade 2 (2B, 2U), **14.6**: 13, 13 t.
grade 3 (3B), **14.6**: 13, 13 t.
grades 1, 2, and 3, **14.6**: 1
permissible amplitude of fluctuations per grade, **11.6**: 33 t., **14.6**: 11, 11 t.
pressure tapings for, **14.6**: 27, 28 f.
See also Test tolerances, reasons for
tolerance field for acceptance grade 1E, **14.6**: 14, 16 f.
tolerance field for acceptance grades 1B, 2B, and 3B, **14.6**: 14, 16 t.
tolerance field for acceptance grades 1U and 2U, **14.6**: 16 f.
Graphite, defined, **5.1-5.6**: 15
Gray cast iron, **12.1-12.6**: 64
Guarantee point, **14.6**: 1, 10
and maximum permissible measurement device uncertainty, **11.6**: 34 t., **14.6**: 12, 12 t.
documentation, **14.6**: 10
Guide vanes, defined, **9.8**: 50
Guideline for dynamics of pumping machinery, **9.6.8**: 1
introduction, **9.6.8**: 1
scope, **9.6.8**: 1
Guides, **9.6.6**: 23, 23 f.
GVF. See Gas volume fraction
Gyroscopic effect, defined, **9.6.8**: 59
 h_{acc} . See Acceleration head
Hands and fingers, caution regarding, **5.1-5.6**: 38
Hard irons, **12.1-12.6**: 65, 92
Hazen-Williams equation, **9.6.6**: 14, 15
Head (h)

- and increased viscosity, **9.6.7**: 1
- and preliminary selection of rotodynamic pump, **9.6.7**: 16
- calculating correction factors (example; metric units), **9.6.7**: 11
- calculating correction factors (example; US customary units), **9.6.7**: 13
- calculating correction factors, **9.6.7**: 8, 9f.
- characteristic curves with viscosity correction factors, **9.6.7**: 2, 3f.
- characteristic curves, **9.6.7**: 1
- Head, defined, **1.1-1.2**: 68, **2.1-2.2**: 31, **11.6**: 7, **12.1-12.6**: 33
- Head loss, **9.6.6**: 13
 - and concentric reducers, **9.6.6**: 4
 - and double suction pumps, **9.6.6**: 4
 - and elbows, undesirable effects of, **9.6.6**: 4, 5 f.
 - and flow improvement devices, **9.6.6**: 2, 30, 30 f.
 - and flow-disturbing pipe lengths, **9.6.6**: 4
 - and piping-generated swirl, **9.6.6**: 2
 - calculations, **9.6.6**: 14
 - design, **9.6.6**: 1, 2 f.
 - factors affecting, **9.6.6**: 14
 - function of, **9.6.6**: 1
 - inlet (suction) piping and check valves, **9.6.6**: 29
 - pipe size requirements, **9.6.6**: 2
 - requirements, **9.6.6**: 1
 - straight pipe length requirements, **9.6.6**: 2, 3 t., 4, 4 f.
 - velocity requirements, **9.6.6**: 2
- Head ratio (Hr), defined, **12.1-12.6**: 42
- Head reduction factor (Rh), **12.1-12.6**: 51
 - defined, **12.1-12.6**: 42
- Head shaft coupling, **2.3**: 29 f., 29
- Head. See Head loss; Operating head; Static head; Total head
- Heat, from drive section energy losses, **5.1-5.6**: 19
- Heavy-duty pusher seals, **12.1-12.6**: 77, 79 f., 80 f.
- Helico-axial pumps, **1.3**: 123, 123f.
- Hermetic integrity test, **5.1-5.6**: 47
 - acceptance criteria alternatives, **4.1-4.6**: 26
 - duration, **4.1-4.6**: 26
 - objective, **4.1-4.6**: 25
 - parameters, **4.1-4.6**: 26
 - procedure, **4.1-4.6**: 26
 - test fluid, **4.1-4.6**: 26
 - test pressure, **4.1-4.6**: 26
 - test temperature, **4.1-4.6**: 26
- Heterogeneous mixture, **6.1-6.5**: 34
 - defined, **12.1-12.6**: 39
- Heterogeneous slurries, **12.1-12.6**: 45
- HI 40.6, **40.7**: 2
- HI Board, defined, **40.7**: 1
- HI Graphics Style Guideline, **40.7**: 11
- HI website, **40.7**: 14
 - contents, **40.7**: 14
 - defined, **40.7**: 1
- High temperature, **5.1-5.6**: 30
- High-chromium iron, **12.1-12.6**: 65
- High-speed integral gear-driven pumps, **1.1-1.2**: 2 f., 6
- High-speed integral gear, close coupled, single stage pump, **1.1-1.2**: 24 f.
- High-viscosity liquids, **5.1-5.6**: 30
- HI-NEMA type C face-mounted motors, standard dimensions, **1.1-1.2**: 84
 - for HI-NEMA type HP and HPH vertical solid-shaft motors (US customary units), **1.1-1.2**: 89 t., 90 f.
 - for type JM, alternating current, face-mounting, close-coupled pump motors (US customary units), **1.1-1.2**: 85 t.
 - for type JP, alternating current, face-mounting, close-coupled pump motors (US customary units), **1.1-1.2**: 87 t.
 - for types JM and JP, alternating current, face-mounting, close-coupled pump motors having rolling element contact bearings, **1.1-1.2**: 86 t.
- Hollow-shaft driver, **2.1-2.2**: 11
 - coupling dimensions, **2.1-2.2**: 44 t.
- Hollow-shaft drivers, **2.1-2.2**: 43, **2.3**: 28 f., 28
- Homogeneous flow, **6.1-6.5**: 34
 - defined, **12.1-12.6**: 40
- Homogeneous mixture, **6.1-6.5**: 34
 - defined, **12.1-12.6**: 39
- Homogeneous slurries, **12.1-12.6**: 45
- Horizontal end suction single-stage pumps, **9.6.2**: 1
 - adjustment for alternate pump mounting, **9.6.2**: 7
 - adjustment for grouted nonmetal baseplate with anchor bolts, **9.6.2**: 8
 - adjustment for spring-mounted metal baseplate, **9.6.2**: 8
 - adjustment for stilt-mounted metal baseplate, **9.6.2**: 7, 8f.
 - adjustment for ungrouted metal baseplate that is anchored down, **9.6.2**: 8
 - adjustment for ungrouted nonmetal baseplate that is anchored down, **9.6.2**: 8
 - criteria for loading allowances, **9.6.2**: 3
 - driver/pump coupling alignment, **9.6.2**: 3
 - fully grouted metal baseplate with anchor bolts, **9.6.2**: 3
 - Groups 1, 2, and 3, defined, **9.6.2**: 2
 - internal pump distortion, **9.6.2**: 3
 - maximum nozzle stress, **9.6.2**: 3
 - nomenclature, definitions, and coordinates, **9.6.2**: 1, 2f.
 - nozzle load adjustment factors, **9.6.2**: 7
 - pressure rating corresponding to temperature other than that of contained liquid, **9.6.2**: 3
 - pump hold-down bolts and fasteners, **9.6.2**: 3
 - pump mounting, **9.6.2**: 3
 - See also ANSI/ASME B73.1 pumps; ANSI/ASME B73.3 pumps; ANSI/ASME B73.5M pumps
 - temperature of pressure-containing components, **9.6.2**: 3
- Horizontal pump, **6.1-6.5**: 1f., 1