2021 Uniform Plumbing Code®

AN AMERICAN NATIONAL STANDARD | IAPMO/ANSI UPC 1 – 2021

READ ME

TABLE OF CONTENTS

Documents
Document Sharing Hub
Full document details: IAPMO ANSI UPC 1-2021

2021 UNIFORM PLUMBING CODE®

AN AMERICAN NATIONAL STANDARD
IAPMO/ANSI UPC 1 – 2021

IAPMO Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Copyright © 2020
International Association of Plumbing and Mechanical Officials
All Rights Reserved

No part of this work may be reproduced or recorded in any form or by any means, except as may be expressly permitted in writing by the publisher.

Twenty-Ninth Edition
First Printing, February 2020

Published by the International Association of Plumbing and Mechanical Officials
4755 E. Philadelphia Street • Ontario, CA 91761-2816 – USA
Main Phone: (909) 472-4100 • Main Fax: (909) 472-4150

Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Important Notices and Disclaimers

The 2021 edition of the *Uniform Plumbing Code* is developed through a consensus standards development process approved by the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus on plumbing issues. While the International Association of Plumbing and Mechanical Officials (IAPMO) administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy of any information or the soundness of any judgments contained in its codes and standards.

IAPMO disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document. IAPMO also makes no guarantee or warranty as to the accuracy or completeness of any information published herein.

In issuing and making this document available, IAPMO is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is IAPMO undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

Updating IAPMO Codes

Users of IAPMO codes should be aware that IAPMO codes may be amended from time to time through the issuance of Tentative Interim Amendments or corrected by Errata. IAPMO codes consist of the current edition of the document together with any Tentative Interim Amendment and any Errata in effect.

In order to determine whether an IAPMO code has been amended through the issuance of Tentative Interim Amendments or corrected by Errata, please visit the IAPMO Group codes information pages on IAPMO's website (www.iapmo.org). The codes information pages provide a list of IAPMO codes with up-to-date, specific information including any issued Tentative Interim Amendments and Errata.

To access the codes information pages for a specific code, go to http://codes.iapmo.org to select from the list of IAPMO codes. For Tentative Interim Amendments, go to the standard council decisions. For Errata, select the archived revision information.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

FOREWORD

Origin and Development

The advantages of a statewide adopted *Uniform Plumbing Code* are recognized throughout the industry. Disorder in the industry because of widely divergent plumbing practices and the use of many different, often conflicting, plumbing codes by local jurisdictions influenced the Western Plumbing Officials Association (now the International Association of Plumbing and Mechanical Officials [IAPMO]) to form a committee. This committee of plumbing inspectors, master and journeyman plumbers, and plumbing engineers, backed by public utility companies and the plumbing industry to create a basic plumbing document for general use. The product of this effort, the first edition of the *Uniform Plumbing Code*® (UPC®) was adopted by IAPMO in 1945. The widespread use of this code over the past seven decades by jurisdictions throughout the United States and internationally is testament to its merit.

Publishing of the 2003 *Uniform Plumbing Code* was a significant milestone because it was the first time in the history of the United States a plumbing code was developed through a true consensus process. The 2021 edition represents the most current approaches in the plumbing field and is the seventh edition developed under the ANSI consensus process. Contributions to the content of this code consists of diverse interests as consumers, enforcing authorities, installers/maintainers, labor, manufacturers, research/standards/ testing laboratories, special experts, and users.

The *Uniform Plumbing Code* provides consumers with safe and sanitary plumbing systems while, at the same time, allowing latitude for innovation and new technologies. The public at large is invited and encouraged to take part in IAPMO's open consensus code development process. This code is updated every three years. The *Uniform Plumbing Code* is dedicated to all those who, in working to achieve "the ultimate plumbing code," have unselfishly devoted their time, effort, and personal funds to create and maintain this, the finest plumbing code in existence today.

The *Uniform Plumbing Code* updates every three years in revision cycles that begin twice each year that takes two years to complete.

Each revision cycle advances according to a published schedule that includes final dates for all major events and contains four basic steps as follows:

1. Public and Committee Proposal Stage;
2. Comment Stage;
3. Association Technical Meeting;
4. Council Appeals and Issuance of Code.

IAPMO develops "full consensus" codes built on a foundation of maximum participation and agreement by a broad range of interests. This philosophy has led to producing technically sound codes that promote health and safety, yet do not stifle design or development.

It is important to stress that the process remains committed to the principles of consensus code development where consensus Technical Committees and Correlating Committees revise codes. The public and membership is offered multiple opportunities to debate, provide input and raise concerns through Amending Motions at the annual Assembly Consideration Session. Anyone may submit an appeal related to the issuance of a document through the IAPMO Standards Council.

The 2021 *Uniform Plumbing Code* is supported by the Mechanical Contractors Association of America (MCAA), the Plumbing-Heating-Cooling Contractors National Association (PHCC-NA), the United Association (UA), and the World Plumbing Council (WPC). The presence of these logos, while reflecting support, does not imply any ownership of the copyright to the UPC, which is held exclusively by IAPMO. Further, the logos of these associations indicate the support of IAPMO's open consensus process being used to develop IAPMO's codes and standards.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

The addresses of the organizations are as follows:
ASSE – 18927 Hickory Creek Drive, Suite 220 • Mokena, IL 60448 • (708) 995-3019
MCAA – 1385 Piccard Drive • Rockville, MD 20850 • (301) 869-5800
PHCC-NA – PO Box 6808 • Falls Church, VA 22040-6808 • (800) 533-7694
UA – Three Park Place • Annapolis, MD 21401 • (410) 269-2000
WPC – World Plumbing Council Secretariat, Auf der Mauer 11 • Postfach CH 8021 • Zurich, Switzerland • www.WorldPlumbing.org

Adoption

The *Uniform Plumbing Code* is available for adoption and use by jurisdictions in the United States and Internationally. Its use within a governmental jurisdiction is accomplished through adoption by reference in accordance with applicable jurisdictional laws. At adoption, jurisdictions should insert the applicable information in bracketed words in the sample ordinance. The sample legislation for adoption of the *Uniform Plumbing Code* on page xiii provides key components, regulations and resolutions.

Revision Markings

Solid vertical lines in the margins indicate a technical change from the requirements of the 2018 edition. An arrow (⟵) in the margin indicates where an entire section, paragraph, exception, figure, or table has been deleted, or an item in a list of items or a table has been deleted.

A double right angle (≪) in the margin indicates that the text or a table has been relocated within the code. The table found on page xv points out the relocations in the 2021 edition of the *Uniform Plumbing Code*.

TIA TIA indicates that the revision is the result of a Tentative Interim Amendment.
TIA For further information on tentative interim amendments see Section 5 of the IAPMO
TIA Regulations Governing Committee Projects available at http://codes.iapmo.org/

A reference in brackets [ ] following a section or paragraph indicates material that has been extracted from another document. A reference in brackets { } following a section or paragraph indicates material that has been extracted from another document and has been modified further by the Technical Committee. This reprinted material is not the complete and official position of the source document on the referenced subject that is represented by the standard in its entirety. Material contained in this document that is taken or extracted from NFPA standards is used with permission of the National Fire Protection Association. This material is not the complete and official position of the NFPA on the reference subject, which is represented solely by the relevant standard in its entirety. NFPA standards can be accessed at www.nfpa.org. In addition, this extracted material may include revisions or modifications developed through IAPMO's standards development process. Therefore, NFPA disclaims responsibility for the content of this Code.

Text that is extracted pursuant to IAPMO's Extract Guidelines, but outside of the regular revision process is denoted with the use of the source document in the margin. This text is not fully processed by IAPMO in accordance with ANSI's public announcement consensus requirements for an American National Standard (ANS) nor approved by ANSI's Board of Standards Review. The next revision cycle processes such text in accordance with those requirements.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

FORMAT OF THE UNIFORM PLUMBING CODE

The format of the *Uniform Plumbing Code* (UPC) arranges each chapter in accordance with a specific subject matter. However, Chapter 3 is dedicated to general requirements that are applicable to every chapter. The subject matters are divided as follows:

CHAPTERS	SUBJECTS
1	Administration
2	Definitions
3	General Regulations
4	Plumbing Fixtures and Fixture Fittings
5	Water Heaters
6	Water Supply and Distribution
7	Sanitary Drainage
8	Indirect Wastes
9	Vents
10	Traps and Interceptors
11	Storm Drainage
12	Fuel Gas Piping
13	Health Care Facilities and Medical Gas and Medical Vacuum Systems
14	Firestop Protection
15	Alternate Water Sources for Nonpotable Applications
16	Nonpotable Rainwater Catchment Systems
17	Referenced Standards
Appendix A	Recommended Rules for Sizing the Water Supply System
Appendix B	Explanatory Notes on Combination Waste and Vent Systems
Appendix C	Alternate Plumbing Systems
Appendix D	Sizing Storm Water Drainage Systems
Appendix E	Manufactured/Mobile Home Parks and Recreational Vehicle Parks
Appendix F	Firefighter Breathing Air Replenishment Systems
Appendix G	Sizing of Venting Systems
Appendix H	Private Sewage Disposal Systems
Appendix I	Installation Standards
Appendix J	Combination of Indoor and Outdoor Combustion and Ventilation Opening Design
Appendix K	Potable Rainwater Catchment Systems
Appendix L	Sustainable Practices
Appendix M	Peak Water Demand Calculator
Appendix N	Impact of Water Temperature on the Potential for Scalding and Legionella Growth

Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

The following is a summary of the scope and intent of the provisions addressed within the chapters and appendices of the *Uniform Plumbing Code*:

Chapter 1 Administration.

Chapter 1 regulates the application, enforcement, and administration of subsequent requirements of the code. As well as establishing the scope of the code, this chapter is concerned with enforcing the requirements contained in the body of the code. A plumbing code, as with any other code, is intended to be adopted as a legally enforceable document to safeguard health, safety, property and public welfare. The code cannot be effective without satisfactory provisions for its administration and enforcement. The Authority Having Jurisdiction is to review the proposed and completed work and to decide whether a plumbing system conforms to the code requirements. As a public servant, the Authority Having Jurisdiction enforces the code in an unbiased, proper manner. The design professional is responsible for the design of a safe plumbing system. The contractor is responsible for installing the system in accordance with the plans.

Chapter 2 Definitions.

To maintain consistency and encourage the use of common terminology, Chapter 2 establishes definitions to provide clarity of terms and promote the use of a common language throughout the code. Understanding definitions within the context of their application enables greater collaboration, efficiency, standardization and interpretation in applying and enforcing terms used throughout the code. Codes are technical documents, and every term can impact the meaning of the code text. Terms not defined have a normally accepted meaning.

Chapter 3 General Regulations.

Chapter 3 regulates the general requirements, not specific to other chapters, for installing plumbing systems. Many regulations are not specific plumbing requirements, but relate to the overall plumbing system. This chapter contains safety requirements for installing plumbing and also contains nonplumbing requirements for identifying pipe, pipe fittings, traps, fixtures, materials and devices used in plumbing systems. Listing method of approval, based on applicable nationally recognized standards, for the safe and proper installation of plumbing systems is essential to ensure protection of public health, safety, and welfare. The safety requirements provide protection for piping, material, and structures, with provisions for installation practices, removing stress and strain of the pipe, sleeving, and hanger support. The building's structural stability is protected by the regulations for cutting and notching of structural members.

Chapter 4 Plumbing Fixtures and Fixture Fittings.

This chapter regulates the minimum number of plumbing fixtures of a specific type and quality for each building. The fixtures must be properly installed to be usable by the individuals occupying the building. The quality and design of every fixture must conform to the applicable referenced standard. Compliance with this chapter will result in a building or structure having acceptable plumbing fixtures for the sanitary, hygienic, cleaning, washing and food preparation needs of the occupants.

Chapter 5 Water Heaters.

Chapter 5 regulates the design, approval, installation, and safety devices of fuel burning and other types of water heaters with the combustion air requirements for ventilation and dilution of flue gases for appliances installed in buildings. This chapter does not apply to direct-vent appliances. In addition, this chapter regulates the design, construction, installation, maintenance of chimneys, vents and their connections to fuel burning appliances. Methods to supply combustion air may be supplied from an indoor air supply, outdoor air supply, a combination of indoor and outdoor air supply, mechanical air supply, or an engineered system. Combustion air provisions are based on the number of openings and the total opening size required based on the total energy input rating of the appliance. Acceptable air supply for combustion and ventilation is necessary for proper operation of fuel burning appliances. A shortage of combustion air can result in incomplete combustion and production of poisonous gases, such as carbon monoxide or appliance overheating. Ventilation air provides cooling for the appliance casing and internal controls. Inadequate ventilation of the space in which an appliance is installed can result in increased surrounding temperatures that stress the appliance itself or other appliances in the vicinity.

Chapter 6 Water Supply and Distribution.

Chapter 6 regulates the design, material and installation of water supply and distribution systems, including residential fire sprinklers. The water supply and distribution system is designed to achieve the correct water pressure and flow rates and avoid cross connections. For fixtures to perform properly, an acceptable supply of potable water is essential to their operation

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

and use. Cross connections and backflow are ranked as the highest priority because of the long history of recognized health risks posed by cross connections, outbreaks, or cases of waterborne disease. Piping materials and components are evaluated for their possible effect on the potable water with which they are in contact. The intent is to control the potential adverse health effects produced by indirect additives, products, and materials that come in contact with potable water. When selecting materials for water supply and distribution systems, consider water pressure, water temperature, compatibility with the water supply, durability, support, and sustainability.

In addition, this chapter regulates the design, location, materials, and installation of multipurpose and stand-alone sprinkler systems that do not include the use of antifreeze. Where systems are installed as a portion of the water distribution system under the requirements of this chapter and are not provided with a fire department connection, backflow protection for the water supply system is not required.

Chapter 7 Sanitary Drainage.

This chapter regulates the design and installation of sanitary drainage systems to ensure they will work as intended. Drainage piping should not be oversized nor undersized, and constructed of approved materials to guard against fouling, deposit of solids, clogging, and with cleanouts so arranged that the pipes may be readily cleaned. The purpose of the sanitary drainage system is to remove effluent discharged from plumbing fixtures and other equipment to an approved point of disposal, such as a public sanitary system or private sewage disposal system.

The basics of a sanitary drainage system include public and private sewage disposal; selection of materials; installation of the building drain and sewer; joining methods for pipe and fittings; drainage fixture units for sizing the drainage system; sumps and ejectors; vent sizing and length of vents; and testing.

Chapter 8 Indirect Wastes.

Chapter 8 regulates indirect waste connections that are required for plumbing fixtures and plumbing appliances dealing with food preparation, dishwashing, potable liquids, and similar equipment. An indirect connection prevents sewage from backing up into a fixture or appliance, thus providing protection against potential health hazards. The waste pipe discharges through an air gap or air break into a waste receptor or standpipe. The protection in the form of an air gap is necessary when the contamination is a potential health hazard or cross connection with the potable water system. Where there is no possibility of contaminating the potable water (nonpotable discharge), the indirect waste pipe may connect in the form of an air break. This method is often preferred to prevent splashing. In addition, health care facilities and special wastes must be protected from contamination that may result from the connection to the drainage system. The waste must be treated to prevent any damage to the piping or sewage treatment process. Waste receptors are sized and designed to prevent splashing and allow for peak discharge conditions.

Chapter 9 Vents.

Chapter 9 regulates the material, design, and installation of vents. A vent system is a pipe or pipes installed in a drainage system that provide a flow of air to and from the system to ventilate it, provide a circulation of air to eliminate trap siphonage, and reduce back-pressure and vacuum surge. In addition, vents provide the rapid and silent flow of waste without exposing occupants of the building to any sewer gases. Proper installation of vents is crucial, as a telltale sign that there is a problem in the drain and vent system is related to the elevation of the horizontal portion of the venting. Venting is not limited to sanitary drainage systems. Venting methods are applicable to other drainage systems such as those for chemical waste, graywater waste, and clear water waste. Sizing the venting system is directly tied to the design of the drainage system. For example, the velocities in the drainage system and its peak flow rates affect the diameters in the venting system. Where the vertical distance between a fixture outlet and trap is excessive, velocities in the entire drainage system will be greater than those in the vent sizing table. All venting methods in this chapter are categorized as either dry vents or wet vents. Vent stacks, stack vents, branch vents, island vents, relief vents, and individual vents are dry vents. Wet vents (horizontal or vertical), circuit vents, combination drain and vents are versions of “wet venting” in which the vent is wetted by drainage flow.

Chapter 10 Traps and Interceptors.

Chapter 10 regulates the material, design, and installation of traps, interceptors, and separators. Traps are required on drainage type plumbing fixtures and must be self-scouring without interior partitions. Interceptors, on the other hand, are designed to control what goes down a drain. Interceptors are used to keep harmful substances from entering the sanitary

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

drainage system, such as grease, sand, oil and other materials. The retained materials need periodic removal to maintain efficiency and function of the separating device. The capacity of an interceptor is based on retention and flow rate. There are many types of interceptors that are used at beauty salons, hospitals, meat, fish or foul packaging, refineries, repair garages, gas stations, car washing facilities, various plants, factories, and processing sites. The designer of the building is responsible for locating interceptors with the expectation for the frequency of maintenance, ease of cleaning and floor space for equipment.

Chapter 11 Storm Drainage.

Chapter 11 regulates the removal of stormwater from roofs, yards, paved areas, and similar areas. The objective of storm drainage systems is to provide a conduit or channel through which runoff will be carried from a point of collection to a point of disposal; this protects the property and the public from the uncontrolled flow of runoff and ensures that drains and inlets are adequately sized to receive the volume of runoff that flows to the drains. For the purpose of system design, it's necessary to specify the duration of a selected storm. All methods used to determine volumes and peak flow use historical data. Drain location must be coordinated with the architectural design of the building. When selecting the type of roof drain to use, the roof construction and its thickness, along with the intended use of the roof, are required. Where the roof perimeter extends above the roof in such a manner that water is entrapped and causes ponding, or if any portion of the roof is designed so water can pond, secondary drainage is required. Where secondary drainage is required, scuppers, or a secondary system of roof drains and pipes, are installed to prevent the accumulation of excessive rainwater.

Chapter 12 Fuel Gas Piping.

Chapter 12 regulates the installation of gas piping in a building, structure or within the property lines of buildings up to 5 psi. Gas piping systems must supply the minimum volume of gas required by each gas appliance to perform their proper operation under working conditions without exceeding the maximum pressure specified by each manufacturer. Because of the hazards associated with fuel gas, it is important to ensure the gas system has been inspected and tested, and that it is safe to turn on the gas supply to the building.

Chapter 13 Health Care Facilities and Medical Gas and Medical Vacuum Systems.

Chapter 13 regulates the installation, inspection, testing, maintenance, performance, and safe practices for medical gas and vacuum systems located in health care facilities. This chapter addresses the installation and maintenance of health care fixtures, devices, and equipment. The purpose of medical gas and medical vacuum systems is to provide safe and sufficient flows at required pressures to the medical gas outlet or vacuum inlet terminals. System design and layout should allow convenient access by the medical staff to outlet and inlet terminals, valves, and equipment during patient care or emergencies, as safety is of primary concern.

Chapter 14 Firestop Protection.

Chapter 14 regulates piping penetrations of fire-resistance-rated walls, partitions, floors, floor and ceiling assemblies, roof and ceiling assemblies, or shaft enclosures through firestopping. To firestop is to create a physical barrier that impedes the spread of smoke, gases, and flames from one compartment in the building design to the next. The firestop is seen as a part that is essential to protecting the lives of people who live or work in the structure, increasing the chances of not succumbing to smoke or gases before they are able to evacuate the building. Fireproofing of this type helps to restore the fire-resistant properties of the building materials before the openings were created as part of the construction process.

Chapter 15 Alternate Water Sources for Nonpotable Applications.

Chapter 15 regulates gray water sources, reclaimed (recycled) water sources and on-site treated nonpotable water systems. Water sources include subsurface irrigation, subsoil irrigation, and mulch basin systems. Subsoil water irrigation provides a means to disperse shallow drip irrigation lines and mulch basins that collect and spread water in various applications. The reclaimed water provisions to on-site nonpotable water systems include gray water and other nonpotable water sources that are used for on-site applications. Water reuse is integral to sustainable water management because it allows water to remain in the environment and be preserved for future use while meeting the water requirements of the present. Water reuse reduces energy use by removing added potable water treatment, offsetting water demands, and providing water for energy production.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Chapter 16 Nonpotable Rainwater Catchment Systems.

Chapter 16 regulates nonpotable rainwater catchment systems that include irrigation; toilet and urinal flushing with proper treatment; provisions where permits are required; maintenance of alternate water sources; and minimum water quality. This chapter provides guidance on how to optimize rainwater use while ensuring there is a decrease of risk to consumers from poor design, installation, and maintenance. Rainwater harvesting is the process of capturing, channeling, and storing water runoff for later use. Most systems are constructed of three principal components: the catchment area, the collection device, and the conveyance system.

Chapter 17 Referenced Standards.

Chapter 17 provides two comprehensive tables with referenced standards. The standards listed in Table 1701.1 are applied as indicated in the applicable reference section(s). A list of additional approved standards, publications, practices, and guides that are not referenced in specific sections appear in Table 1701.2.

Referenced standards set forth specific details of accepted practices, materials specifications, or test methods in many specialized applications. Standards provide an efficient method of conveying complex information and specifications on the performance requirements for materials, products, systems, application, and installation. The manner and purpose for a standard's use and, in turn, code compliance, must be definitive in all references to the standard. If the standard is intended to be a requirement for judging code compliance, the code must state its intent for use. The standard should adequately address a defined need and at the same time specify the minimum performance requirements, technical characteristics and methods of testing, and required test results.

The referenced standards tables are organized in a manner that makes it easy to find specific standards in alphabetical order, and by acronym of the publishing agency of the standard. The tables list the title of the standard, the edition, and any addenda. Contact information for each publishing agency is provided at the end of the chapter.

Appendix A Recommended Rules for Sizing the Water Supply System.

Appendix A provides a method of sizing the water supply and distribution system that provides precise calculations to establish the proper pressures and flow to the system's fixtures. The goal of sizing the system is to deliver an acceptable volume of water to the most hydraulically remote fixture during minimum pressure and maximum flow conditions; provide satisfactory water pressure to the most hydraulically remote fixture during minimum pressure and maximum flow conditions; and to prevent excessive water velocity during maximum flow conditions.

Appendix B Explanatory Notes on Combination Waste and Vent Systems.

Appendix B contains general guidelines for the design and installation of combination waste and vent systems. These systems are designed for waste piping and are purposely oversized to serve as both a waste and vent pipe to avoid excessive pneumatic effects at fixture drains.

Appendix C Alternate Plumbing Systems.

The intent of this appendix is to provide clarification of procedures for the design and approval of engineered plumbing systems, alternate materials, and equipment that are not specifically covered in other parts of the code. Alternative methods are allowed to be used where approved by the authority having jurisdiction. Approval of alternatives is based on a demonstration showing that the method or material used is at least equivalent in strength, deflection, and capacity to that provided by the prescriptive methods and materials.

Appendix D Sizing Storm Water Drainage Systems.

Appendix D provides general guidelines for the sizing of stormwater drainage systems. There are two pieces of information that must always be a given. They are the roof size and the rate of rainfall for the area.

Appendix E Manufactured/Mobile Home Parks and Recreational Vehicle Parks.

The provisions of this appendix apply to the plumbing and drainage systems of mobile home and recreational vehicle parks. These provisions also apply to the use, maintenance, and installation for supplying fuel gas, water, electricity, and disposal of sewage from accessory buildings or structures, and building components.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Appendix F Firefighter Breathing Air Replenishment Systems.

Appendix F provides guidance on installing firefighter breathing air replenishment systems. System components include outside fire department connection panel, interior air fill panel or station, interconnected piping distribution system and pressure monitoring switch. Fire departments access the system through an outside connection panel and are able to pump air into the system. The firefighters inside the structure access the system at fill stations that are found throughout the building. The piping distribution system is made from stainless tubing or other approved materials. It delivers compressed air to the building interior air fill stations and interior air fill panels. The tubing also acts as a conduit in the interior of the building between the outside connection panel and the air storage system. If the system becomes over-pressurized, the air monitoring system also acts as a pressure relief. A system isolation valve is placed alongside each interior air fill station and interior air fill panel to isolate the system.

Appendix G Sizing of Venting Systems.

Appendix G provides added information on the sizing of gas vents. This appendix is useful to the end user for the proper sizing of venting systems. A series of examples are given that show how to use the tables and other requirements of Chapter 5.

Appendix H Private Sewage Disposal Systems.

Appendix H provides general guidelines for the materials, design, and installation of new or existing private sewage disposal systems. Where a building cannot be served by a public sewer system, the building site must be provided with a system for treating the waste water generated from the use of plumbing fixtures in the building. The appendix addresses site evaluations, materials, soil absorption systems, holding tanks, cesspools and on-site waste-water treatment systems. Private sewage disposal systems must be designed based on the soil conditions, constructed using approved materials, and installed according to prescribed dimensions.

Appendix I Installation Standards.

Installation Standards (IS) are industry standards that specify procedures for installation of plumbing and mechanical products, and the inspection methods and procedures employed for the examination of such systems. These comprehensive standards add detailed information and guidance where a manufacturer or product installation instructions may not fully address. They give the user confidence with options from industry experts for installing plumbing products and assemblies in a safe and professional manner.

Appendix J Combination of Indoor and Outdoor Combustion and Ventilation Opening Design.

Appendix J provides an example of how to determine the required combination of indoor and outdoor combustion air opening sizes for appliances. The combustion air example also provides a table that contains the required volume of a space per the appliance Btu/h input that is based on the standard method.

Appendix K Potable Rainwater Catchment Systems.

Potable rainwater catchment system is defined as a system that uses the principal of collecting and using rain from a rooftop or other man-made, aboveground collection surface. This appendix applies to new rainwater catchment installations, as well as changes, additions, maintenance, and repairs to existing installations. Rainwater harvesting is the practice of collecting the water produced during rainfall events before it has a chance to run off into a river or stream or soak into the ground and become groundwater.

Appendix L Sustainable Practices.

This appendix provides a comprehensive set of technically sound provisions that encourage sustainable practices and works toward improving the design and construction of plumbing systems that result in a positive long-term environmental impact. Environmental sustainability is important because it involves natural resources that human beings need for economic or manufactured capital. Their sustainability is defined by their reliance on infinitely available resources that are naturally occurring, constant, and free to access.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Appendix M Peak Water Demand Calculator.

This appendix provides a method for estimating the demand load for the building water supply and principal branches for single- and multi-family dwellings with water-conserving plumbing fixtures, fixture fittings, and appliances.

Appendix N Impact Of Water Temperature On The Potential For Scalding And Legionella Growth

Legionnaires' disease is a serious issue that is a threat to many citizens. It is known that the higher the temperature, the lower the risk for Legionella growth, but the higher the temperature, the higher the possibility for scalding. This appendix addresses Legionella growth potential and scald potential within specified temperature ranges. It contains definitions for terms used to describe water temperatures such as cold, tepid, warm, tempered hot, and disinfecting hot. Since plumbing systems operate within various temperature ranges, the public has a document that identifies such temperature ranges and the "potential" dangers within these temperature ranges.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

SAMPLE LEGISLATION FOR ADOPTION OF THE UNIFORM PLUMBING CODE

The Uniform Codes are designed to be adopted by jurisdictions through an ordinance. Jurisdictions wishing to adopt the 2021 *Uniform Plumbing Code* as an enforceable regulation governing plumbing systems by reference should ensure the legal basis under which adoption and implementation are included in the ordinance.

The following sample ordinance is a guide for drafting an ordinance for adoption that addresses key components regulations and resolutions.

ORDINANCE NO.

An ordinance of the [JURISDICTION] adopting the 2021 edition of the *Uniform Plumbing Code*, regulating and controlling the design, construction, quality of materials, erection, installation, alteration, repair, location, relocation, replacement, addition to, use or maintenance of plumbing systems in the [JURISDICTION]; providing for the issuance of permits and collection of fees therefor; repealing Ordinance No. of the [JURISDICTION] and all other ordinances and parts of the ordinances in conflict therewith.

The [GOVERNING BODY] of the [JURISDICTION] does ordain as follows:

Section 1 Codes Adopted by Reference. That certain documents, three (3) copies of which are on file in the office of the [JURISDICTION'S KEEPER OF RECORDS] and the [JURISDICTION], being marked and designated as the 2021 *Uniform Plumbing Code*, including Appendix Chapters [FILL IN THE APPENDIX CHAPTERS BEING ADOPTED], as published by the International Association of Plumbing and Mechanical Officials, be and is hereby adopted as the Code of the [JURISDICTION], in the State of [STATE NAME] regulating and controlling the design, construction, quality of materials, erection, installation, alteration, repair, location, relocation, replacement, addition to, use or maintenance of plumbing systems as herein provided; providing for the issuance of permits and collection of fees therefor; and each and all of the regulations, provisions, penalties, conditions and terms of such 2021 *Uniform Plumbing Code* on file in the office of the [JURISDICTION] are hereby referred to, adopted, and made a part hereof, as if fully set out in this ordinance.

Section 2 Modifications. The following sections are hereby revised:
Section 101.1. Insert: [NAME OF JURISDICTION]
Section 104.5. Insert: [APPROPRIATE FEE SCHEDULE]

Section 3 Conflicting Ordinances Repealed. That Ordinance No. of [JURISDICTION] entitled
[TITLE OF THE ORDINANCE OR ORDINANCES IN EFFECT AT THE PRESENT TIME SO THAT THEY WILL BE REPEALED BY MENTION] and all other ordinances or parts of ordinances in conflict herewith are hereby repealed.

Section 4 Preemption. [JURISDICTION] hereby fully occupies and preempts the entire field of regulation of design, construction, quality of materials, erection, installation, alteration, repair, location, relocation, replacement, addition to, use or maintenance of plumbing systems; and provision for the issuance of permits and collection of fees therefor; within the boundaries of [JURISDICTION]. [AS APPROPRIATE] Cities, towns, and counties or other municipalities may enact only those laws and ordinances relating to this field as specifically authorized by state law and consistent with this ordinance. Local laws and ordinances that are inconsistent with, more restrictive than, or exceed the requirements of [ORDINANCE NO.] shall not be enacted and are hereby expressly preempted and repealed, regardless of the nature of the code, charter, or home rule status of such city, town, county, or municipality.

Section 5 Severability. That if any section, subsection, sentence, clause or phrase of this ordinance is, for any reason, held to be unconstitutional, such decision shall not affect the validity of the remaining portions of this ordinance. The [GOVERNING BODY] hereby declares that it would have passed this ordinance, and each section, subsection, clause or phrase thereof, irrespective of the fact that any one or more sections, subsections, sentences, clauses and phrases be declared unconstitutional.

Section 6 Legal Notice. That the [JURISDICTION'S KEEPER OF RECORDS] is hereby ordered and directed to cause this ordinance to be published. (An additional provision may be required to direct the number of times the ordinance is to be published and to specify that it is to be in a newspaper in general circulation. Posting may also be required.)

Section 7 Violations and Penalties. [INCORPORATE PENALTIES FOR VIOLATIONS]

Section 8 Effective Date. That this ordinance and the rules, regulations, provisions, requirements, orders and matters established and adopted hereby shall take effect and be in full force and effect [TIME PERIOD] from and after the date of its final passage and adoption.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

COMMITTEE ON UNIFORM PLUMBING CODE

These lists represent the membership at the time the Committee was balloted on the final text of this edition. Since that time, changes in the membership may have occurred.

IAPMO Standards Council
Bill Erickson, Chairman
CJ Erickson Plumbing Company [U]

JT Baca, State of New Mexico [E]
Carl Crimmins, MN State Pipe Trades, Retired [SE]
James Majerowicz, Plumbers JAC LU 130 [L]
Rich Prospal, Prospal Consulting Services [C]
Linden Raimer, Raimer Consulting Services, LLC [U]
Ron Rice, City of St. Paul, Retired [C]
Robert "Bud" Riestenberg, Piping Systems, Inc. [U]

Nonvoting

Gabriella M. Davis, Secretary
International Association of Plumbing and Mechanical Officials
Hugo Aguilar, Recording Secretary
International Association of Plumbing and Mechanical Officials

IAPMO Uniform Plumbing Code Technical Committee
Dan Daniels, *Chairman*
Self [C]

Bob Adler, City of San Jose [E]
Sarah Aguilar McCabe Plumbing [I/M]
Julius Ballanco JB Engineering & Code Consulting [SE]
Domenico Barbato, City of Los Angeles Department of Building & Safety [E]
DJ Berger National ITC Corporation [U]
Raymond Boyd, United Association [L]
Jeremy Brown, NSF International [R/S/T]
Richard Church, Plastic Pipe & Fittings Association (PPFA) [M]
Pennie Feehan Copper Development Association (CDA) [M]
Dave Mann, CA State Pipe Trades [L]
Rick Moreno Astro Mechanical/CPMCA [I/M]
John Nielsen State of Idaho – Division of Building Safety [E]
Phil Ribbs PHR Consultants [SE]
Arnold Rodio Pace Setter Plumbing [I/M]
Robert Sewell UA Local 159 [L]
Matt Sigler Plumbing Manufacturers International (PMI) [M]
Billy Smith ASPE [SE]
Larry Soskin ACE Duraflo [M]
Jim Stack, Plumbing Heating Cooling Contractors (PHCC) [I/M]
Don Taylor Dittmann Plumbing [U]

Alternates

Gary Bonetti Jr, Local 342 [L]
Terry Burger, NSF International [R/S/T]
Michael Cudahy, Plastic Pipe & Fittings Association (PPFA) [M]
Shawn Hargis, City of Los Angeles Department of Building & Safety [E]
David Ledda, City/County of San Francisco [E]
James Pavesic, United Association [L]
Chuck White, Plumbing Heating Cooling Contractors (PHCC) [I/M]

Nonvoting

Heath Dehn, National Fire Protection Association (NFPA) [R/S/T]
Enrique Gonzalez, IAPMO Staff Liaison
Doug Marian, ASSE [R/S/T]
Laura Moreno, National Fire Protection Association (NFPA) [R/S/T]
David Straub, **Ex-Officio** IAPMO [E]

COMMITTEE MEMBERSHIP CLASSIFICATION ABBREVIATIONS

These classifications apply to Technical Committee members and represent their principal interest in the activity of a committee.

M *Manufacturer:* A representative of a maker or marketer of a product, assembly or system, or portion thereof, that is affected by the standard.
U *User:* A representative of an entity that is subject to the provisions of the standard or that voluntarily uses the standard.
I/M *Installer/Maintainer:* A representative of an entity that is in the business of installing or maintaining a product, assembly or system affected by the standard.
L *Labor:* A labor representative or employee concerned with safety in the workplace.
R/S/T *Research/Standards/Testing Laboratory:* A representative of an independent research organization; an organization that develops codes, standards or other similar documents; or an independent testing laboratory.
E *Enforcing Authority:* A representative or an agency or an organization that promulgates and/or enforces standards.
C *Consumer:* A person who is, or represents, the ultimate purchaser of a product, system, or service affected by the standard, but who is not included in the *User* classification.
SE *Special Expert:* A person not representing any of the previous classifications, but who has special expertise in the scope of the standard or portion thereof.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

2021 Location	2018 Location
209.0 General Anesthesia and Levels of Sedation/Analgesia	214.0 Levels of Sedation
209.0 Deep Sedation/Analgesia	214.0 Deep Sedation/Analgesia
209.0 General Anesthesia	214.0 General Anesthesia
209.0 Minimal Sedation (Anxiolysis)	214.0 Minimal Sedation (Anxiolysis)
209.0 Moderate Sedation/ Analgesia (Conscious Sedation)	214.0 Moderate Sedation/ Analgesia (Conscious Sedation)
210.0 Health Care Facility's Governing Body	209.0 Governing Body
216.0 Nonwater Urinal with Drain Cleansing Action	223.0 Urinal, Hybrid
509.3.4	509.3.4.1
509.6.1(2) – 509.6.1(7)	509.6.1.1 – 509.6.1.6
509.6.1.1	509.6.1.7
509.7.4(1) – 509.7.4(3)	509.7.4.1 – 509.7.4.3
609.9 – 609.12.2	609.8 – 609.11.2
Table 702.1(1)	Table 702.2(1)
Table 702.2	Table 702.2(2)
911.3	911.4
911.3.1	911.4.1
911.3.2	911.4.2
1208.6.4.2 – 1208.6.4.5	1208.6.4.1 – 1208.6.4.4
1208.6.7.1 – 1208.6.7.3	1208.6.7(1) – 1208.6.7(3)
1208.6.9 – 1208.6.10	1208.6.10 – 1208.6.11
Table 1208.6.9.2	Table 1208.6.10.2
1208.6.10.1	1208.6.11.2
1208.6.10.4 – 1208.6.13.5	1208.6.11.3 – 1208.6.14.5
1208.8.6, 1208.8.7	1208.8.7, 1208.8.8
1208.10.6	1208.8.6
1208.11 – 1208.15.1	1208.10 – 1208.14.1
1210.3	1210.2
1210.3.1	1208.6.9
1210.3.2 – 1210.8.2	1210.2.1 – 1210.7.2
Table 1210.3.5.1	Table 1210.2.4.1
1211.4 – 1211.7.1	1211.3 – 1211.6.1
1301.4, 1301.5	1301.5, 1301.6
1302.1.2, 1302.1.3	1302.1.1, 1302.1.2
1304.2 – 1304.5	1304.5 – 1304.6.3
1306.0 – 1306.3	1319.0 – 1319.3
1306.4	1317.4

2021 Location	2018 Location
1307.0	1312.0
1307.1	1301.4
1307.3, 1307.4	1312.1, 1312.2
1308.0 – 1308.2	1315.0 – 1315.2
1308.3	1312.3
1310.0, 1310.1	1313.0, 1313.1
1310.3 – 1310.3.2	1313.2 – 1313.2.2
1310.4	1313.7
1310.5	1313.7.2
1311.1, 1311.2	1313.5, 1313.5.1
1311.3 – 1311.6	1313.6 – 1313.6.3
1312.0 – 1312.2	1314.0 – 1314.2
1312.3	1314.4
1313.1 – 1313.5	1314.5 – 1314.5.4
1314.0	1311.0
1314.2	1311.1.1
1314.3	1311.1.3
1314.4	1311.1.2
1314.5	1311.1
1314.6 – 1314.10	1311.2 – 1311.6
1314.10.3	1311.6.3
1314.11	1311.7
1314.12, 1314.12.1	1311.9, 1311.9.1
1315.0 – 1315.3	1316.0 – 1316.2.1
1315.15	1316.3
1316.1, 1316.2	1315.2.2, 1315.3
1317.1.2	1317.1.1
1318.0 – 1318.4	1308.0 – 1308.4
1318.6	1310.1
1319.1	1308.5
1320.0 – 1320.2.1	1309.0 – 1309.3
1321.1 – 1321.5	1309.4 – 1309.4.4
1321.7 – 1321.12.4	1309.5 – 1309.10.4
1322.1	1309.16
1322.1.1	1309.16.2
1322.1.3	1309.16.3
1322.1.5, 1322.2	1309.16.4, 1309.17
1322.2.1	1309.16.1

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

SECTION RELOCATION

2021 Location	2018 Location
1322.3 – 1322.5	1309.11 – 1309.13
1322.6	1309.15
1322.6.1	1309.14
1322.7	1309.18
1323.0	1310.0
1323.1 – 1323.1.6	1310.2 – 1310.2.6
Table 1323.1.4(1)	Table 1310.2.1(2)
Table 1323.1.4(2)	Table 1310.2.1(3)
Table 1323.1.4(3)	Table 1310.2.1(4)
Table 1323.1.4(4)	Table 1310.2.1(5)
Table 1323.1.4(5)	Table 1310.2.1(6)
Table 1323.1.4(6)	Table 1310.2.1(7)
Table 1323.1.5(1)	Table 1310.2.1(1)
Table 1323.1.5(2)	Table 1310.2.2(1)
1323.2 – 1323.2.2	1310.3 – 1310.3.2
1323.3, 1323.3.1	1310.4, 1310.4.1
1323.3.2	1310.4.3
1323.3.3	1310.4.2
1323.4 – 1323.4.5	1310.5 – 1310.5.5
Table 1323.4.4	Table 1310.5.4(1)
1323.5	1310.3.3
1323.5.1 – 1323.7.2	1310.6 – 1310.8.2
1323.8	1304.2
1323.9, 1323.9.1	1310.9, 1310.9.1
1323.10 – 1323.10.3	1306.1 – 1306.3
1323.11 – 1323.11.6	1307.1 – 1307.7
1323.12 – 1323.13.2	1310.10 – 1310.11.2
1323.14 – 1323.14.6	1311.10 – 1311.10.6
1323.15	1316.4
1324.0 – 1324.2.1	1318.0 – 1318.3
1324.3	1318.4.1
1324.4	1318.4
1324.5 – 1324.5.1.2	1318.5 – 1318.5.3
1324.5.2 – 1324.5.2.6	1318.8 – 1318.8.6
1324.5.3 – 1324.5.3.2	1318.12 – 1318.12.2
1324.5.4 – 1324.5.5.5	1318.9 – 1318.10.5
1324.5.5.6	1318.10.7
1324.5.5.7	1318.10.6

2021 Location	2018 Location
1324.5.7 – 1324.5.7.2	1318.16 – 1318.16.2
1324.5.8	1309.8.9(4)
1324.5.9 – 1324.5.9.2	1309.8.9(1) – 1309.8.9(3)
1324.5.9.3, 1324.5.9.4	1309.8.9(5), 1309.8.9(6)
1324.5.10.1 – 1324.5.11	1318.14.3 – 1318.15
Table 1324.5.11	Table 1318.15
1325.1	1304.3
1325.4	1313.3
1325.6	1314.2.1
1325.10	1317.2
1326.1	1304.4
1327.2	1311.8
1327.3	1317.3
Table 1327.6	Table 1310.5.4(2)
1327.7 – 1327.7.6	1318.11 – 1318.11(6)
1327.8 – 1327.8.2	1318.14 – 1318.14.2
1602.9	1602.9.2
1603.0 – 1603.2	1602.9, 1602.9.1
Figure 1603.2	Figure 1602.9.1
1603.3	1603.2
1603.4 – 1603.5	1602.9.3 – 1602.9.6
Table 1603.5	Table 1602.9.6
1603.6	1603.0, 1603.1
1603.7 – 1603.20	1603.3 – 1603.16
Table K 104.3.1	Table K 104.3(1)
Table K 104.3.3	Table K 104.3(2)
K 104.4	K 106.0, K 106.1
K 104.4.1, K 104.4.2	K 104.4, K104.5
K 104.4.3	K 106.2
K 104.5	K 104.6
K 106.0, K 106.1	K 106.3
K 106.2 – K 106.5	K 106.4 – K 106.7
L 402.8 – L 402.10	L 402.7 – L 402.9
L 404.8 – L404.11	L 404.7 – L 404.10
L 411.14	L 411.12

Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

TABLE OF CONTENTS

CHAPTER 1 ADMINISTRATION 1
101.0 General 1
101.1 Title 1
101.2 Scope 1
101.3 Purpose 1
101.4 Unconstitutional 1
101.5 Validity 1
102.0 Applicability 1
102.1 Conflicts Between Codes 1
102.2 Existing Installations 1
102.3 Maintenance 1
102.4 Additions, Alterations, Renovations, or Repairs 1
102.5 Health and Safety 1
102.6 Changes in Building Occupancy . . . 1
102.7 Moved Structures 1
102.8 Appendices 1
103.0 Duties and Powers of the Authority Having Jurisdiction 2
103.1 General 2
103.2 Liability 2
103.3 Applications and Permits 2
103.4 Right of Entry 2
104.0 Permits 2
104.1 Permits Required 2
104.2 Exempt Work 2
104.3 Application for Permit 2
104.4 Permit Issuance 3
104.5 Fees 4
105.0 Inspections and Testing 4
105.1 General 4
105.2 Required Inspections 4
105.3 Testing of Systems 5
105.4 Connection to Service Utilities 5
106.0 Violations and Penalties 5
106.1 General 5
106.2 Notices of Correction or Violation 5
106.3 Penalties 5
106.4 Stop Orders 6
106.5 Authority to Disconnect Utilities in Emergencies 6
106.6 Authority to Condemn 6
107.0 Board of Appeals 6
107.1 General 6
107.2 Limitations of Authority 6
Table 104.5 Plumbing Permit Fees 7

CHAPTER 2 DEFINITIONS 9
201.0 General 9
201.1 Applicability 9
202.0 Definition of Terms 9
202.1 General 9

CHAPTER 3 GENERAL REGULATIONS 21
301.0 General 21
301.1 Applicability 21
301.2 Minimum Standards 21
301.3 Alternate Materials and Methods of Construction Equivalency 21
301.4 Flood Hazard Areas 21
301.5 Alternative Engineered Design 22
302.0 Iron Pipe Size (IPS) Pipe 22
302.1 General 22
303.0 Disposal of Liquid Waste 22
303.1 General 22
304.0 Connections to Plumbing System Required 22
304.1 General 22
305.0 Damage to Drainage System or Public Sewer 22
305.1 Unlawful Practices 22
306.0 Industrial Wastes 22
306.1 Detrimental Wastes 22
306.2 Safe Discharge 22
307.0 Location 22
307.1 System 22
307.2 Ownership 23
308.0 Improper Location 23
308.1 General 23
309.0 Workmanship 23
309.1 Engineering Practices 23
309.2 Concealing Imperfections 23
309.3 Burred Ends 23
309.4 Installation Practices 23
309.5 Sound Transmission 23
309.6 Dead Legs 23
310.0 Prohibited Fittings and Practices 23
310.1 Fittings 23

Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

310.2 Drainage and Vent Piping 23
310.3 Waste Connection 23
310.4 Use of Vent and Waste Pipes 23
310.5 Obstruction of Flow 23
310.6 Dissimilar Metals 23
310.7 Direction of Flow 23
310.8 Screwed Fittings 23
311.0 Independent Systems 23
311.1 General 23
312.0 Protection of Piping, Materials, and Structures 23
312.1 General 23
312.2 Installation 23
312.3 Building Sewer and Drainage Piping 24
312.4 Corrosion, Erosion, and Mechanical Damage 24
312.5 Protectively Coated Pipe 24
312.6 Freezing Protection 24
312.7 Fire-Resistant Construction 24
312.8 Waterproofing of Openings 24
312.9 Steel Nail Plates 24
312.10 Sleeves 24
312.11 Structural Members 24
312.12 Rodentproofing 24
313.0 Hangers and Supports 24
313.1 General 24
313.2 Material 24
313.3 Suspended Piping 24
313.4 Alignment 24
313.5 Underground Installation 24
313.6 Hanger Rod Sizes 24
Table 313.6 Hanger Rod Sizes 24
313.7 Gas Piping 24
314.0 Trenching, Excavation, and Backfill 24
314.1 Trenches 24
314.2 Tunneling and Driving 25
314.3 Open Trenches 25
314.4 Excavations 25
315.0 Joints and Connections 25
315.1 Unions 25
315.2 Prohibited Joints and Connections 25
316.0 Increasers and Reducers 25
316.1 General 25
317.0 Food-Handling Establishments 25
317.1 General 25
318.0 Test Gauges 25
318.1 General 25
318.2 Pressure Tests (10 psi or less) . . .25
318.3 Pressure Tests (greater than 10 psi to 100 psi) 25
318.4 Pressure Tests (exceeding 100 psi) 25
318.5 Pressure Range 26
319.0 Medical Gas and Vacuum Systems 26
319.1 General 26
320.0 Rehabilitation of Piping Systems . .26
320.1 General 26
Table 313.3 Hangers and Supports 26

CHAPTER 4 PLUMBING FIXTURES AND FIXTURE FITTINGS 27

401.0 General 27
401.1 Applicability 27
401.2 Quality of Fixtures 27
402.0 Installation 27
402.1 Cleaning 27
402.2 Joints 27
402.3 Securing Fixtures 27
402.4 Wall-Hung Fixtures 27
402.5 Setting 27
402.6 Flanged Fixture Connections 27
402.7 Supply Fittings 27
402.8 Installation 27
402.9 Design and Installation of Plumbing Fixtures 28
402.10 Slip Joint Connections 28
402.11 Future Fixtures 28
403.0 Accessible Plumbing Facilities 28
403.1 General 28
403.2 Fixtures and Fixture Fittings for Persons with Disabilities 28
403.3 Exposed Pipes and Surfaces 28
404.0 Waste Fittings and Overflows 28
404.1 Waste Fittings 28
404.2 Overflows 28
405.0 Prohibited Fixtures 28
405.1 Prohibited Water Closets 28
405.2 Prohibited Urinals 28
405.3 Miscellaneous Fixtures 28
406.0 Special Fixtures and Specialties . . .28
406.1 Water and Waste Connections 28
406.2 Special Use Sinks 28
406.3 Special Use Fixtures 28
406.4 Zinc Alloy Components 28

Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

407.0 Lavatories 28
407.1 Application 28
407.2 Water Consumption 28
407.3 Limitation of Hot Water Temperature for Public Lavatories 29
407.4 Transient Public Lavatories 29
407.5 Waste Outlet 29
407.6 Overflow 29
408.0 Showers 29
408.1 Application 29
408.2 Water Consumption 29
408.3 Individual Shower and Tub-Shower Combination Control Valves 29
408.4 Waste Outlet 29
408.5 Finished Curb or Threshold 29
408.6 Shower Compartments 29
408.7 Lining for Showers and Receptors 30
408.8 Public Shower Floors 30
408.9 Location of Valves and Heads 30
408.10 Water Supply Riser 30
409.0 Bathtubs and Whirlpool Bathtubs 30
409.1 Application 30
409.2 Waste Outlet 31
409.3 Overflow 31
409.4 Limitation of Hot Water Temperature in Bathtubs and Whirlpool Bathtubs 31
409.5 Backflow Protection 31
409.6 Installation and Access 31
410.0 Bidets 31
410.1 Application 31
410.2 Backflow Protection 31
410.3 Limitation of Water Temperature in Bidets 31
411.0 Water Closets 31
411.1 Application 31
411.2 Water Consumption 31
411.3 Water Closet Seats 31
411.4 Personal Hygiene Devices 31
412.0 Urinals 31
412.1 Application 31
412.2 Backflow Protection 32
413.0 Flushing Devices 32
413.1 Where Required 32
413.2 Flushometer Valves 32
413.3 Flush Tanks 32
413.4 Water Supply for Flush Tanks 32
413.5 Overflows in Flush Tanks 32
414.0 Dishwashing Machines 32
414.1 Application 32
414.2 Backflow Protection 32
414.3 Drainage Connection 32
415.0 Drinking Fountains 32
415.1 Application 32
415.2 Drinking Fountain Alternatives 32
415.3 Drainage Connection 32
415.4 Location 32
416.0 Emergency Eyewash and Shower Equipment 32
416.1 Application 32
416.2 Water Supply 32
416.3 Installation 32
416.4 Location 32
416.5 Drain 33
417.0 Faucets and Fixture Fittings 33
417.1 Application 33
417.2 Deck Mounted Bath/Shower Valves 33
417.3 Handheld Showers 33
417.4 Faucets and Fixture Fittings with Hose Connected Outlets 33
417.5 Separate Controls for Hot and Cold Water 33
417.6 Low-Pressure Water Dispenser 33
418.0 Floor Drains 33
418.1 Application 33
418.2 Strainer 33
418.3 Location of Floor Drains 33
418.4 Food Storage Areas 33
418.5 Floor Slope 33
419.0 Food Waste Disposers 33
419.1 Application 33
419.2 Drainage Connection 33
419.3 Water Supply 33
420.0 Sinks 33
420.1 Application 33
420.2 Water Consumption 33
420.3 Pre-Rinse Spray Valve 33
420.4 Waste Outlet 34
421.0 Floor Sinks 34
421.1 Application 34
421.2 Strainers 34
422.0 Minimum Number of Required Fixtures 34
422.1 Fixture Count 34

Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

422.2 Separate Facilities 34
422.3 Fixture Requirements for Special Occupancies 34
422.4 Toilet Facilities Serving Employees and Customers 34
422.5 Toilet Facilities for Workers 34
Table 422.1 Minimum Plumbing Facilities 35

CHAPTER 5 WATER HEATERS 41
501.0 General 41
501.1 Applicability 41
Table 501.1(1) Water Heaters 41
502.0 Permits 41
502.1 General 41
503.0 Inspection 41
503.1 Inspection of Chimneys or Vents . .41
503.2 Final Water Heater Inspection 41
504.0 Water Heater Requirements 41
504.1 Location 41
504.2 Vent 41
Table 501.1(2) First Hour Rating 41
504.3 Clearance 42
504.4 Pressure-Limiting Devices 42
504.5 Temperature-Limiting Devices 42
504.6 Temperature, Pressure, and Vacuum Relief Devices 42
505.0 Oil-Burning and Other Water Heaters 42
505.1 Water Heaters 42
505.2 Safety Devices 42
505.3 Oil-Fired Water Heaters 42
505.4 Indirect-Fired Water Heaters 42
506.0 Air for Combustion and Ventilation 42
506.1 General 42
506.2 Indoor Combustion Air 42
506.3 Indoor Opening Size and Location 43
506.4 Outdoor Combustion Air 43
506.5 Combination Indoor and Outdoor Combustion Air 45
506.6 Engineered Installations 45
506.7 Mechanical Combustion Air Supply 45
506.8 Louvers, Grilles, and Screens 45
506.9 Combustion Air Ducts 45
507.0 Appliance and Equipment Installation Requirements 46
507.1 Dielectric Insulator 46
507.2 Seismic Provisions 46
507.3 Appliance Support 46
507.4 Ground Support 46
507.5 Drainage Pan 46
507.6 Added or Converted Equipment or Appliances 46
507.7 Types of Gases 46
507.8 Safety Shutoff Devices for Unlisted LP-Gas Appliance Used Indoors 46
507.9 Use of Air or Oxygen Under Pressure 46
507.10 Protection of Gas Appliances from Fumes or Gases other than Products of Combustion 46
507.11 Process Air 46
507.12 Flammable Vapors 46
507.13 Installation in Residential Garages 46
507.14 Installation in Commercial Garages 47
507.15 Installation in Aircraft Hangars 47
507.16 Venting of Flue Gases 47
507.17 Extra Device or Attachment 47
507.18 Adequate Capacity of Piping 47
507.19 Avoiding Strain on Gas Piping 47
507.20 Gas Appliance Pressure Regulators 47
507.21 Venting of Gas Appliance Pressure Regulators 47
507.22 Bleed Lines for Diaphragm-Type Valves 47
507.23 Combination of Appliances and Equipment 47
507.24 Installation Instructions 47
507.25 Protection of Outdoor Appliances 48
507.26 Accessibility for Service 48
507.27 Clearance to Combustible Materials 48
508.0 Appliances on Roofs 48
508.1 General 48
508.2 Installation of Appliances on Roofs 48
508.3 Appliances on Roofs 48
508.4 Appliances in Attics and Under-Floor Spaces 48
509.0 Venting of Appliances 49
509.1 Listing 49
509.2 Connection to Venting Systems 49

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

509.3 Minimum Safe Performance 49
509.4 Type of Venting System to be Used 50
Table 509.4 Type of Venting System to be Used 50
509.5 Masonry, Metal, and Factory-Built Chimneys 50
509.6 Gas Vents 52
Table 509.6.1 Roof Slope Heights 53
509.7 Single-Wall Metal Pipe 55
Table 509.7.3.4(1) Clearances for Connectors 55
Table 509.7.3.4(2) Reduction of Clearances with Specified Forms of Protection 57
509.8 Through-the-Wall Vent Termination 58
Table 509.8.2 Through-the-Wall Direct-Vent Termination Clearances 58
509.9 Condensation Drain 59
509.10 Vent Connectors for Category I Appliances 59
Table 509.10.1.3 Minimum Thickness for Galvanized Steel Vent Connectors for Low-Heat Appliances 59
Table 509.10.1.4 Minimum Thickness for Steel Vent Connectors for Medium-Heat Appliances 60
509.11 Vent Connectors for Category II, Category III, and Category IV Appliances 61
509.12 Draft Hoods and Draft Controls . . .61
509.13 Manually Operated Dampers 62
509.14 Automatically Operated Vent Dampers 62
509.15 Obstructions 62
510.0 Sizing of Category I Venting Systems 62
510.1 Single Appliance Vent Table 510.1.2(1) through Table 510.1.2(6) 62
510.2 Multiple Appliance Vent Table 510.2(1) through Table 510.2(9) . . .63
Table 510.2.1 Vent Connector Maximum Length 64
Table 510.1.2(1) Type B Double-Wall Gas Vent 68
Table 510.1.2(2) Type B Double-Wall Gas Vent 71
Table 510.1.2(3) Masonry Chimney 73
Table 510.1.2(4) Masonry Chimney 75
Table 510.1.2(5) Single-Wall Metal Pipe or Type B Asbestos-Cement Vent . . .77
Table 510.1.2(6) Exterior Masonry Chimney 78
Table 510.2(1) Type B Double-Wall Vent 79
Table 510.2(2) Type B Double-Wall Vent 83
Table 510.2(3) Masonry Chimney 85
Table 510.2(4) Masonry Chimney 87
Table 510.2(5) Single-Wall Metal Pipe or Type B Asbestos-Cement Vent . . .89
Table 510.2(6) Exterior Masonry Chimney 89
Table 510.2(7) Exterior Masonry Chimney 90
Table 510.2(8) Exterior Masonry Chimney 91
Table 510.2(9) Exterior Masonry Chimney 92

CHAPTER 6 WATER SUPPLY AND DISTRIBUTION 93

601.0 General 93
601.1 Applicability 93
601.2 Water Supply and Flushing 93
601.3 Identification of a Potable and Nonpotable Water System 93
Table 601.3.2 Minimum Length of Color Field and Size of Letters 93
602.0 Unlawful Connections 93
602.1 Prohibited Installation 93
602.2 Cross-Contamination 94
602.3 Backflow Prevention 94
602.4 Approval by Authority 94
603.0 Cross-Connection Control 94
603.1 General 94
603.2 Approval of Devices or Assemblies 94
603.3 Backflow Prevention Devices, Assemblies, and Methods 94
Table 603.2 Backflow Prevention Devices, Assemblies, and Methods 95
Table 603.3.1 Minimum Air Gaps for Water Distribution 97
603.4 General Requirements 97
603.5 Specific Requirements 98
604.0 Materials 100
604.1 Pipe, Tube, and Fittings 100
604.2 Lead Content 100
604.3 Copper or Copper Alloy Tube . . .100
604.4 Hard-Drawn Copper or Copper Alloy Tubing 100
604.5 Flexible Connectors 100
604.6 Cast-Iron Fittings 100
604.7 Malleable Iron Fittings 100
604.8 Previously Used Piping and Tubing 100
604.9 Epoxy Coating 100
604.10 Plastic Materials 100

AVA Documents Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Table 604.1 Materials for Building Supply and Water Distribution Piping and Fittings 101
604.11 Solder 101
604.12 Flexible Corrugated Connectors . .101
604.13 Water Heater Connectors 101
605.0 Joints and Connections 102
605.1 Copper or Copper Alloy Pipe, Tubing, and Joints 102
605.2 CPVC Plastic Pipe and Joints . . .102
605.3 CPVC/AL/CPVC Plastic Pipe and Joints 103
605.4 Ductile Iron Pipe and Joints 103
605.5 Galvanized Steel Pipe and Joints 103
605.6 PE Plastic Pipe/Tubing and Joints 103
605.7 PE-AL-PE Plastic Pipe/Tubing and Joints 104
605.8 PE-RT 104
605.9 PEX Plastic Tubing and Joints . . .104
605.10 PEX-AL-PEX Plastic Tubing and Joints 104
605.11 Polypropylene (PP) Piping and Joints 105
605.12 PVC Plastic Pipe and Joints 105
605.13 Stainless Steel Pipe and Joints . .105
605.14 Slip Joints 105
605.15 Dielectric Unions 105
605.16 Joints Between Various Materials 105
606.0 Valves 106
606.1 General 106
606.2 Fullway Valve 106
606.3 Multidwelling Units 106
606.4 Multiple Openings 106
606.5 Control Valve 106
606.6 Accessible 106
606.7 Multiple Fixtures 106
606.8 Check Valve Required 106
606.9 Leak Detection Devices 106
607.0 Potable Water Supply Tanks 106
607.1 General 106
607.2 Potable Water Tanks 106
607.3 Venting 106
607.4 Overflow 106
607.5 Valves 106
608.0 Water Pressure, Pressure Regulators, Pressure Relief Valves, and Vacuum Relief Valves 106
608.1 Inadequate Water Pressure 106
608.2 Excessive Water Pressure 106
608.3 Expansion Tanks, and Combination Temperature and Pressure-Relief Valves 107
608.4 Pressure Relief Valves 107
608.5 Discharge Piping 107
608.6 Water-Heating Devices 107
608.7 Vacuum Relief Valves 107
609.0 Installation, Testing, Unions, and Location 107
609.1 Installation 107
609.2 Trenches 107
609.3 Under Concrete Slab 107
609.4 Testing 108
609.5 Unions 108
609.6 Location 108
609.7 Abutting Lot 108
609.8 Pumps 108
609.9 Low-Pressure Cutoff Required on Booster Pumps for Water Distribution Systems 108
609.10 Disinfection of Potable Water System 108
609.11 Water Hammer 108
609.12 Pipe Insulation 108
610.0 Size of Potable Water Piping 109
610.1 Size 109
610.2 Pressure Loss 109
610.3 Quantity of Water 109
610.4 Sizing Water Supply and Distribution Systems 109
610.5 Sizing per Appendices A and C 109
610.6 Friction and Pressure Loss 109
610.7 Conditions for Using Table 610.4 109
610.8 Size of Meter and Building Supply Pipe Using Table 610.4 . .109
610.9 Size of Branches 109
610.10 Sizing for Flushometer Valves . . .109
Table 610.10 Flushometer Fixture Units for Water Sizing Using Table 610.3 110
610.11 Sizing Systems for Flushometer Tanks 110
610.12 Sizing for Velocity 110
610.13 Exceptions 110
Table 610.3 Water Supply Fixture Units (WSFU) and Minimum Fixture Branch Pipe Sizes 111

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Table 610.4 Fixture Unit Table for Determining Water Pipe and Meter Sizes 112
611.0 Drinking Water Treatment Units 113
611.1 Application 113
611.2 Air Gap Discharge 113
611.3 Connection Tubing 113
611.4 Sizing of Residential Softeners . . .113
Table 611.4 Sizing of Residential Water Softeners 113
612.0 Residential Fire Sprinkler Systems 113
612.1 Where Required 113
612.2 Types of Systems 113
612.3 Sprinklers 113
Table 611.1 Drinking Water Treatment Units 113
Table 612.3.3.1 Locations Where Intermediate Temperature Sprinklers are Required 114
Table 612.3.6 Minimum Separation From Obstruction 115
612.4 Sprinkler Piping System 116
612.5 Sprinkler Piping Design 116
Table 612.5.3.2(1) Water Service Pressure Loss (PL_{WS}) 117
Table 612.5.3.2(2) Minimum Water Meter Pressure Loss (PL_m) 118
Table 612.5.3.2(3) Elevation Loss (PL_e) 118
612.6 Instructions and Signs 118
612.7 Inspection and Testing 119
Table 612.5.3.2(4) Allowable Pipe Length for ¾ Inch Type M Copper Water Tubing 120
Table 612.5.3.2(5) Allowable Pipe Length for 1 Inch Type M Copper Water Tubing 121
Table 612.5.3.2(6) Allowable Pipe Length for ¾ Inch IPS CPVC Pipe 122
Table 612.5.3.2(7) Allowable Pipe Length for 1 Inch IPS CPVC Pipe 123
Table 612.5.3.2(8) Allowable Pipe Length for ¾ Inch PEX Tubing 124
Table 612.5.3.2(9) Allowable Pipe Length for 1 Inch PEX Tubing 125

CHAPTER 7 SANITARY DRAINAGE 127
PART I Drainage Systems 127
701.0 General 127
701.1 Applicability 127
701.2 Drainage Piping 127
701.3 Drainage Fittings 127
701.4 Continuous Wastes 127
701.5 Lead 127
701.6 Caulking Ferrules 127
701.7 Soldering Bushings 127
Table 701.6 Caulking Ferrules 127
Table 701.7 Soldering Bushings 127
702.0 Fixture Unit Equivalents 127
702.1 Trap Size 127
Table 701.2 Materials for Drain, Waste, Vent Pipe and Fittings 128
Table 702.1 Drainage Fixture Unit Values (DFU) 129
Table 702.1(1) Maximum Drainage Fixture Units for a Trap and Trap Arm . . .130
702.2 Intermittent Flow 130
Table 702.2 Discharge Capacity in Gallons Per Minute for Intermittent Flow Only 130
702.3 Continuous Flow 130
703.0 Size of Drainage Piping 130
703.1 Minimum Size 130
703.2 Maximum Number of Fixture Units 130
703.3 Sizing per Appendix C 130
704.0 Fixture Connections (Drainage) . .130
704.1 Inlet Fittings 130
704.2 Single Vertical Drainage Pipe 130
704.3 Commercial Sinks 130
705.0 Joints and Connections 130
705.1 ABS and ABS Co-Extruded Plastic Pipe and Joints 130
705.2 Cast-Iron Pipe and Joints 130
Table 703.2 Maximum Unit Loading and Maximum Length of Drainage and Vent Piping 131
705.3 Copper or Copper Alloy Pipe (DWV) and Joints 131
705.4 Galvanized Steel Pipe and Joints 132
705.5 Polyethylene (PE) Sewer Pipe . . .132
705.6 PVC and PVC Co-Extruded Plastic Pipe and Joining Methods 132
705.7 Stainless Steel Pipe and Joints . . .132
705.8 Vitrified Clay Pipe and Joints 133
705.9 Special Joints 133
705.10 Joints Between Various Materials 133
706.0 Changes in Direction of Drainage Flow 133

AVA Documents Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

706.1 Approved Fittings 133
706.2 Horizontal to Vertical 133
706.3 Horizontal to Horizontal 133
706.4 Vertical to Horizontal 133
707.0 Cleanouts 133
707.1 Plug 133
Table 707.1 Cleanouts 134
707.2 Approved 134
Table 707.2 Cleanout Materials for Drain, Waste, and Vent 134
707.3 Watertight and Gastight 134
707.4 Location 134
707.5 Cleaning 134
707.6 Extension 134
707.7 Interceptor 134
707.8 Access 134
707.9 Clearance 134
707.10 Fittings 134
707.11 Pressure Drainage Systems 134
707.12 Countersunk Cleanout Plugs 134
707.13 Hubless Blind Plugs 135
707.14 Trap Arms 135
708.0 Grade of Horizontal Drainage Piping 135
708.1 General 135
709.0 Gravity Drainage Required 135
709.1 General 135
710.0 Drainage of Fixtures Located Below the Next Upstream Manhole or Below the Main Sewer Level 135
710.1 Backflow Protection 135
710.2 Sewage Discharge 135
710.3 Sewage Ejector and Pumps 135
710.4 Discharge Line 135
710.5 Size of Building Drains and Sewers 135
710.6 Backwater Valves 135
710.7 Drainage and Venting Systems . .135
710.8 Sump and Receiving Tank Construction 135
710.9 Alarm 135
710.10 Sump and Receiving Tank Covers and Vents 136
710.11 Air Tanks 136
710.12 Grinder Pump Ejector 136
710.13 Macerating Toilet Systems and Pumped Waste Systems 136
711.0 Suds Relief 136
711.1 General 136
712.0 Testing 136
712.1 Media 136
712.2 Water Test 136
712.3 Air Test 136
PART II Building Sewers 137
713.0 Sewer Required 137
713.1 Where Required 137
713.2 Private Sewage Disposal System 137
713.3 Public Sewer 137
713.4 Public Sewer Availability 137
713.5 Permit 137
713.6 Lot 137
713.7 Installation 137
714.0 Damage to Public Sewer or Private Sewage Disposal System 137
714.1 Unlawful Practices 137
714.2 Prohibited Water Discharge 137
714.3 Prohibited Sewer Connection 137
714.4 Commercial Food Waste Disposer 137
714.5 Tanks 137
715.0 Building Sewer Materials 137
715.1 Materials 137
715.2 Joining Methods and Materials . . .137
715.3 Existing Sewers 137
716.0 Markings 137
716.1 General 137
717.0 Size of Building Sewers 137
717.1 General 137
Table 717.1 Maximum/Minimum Fixture Unit Loading on Building Sewer Piping 138
718.0 Grade, Support, and Protection of Building Sewers . . .138
718.1 Slope 138
718.2 Support 138
718.3 Protection from Damage 138
719.0 Cleanouts. 138
719.1 Locations 138
719.2 No Additional Cleanouts 138
719.3 Building Sewer Cleanouts 138
719.4 Cleaning 138
719.5 Access 138
719.6 Manholes 138
720.0 Sewer and Water Pipes 138
720.1 General 138

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

721.0 Location 138
721.1 Building Sewer 138
Table 721.1 Minimum Horizontal Distance Required from Building Sewer 139
721.2 Abutting Lot 139
722.0 Abandoned Sewers and Sewage Disposal Facilities 139
722.1 Building (House) Sewer 139
722.2 Cesspools, Septic Tanks, and Seepage Pits 139
722.3 Filling 139
722.4 Ownership 139
722.5 Disposal Facilities 139
723.0 Building Sewer Test 139
723.1 General 139

CHAPTER 8 INDIRECT WASTES 141
801.0 General 141
801.1 Applicability 141
801.2 Air Gap or Air Break Required . . .141
801.3 Food and Beverage Handling Establishments 141
801.4 Bar and Fountain Sink Traps 141
801.5 Connections from Water Distribution System 141
801.6 Sterilizers 141
801.7 Drip or Drainage Outlets 141
802.0 Approvals 141
802.1 General 141
803.0 Indirect Waste Piping 141
803.1 Materials 141
803.2 Copper and Copper Alloys 141
803.3 Pipe Size and Length 141
804.0 Indirect Waste Receptors 142
804.1 Standpipe Receptors 142
805.0 Pressure Drainage Connections 142
805.1 General 142
806.0 Sterile Equipment 142
806.1 General 142
807.0 Appliances 142
807.1 Non-Classed Apparatus 142
807.2 Undiluted Condensate Waste 142
807.3 Domestic Dishwashing Machine 142
808.0 Cooling Water 142
808.1 General 142
809.0 Drinking Fountains 142
809.1 General 142
810.0 Steam and Hot Water Drainage Condensers and Sumps 142
810.1 High-Temperature Discharge 142
Table 810.1 Pipe Connections in Blowoff Condensers and Sumps 143
810.2 Sumps, Condensers, and Intercepting Tanks 143
810.3 Cleaning 143
810.4 Strainers 143
811.0 Chemical Wastes 143
811.1 Pretreatment 143
811.2 Waste and Vent Pipes 143
811.3 Joining Materials 143
811.4 Access 143
811.5 Permanent Record 143
811.6 Chemical Vent 143
811.7 Discharge 143
811.8 Diluted Chemicals 143
812.0 Clear Water Wastes 143
812.1 General 143
813.0 Swimming Pools 143
813.1 General 143
814.0 Condensate Waste and Control . . .143
814.1 Condensate Disposal 143
814.2 Condensate Control 144
814.3 Condensate Waste Pipe Material and Sizing 144
Table 814.3 Minimum Condensate Pipe Size 144
814.4 Appliance Condensate Drains . . .144
814.5 Point of Discharge 144
814.6 Condensate Waste from Air-Conditioning Coils 144
814.7 Plastic Fittings 144

CHAPTER 9 VENTS 145
901.0 General 145
901.1 Applicability 145
901.2 Vents Required 145
901.3 Trap Seal Protection 145
902.0 Vents Not Required 145
902.1 Interceptor 145
902.2 Bars, Soda Fountains, and Counter 145
903.0 Materials 145
903.1 Applicable Standards 145
903.2 Use of Copper or Copper Alloy Tubing 145
903.3 Changes in Direction 145
904.0 Size of Vents 145

AVA Documents Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

904.1 Size 145
904.2 Length 145
905.0 Vent Pipe Grades and Connections 145
905.1 Grade 145
905.2 Horizontal Drainage Pipe 146
905.3 Vent Pipe Rise 146
905.4 Roof Termination 146
905.5 Location of Opening 146
905.6 Common Vertical Pipe 146
906.0 Vent Termination 146
906.1 Roof Termination 146
906.2 Clearance 146
906.3 Use of Roof 146
906.4 Outdoor Installations 146
906.5 Joints 146
906.6 Lead 146
906.7 Frost or Snow Closure 146
907.0 Vent Stacks and Relief Vents 146
907.1 Drainage Stack 146
907.2 Yoke Vent 146
908.0 Wet Venting 146
908.1 Vertical Wet Venting 146
908.2 Horizontal Wet Venting for a Bathroom Group 146
909.0 Special Venting for Island Fixtures 147
909.1 General 147
910.0 Combination Waste and Vent Systems 147
910.1 Where Permitted 147
910.2 Approval 147
910.3 Vents 147
910.4 Size 147
910.5 Vertical Waste Pipe 147
910.6 Cleanouts 147
910.7 Fixtures 147
911.0 Circuit Venting 147
911.1 Circuit Vent Permitted 147
911.2 Circuit Vent Size and Connection 148
911.3 Relief Vent 148
911.4 Slope and Size of Horizontal Branch 148
911.5 Additional Fixtures 148
912.0 Engineered Vent System 148
912.1 General 148
912.2 Minimum Requirements 148

CHAPTER 10 TRAPS AND INTERCEPTORS 149

1001.0 General 149
1001.1 Applicability 149
1001.2 Where Required 149
1002.0 Traps Protected by Vent Pipes . .149
1002.1 Vent Pipes 149
1002.2 Fixture Traps 149
Table 1002.2 Horizontal Lengths of Trap Arms 149
1002.3 Change of Direction 149
1002.4 Vent Pipe Opening 149
1003.0 Traps — Described 149
1003.1 General Requirements 149
1003.2 Slip Joint Fittings 149
1003.3 Size 149
1004.0 Traps 149
1004.1 Prohibited 149
1004.2 Movable Parts 149
1005.0 Trap Seals 150
1005.1 General 150
1006.0 Floor Drain Traps 150
1006.1 General 150
1007.0 Trap Seal Protection 150
1007.1 General 150
1007.2 Trap Seal Primers 150
1008.0 Building Traps 150
1008.1 General 150
1009.0 Interceptors (Clarifiers) and Separators 150
1009.1 Where Required 150
1009.2 Approval 150
1009.3 Design 150
1009.4 Relief Vent 150
1009.5 Location 150
1009.6 Maintenance of Interceptors 150
1009.7 Discharge 150
1010.0 Slaughterhouses, Packing Establishments, etc 150
1010.1 General 150
1011.0 Minimum Requirements for Auto Wash Racks 150
1011.1 General 150
1012.0 Commercial and Industrial Laundries 150
1012.1 General 150
1013.0 Bottling Establishments 150
1013.1 General 150
1014.0 Grease Interceptors 150

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

1014.1 General 150
1014.2 Hydromechanical Grease Interceptors 151
Table 1014.2.1 Hydromechanical Grease Interceptor Sizing Using Gravity Flow Rates 151
1014.3 Gravity Grease Interceptors 152
Table 1014.3.6 Gravity Grease Interceptor Sizing 152
1015.0 FOG (Fats, Oils, and Greases) Disposal System 153
1015.1 Purpose 153
1015.2 Components, Materials, and Equipment 153
1015.3 Sizing and Installation 153
1015.4 Performance 153
1016.0 Sand Interceptors 153
1016.1 Discharge 153
1016.2 Authority Having Jurisdiction 153
1016.3 Construction and Size 153
1016.4 Separate Use 153
1017.0 Oil and Flammable Liquid Interceptors 153
1017.1 Interceptors Required 153
1017.2 Design of Interceptors 153

CHAPTER 11 STORM DRAINAGE 155
1101.0 General 155
1101.1 Applicability 155
1101.2 Where Required 155
1101.3 Storm Water Drainage to Sanitary Sewer Prohibited 155
1101.4 Material Uses 155
Table 1101.4.6 Materials for Subsoil Drain Pipe and Fittings 155
1101.5 Expansion Joints Required 155
1101.6 Subsoil Drains 155
1101.7 Building Subdrains 156
1101.8 Areaway Drains 156
1101.9 Window Areaway Drains 156
1101.10 Filling Stations and Motor Vehicle Washing Establishments 156
1101.11 Paved Areas 156
1101.12 Roof Drainage 156
1101.13 Cleanouts 157
1101.14 Rainwater Sumps 157
1101.15 Traps on Storm Drains and Leaders 157
1101.16 Leaders, Conductors, and Connections 157
1102.0 Roof Drains 157
1102.1 Applications 157
1102.2 Dome Strainers Required 157
1102.3 Roof Drain Flashings 157
1103.0 Size of Leaders, Conductors, and Storm Drains 157
1103.1 Vertical Conductors and Leaders 157
1103.2 Size of Horizontal Storm Drains and Sewers 157
1103.3 Size of Roof Gutters 157
1103.4 Side Walls Draining onto a Roof 157
Table 1103.1 Sizing Roof Drains, Leaders, and Vertical Rainwater Piping . . .158
1104.0 Values for Continuous Flow 158
1104.1 General 158
1105.0 Controlled-Flow Roof Drainage 158
1105.1 Application 158
Table 1105.1(1) Controlled-Flow Maximum Roof Water Depth 159
Table 1105.1(2) Distance of Scupper Bottoms Above Roof 159
1105.2 Setback Roofs 159
1106.0 Engineered Storm Drainage System 159
1106.1 General 159
1106.2 Siphonic Roof Drainage Systems 159
1106.3 Siphonic Roof Drains 159
1107.0 Testing 159
1107.1 Testing Required 159
1107.2 Methods of Testing Storm Drainage Systems 159
Table 1103.2 Sizing of Horizontal Rainwater Piping 160
Table 1103.3 Size of Gutters 161

CHAPTER 12 FUEL GAS PIPING 163
1201.0 General 163
1201.1 Applicability 163
1202.0 Coverage of Piping System 163
1202.1 General 163
1202.2 Piping System Requirements 163
1202.3 Applications 163
1203.0 Inspection 163
1203.1 Inspection Notification 163
1203.2 Excavation 163
1203.3 Type of Inspections 163

AVA Documents Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

1203.4 Inspection Waived 164
1204.0 Certificate of Inspection 164
1204.1 Issuance 164
1204.2 Gas Supplier 164
1204.3 Unlawful 164
1205.0 Authority to Render Gas Service 164
1205.1 Authorized Personnel 164
1205.2 Outlets 164
1206.0 Authority to Disconnect 164
1206.1 Disconnection 164
1206.2 Notice 164
1206.3 Capped Outlets 164
1207.0 Temporary Use of Gas 164
1207.1 General 164
1208.0 Gas Piping System Design, Materials, and Components 164
1208.1 Installation of Piping System 164
1208.2 Provision for Location of Point of Delivery 164
1208.3 Interconnections Between Gas Piping Systems 164
1208.4 Sizing of Gas Piping Systems . . .164
Table 1208.4.1 Approximate Gas Input for Typical Appliances 165
1208.5 Maximum Operating Pressure in Buildings 165
1208.6 Acceptable Piping Materials and Joining Methods 165
Table 1208.6.9.2 Specifications for Threading Metallic Pipe 167
1208.7 Gas Meters 168
1208.8 Gas Pressure Regulators 169
1208.9 Overpressure Protection Required 169
1208.10 Overpressure Protection Devices 169
1208.11 Pressure Limitation Requirements 170
1208.12 Backpressure Protection 170
1208.13 Low-Pressure Protection 170
1208.14 Shutoff Valves 171
1208.15 Expansion and Flexibility 171
1209.0 Excess Flow Valve 171
1209.1 General 171
1210.0 Gas Piping Installation 171
1210.1 Piping Underground 171
1210.2 CSST Piping Systems 172
1210.3 Installation of Aboveground Piping 172
Table 1210.3.5.1 Support of Piping 173
1210.4 Concealed Piping in Buildings . . .173
1210.5 Piping in Vertical Chases 173
1210.6 Gas Pipe Turns 174
1210.7 Drips and Sediment Traps 174
1210.8 Outlets 174
1210.9 Manual Gas Shutoff Valves 174
1210.10 Prohibited Devices 175
1210.11 Systems Containing Gas-Air Mixtures Outside the Flammable Range 175
1210.12 Systems Containing Flammable Gas-Air Mixtures 175
1211.0 Electrical Bonding and Grounding 176
1211.1 Pipe and Tubing Other than CSST 176
1211.2 Bonding of CSST Gas Piping 176
1211.3 Arc-Resistant Jacketed CSST . . .176
1211.4 Prohibited Use 176
1211.5 Lightning Protection System 176
1211.6 Electrical Circuits 176
1211.7 Electrical Connections 177
1212.0 Appliance and Equipment Connections to Building Piping . . .177
1212.1 Connecting Appliances and Equipment 177
1212.2 Suspended Low-Intensity Infrared Tube Heaters 177
1212.3 Use of Nonmetallic Gas Hose Connectors 177
1212.4 Injection (Bunsen) Burners 177
1212.5 Connection of Portable and Mobile Industrial Gas Appliances 177
1212.6 Appliance Shutoff Valves and Connections 178
1212.7 Quick-Disconnect Devices 178
1212.8 Gas Convenience Outlets 178
1212.9 Sediment Trap 178
1212.10 Installation of Piping 178
1212.11 Liquefied Petroleum Gas Facilities and Piping 178
1213.0 Pressure Testing, Inspection, and Purging 178
1213.1 Piping Installations 178
1213.2 Test Preparation 179
1213.3 Test Pressure 179
1213.4 Detection of Leaks and Defects . .179
1213.5 Piping System Leak Test 179
1213.6 Purging Requirements 179

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Table 1213.6.1 Size and Length of Piping 180
1214.0 Required Gas Supply 181
1214.1 General 181
1214.2 Volume 181
1214.3 Gas Appliances 181
1214.4 Size of Piping Outlets 181
1215.0 Required Gas Piping Size 181
1215.1 Pipe Sizing Methods 181
1215.2 Sizing of Gas Piping Systems ...181
1215.3 Sizing Equations 181
Table 1215.3 *Cr* and *Y* for Natural Gas and Undiluted Propane at Standard Conditions 182
1215.4 Sizing of Piping Sections 182
1215.5 Engineering Methods 182
1215.6 Variable Gas Pressure 182
Table 1215.2(1) Schedule 40 Metallic Pipe 184
Table 1215.2(2) Schedule 40 Metallic Pipe 185
Table 1215.2(3) Schedule 40 Metallic Pipe 186
Table 1215.2(4) Schedule 40 Metallic Pipe 187
Table 1215.2(5) Schedule 40 Metallic Pipe 188
Table 1215.2(6) Schedule 40 Metallic Pipe 189
Table 1215.2(7) Semi-Rigid Copper Tubing 190
Table 1215.2(8) Semi-Rigid Copper Tubing 191
Table 1215.2(9) Semi-Rigid Copper Tubing 192
Table 1215.2(10) Semi-Rigid Copper Tubing 193
Table 1215.2(11) Semi-Rigid Copper Tubing 194
Table 1215.2(12) Semi-Rigid Copper Tubing 195
Table 1215.2(13) Semi-Rigid Copper Tubing 196
Table 1215.2(14) Corrugated Stainless Steel Tubing (CSST) 197
Table 1215.2(15) Corrugated Stainless Steel Tubing (CSST) 198
Table 1215.2(16) Corrugated Stainless Steel Tubing (CSST) 199
Table 1215.2(17) Corrugated Stainless Steel Tubing (CSST) 200
Table 1215.2(18) Corrugated Stainless Steel Tubing (CSST) 201
Table 1215.2(19) Polyethylene Plastic Pipe 202
Table 1215.2(20) Polyethylene Plastic Pipe 203
Table 1215.2(21) Polyethylene Plastic Pipe 204
Table 1215.2(22) Polyethylene Plastic Tubing 205
Table 1215.2(23) Polyethylene Plastic Tubing 205
Table 1215.2(24) Schedule 40 Metallic Pipe 206
Table 1215.2(25) Schedule 40 Metallic Pipe 207
Table 1215.2(26) Schedule 40 Metallic Pipe 208
Table 1215.2(27) Schedule 40 Metallic Pipe 209
Table 1215.2(28) Semi-Rigid Copper Tubing 210
Table 1215.2(29) Semi-Rigid Copper Tubing 211
Table 1215.2(30) Semi-Rigid Copper Tubing 212
Table 1215.2(31) Corrugated Stainless Steel Tubing (CSST) 213
Table 1215.2(32) Corrugated Stainless Steel Tubing (CSST) 214
Table 1215.2(33) Corrugated Stainless Steel Tubing (CSST) 215
Table 1215.2(34) Polyethylene Plastic Pipe 216
Table 1215.2(35) Polyethylene Plastic Pipe 217
Table 1215.2(36) Polyethylene Plastic Tubing 218

CHAPTER 13 HEALTH CARE FACILITIES AND MEDICAL GAS AND MEDICAL VACUUM SYSTEMS 219

PART I General Requirements 219
1301.0 General Requirements 219
1301.1 Applicability 219
1301.2 Where Not Applicable 219
1301.3 Conflict of Requirements 219
1301.4 Where Required 219
1301.5 Existing Systems 219
1302.0 Design Requirements 219
1302.1 Risk Categories 219
1302.2 Patient Care Spaces 219
1302.3 Anesthesia 219
1302.4 Wet Procedure Locations 219
1303.0 Health Care Facilities 219
1303.1 Drinking Fountain Control Valves 219
1303.2 Psychiatric Patient Rooms 219
1303.3 Locations for Ice Storage 220
1303.4 Sterilizers and Bedpan Steamers 220
1303.5 Aspirators 220
1303.6 Drains 220
1303.7 Clinical Sinks 220
1303.8 Water Supply for Hospitals 220
1303.9 Work Performed in Occupied Healthcare Facilities 220
1304.0 Medical Gas and Medical Vacuum Piping Systems 220
1304.1 General 220
1304.2 Certification of Systems 220
1304.3 Construction Documents 220
1304.4 Extent of Work 220
1304.5 Record 220
1305.0 System Performance 220
1305.1 Required Operating Pressures ...220
1305.2 Minimum Flow Rates 220

Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

1305.3 Minimum Station Outlets and Inlets 220
1306.0 System Certification 220
1306.1 Certification 220
1306.2 Certification Tests 220
Table 1305.1 Standard Designation Colors and Operating Pressures for Gas and Vacuum Systems 221
1306.3 Report Items 221
1306.4 Components 221
PART II Category 1 Piped Gas and Vacuum Systems 221
1307.0 Central Supply Systems 221
1307.1 Terms 221
Table 1305.2 Minimum Flow Rates 221
1307.2 Nature of Hazards of Gas and Vacuum Systems 221
1307.3 Permitted Locations for Medical Gases 221
Table 1305.3 Minimum Outlets and Inlets Per Station 222
1307.4 Materials 222
1308.0 Pressure-Regulating Equipment . .222
1308.1 Where Required 222
1308.2 Pressure Relief Valves 222
1308.3 Pressure-Relief Valve Requirements 223
1309.0 Oxygen Concentrator Supply Units 223
1309.1 Oxygen Requirements 223
1309.2 Particulate Size 223
1309.3 Suitability 223
1309.4 Compatible Materials 223
1309.5 Oxygen Concentrator Components 223
1309.6 Supply Air Quality 223
1309.7 Electrical Components 223
1309.8 Vent Valve 223
1309.9 Valved Sample Port 223
1309.10 Suitable Filter 223
1309.11 Check Valve 223
1309.12 Outlet Valve 223
1309.13 Oxygen Concentration Monitor . . .223
1310.0 Category 1 Medical Air Central Supply Systems 224
1310.1 Quality of Medical Air 224
1310.2 Uses of Medical Air 224
1310.3 Medical Air Compressors 224
1310.4 Medical Air Receivers 224
1310.5 Valves 224
1311.0 Compressor Intake 224
1311.1 Air Sources 224
1311.2 Medical Air Compressor Source 224
1311.3 Air Intakes 224
1311.4 Location 224
1311.5 Separate Compressors 225
1311.6 Screening 225
1312.0 Medical Surgical Vacuum Central Supply Systems 225
1312.1 General 225
1312.2 Medical-Surgical Vacuum Sources 225
1312.3 Vacuum Receivers 225
1312.4 Vacuum Filtration 225
1312.5 Piping Arrangement and Redundancies 225
1312.6 Piping Serviceability 226
1312.7 Shutoff Valve 226
1313.0 Medical-Surgical Vacuum Exhaust 226
1313.1 Vacuum Source Exhausts 226
1313.2 Location 226
1313.3 Screening 226
1313.4 Dips and Loops 226
1313.5 Multiple Pumps 226
1314.0 Valves 226
1314.1 Gas and Vacuum Shutoff Valves 226
1314.2 Security 226
1314.3 Labeled 226
1314.4 Accessibility 226
1314.5 Valve Types 226
Table 1314.5 Positive Pressure Gases 226
1314.6 Source Valves 227
1314.7 Main Line Valve 227
1314.8 Riser Valves 227
1314.9 Service Valves 227
1314.10 Zone Valves 227
1314.11 In-Line Shutoff Valves 227
1314.12 Valves for Future Connections . . .227
1315.0 Station Outlets and Inlets 227
1315.1 General 227
1315.2 Required Valves 227
1315.3 Secondary Valve 227
1315.4 Identification 227
1315.5 Threaded Outlets/Fittings 227
1315.6 Gas-Specific Station Outlet/Inlet 227

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

1315.7 Common Parts 227
1315.8 Marking of Components 228
1315.9 Components Not Specific to a Vacuum 228
1315.10 Factory-Installed Copper Inlet Tubes 228
1315.11 Factory-Installed Copper Outlet Tubes 228
1315.12 Protection from Damage 228
1315.13 Multiple Wall Outlets/Inlets 228
1315.14 Nonstandard Operation Pressures 228
1315.15 Post Installation 228
1316.0 Pressure and Vacuum Indicator Locations 228
1316.1 Isolation 228
1316.2 Pressure and Vacuum Indicator Locations 228
1317.0 Warning Systems 228
1317.1 Category 1 228
1318.0 Piping Materials for Field-Installed Positive Pressure Medical Gas Systems 229
1318.1 General 229
1318.2 Cleaning 229
1318.3 Delivery 229
1318.4 Tubes for Medical Gas Systems .229
1318.5 Manufacturer Markings 229
1318.6 Documentation 229
1319.0 Piping Materials for Field-Installed Medical-Surgical Vacuum Systems 229
1319.1 Tubes for Medical Vacuum Systems 229
1320.0 Joints and Connections 229
1320.1 General 229
1320.2 Changes in Direction 229
1321.0 Brazed Joints 229
1321.1 Brazed Joints and Fittings 229
1321.2 Tube Joints 230
1321.3 Filler Metals 230
1321.4 Copper-to-Copper Joints 230
1321.5 Accessible 230
1321.6 Purging 230
1321.7 Tube Ends 230
1321.8 Cleaning Procedures 230
1321.9 Brazing Dissimilar Metals 230
1321.10 Nitrogen Purge 230
1321.11 Assembling and Heating Brazed Joints 231
1321.12 Inspection of Brazed Joints 231
1322.0 Welded Joints 231
1322.1 Welded Joints Procedure 231
1322.2 Welding for Stainless Tube 232
1322.3 Memory Metal Fittings 232
1322.4 Axially Swaged Fittings 232
1322.5 Threaded Fittings 232
1322.6 Other Types of Fittings 232
1322.7 Prohibited Joints 232
1323.0 Installation of Piping and Equipment 232
1323.1 Required Pipe Sizing 232
Table 1323.1.5(1) System Sizing – Flow Requirements for Station Outlets and Inlets1 233
Table 1323.1.5(2) Maximum Permitted Pressure Loss In Medical Gas and Medical Vacuum Systems 233
1323.2 Pipe Protection 233
1323.3 Location of Piping 233
1323.4 Pipe Support 233
Table 1323.1.4(1) Pressure Loss for Medical Air 234
Table 1323.1.4(2) Pressure Loss for Nitrogen 234
Table 1323.1.4(3) Pressure Loss for Nitrous Oxide and Carbon Dioxide 235
Table 1323.1.4(4) Pressure Loss for Oxygen 235
Table 1323.1.4(5) Pressure Loss for Vacuum 236
Table 1323.1.4(6) Pressure Loss for Vacuum (Category 3) 236
1323.5 Frost Protection 237
Table 1323.4.4 Maximum Pipe Support Spacing 237
1323.6 Connectors 238
1323.7 Prohibited System Interconnections 238
1323.8 Manufacturer's Instructions 238
1323.9 Changes in System Use 238
1323.10 Qualifications of Installers 238
1323.11 Qualification of Brazing Procedures and Brazing 238
1323.12 Breaching or Penetrating Medical Gas Piping 239
1323.13 Labeling, Identification and Operating Pressure 239
1323.14 Identification of Shutoff Valves . . .239
1323.15 Identification 240
1324.0 Performance Criteria and Testing Category 1 (Gases, Medical Surgical Vacuum) 240
1324.1 Where Required 240
1324.2 Breached Systems 240

AVA Documents Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

1324.3 Test Gas 240
1324.4 Initial Piping Blowdown 240
1324.5 Initial Pressure Tests– Medical Gas and Vacuum Systems 240
Table 1324.5.11 Gas Concentrations 242
PART III Category 2 Piped Gas and Vacuum Systems 242
1325.0 Category 2 Piped Gas and Vacuum Systems 242
1325.1 General 242
1325.2 Nature of Hazards of Gas and Vacuum Systems 243
1325.3 Central Supply Systems 243
1325.4 Category 2 Medical Air Supply Systems 243
1325.5 Oxygen Concentrators 243
1325.6 Category 2 Medical-Surgical Vacuum 243
1325.7 Valves 243
1325.8 Station Outlets and Inlets 243
1325.9 Pressure and Vacuum Indicators 243
1325.10 Warning Systems (Category 2) 243
1325.11 Category 2 Distribution 243
1325.12 Labeling and Identification 243
1325.13 Performance Criteria and Testing — Category 2 (Gas, Medical–Surgical and Vacuum) . .243
PART IV Category 3 Piped Gas and Vacuum Systems 243
1326.0 Category 3 Piped Gas and Vacuum Systems 243
1326.1 General 243
1326.2 Nature of Hazards of Gas and Vacuum Systems 243
1326.3 Medical Air Supply Systems 243
1326.4 Oxygen Central Supply Systems Using Concentrators . . .243
1326.5 Medical–Surgical Vacuum 243
1326.6 Valves 243
1326.7 Station Outlets and Inlets 243
1326.8 Pressure and Vacuum Indicators 243
1326.9 Warning Systems 243
1326.10 Distribution 244
1326.11 Labeling and Identification 244
PART V Dental Gas and Vacuum Systems 244
1327.0 Dental Gas and Vacuum Systems 244
1327.1 General 244
1327.2 Emergency Shutoff Valves (Oxygen and Nitrous Oxide) 244
1327.3 Warning Systems (Oxygen and Nitrous Oxide) 244
1327.4 Initial Pressure Test 244
1327.5 Maximum Copper Tube Support Spacing 244
1327.6 Maximum Plastic Pipe Support Spacing 244
Table 1327.5 Maximum Copper Tube Support Spacing 245
Table 1327.6 Maximum Plastic Pipe Support Spacing 245
1327.7 Standing Pressure Tests for Oxygen and Nitrous Oxide Piping 245
1327.8 Verifier Operational Pressure Test 245

CHAPTER 14 FIRESTOP PROTECTION 247
1401.0 General 247
1401.1 Applicability 247
1402.0 Construction Documents 247
1402.1 Penetrations 247
1403.0 Installation 247
1403.1 Materials 247
1404.0 Combustible Piping Installations 247
1404.1 General Requirements 247
1404.2 Fire-Resistance Rating 247
1404.3 Firestop Systems 247
1404.4 Connections 247
1404.5 Insulation and Coverings 247
1404.6 Sleeves 247
1405.0 Noncombustible Piping Installations 247
1405.1 General Requirements 247
1405.2 Fire-Resistance Rating 247
1405.3 Firestop Systems 247
1405.4 Connections 247
1405.5 Unshielded Couplings 248
1405.6 Sleeves 248
1405.7 Insulation and Coverings 248
1406.0 Required Inspection 248
1406.1 General 248
1406.2 Examination 248
1406.3 Penetrations 248
1406.4 Field Installations 248

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

CHAPTER 15 ALTERNATE WATER SOURCES FOR NONPOTABLE APPLICATIONS 249

1501.0 General 249
1501.1 Applicability 249
1501.2 System Design 249
1501.3 Permit 249
1501.4 Component Identification 249
1501.5 Maintenance and Inspection 249
Table 1501.5 Minimum Alternate Water Source Testing, Inspection, and Maintenance Frequency 249
1501.6 Operation and Maintenance Manual 249
1501.7 Minimum Water Quality Requirements 250
1501.8 Material Compatibility 250
1501.9 Commercial, Industrial, and Institutional Restroom Signs 250
1501.10 System Controls 250
1502.0 Inspection and Testing 250
1502.1 General 250
1502.2 Supply System Inspection and Test 250
1502.3 Annual Cross-Connection Inspection and Testing 250
1502.4 Separation Requirements 251
1502.5 Abandonment 251
1502.6 Sizing 251
1503.0 Gray Water Systems 251
1503.1 General 251
1503.2 System Requirements 251
1503.3 Connections to Potable and Reclaimed (Recycled) Water Systems 251
1503.4 Location 252
Table 1503.4 Location of Gray Water System . . .252
1503.5 Plot Plan Submission 252
1503.6 Prohibited Location 252
1503.7 Drawings and Specifications 252
1503.8 Procedure for Estimating Gray Water Discharge 252
1503.9 Gray Water System Components 253
1504.0 Subsurface Irrigation System Zones 253
1504.1 General 253
1504.2 Required Area of Subsurface Irrigation Fields, Subsoil Irrigation Fields, and Mulch Basins 253
1504.3 Determination of Maximum Absorption Capacity 254
1504.4 Groundwater Level 254
Table 1504.2 Design of Six Typical Soils 254
1504.5 Subsurface and Subsoil Irrigation Field Design and Construction 254
Table 1504.5.5 Subsurface Irrigation Design Criteria for Six Typical Soils 254
1504.6 Mulch Basin Design and Construction 254
1504.7 Subsoil Irrigation Field 255
Table 1504.7.3 Subsoil Irrigation Field Construction 255
1504.8 Gray Water System Color and Marking Information 255
1504.9 Other Collection and Distribution Systems 255
1504.10 Testing 255
1504.11 Maintenance 255
1505.0 Reclaimed (Recycled) Water Systems 255
1505.1 General 255
1505.2 Permit 255
1505.3 System Changes 255
1505.4 Connections to Potable or Reclaimed (Recycled) Water Systems 255
1505.5 Initial Cross-Connection Test 256
1505.6 Reclaimed (Recycled) Water System Materials 256
1505.7 Reclaimed (Recycled) Water System Color and Marking Information 256
1505.8 Valves 256
1505.9 Hose Bibbs 256
1505.10 Required Appurtenances 256
1505.11 Same Trench as Potable Water Pipes 256
1505.12 Signs 256
1505.13 Inspection and Testing 256
1506.0 On-Site Treated Nonpotable Water Systems 256
1506.1 General 256
1506.2 Plumbing Plan Submission 256
1506.3 System Changes 256
1506.4 Connections to Potable or Reclaimed (Recycled) Water Systems 256
1506.5 Initial Cross-Connection Test 256
1506.6 On-Site Treated Nonpotable Water System Materials 256

AVA Documents Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

1506.7 On-Site Treated Nonpotable Water Devices and Systems 256
1506.8 On-Site Treated Nonpotable Water System Color and Marking Information 257
1506.9 Design and Installation 257
1506.10 Valves 257
1506.11 Signs 257
1506.12 Inspection and Testing 257

CHAPTER 16 NONPOTABLE RAINWATER CATCHMENT SYSTEMS 259

1601.0 General 259
1601.1 Applicability 259
1601.2 System Design 259
1601.3 Permit 259
1601.4 Component Identification 259
1601.5 Maintenance and Inspection 259
Table 1601.5 Minimum Alternate Water Source Testing, Inspection, and Maintenance Frequency 259
1601.6 Operation and Maintenance Manual 260
1601.7 Minimum Water Quality Requirements 260
1601.8 Material Compatibility 260
1601.9 System Controls 260
1601.10 Separation Requirements 260
1601.11 Abandonment 260
1601.12 Sizing 260
1602.0 Nonpotable Rainwater Catchment Systems 260
1602.1 General 260
1602.2 Plumbing Plan Submission 260
1602.3 System Changes 260
1602.4 Connections to Potable or Reclaimed (Recycled) Water Systems 260
1602.5 Initial Cross-Connection Test 260
1602.6 Sizing 260
1602.7 Rainwater Catchment System Materials 261
1602.8 Rainwater Catchment System Color and Marking Information . . .261
1602.9 Deactivation and Drainage for Cross-Connection Test 261
1603.0 Design and Installation 261
1603.1 Rainwater Catchment Systems . .261
1603.2 Outside Hose Bibbs 261
1603.3 Construction 261
1603.4 Rainwater Catchment Collection Surfaces 261
1603.5 Minimum Water Quality 261
1603.6 Rainwater Storage Tanks 261
1603.7 Location 261
1603.8 Above Grade 261
1603.9 Below Grade 261
Table 1603.5 Minimum Water Quality 262
1603.10 Drainage and Overflow 262
1603.11 Opening and Access Protection . . .262
1603.12 Marking 262
1603.13 Storage Tank Venting 262
1603.14 Pumps 262
1603.15 Roof Drains 262
1603.16 Water Quality Devices and Equipment 262
1603.17 Freeze Protection 262
1603.18 Debris Removal 262
1603.19 Required Filters 262
1603.20 Roof Gutters 263
1604.0 Signs 263
1604.1 General 263
1604.2 Commercial, Industrial, and Institutional Restroom Signs 263
1604.3 Equipment Room Signs 263
1605.0 Inspection and Testing 263
1605.1 General 263
1605.2 Supply System Inspection and Test 263
1605.3 Annual Cross-Connection Inspection and Testing 263

CHAPTER 17 REFERENCED STANDARDS . . .265

1701.0 General 265
1701.1 Standards 265
Table 1701.1 Referenced Standards 265
1701.2 Standards, Publications, Practices, and Guides 279
Table 1701.2 Standards, Publications, Practices, and Guides 279

APPENDICES TABLE OF CONTENTS 287

Appendix A Recommended Rules for Sizing the Water Supply System 289
Appendix B Explanatory Notes on Combination Waste and Vent Systems 303
Appendix C Alternate Plumbing Systems 305

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Appendix D	Sizing Storm Water Drainage Systems	.313
Appendix E	Manufactured/Mobile Home Parks and Recreational Vehicle Parks	.321
Appendix F	Firefighter Breathing Air Replenishment Systems	.331
Appendix G	Sizing of Venting Systems	.335
Appendix H	Private Sewage Disposal Systems	.345
Appendix I	Installation Standards	.355
Appendix J	Combination of Indoor and Outdoor Combustion and Ventilation Opening Design	.393
Appendix K	Potable Rainwater Catchment Systems	.395
Appendix L	Sustainable Practices	.399
Appendix M	Peak Water Demand Calculator	.415
Appendix N	Impact Of Water Temperature On The Potential for Scalding and Legionella Growth	.421

USEFUL TABLES . . . . . **.423**

INDEX . . . . . **.433**

Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

CHAPTER 1
ADMINISTRATION

101.0 General.

101.1 Title. This document shall be known as the "Uniform Plumbing Code,'' may be cited as such, and will be referred to herein as "this code."

101.2 Scope. The provisions of this code shall apply to the erection, installation, alteration, repair, relocation, replacement, addition to, use, or maintenance of plumbing systems within this jurisdiction.

101.3 Purpose. This code is an ordinance providing minimum requirements and standards for the protection of the public health, safety, and welfare.

101.4 Unconstitutional. Where a section, subsection, sentence, clause, or phrase of this code is, for a reason, held to be unconstitutional, such decision shall not affect the validity of the remaining portions of this code. The legislative body hereby declares that it would have passed this code, and each section, subsection, sentence, clause, or phrase thereof, irrespective of the fact that one or more sections, subsections, sentences, clauses, and phrases are declared unconstitutional.

101.5 Validity. Where a provision of this code, or the application thereof to a person or circumstance, is held invalid, the remainder of the code, or the application of such provision to other persons or circumstances, shall not be affected thereby.

102.0 Applicability.

102.1 Conflicts Between Codes. Where the requirements within the jurisdiction of this plumbing code conflict with the requirements of the mechanical code, this code shall prevail. In instances where this code, applicable standards, or the manufacturer's installation instructions conflict, the more stringent provisions shall prevail. Where there is a conflict between a general requirement and a specific requirement, the specific requirement shall prevail.

102.2 Existing Installations. Plumbing systems lawfully in existence at the time of the adoption of this code shall be permitted to have their use, maintenance, or repair continued where the use, maintenance, or repair is in accordance with the original design and location and no hazard to life, health, or property has been created by such plumbing system.

102.3 Maintenance. The plumbing and drainage system, both existing and new, of a premise under the Authority Having Jurisdiction shall be maintained in a sanitary and safe operating condition. Devices or safeguards required by this code shall be maintained in accordance with the code edition under which installed.

The owner or the owner's designated agent shall be responsible for maintenance of plumbing systems. To determine compliance with this subsection, the Authority Having Jurisdiction shall be permitted to cause a plumbing system to be reinspected.

102.4 Additions, Alterations, Renovations, or Repairs. Additions, alterations, renovations or repairs shall conform to that required for a new system without requiring the existing plumbing system to be in accordance with the requirements of this code. Additions, alterations, renovations, or repairs shall not cause an existing system to become unsafe, insanitary, or overloaded.

Additions, alterations, renovations, or repairs to existing plumbing installations shall comply with the provisions for new construction unless such deviations are found to be necessary and are first approved by the Authority Having Jurisdiction.

102.4.1 Building Sewers and Drains. Existing building sewers and building drains shall be permitted to be used in connection with new buildings or new plumbing and drainage work where they are found on examination and test to be in accordance with the requirements governing new work, and the proper Authority Having Jurisdiction shall notify the owner to make changes necessary to be in accordance with this code. No building, or part thereof, shall be erected or placed over a part of a drainage system that is constructed of materials other than those approved elsewhere in this code for use under or within a building.

102.4.2 Openings. Openings into a drainage or vent system, excepting those openings to which plumbing fixtures are properly connected or which constitute vent terminals, shall be permanently plugged or capped in an approved manner, using the appropriate materials in accordance with this code.

102.5 Health and Safety. Where compliance with the provisions of this code fails to eliminate or alleviate a nuisance, or other dangerous or insanitary condition that involves health or safety hazards, the owner or the owner's agent shall install such additional plumbing and drainage facilities or shall make such repairs or alterations as ordered by the Authority Having Jurisdiction.

102.6 Changes in Building Occupancy. Plumbing systems that are a part of a building or structure undergoing a change in use or occupancy, as defined in the building code, shall be in accordance with the requirements of this code that are applicable to the new use or occupancy.

102.7 Moved Structures. Parts of the plumbing system of a building or part thereof that is moved from one foundation to another, or from one location to another, shall be in accordance with the provisions of this code for new installations and completely tested as prescribed elsewhere in this section for new work, except that walls or floors need not be removed during such test where other equivalent means of inspection acceptable to the Authority Having Jurisdiction are provided.

102.8 Appendices. The provisions in the appendices are intended to supplement the requirements of this code and shall not be considered part of this code unless formally adopted as such.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

103.0 Duties and Powers of the Authority Having Jurisdiction.

103.1 General. The Authority Having Jurisdiction shall be the Authority duly appointed to enforce this code. For such purposes, the Authority Having Jurisdiction shall have the powers of a law enforcement officer. The Authority Having Jurisdiction shall have the power to render interpretations of this code and to adopt and enforce rules and regulations supplemental to this code as deemed necessary in order to clarify the application of the provisions of this code. Such interpretations, rules, and regulations shall comply with the intent and purpose of this code.

In accordance with the prescribed procedures and with the approval of the appointing authority, the Authority Having Jurisdiction shall be permitted to appoint a such number of technical officers, inspectors, and other employees as shall be authorized from time to time. The Authority Having Jurisdiction shall be permitted to deputize such inspectors or employees as necessary to carry out the functions of the code enforcement agency.

The Authority Having Jurisdiction shall be permitted to request the assistance and cooperation of other officials of this jurisdiction so far as required in the discharge of the duties in accordance with this code or other pertinent law or ordinance.

103.2 Liability. The Authority Having Jurisdiction charged with the enforcement of this code, acting in good faith and without malice in the discharge of the Authority Having Jurisdiction's duties, shall not thereby be rendered personally liable for damage that accrues to persons or property as a result of an act or by reason of an act or omission in the discharge of duties. A suit brought against the Authority Having Jurisdiction or employee because of such act or omission performed in the enforcement of provisions of this code shall be defended by legal counsel provided by this jurisdiction until final termination of such proceedings.

103.3 Applications and Permits. The Authority Having Jurisdiction shall be permitted to require the submission of plans, specifications, drawings, and such other information in accordance with the Authority Having Jurisdiction, prior to the commencement of, and at a time during the progress of, work regulated by this code.

The issuance of a permit upon construction documents shall not prevent the Authority Having Jurisdiction from thereafter requiring the correction of errors in said construction documents or from preventing construction operations being carried on thereunder where in violation of this code or of other pertinent ordinance or from revoking a certificate of approval where issued in error.

103.3.1 Licensing. Provision for licensing shall be determined by the Authority Having Jurisdiction.

103.4 Right of Entry. Where it is necessary to make an inspection to enforce the provisions of this code, or where the Authority Having Jurisdiction has reasonable cause to believe that there exists in a building or upon premises a condition or violation of this code that makes the building or premises unsafe, insanitary, dangerous, or hazardous, the Authority Having Jurisdiction shall be permitted to enter the building or premises at reasonable times to inspect or to perform the duties imposed by the Authority Having Jurisdiction by this code, provided that where such building or premises is occupied, the Authority Having Jurisdiction shall present credentials to the occupant and request entry. Where such building or premises is unoccupied, the Authority Having Jurisdiction shall first make a reasonable effort to locate the owner or other person having charge or control of the building or premises and request entry. Where entry is refused, the Authority Having Jurisdiction has recourse to every remedy provided by law to secure entry.

Where the Authority Having Jurisdiction shall have first obtained an inspection warrant or other remedy provided by law to secure entry, no owner, occupant, or person having charge, care or control of a building or premises shall fail or neglect, after a request is made as herein provided, to promptly permit entry herein by the Authority Having Jurisdiction for the purpose of inspection and examination pursuant to this code.

104.0 Permits.

104.1 Permits Required. It shall be unlawful for a person, firm, or corporation to make an installation, alteration, repair, replacement, or remodel a plumbing system regulated by this code except as permitted in Section 104.2, or to cause the same to be done without first obtaining a separate plumbing permit for each separate building or structure.

104.2 Exempt Work. A permit shall not be required for the following:

(1) The stopping of leaks in drains, soil, waste, or vent pipe, provided, however, that a trap, drainpipe, soil, waste, or vent pipe become defective, and it becomes necessary to remove and replace the same with new material, the same shall be considered as new work and a permit shall be procured and inspection made as provided in this code.

(2) The clearing of stoppages, including the removal and reinstallation of water closets, or the repairing of leaks in pipes, valves, or fixtures, provided such repairs do not involve or require the replacement or rearrangement of valves, pipes, or fixtures.

Exemption from the permit requirements of this code shall not be deemed to grant authorization for work to be done in violation of the provisions of the code or other laws or ordinances of this jurisdiction.

104.3 Application for Permit. To obtain a permit, the applicant shall first file an application therefore in writing on a form furnished by the Authority Having Jurisdiction for that purpose. Such application shall:

(1) Identify and describe the work to be covered by the permit for which application is made.

(2) Describe the land upon which the proposed work is to be done by legal description, street address, or similar description that will readily identify and locate the proposed building or work.

(3) Indicate the use or occupancy for which the proposed work is intended.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

(4) Be accompanied by construction documents in accordance with Section 104.3.1.

(5) Be signed by the permittee or the permittee's authorized agent. The Authority Having Jurisdiction shall be permitted to require evidence to indicate such authority.

(6) Give such other data and information in accordance with the Authority Having Jurisdiction.

104.3.1 Construction Documents. Construction documents, engineering calculations, diagrams, and other data shall be submitted in two or more sets with each application for a permit. The construction documents, computations, and specifications shall be prepared by, and the plumbing designed by, a registered design professional. Construction documents shall be drawn to scale with clarity to identify that the intended work to be performed is in accordance with the code.

Exception: The Authority Having Jurisdiction shall be permitted to waive the submission of construction documents, calculations, or other data where the Authority Having Jurisdiction finds that the nature of the work applied for is such that reviewing of construction documents is not necessary to obtain compliance with the code.

104.3.2 Plan Review Fees. Where a plan or other data is required to be submitted in accordance with Section 104.3.1, a plan review fee shall be paid at the time of submitting construction documents for review.

The plan review fees for plumbing work shall be determined and adopted by this jurisdiction.

The plan review fees specified in this subsection are separate fees from the permit fees specified in Section 104.5.

Where plans are incomplete or changed so as to require additional review, a fee shall be charged at the rate shown in Table 104.5.

104.3.3 Time Limitation of Application. Applications for which no permit is issued within 180 days following the date of application shall expire by limitation, plans and other data submitted for review thereafter, shall be returned to the applicant or destroyed by the Authority Having Jurisdiction. The Authority Having Jurisdiction shall be permitted to exceed the time for action by the applicant for a period not to exceed 180 days upon request by the applicant showing that circumstances beyond the control of the applicant have prevented the action from being taken. No application shall be extended more than once. In order to renew action on an application after expiration, the applicant shall resubmit plans and pay a new plan review fee.

104.4 Permit Issuance. The application, construction documents, and other data filed by an applicant for a permit shall be reviewed by the Authority Having Jurisdiction. Such plans shall be permitted to be reviewed by other departments of this jurisdiction to verify compliance with applicable laws under their jurisdiction. Where the Authority Having Jurisdiction finds that the work described in an application for permit and the plans, specifications, and other data filed therewith are in accordance with the requirements of the code and other pertinent laws and ordinances and that the fees specified in Section 104.5 have been paid, the Authority Having Jurisdiction shall issue a permit therefore to the applicant.

104.4.1 Approved Plans or Construction Documents. Where the Authority Having Jurisdiction issues the permit where plans are required, the Authority Having Jurisdiction shall endorse in writing or stamp the construction documents "APPROVED." Such approved construction documents shall not be changed, modified, or altered without authorization from the Authority Having Jurisdiction, and the work shall be done in accordance with approved plans.

The Authority Having Jurisdiction shall be permitted to issue a permit for the construction of a part of a plumbing system before the entire construction documents for the whole system have been submitted or approved, provided adequate information and detailed statements have been filed in accordance with the pertinent requirements of this code. The holder of such permit shall be permitted to proceed at the holder's risk without assurance that the permit for the entire building, structure, or plumbing system will be granted.

104.4.2 Validity of Permit. The issuance of a permit or approval of construction documents shall not be construed to be a permit for, or an approval of, a violation of the provisions of this code or other ordinance of the jurisdiction. No permit presuming to give authority to violate or cancel the provisions of this code shall be valid.

The issuance of a permit based upon plans, specifications, or other data shall not prevent the Authority Having Jurisdiction from thereafter requiring the correction of errors in said plans, specifications, and other data or from preventing building operations being carried on thereunder where in violation of this code or of other ordinances of this jurisdiction.

104.4.3 Expiration. A permit issued by the Authority Having Jurisdiction under the provisions of this code shall expire by limitation and become null and void where the work authorized by such permit is not commenced within 180 days from the date of such permit, or where the work authorized by such permit is suspended or abandoned at a time after the work is commenced for a period of 180 days. Before such work is recommenced, a new permit shall first be obtained to do so, and the fee, therefore, shall be one-half the amount required for a new permit for such work, provided no changes have been made or will be made in the original construction documents for such work, and provided further that such suspensions or abandonment has not exceeded 1 year.

104.4.4 Extensions. A permittee holding an unexpired permit shall be permitted to apply for an extension of the time within which work shall be permitted to commence under that permit where the permittee is unable to commence work within the time required by this section. The Authority Having Jurisdiction shall be permitted to extend the time for action by the permittee for a period not exceeding 180 days upon [illegible] by the per-

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

mittee showing that circumstances beyond the control of the permittee have prevented the action from being taken. No permit shall be extended more than once. In order to renew action on a permit after expiration, the permittee shall pay a new full permit fee.

104.4.5 Suspension or Revocation. The Authority Having Jurisdiction shall be permitted to, in writing, suspend or revoke a permit issued under the provisions of this code where the permit is issued in error or on the basis of incorrect information supplied or in violation of other ordinance or regulation of the jurisdiction.

104.4.6 Retention of Plans. One set of approved construction documents and computations shall be retained by the Authority Having Jurisdiction until final approval of the work covered therein.

One set of approved construction documents, computations, and manufacturer's installation instructions shall be returned to the applicant and said set shall be kept on the site of the building or work at times during which the work authorized thereby is in progress.

104.5 Fees. Fees shall be assessed in accordance with the provisions of this section and as set forth in the fee schedule, Table 104.5. The fees are to be determined and adopted by this jurisdiction.

104.5.1 Work Commencing Before Permit Issuance. Where work for which a permit is required by this code has been commenced without first obtaining said permit, a special investigation shall be made before a permit is issued for such work.

104.5.2 Investigation Fees. An investigation fee, in addition to the permit fee, shall be collected whether a permit is then or subsequently issued. The investigation fee shall be equal to the amount of the permit fee that is required by this code if a permit were to be issued. The payment of such investigation fee shall not exempt a person from compliance with other provisions of this code, nor from a penalty prescribed by law.

104.5.3 Fee Refunds. The Authority Having Jurisdiction shall be permitted to authorize the refunding of a fee as follows:

(1) The amount paid hereunder that was erroneously paid or collected.

(2) Refunding of not more than a percentage, as determined by this jurisdiction where no work has been done under a permit issued in accordance with this code.

The Authority Having Jurisdiction shall not authorize the refunding of a fee paid except upon written application filed by the original permittee not to exceed 180 days after the date of fee payment.

105.0 Inspections and Testing.

105.1 General. Plumbing systems for which a permit is required by this code shall be inspected by the Authority Having Jurisdiction.

No plumbing system or portion thereof shall be covered, concealed, or put into use until inspected and approved as prescribed in this code. Neither the Authority Having Jurisdiction nor the jurisdiction shall be liable for expense entailed in the removal or replacement of material required to permit inspection. Plumbing systems regulated by this code shall not be connected to the water, the energy fuel supply, or the sewer system until authorized by the Authority Having Jurisdiction.

105.2 Required Inspections. New plumbing work and such portions of existing systems as affected by new work, or changes, shall be inspected by the Authority Having Jurisdiction to ensure compliance with the requirements of this code and to ensure that the installation and construction of the plumbing system are in accordance with approved plans. The Authority Having Jurisdiction shall make the following inspections and other such inspections as necessary. The permittee or the permittee's authorized agent shall be responsible for the scheduling of such inspections as follows:

(1) The underground inspection shall be made after trenches or ditches are excavated and bedded, piping installed, and before backfill is put in place.

(2) Rough-in inspection shall be made prior to the installation of wall or ceiling membranes.

(3) Final inspection shall be made upon completion of the installation.

105.2.1 Uncovering. Where a drainage or plumbing system, building sewer, private sewage disposal system, or part thereof, which is installed, altered, or repaired, is covered or concealed before being inspected, tested, and approved as prescribed in this code, it shall be uncovered for inspection after notice to uncover the work has been issued to the responsible person by the Authority Having Jurisdiction.

The requirements of this section shall not be considered to prohibit the operation of plumbing installed to replace existing equipment or fixtures serving an occupied portion of the building in the event a request for inspection of such equipment or fixture has been filed with the Authority Having Jurisdiction not more than 72 hours after such replacement work is completed, and before a portion of such plumbing system is concealed by a permanent portion of the building.

105.2.1.1 Water Supply System. No water supply system or portion thereof shall be covered or concealed until it first has been tested, inspected, and approved.

105.2.1.2 Covering or Using. No plumbing or drainage system, building sewer, private sewer disposal system, or part thereof, shall be covered, concealed, or put into use until it has been tested, inspected, and accepted as prescribed in this code.

105.2.2 Other Inspections. In addition to the inspections required by this code, the Authority Having Jurisdiction shall be permitted to require other inspections to ascertain compliance with the provisions of this code and other laws that are enforced by the Authority Having Jurisdiction.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

105.2.3 Inspection Requests. It shall be the duty of the person doing the work authorized by a permit to notify the Authority Having Jurisdiction that such work is ready for inspection. The Authority Having Jurisdiction shall be permitted to require that a request for inspection be filed not less than 1 working day before such inspection is desired. Such request shall be permitted to be made in writing or by telephone, at the option of the Authority Having Jurisdiction.

It shall be the duty of the person requesting inspections in accordance with this code to provide access to and means for inspection of such work.

105.2.4 Advance Notice. It shall be the duty of the person doing the work authorized by the permit to notify the Authority Having Jurisdiction, orally or in writing that said work is ready for inspection. Such notification shall be given not less than 24 hours before the work is to be inspected.

105.2.5 Responsibility. It shall be the duty of the holder of a permit to make sure that the work will stand the test prescribed before giving the notification.

The equipment, material, and labor necessary for inspection or tests shall be furnished by the person to whom the permit is issued or by whom inspection is requested.

105.2.6 Reinspections. A reinspection fee shall be permitted to be assessed for each inspection or reinspection where such portion of work for which inspection is called is not complete or where required corrections have not been made.

This provision shall not be interpreted as requiring reinspection fees the first time a job is rejected for failure to be in accordance with the requirements of this code, but as controlling the practice of calling for inspections before the job is ready for inspection or reinspection.

Reinspection fees shall be permitted to be assessed where the approved plans are not readily available to the inspector, for failure to provide access on the date for which the inspection is requested, or for deviating from plans requiring the approval of the Authority Having Jurisdiction.

To obtain reinspection, the applicant shall file an application therefore in writing upon a form furnished for that purpose and pay the reinspection fee in accordance with Table 104.5.

In instances where reinspection fees have been assessed, no additional inspection of the work will be performed until the required fees have been paid.

105.3 Testing of Systems. Plumbing systems shall be tested and approved in accordance with this code or the Authority Having Jurisdiction. Tests shall be conducted in the presence of the Authority Having Jurisdiction or the Authority Having Jurisdiction's duly appointed representative.

No test or inspection shall be required where a plumbing system, or part thereof, is set up for exhibition purposes and has no connection with a water or drainage system. In cases where it would be impractical to provide the required water or air tests, or for minor installations and repairs, the Authority Having Jurisdiction shall be permitted to make such inspection as deemed advisable in order to be assured that the work has been performed in accordance with the intent of this code. Joints and connections in the plumbing system shall be gastight and watertight for the pressures required by the test.

105.3.1 Defective Systems. An air test shall be used in testing the sanitary condition of the drainage or plumbing system of building premises where there is reason to believe that it has become defective. In buildings or premises condemned by the Authority Having Jurisdiction because of an insanitary condition of the plumbing system, or part thereof, the alterations in such system shall be in accordance with the requirements of this code.

105.3.2 Retesting. Where the Authority Having Jurisdiction finds that the work will not pass the test, necessary corrections shall be made, and the work shall be resubmitted for test or inspection.

105.3.3 Approval. Where prescribed tests and inspections indicate that the work is in accordance with this code, a certificate of approval shall be issued by the Authority Having Jurisdiction to the permittee on demand.

105.4 Connection to Service Utilities. No person shall make connections from a source of energy or fuel to a plumbing system or equipment regulated by this code and for which a permit is required until approved by the Authority Having Jurisdiction. No person shall make connection from a water-supply line nor shall connect to a sewer system regulated by this code and for which a permit is required until approved by the Authority Having Jurisdiction. The Authority Having Jurisdiction shall be permitted to authorize temporary connection of the plumbing equipment to the source of energy or fuel for the purpose of testing the equipment.

106.0 Violations and Penalties.

106.1 General. It shall be unlawful for a person, firm, or corporation to erect, construct, enlarge, alter, repair, move, improve, remove, convert, demolish, equip, use, or maintain plumbing or permit the same to be done in violation of this code.

106.2 Notices of Correction or Violation. Notices of correction or violation shall be written by the Authority Having Jurisdiction and shall be permitted to be posted at the site of the work or mailed or delivered to the permittee or their authorized representative.

Refusal, failure, or neglect to comply with such notice or order within 10 days of receipt thereof, shall be considered a violation of this code and shall be subject to the penalties set forth by the governing laws of the jurisdiction.

106.3 Penalties. A person, firm, or corporation violating a provision of this code shall be deemed guilty of a misdemeanor, and upon conviction thereof, shall be punishable by a fine, imprisonment, or both set forth by the governing laws of the jurisdiction. Each separate day or portion thereof, during which a violation of this code occurs or continues, shall be deemed to constitute a separate offense.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

106.4 Stop Orders. Where work is being done contrary to the provisions of this code, the Authority Having Jurisdiction shall be permitted to order the work stopped by notice in writing served on persons engaged in the doing or causing such work to be done, and such persons shall forthwith stop work until authorized by the Authority Having Jurisdiction to proceed with the work.

106.5 Authority to Disconnect Utilities in Emergencies. The Authority Having Jurisdiction shall have the authority to disconnect a plumbing system to a building, structure, or equipment regulated by this code in case of emergency where necessary to eliminate an immediate hazard to life or property.

106.6 Authority to Condemn. Where the Authority Having Jurisdiction ascertains that a plumbing system or portion thereof, regulated by this code, has become hazardous to life, health, or property, or has become insanitary, the Authority Having Jurisdiction shall order in writing that such plumbing either be removed or placed in a safe or sanitary condition. The order shall fix a reasonable time limit for compliance. No person shall use or maintain defective plumbing after receiving such notice.

Where such plumbing system is to be disconnected, written notice shall be given. In cases of immediate danger to life or property, such disconnection shall be permitted to be made immediately without such notice.

107.0 Board of Appeals.

107.1 General. In order to hear and decide appeals of orders, decisions, or determinations made by the Authority Having Jurisdiction relative to the application and interpretations of this code, there shall be and is hereby created a Board of Appeals consisting of members who are qualified by experience and training to pass upon matters pertaining to plumbing design, construction, and maintenance and the public health aspects of plumbing systems and who are not employees of the jurisdiction. The Authority Having Jurisdiction shall be an ex-officio member and shall act as secretary to said board but shall have no vote upon a matter before the board. The Board of Appeals shall be appointed by the governing body and shall hold office at its pleasure. The board shall adopt rules of procedure for conducting its business and shall render decisions and findings in writing to the appellant with a duplicate copy to the Authority Having Jurisdiction.

107.2 Limitations of Authority. The Board of Appeals shall have no authority relative to interpretation of the administrative provisions of this code, nor shall the board be empowered to waive requirements of this code.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

TABLE 104.5
PLUMBING PERMIT FEES

Permit Issuance

1. For issuing each permit ..... *_____
2. For issuing each supplemental permit ..... *_____

Unit Fee Schedule (in addition to Item 1 and Item 2 above)

1. For each plumbing fixture on one trap or a set of fixtures on one trap (including water, drainage piping, and backflow protection therefore) ..... *_____
2. For each building sewer and each trailer park sewer ..... *_____
3. Rainwater systems – per drain (inside building) ..... *_____
4. For each cesspool (where permitted) ..... *_____
5. For each private sewage disposal system ..... *_____
6. For each water heater, vent, or both ..... *_____
7. For each gas piping system of one to five outlets ..... *_____
8. For each additional gas piping system outlet, per outlet ..... *_____
9. For each industrial waste pretreatment interceptor, including its trap and vent, except kitchen-type grease interceptors functioning as fixture traps ..... *_____
10. For each installation, alteration, or repair of water piping, water treating equipment, or both ..... *_____
11. For each repair or alteration of drainage or vent piping, each fixture ..... *_____
12. For each lawn sprinkler system on one meter including backflow protection devices therefore ..... *_____
13. For atmospheric-type vacuum breakers not referenced in Item 12:
    - One to 5 ..... *_____
    - Over 5, each ..... *_____
14. For each backflow protective device other than atmospheric-type vacuum breakers:
    - Two inches (50 mm) in diameter and smaller ..... *_____
    - Over 2 inches (50 mm) in diameter ..... *_____
15. For each gray water system ..... *_____
16. For initial installation and testing of a reclaimed water system ..... *_____
17. For each annual cross-connection testing of a reclaimed water system (excluding initial test) ..... *_____
18. For each medical gas piping system serving one to five inlet(s)/outlet(s) for a specific gas ..... *_____
19. For each additional medical gas inlet(s)/outlet(s) ..... *_____

Other Inspections and Fees

1. Inspections outside of normal business hours ..... *_____
2. Reinspection fee ..... *_____
3. Inspections for which no fee is specifically indicated ..... *_____
4. Additional plan review required by changes, additions, or revisions to approved plans (minimum charge – ½ hour) ..... *_____

For SI units: 1 inch = 25 mm

* Jurisdiction will indicate their fees here

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

CHAPTER 2
DEFINITIONS

201.0 General.

201.1 Applicability. For the purpose of this code, the following terms have the meanings indicated in this chapter.

No attempt is made to define ordinary words, which are used in accordance with their established dictionary meanings, except where a word has been used loosely, and it is necessary to define its meaning as used in this code to avoid misunderstanding.

202.0 Definition of Terms.

202.1 General. The definitions of terms are arranged alphabetically according to the first word of the term.

203.0 – A –

ABS. Acrylonitrile-butadiene-styrene.

Accepted Engineering Practice. That which conforms to technical or scientific-based principles, tests, or standards that are accepted by the engineering profession.

Accessible. Where applied to a fixture, connection, appliance, or equipment, "accessible" means having access thereto, but which first may require the removal of an access panel, door, or similar obstruction.

Accessible, Readily. Having a direct access without the necessity of removing a panel, door, or similar obstruction.

Air Break. A physical separation which may be a low inlet into the indirect waste receptor from the fixture, appliance, or device indirectly connected.

Air Gap, Drainage. The unobstructed vertical distance through the free atmosphere between the lowest opening from a pipe, plumbing fixture, appliance, or appurtenance conveying waste to the flood-level rim of the receptor.

Air Gap, Water Distribution. The unobstructed vertical distance through the free atmosphere between the lowest opening from a pipe or faucet conveying potable water to the flood-level rim of a tank, vat, or fixture.

Alternate Water Source. Nonpotable source of water that includes but not limited to gray water, on-site treated nonpotable water, rainwater, and reclaimed (recycled) water.

Anchors. See Supports.

Appliance. A device that utilizes an energy source to produce light, heat, power, refrigeration, air conditioning, or compressed fuel gas. This definition also shall include a vented decorative appliance.

Appliance, Low-Heat. A fuel-burning appliance that produces a continuous flue gas temperature, at the point of entrance to the flue, of not more than 1000°F (538°C).

Appliance, Medium-Heat. A fuel-burning appliance that produces a continuous flue gas temperature, at the point of entrance to the flue, of more than 1000°F (538°C) and less than 2000°F (1093°C).

Appliance Categorized Vent Diameter/Area. The minimum vent diameter/area permissible for Category I appliances to maintain a nonpositive vent static pressure when tested in accordance with nationally recognized standards. [NFPA 54:3.3.6]

Appliance Fuel Connector. An assembly of listed semirigid or flexible tubing and fittings to carry fuel between a fuel-piping outlet and a fuel-burning appliance.

Approved. Acceptable to the Authority Having Jurisdiction.

Approved Testing Agency. An organization primarily established for purposes of testing to approved standards and approved by the Authority Having Jurisdiction.

Area Drain. A receptor designed to collect surface or storm water from an open area.

Aspirator. A fitting or device supplied with water or other fluid under positive pressure that passes through an integral orifice or constriction, causing a vacuum.

Authority Having Jurisdiction. The organization, office, or individual responsible for enforcing the requirements of a code or standard, or for approving equipment, materials, installations, or procedures. The Authority Having Jurisdiction shall be a federal, state, local, or other regional department or an individual such as a plumbing official, mechanical official, labor department official, health department official, building official, or others having statutory authority. In the absence of statutory authority, the Authority Having Jurisdiction may be some other responsible party. This definition shall include the Authority Having Jurisdiction's duly authorized representative.

204.0 – B –

Backflow. The flow of water or other liquids, mixtures, or substances into the distributing pipes of a potable supply of water from sources other than its intended source. See Backpressure Backflow and Backsiphonage.

Backflow Connection. An arrangement whereby backflow can occur.

Backflow Preventer. A backflow prevention device, an assembly, or another method to prevent backflow into the potable water system.

Backpressure Backflow. Backflow due to an increased pressure above the supply pressure, which may be due to pumps, boilers, gravity, or other sources of pressure.

Backsiphonage. The flowing back of used, contaminated, or polluted water from a plumbing fixture or vessel into a water supply pipe due to a pressure less than atmospheric in such pipe. See Backflow.

Backwater Valve. A device installed in a drainage system to prevent reverse flow.

Bathroom. A room equipped with a shower, bathtub, or combination bath/shower.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Bathroom, Half. A room equipped with only a water closet and lavatory.

Bathroom Group. Any combination of fixtures, not to exceed one water closet, two lavatories, either one bathtub or one combination bath/shower, and one shower, and may include a bidet and an emergency floor drain.

Battery of Fixtures. A group of two or more similar, adjacent fixtures that discharge into a common horizontal waste or soil branch.

Bedpan Steamer. A fixture that is used to sterilize bedpans by way of steam.

Boiler Blowoff. An outlet on a boiler to permit emptying or discharge of sediment.

Bonding Conductor or Jumper. A reliable conductor to ensure the required electrical conductivity between metal parts required to be electrically connected. [NFPA 70:100 (Part I)]

Bottle Filling Station. A plumbing fixture connected to the potable water distribution system and sanitary drainage system that is designed and intended for filling personal use drinking water bottles or containers not less than 10 inches (254 mm) in height. Such fixtures can be separate from or integral to a drinking fountain and can incorporate a water filter and a cooling system for chilling the drinking water.

Branch. A part of the piping system other than a main, riser, or stack.

Branch, Fixture. See Fixture Branch.

Branch, Horizontal. See Horizontal Branch.

Branch Vent. A vent connecting one or more individual vents with a vent stack or stack vent.

Building. A structure built, erected, and framed of component structural parts designed for the housing, shelter, enclosure, or support of persons, animals, or property of any kind.

Building Drain. That part of the lowest piping of a drainage system that receives the discharge from soil, waste, and other drainage pipes inside the walls of the building and conveys it to the building sewer beginning 2 feet (610 mm) outside the building wall.

Building Drain (Sanitary). A building drain that conveys sewage only.

Building Drain (Storm). A building drain that conveys storm water or another drainage, but no sewage.

Building Sewer. That part of the horizontal piping of a drainage system that extends from the end of the building drain and that receives the discharge of the building drain and conveys it to a public sewer, private sewer, private sewage disposal system, or another point of disposal.

Building Sewer (Combined). A building sewer that conveys both sewage and storm water or other drainage.

Building Sewer (Sanitary). A building sewer that conveys sewage only.

Building Sewer (Storm). A building sewer that conveys storm water or another drainage, but no sewage.

Building Subdrain. That portion of a drainage system that does not drain by gravity into the building sewer.

Building Supply. The pipe is carrying potable water from the water meter or another source of water supply to a building or other point of use or distribution on the lot.

205.0 – C –

Category 1. Activities, systems, or equipment whose failure is likely to cause major injury or death to patients, staff, or visitors. [NFPA 99:3.3.158.1]

Category 2. Activities, systems, or equipment whose failure is likely to cause minor injury to patients, staff, or visitors. [NFPA 99:3.3.158.2]

Category 3. Activities, systems, or equipment whose failure is not likely to cause injury to patients, staff, or visitors, but can cause discomfort. [NFPA 99:3.3.158.3]

Category 3 Vacuum System. A Category 3 vacuum distribution system that can be either a wet system designed to remove liquids, air-gas, or solids from the treated area; or a dry system designed to trap liquid and solids before the service inlet and to accommodate air-gas only through the service inlet. [NFPA 99:3.3.21]

Category 4. Activities, systems, or equipment whose failure would have no impact on patient care. [NFPA 99:3.3.158.4]

Certified Backflow Assembly Tester. A person who has shown competence to test and maintain backflow assemblies to the satisfaction of the Authority Having Jurisdiction.

Cesspool. A lined excavation in the ground that receives the discharge of a drainage system or part thereof, so designed as to retain the organic matter and solids discharging therein but permitting the liquids to seep through the bottom and sides.

Chemical Waste. See Special Wastes.

Chimney. One or more passageways, vertical or nearly so, for conveying flue or vent gases to the outdoors. [NFPA 54:3.3.18]

Chimney, Factory-Built. A chimney composed of listed factory-built components assembled in accordance with the manufacturer's installation instructions to form the completed chimney. [NFPA 54:3.3.18.2]

Chimney, Masonry. A field-constructed chimney of solid masonry units, bricks, stones, listed masonry chimney units, or reinforced Portland cement concrete, lined with suitable chimney flue liners. [NFPA 54:3.3.18.3]

Chimney, Metal. A chimney constructed of metal with a minimum thickness not less than 0.127 inches (3.23 mm) (No. 10 manufacturer's standard gauge) steel sheet.

Chimney Classifications:

Chimney, High-Heat Appliance-Type. A factory-built, masonry, or metal chimney suitable for removing the products of combustion from fuel-burning high-heat appliances producing combustion gases in excess of 2000°F (1093°C), measured at the appliance flue outlet.

Chimney, Low-Heat Appliance-Type. A factory-built, masonry, or metal chimney suitable for removing the products of combustion from fuel-burning low-heat appliances producing combustion gases not in excess of 1000°F (538°C) under normal operating conditions, but

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

capable of producing combustion gases of 1400°F (760°C) during intermittent forced firing for periods up to one hour. Temperatures are measured at the appliance flue outlet.

Chimney, Medium-Heat Appliance-Type. A factory-built, masonry, or metal chimney suitable for removing the products of combustion from fuel-burning medium-heat appliances producing combustion gases, not in excess of 2000°F (1093°C), measured at the appliance flue outlet.

Chimney, Residential Appliance-Type. A factory-built or masonry chimney suitable for removing products of combustion from residential-type appliances producing combustion gases, not in excess of 1000°F (538°C), measured at the appliance flue outlet. Factory-built Type HT chimneys have high-temperature thermal shock resistance.

Circuit Vent. The vent that connects to a horizontal drainage branch and vents two traps to a maximum of eight traps connected into a battery of fixtures.

Clarifier. See Interceptor (Clarifier).

Clear Water Waste. Cooling water and condensate drainage from refrigeration and air-conditioning equipment; cooled condensate from steam heating systems, and cooled boiler blowdown water.

Clinical Sink. A fixture that has the same flushing and cleansing characteristics of a water closet that is used to receive the wastes from a bedpan. Also, known as a bedpan washer.

Coastal High Hazard Areas. An area within the flood hazard area that is subject to high-velocity wave action, and shown on a Flood Insurance Rate Map or other flood hazard map as Zone V, VO, VE or V1-30.

Code. A standard that is an extensive compilation of provisions covering broad subject matter or that is suitable for adoption into law independently of other codes and standards.

Combination Temperature and Pressure-Relief Valve. A relief valve that actuates when a set temperature, pressure, or both is reached. Also, known as a T&P Valve.

Combination Thermostatic/Pressure Balancing Valve. A mixing valve that senses outlet temperature and incoming hot and cold water pressure and compensates for fluctuations in incoming hot and cold water temperatures, pressures, or both to stabilize outlet temperatures.

Combination Waste and Vent System. A specially designed system of waste piping embodying the horizontal wet venting of one or more sinks or floor drains using a common waste and vent pipe adequately sized to provide free movement of air above the flow line of the drain.

Combined Building Sewer. See Building Sewer (Combined).

Combustible Material. A material that, in the form in which it is used and under the conditions anticipated, will ignite and burn; a material that does not meet the definition of noncombustible. [NFPA 54:3.3.64.1]

Commercial Modular System. A drinking water treatment unit system consisting of multiple components attached to a manifold, produced specifically for food service applications, and not intended for use in residential applications.

Common. That part of a plumbing system that is so designed and installed as to serve more than one appliance, fixture, building, or system.

Condensate. The liquid phase produced by condensation of a gas or vapor.

Conductor. A pipe inside the building that conveys storm water from the roof to a storm drain, combined building sewer, or other approved point of disposal.

Confined Space. A room or space having a volume less than 50 cubic feet per 1000 British thermal units per hour (Btu/h) (4.83 m^3/kW) of the aggregate input rating of all fuel-burning appliances installed in that space.

Construction Documents. Plans, specifications, written, graphic, and pictorial documents prepared or assembled for describing the design, location, and physical characteristics of the elements of a project necessary for obtaining a permit.

Contamination. An impairment of the quality of the potable water that creates an actual hazard to the public health through poisoning or the spread of disease by sewage, industrial fluids, or waste. Also, defined as High Hazard.

Continuous Vent. A vertical vent that is a continuation of the drain to which it connects.

Continuous Waste. A drain is connecting the compartments of a set of fixtures to a trap or connecting other permitted fixtures to a common trap.

Copper Alloy. A homogenous mixture of two or more metals in which copper is the primary component, such as brass and bronze.

CPVC. Chlorinated Polyvinyl Chloride.

Critical Care Area. See Patient Care Space, Category 1.

Critical Level. The critical level (C-L or C/L) marking on a backflow prevention device or vacuum breaker is a point conforming to approved standards and established by the testing laboratory (usually stamped on the device by the manufacturer) that determines the minimum elevation above the flood-level rim of the fixture or receptor served at which the device may be installed. Where a backflow prevention device does not bear a critical level marking, the bottom of the vacuum breaker, combination valve, or the bottom of such approved device shall constitute the critical level.

Cross-Connection. A connection or arrangement, physical or otherwise, between a potable water supply system and a plumbing fixture or a tank, receptor, equipment, or device, through which it may be possible for nonpotable, used, unclean, polluted, and contaminated water, or other substances to enter into a part of such potable water system under any condition.

206.0 – D –

Dead Leg. A section of potable water pipe which contains water that has no flow or does not circulate.

Debris Excluder. A device installed on the rainwater catchment conveyance system to prevent the accumulation of leaves, needles, or other debris in the system.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Department Having Jurisdiction. The Authority Having Jurisdiction, including any other law enforcement agency affected by a provision of this code, whether such agency is specifically named or not.

Design Flood Elevation. The elevation of the "design flood," including wave height, relative to the datum specified on the community's legally designated flood hazard map. In areas designated as Zone AO, the design flood elevation is the elevation of the highest existing grade of the building's perimeter plus the depth number (in feet) specified on the flood hazard map. In areas designated as Zone AO where a depth number is not specified on the map, the depth number is taken as being equal to 2 feet (610 mm).

Developed Length. The length along the centerline of a pipe and fittings.

Diameter. Unless specifically stated, "diameter" is the nominal diameter as designated commercially.

Direct-Vent Appliances. Appliances that are constructed and installed so that all air for combustion is derived directly from the outdoors and all flue gases are discharged to the outdoors. [NFPA 54:3.3.5.3]

Domestic Sewage. The liquid and water-borne wastes derived from the ordinary living processes, free from industrial wastes, and of such character as to permit satisfactory disposal, without special treatment, into the public sewer or by means of a private sewage disposal system.

Downspout. The rain leader from the roof to the building storm drain, combined building sewer, or other means of disposal located outside of the building. See Conductor and Leader.

Drain. A pipe that carries waste or waterborne wastes in a building drainage system.

Drainage System. Includes all the piping within public or private premises that conveys sewage, storm water, or other liquid wastes to a legal point of disposal, but does not include the mains of a public sewer system or a public sewage treatment or disposal plant.

Drinking Fountain. A plumbing fixture connected to the potable water distribution system and sanitary drainage system that provides drinking water in a flowing stream so that the user can consume water directly from the fixture without the use of accessories. Drinking fountains should also incorporate a bottle filling station and can incorporate a water filter and a cooling system for chilling the drinking water.

Dry Vent. A vent that does not receive the discharge of any sewage or waste.

Durham System. Soil or waste system in which all piping is threaded pipe, tubing, or other such rigid construction, using recessed drainage fittings to correspond to the types of piping.

207.0 – E –

Effective Ground-Fault Current Path. An intentionally constructed, low impedance electrically conductive path designed and intended to carry current under ground-fault conditions from the point of a ground fault on a wiring system to the electrical supply source and that facilitates the operation of the overcurrent protective device or ground-fault detectors. [NFPA 54:3.3.3.34]

Effective Opening. The minimum cross-sectional area at the point of water supply discharge measured or expressed in terms of (1) diameter of a circle or (2) where the opening is not circular, the diameter of a circle of equivalent cross-sectional area. (This applies to an air gap).

Emergency Floor Drain. A floor drain that does not receive discharge from any fixture drain or indirect waste pipe, and serves to protect from damage where accidental spills, leaks or fixture backups occur.

Essentially Nontoxic Transfer Fluid. Essentially nontoxic at practically nontoxic, Toxicity Rating Class 1 (reference "Clinical Toxicology of Commercial Products" by Gosselin, Smith, Hodge, & Braddock).

Exam Room Sink. A sink used in the patient exam room of a medical or dental office with a primary purpose of the washing of hands.

Excess Flow Valve (EFV). A valve designed to activate when the fuel gas passing through it exceeds a prescribed flow rate. [NFPA 54:3.3.99.3]

Existing Work. A plumbing system or any part thereof that has been installed prior to the effective date of this code.

Expansion Joint. A fitting or arrangement of pipe and fittings that permit the contraction and expansion of a piping system.

Expansion Tank. A vessel used to protect potable water systems from excessive pressure.

208.0 – F –

F Rating. The time period that the penetration firestop system limits the spread of fire through the penetration, where tested in accordance with ASTM E814 or UL 1479.

Fixture Branch. A water supply pipe between the fixture supply pipe and the water distribution pipe.

Fixture Drain. The drain from the trap of a fixture to the junction of that drain with any other drain pipe.

Fixture Fitting. A device that controls and guides the flow of water.

Fixture Supply. A water supply pipe is connecting the fixture with the fixture branch.

Fixture Unit. A quantity in terms of which the load-producing effects on the plumbing system of different kinds of plumbing fixtures are expressed on some arbitrarily chosen scale.

Flammable Vapor or Fumes. The concentration of flammable constituents in the air that exceeds 25 percent of its lower flammability limit (LFL).

Flood Hazard Area. The greater of the following two areas:

(1) The area within a floodplain subject to a 1 percent or greater chance of flooding in any given year.

(2) The area designated as a flood hazard area on a community's flood hazard map, or otherwise legally designated.

AVA Documents
Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021

Flood Level. See Flooded.

Flood-Level Rim. The top edge of a receptor from which water overflows.

Flooded. A fixture is flooded where the liquid therein rises to the flood-level rim.

Flue Collar. That portion of an appliance designed for the attachment of a draft hood, vent connector, or venting system. [NFPA 54:3.3.44]

Flush Tank. A tank located above or integral with water closets, urinals, or similar fixtures for the purpose of flushing the usable portion of the fixture.

Flush Valve. A valve located at the bottom of a tank for flushing water closets and similar fixtures.

Flushometer Tank. A tank integrated within an air accumulator vessel that is designed to discharge a predetermined quantity of water to fixtures for flushing purposes.

Flushometer Valve. A valve that discharges a predetermined quantity of water to fixtures for flushing purposes and is actuated by direct water pressure.

FOG Disposal System. A grease interceptor that reduces nonpetroleum fats, oils, and grease (FOG) in the effluent by separation, mass, and volume reduction.

Fuel Gas. Natural, manufactured liquefied petroleum, or a mixture of these.

209.0 – G –

Gang or Group Shower. Two or more showers in a common area.

Gas Piping. An installation of pipe, valves, or fittings that are used to convey fuel gas, installed on a premise or in a building, but shall not include:

(1) A portion of the service piping.

(2) An approved piping connection 6 feet (1829 mm) or less in length between an existing gas outlet and a gas appliance in the same room with the outlet.

Gas Piping System. An arrangement of gas piping or regulators after the point of delivery and each arrangement of gas piping serving a building, structure, or premises, whether individually metered or not.

General Anesthesia and Levels of Sedation/Analgesia.

Deep Sedation/Analgesia. A drug-induced depression of consciousness during which patients cannot be easily aroused but respond purposefully following repeated or painful stimulation. The ability to independently maintain ventilatory function may be impaired. Patients may require assistance in maintaining a patient airway, and spontaneous ventilation may be inadequate. Cardiovascular function is usually maintained. [NFPA 99:3.3.66.2]

General Anesthesia. A drug-induced loss of consciousness during which patients are not arousable, even by painful stimulation. The ability to independently maintain ventilatory function is often impaired. Patients often require assistance in maintaining a patent airway, and positive pressure ventilation may be required because of depressed spontaneous ventilation or drug-induced depression of neuromuscular function. Cardiovascular function may be impaired. [NFPA 99:3.3.66.1]

Minimal Sedation (Anxiolysis). A drug-induced state during which patients respond normally to verbal commands. Although cognitive function and coordination may be impaired, ventilatory and cardiovascular functions are unaffected. [NFPA 99:3.3.66.4]

Moderate Sedation/Analgesia (Conscious Sedation). A drug-induced depression of consciousness during which patients respond purposefully to verbal commands, either alone or accompanied by light tactile stimulation. No interventions are required to maintain a patient airway, and spontaneous ventilation is adequate. Cardiovascular function is usually maintained. [NFPA 99:3.3.66.3]

Grade. The slope or fall of a line of pipe in reference to a horizontal plane. In drainage, it is usually expressed as the fall in a fraction of an inch (mm) or percentage slope per foot (meter) length of pipe.

Gravity Grease Interceptor. A plumbing appurtenance or appliance that is installed in a sanitary drainage system to intercept nonpetroleum fats, oils, and greases (FOG) from a wastewater discharge and is identified by volume, 30 minute retention time, baffle(s), not less than two compartments, a total volume of not less than 300 gallons (1135 L), and gravity separation. [These interceptors comply with the requirements of Chapter 10 or are designed by a registered design professional.] Gravity grease interceptors are generally installed outside.

Gray Water. Untreated wastewater that has not come into contact with toilet waste, kitchen sink waste, dishwasher waste or similarly contaminated sources. Gray water includes wastewater from bathtubs, showers, lavatories, clothes washers, and laundry tubs. Also, known as grey water, graywater, and greywater.

Gray Water Diverter Valve. A valve that directs gray water to the sanitary drainage system or a subsurface irrigation system.

Grease Interceptor. A plumbing appurtenance or appliance that is installed in a sanitary drainage system to intercept nonpetroleum fats, oil, and greases (FOG) from a wastewater discharge.

Grease Removal Device (GRD). A hydromechanical grease interceptor that automatically, mechanically removes non-petroleum fats, oils and grease (FOG) from the interceptor, the control of which are either automatic or manually initiated.

Grounding Electrode. A conducting object through which a direct connection to earth is established. [NFPA 70:100 (Part I)]

Group Wash Fixture. A lavatory that allows more than one person to utilize the fixture at the same time. The fixture has one or more drains and one or more faucets.

AVA Documents Document Sharing Hub

Full document details: IAPMO ANSI UPC 1-2021