IEC 60092-353

Edition 4.0 2016-09

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Electrical installations in ships – Part 353: Power cables for rated voltages 1 kV and 3 kV

Installations électriques à bord des navires – Partie 353: Câbles d'énergie pour les tensions assignées 1 kV et 3 kV

IEC 60092-353:2016-09(en-fr)

Documents
Document Sharing Hub
Full document details: IEC 60092-353 2016

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue
Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub
La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,…). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished
Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org
Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary
65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

Documents
Document Sharing Hub

Full document details: IEC 60092-353 2016

IEC 60092-353

Edition 4.0 2016-09

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Electrical installations in ships – Part 353: Power cables for rated voltages 1 kV and 3 kV

Installations électriques à bord des navires – Partie 353: Câbles d'énergie pour les tensions assignées 1 kV et 3 kV

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.060.20; 47.020.60

ISBN 978-2-8322-3623-9

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

Documents
Document Sharing Hub

Full document details: IEC 60092-353 2016

CONTENTS

FOREWORD 4
1 Scope and object 6
2 Normative references 6
3 Terms and definitions 7
4 General requirements 7
4.1 Rated voltage 7
4.2 Markings 8
4.2.1 Indication of origin and voltage identification 8
4.2.2 Continuity of marking 8
4.2.3 Core identification 8
5 Constructional requirements 8
5.1 General description 8
5.1.1 Overview 8
5.1.2 Unarmoured cables (excluding 1,8/3 kV) 8
5.1.3 Armoured cables 9
5.2 Conductors 10
5.3 Insulation 10
5.3.1 Material 10
5.3.2 Application 10
5.3.3 Thickness of insulation 10
5.4 Cabling (including fillers and binders) 11
5.5 Inner covering 11
5.5.1 General 11
5.5.2 Thickness of inner covering 11
5.6 Screen 12
5.6.1 Construction 12
5.6.2 Application 13
5.7 Inner sheath 13
5.7.1 Material 13
5.7.2 Application 13
5.7.3 Thickness of inner sheath 13
5.8 Braid armour 13
5.8.1 General 13
5.8.2 Braid wire diameter 14
5.8.3 Coverage density 14
5.8.4 Application of the armour 14
5.9 Outer sheath 14
5.9.1 Material 14
5.9.2 Application 14
5.9.3 Thickness of outer sheath 14
5.9.4 Colour of outer sheath 15
6 Tests – Methods and requirements 15
Annex A (informative) Alternative enhanced insulation thickness for 0,6/1 kV 18
Annex B (informative) Identification of cores of multicore cables 19
B.1 Inscription 19

AVA Documents
Document Sharing Hub
Full document details: IEC 60092-353 2016

B.2 Arrangement of the marks 19
B.3 Spacing and dimensions of the marks 19
B.4 Appearance of inscription 20
Bibliography 21

Figure B.1 – Arrangement of the marks 19

Table 1 – Insulation thickness 11
Table 2 – Thickness of extruded inner covering and fictitious diameters 12
Table 3 – Requirements of drain wire 12
Table 4 – Tests applicable to all cables *(1 of 2)* 15
Table 5 – Additional tests required for halogen-free cables 16
Table 6 – Additional test required for low smoke cables 17
Table 7 – Additional test required for fire resistant cables 17
Table 8 – Additional tests required for specific performances 17
Table A.1 – Alternative enhanced insulation thickness for 0,6/1 kV 18
Table B.1 – Dimensions of the marks 20

Documents
Document Sharing Hub

Full document details: IEC 60092-353 2016

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRICAL INSTALLATIONS IN SHIPS –

Part 353: Power cables for rated voltages 1 kV and 3 kV

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60092-353 has been prepared by Subcommittee 18A: Electric cables for ships and mobile and fixed offshore units of IEC Technical Committee 18: Electrical installations of ships and of mobile and fixed offshore units.

This fourth edition cancels and replaces the third edition published in 2011. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) updated references to IEC 60092-350 for general construction and test methods and IEC 60092-360 for insulating and sheathing materials.

Documents
Document Sharing Hub

Full document details: IEC 60092-353 2016

The text of this document is based on the following documents:

FDIS	Report on voting
18A/399/FDIS	18A/400/RVD

Full information on the voting for the approval of this document can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts of the IEC 60092 series, under the general title *Electrical installations in ships*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

Documents
Document Sharing Hub

Full document details: IEC 60092-353 2016

ELECTRICAL INSTALLATIONS IN SHIPS –

Part 353: Power cables for rated voltages 1 kV and 3 kV

1 Scope and object

This part of IEC 60092 is applicable to shipboard and offshore non radial field power cables with extruded solid insulation, having a voltage rating of 0,6/1 (1,2) kV or 1,8/3 (3,6) kV intended for fixed installations.

Cables designed to maintain circuit integrity during fire are included.

The various types of power cables are given in 5.1. The constructional requirements and test methods are aligned with those indicated in IEC 60092-350, unless otherwise specified in this document.

The object of this document is

– to standardize cables whose safety and reliability is ensured when they are installed in accordance with the requirements of IEC 60092-352 or IEC 61892-4,
– to lay down standard manufacturing requirements and characteristics of such cables directly or indirectly bearing on safety, and
– to specify test methods for checking conformity with those requirements.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-461, *International Electrotechnical Vocabulary – Part 461: Electric cables*

IEC 60092-350:2014, *Electrical installations in ships – Part 350: General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications*

IEC 60092-360, *Electrical installations in ships – Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables*

IEC 60228, *Conductors of insulated cables*

IEC 60331-1, *Tests for electric cables under fire conditions – Circuit integrity – Part 1: Test method for fire with shock at a temperature of at least 830 °C for cables of rated voltage up to and including 0,6/1,0 kV and with an overall diameter exceeding 20 mm*

IEC 60331-2, *Tests for electric cables under fire conditions – Circuit integrity – Part 2: Test method for fire with shock at a temperature of at least 830 °C for cables of rated voltage up to and including 0,6/1,0 kV and with an overall diameter not exceeding 20 mm*

Documents
Document Sharing Hub
Full document details: IEC 60092-353 2016

IEC 60331-21, *Tests for electric cables under fire conditions – Circuit integrity – Part 21: Procedures and requirements – Cables of rated voltage up to and including 0,6/1,0 kV*

IEC 60332-1-2, *Tests on electric and optical fibre cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable – Procedure for 1 kW pre-mixed flame*

IEC 60332-3-22, *Tests on electric cables and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A*

IEC 60445, *Basic and safety principles for man-machine interface, marking and identification – Identification of equipment terminals, conductor terminations and conductors*

IEC 60684-2, *Flexible insulating sleeving – Part 2: Methods of test*

IEC 60754-1, *Test on gases evolved during combustion of materials from cables – Part 1: Determination of the halogen acid gas content*

IEC 60754-2, *Test on gases evolved during combustion of materials from cables – Part 2: Determination of acidity (by pH measurement) and conductivity*

IEC 61034-2, *Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60092-350 and in IEC 60050-461 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

4 General requirements

4.1 Rated voltage

The standard method of designating the rated voltages of cables covered by this document shall take the following form:

$$U_o/U\ (U_m)$$

where

U_o is the rated power-frequency voltage between phase conductor and earth or metallic screen, for which the cable is designed;

U is the rated power-frequency voltage between phase conductors for which the cable is designed;

U_m is the maximum value of the “highest system voltage” for which the equipment (including cable) may be used (see IEC 60038).

All voltages are given as RMS values.

Documents
Document Sharing Hub

Full document details: IEC 60092-353 2016

The standard rated voltages U_o/U (U_m) of the cables considered in this document are the following:

$$U_o/U\ (U_m) = 0{,}6/1\ (1{,}2)\ \text{kV and } 1{,}8/3\ (3{,}6)\ \text{kV}$$

For 0,6/1 (1,2) kV cables, DC voltage up to a maximum of 1,5 times the AC voltage may be used provided that the voltage to earth does not exceed 0,9 kV.

4.2 Markings

4.2.1 Indication of origin and voltage identification

Cables shall comply with IEC 60092-350:2014, 4.1.3, with respect to

a) indication of origin,
b) rated voltage and cable construction (number of cores and cross sectional area of the construction),
c) continuity of marking, and
d) durability/legibility.

4.2.2 Continuity of marking

The marking is deemed to be continuous if the distance between the end of any marking and the beginning of the next does not exceed

a) 550 mm if the marking is on the outer surface of the cable, and
b) 275 mm in all other cases.

4.2.3 Core identification

4.2.3.1 General

Cable cores shall be clearly identified by either colours or numbers.

4.2.3.2 Coloured cores

The core colours shall be in accordance with IEC 60445.

4.2.3.3 Numbered cores – Multicore cables

Identification shall be made by inscription of numbers on each core starting from the centre beginning with 1 in accordance with Annex B.

5 Constructional requirements

5.1 General description

5.1.1 Overview

Shipboard and offshore cables for fixed installations shall be single or multicore cables generally constructed as follows.

5.1.2 Unarmoured cables (excluding 1,8/3 kV)

a) Single-core unarmoured unsheathed cable
   - copper conductor, see 5.2;

Documents
Document Sharing Hub
Full document details: IEC 60092-353 2016

- insulation applied as a single layer of insulating compound of one of the types described in 5.3 with an enhanced thickness equivalent to that of a combined insulation and outer sheath for use in unarmoured cables installed in an adequately protected environment (see 5.3.3 for the thickness).

b) Unarmoured single- or double-sheathed cable

- copper conductor, see 5.2;
- insulation, see 5.3;
- cabling (for multicore cables), see 5.4;
- inner covering (optional, but mandatory when a braided or a metal tape electrostatic screening is applied over the core lay-up), see 5.5;
- electrostatic screening (optional), see 5.6;
- inner sheath (optional), see 5.7;
- outer sheath applied as either one or two layer systems, see 5.9.

5.1.3 Armoured cables

a) Armoured single-sheathed cable with outer sheath only

- copper conductor, see 5.2;
- insulation, see 5.3;
- cabling (for multicore cables), see 5.4;
- inner covering below electrostatic screening (optional, but mandatory when a braided or a metal tape electrostatic screening is applied over the core lay-up), see 5.5;
- electrostatic screening (optional), see 5.6;
- inner covering (optional, but mandatory in case of a braid armour of galvanised steel wires in which case the inner covering shall be extruded), see 5.5;
- braid armour, see 5.8;
- outer sheath applied as either one- or two-layer systems, see 5.9.

NOTE 1 Variable frequency drives induce specific electrical constraints on the connected power cables (for example voltage peaks, harmonics, reflection or earthing method among other electrical stresses).

b) Armoured double-sheathed cable with inner and outer sheath

- copper conductor, see 5.2;
- insulation, see 5.3;
- cabling (for multicore cables), see 5.4;
- inner covering (optional, but mandatory when a braided or a metal tape electrostatic screening is applied over the core lay-up), see 5.5;
- electrostatic screening (optional), see 5.6;
- inner sheath, see 5.7;
- braid armour, see 5.8;
- outer sheath applied as either one or two layer systems, see 5.9.

NOTE 2 The use of a thermoplastic inner sheath (ST2 or SHF1) is not compatible with cross-linking technology of elastomeric outer sheath.

c) Armoured single-sheathed cable with inner sheath only

- copper conductor, see 5.2;
- insulation, see 5.3;
- cabling (for multicore cables), see 5.4;

Documents
Document Sharing Hub
Full document details: IEC 60092-353 2016

- inner covering (optional, but mandatory when a braided or a metal tape electrostatic screening is applied over the core lay-up), see 5.5;
- electrostatic screening (optional), see 5.6;
- inner sheath, see 5.7;
- braid armour, see 5.8.

Cables for installation in spaces where corrosion may occur, for example weather decks, wet locations, battery compartments, refrigeration rooms, should have an outer sheath over the braid, unless the braid itself is corrosion-resistant.

5.2 Conductors

The material, metal coating, class and form of the conductors shall be in accordance with IEC 60092-350. For cables having rated voltage 1,8/3 kV, only circular stranded compacted or non-compacted conductors with a minimum cross-section of 10 mm² are permitted. A separator between conductors and insulation is permitted.

5.3 Insulation

5.3.1 Material

The insulating compounds and their designations shall be as given in IEC 60092-360, as follows:

– for 0,6/1 (1,2) kV cables, types EPR, HEPR, XLPE, HF 90 or S 95 shall be used;
– for 1,8/3 (3,6) kV cables, types only EPR, HEPR, XLPE shall be used.

The insulation system shall consist of one of the options a) to c) as listed in IEC 60092-350:2014, 4.3.1.

5.3.2 Application

The application shall be as detailed in IEC 60092-350:2014, 4.3.2.

5.3.3 Thickness of insulation

The thickness of the insulation shall be as specified in Table 1 hereinafter and meet the requirements of IEC 60092-350:2014, 4.3.3.

For single-core unarmoured unsheathed cables (see 5.1.2 a)), the total insulation thickness shall be the sum of

a) the thickness t_j as specified in Table 1, and
b) the thickness as calculated in accordance with 5.9.3 a), with fictitious diameter $D = d_L + 2\ t_i$ (see also IEC 60092-350:2014, A.3.1 and A.3.2). The total thickness shall meet the requirements of IEC 60092-350:2014, 4.3.3.

Documents
Document Sharing Hub
Full document details: IEC 60092-353 2016

Table 1 – Insulation thickness

Nominal cross sectional area of conductor	0,6/1 kV		1,8/3 kV	
	EPR S 95	HEPR HF90 XLPE	EPR	HEPR XLPE
mm^2	mm	mm	mm	mm
1	1,0	0,7	–	–
1,5	1,0	0,7	–	–
2,5	1,0	0,7	–	–
4	1,0	0,7	–	–
6	1,0	0,7	–	–
10	1,0	0,7	2,2	2,0
16	1,0	0,7	2,2	2,0
25	1,2	0,9	2,2	2,0
35	1,2	0,9	2,2	2,0
50	1,4	1,0	2,2	2,0
70	1,4	1,1	2,2	2,0
95	1,6	1,1	2,4	2,0
120	1,6	1,2	2,4	2,0
150	1,8	1,4	2,4	2,0
185	2,0	1,6	2,4	2,0
240	2,2	1,7	2,4	2,0
300	2,4	1,8	2,4	2,0
400	2,6	2,0	2,6	2,0
500	2,8	2,2	2,8	2,2
630	2,8	2,4	2,8	2,4

NOTE Alternative enhanced insulation thickness can be given in some countries for legal reasons. These alternative values are based on those given in Annex A.

5.4 Cabling (including fillers and binders)

Cores of a multicore cable shall be laid up, and the interstices filled if necessary with fillers, inner covering or inner sheath (outer sheath in the case of unarmoured cables) according to IEC 60092-350:2014, 4.5.

5.5 Inner covering

5.5.1 General

The inner covering, if any, may be extruded (mandatory below galvanized steel wire braid) or lapped. The relevant material and characteristics shall be in accordance with IEC 60092-350:2014, 4.6.

5.5.2 Thickness of inner covering

The values of the (approximate) thickness of extruded inner covering for the calculation of fictitious diameters are given in Table 2.

Documents
Document Sharing Hub

Full document details: IEC 60092-353 2016

Table 2 – Thickness of extruded inner covering and fictitious diameters

Fictitious diameter over laid up cores		Thickness of extruded inner covering
Above mm	Up to and including mm	(approximate value) mm
–	25	1,0
25	35	1,2
35	45	1,4
45	60	1,6
60	80	1,8
80	–	2,0

The values of the (approximate) thickness of lapped covering for the calculation of the fictitious diameters are 0,4 mm for fictitious diameter over laid-up cores up to and including 40 mm and 0,6 mm for larger diameters.

NOTE For the calculation of fictitious diameter, see IEC 60092-350:2014, Annexes A and C.

5.6 Screen

5.6.1 Construction

5.6.1.1 General

The screen, if any, shall be a collective metallic screen and shall be in accordance with IEC 60092-350:2014, 4.4.2, and shall consist of one or more tapes, a braid or a combination of a braid with tape(s).

5.6.1.2 Metal/polyester tape

The laminated electrostatic screening tape shall be applied with the metallic side in electrical contact with a drain wire. The minimum overlap of the laminated tape shall be 15 % of its total width, to ensure coverage in case of bending of the cable. The laminated tape shall be either aluminium bonded to polyester having a minimum thickness of aluminium of 0,008 mm and a minimum thickness of polyester of 0,010 mm, or copper bonded to polyester having a minimum thickness of copper of 0,018 mm and a minimum thickness of polyester of 0,023 mm.

The drain wire shall be composed of a number of strands of tinned annealed copper wires in the case of aluminium laminate tape and either plain or tinned annealed copper wires in the case of copper laminate tape. The drain wire shall have a maximum resistance in accordance with Table 3.

Table 3 – Requirements of drain wire

Nominal area of conductor of the cores mm^2	Maximum drain wire resistance ohm/km
1,0 to 1,5	28,3
2,5 and above	21,2

Polyester tape of either 0,023 mm or 0,050 mm nominal thickness shall be applied over the screen with a minimum overlap of 15 % of its total width.

AVA Documents
Document Sharing Hub

Full document details: IEC 60092-353 2016