IEC 60335-2-110

Edition 1.1 2019-10

CONSOLIDATED VERSION

colour inside

Household and similar electrical appliances – Safety – Part 2-110: Particular requirements for commercial microwave appliances with insertion or contacting applicators

IEC 60335-2-110:2013-09+AMD1:2019-10 CSV(en)

AVA Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

IEC 60335-2-110

Edition 1.1 2019-10

CONSOLIDATED VERSION

colour inside

Household and similar electrical appliances – Safety – Part 2-110: Particular requirements for commercial microwave appliances with insertion or contacting applicators

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 97.040.20

ISBN 978-2-8322-7582-5

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

IEC 60335-2-110

Edition 1.1 2019-10

REDLINE VERSION

colour inside

Household and similar electrical appliances – Safety – Part 2-110: Particular requirements for commercial microwave appliances with insertion or contacting applicators

IEC 60335-2-110:2013-09+AMD1:2019-10 CSV(en)

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

CONTENTS

FOREWORD 4
INTRODUCTION 7
1 Scope 8
2 Normative references 9
3 Terms and definitions 9
4 General requirement 13
5 General conditions for the tests 13
6 Classification 13
7 Marking and instructions 13
8 Protection against access to live parts 18
9 Starting of motor-operated appliances 18
10 Power input and current 19
11 Heating 19
12 Void 19
13 Leakage current and electric strength at operating temperature 19
14 Transient overvoltages 19
15 Moisture resistance 19
16 Leakage current and electric strength 20
17 Overload protection of transformers and associated circuits 20
18 Endurance 20
19 Abnormal operation 21
20 Stability and mechanical hazards 22
21 Mechanical strength 22
22 Construction 24
23 Internal wiring 27
24 Components 27
25 Supply connection and external flexible cords 28
26 Terminals for external conductors 29
27 Provision for earthing 29
28 Screws and connections 29
29 Clearances, creepage distances and solid insulation 29
30 Resistance to heat and fire 29
31 Resistance to rusting 29
32 Radiation, toxicity and similar hazards 29
101 Protection against accessibility to microwave-containing regions 31
Annex AA (informative) Rationales for the microwave barrier and associated leakage tests 40
Bibliography 45

Figure 101 – Test rod for interlock concealment 33
Figure 102 – Arrangement for measurement of microwave leakage 34

AVA Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

Figure 103 – Construction site, overview of different applicator types and their use 35
Figure 104 – Large area contacting applicator without traction drive 36
Figure 105 – Large area contacting applicator with traction drive 37
Figure 106 – Insertion applicator 38
Figure 107 – Small area contacting applicator 39

Table 101 – Specifications for microwave barriers 32

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –

Part 2-110: Particular requirements for commercial microwave appliances with insertion or contacting applicators

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER
This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.

This Consolidated version of IEC 60335-2-110 bears the edition number 1.1. It consists of the first edition (2013-09) [documents 61B/477/FDIS and 61B/483/RVD] and its amendment 1 (2019-10) [documents 61B/613/CDV and 61B/637/RVC as well as 61B/614/CDV and 61B/638/RVC]. The technical content is identical to the base edition and its amendment.

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

This part of International Standard IEC 60335 has been prepared by subcommittee SC61B: Safety of microwave appliances for household and commercial use, of IEC technical committee 61: Safety of household and similar electrical appliances.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This part 2 is to be used in conjunction with the latest edition of IEC 60335-1 and its amendments. It was established on the basis of the fifth edition (2010) of that standard.

NOTE 1 When “Part 1” is mentioned in this standard, it refers to IEC 60335-1.

This part 2 supplements or modifies the corresponding clauses in IEC 60335-1, so as to convert that publication into the IEC standard: Safety requirements for commercial microwave appliances with insertion or contacting applicators.

When a particular subclause of Part 1 is not mentioned in this part 2, that subclause applies as far as is reasonable. When this standard states “addition”, “modification” or “replacement”, the relevant text in Part 1 is to be adapted accordingly.

NOTE 2 The following numbering system is used:

– subclauses, tables and figures that are numbered starting from 101 are additional to those in Part 1;
– unless notes are in a new subclause or involve notes in Part 1, they are numbered starting from 101, including those in a replaced clause or subclause;
– additional annexes are lettered AA, BB, etc.

NOTE 3 The following print types are used:

– requirements: in roman type;
– *test specifications: in italic type;*
– notes: in small roman type.

Words in **bold** in the text are defined in Clause 3. When a definition concerns an adjective, the adjective and the associated noun are also in **bold**.

NOTE 4 The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations can need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 12 months or later than 36 months from the date of publication.

A list of all parts of the IEC 60335 series, under the general title: *Household and similar electrical appliances – Safety*, can be found on the IEC website.

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

INTRODUCTION

It has been assumed in the drafting of this International Standard that the execution of its provisions is entrusted to appropriately qualified and experienced persons.

This standard recognizes the internationally accepted level of protection against hazards such as electrical, mechanical, thermal, fire and radiation of appliances when operated as in normal use taking into account the manufacturer's instructions. It also covers abnormal situations that can be expected in practice and takes into account the way in which electromagnetic phenomena can affect the safe operation of appliances.

This standard takes into account the requirements of IEC 60364 as far as possible so that there is compatibility with the wiring rules when the appliance is connected to the supply mains. However, national wiring rules may differ.

If an appliance within the scope of this standard also incorporates functions that are covered by another part 2 of IEC 60335, the relevant part 2 is applied to each function separately, as far as is reasonable. If applicable, the influence of one function on the other is taken into account.

When a part 2 standard does not include additional requirements to cover hazards dealt with in Part 1, Part 1 applies.

NOTE 1 This means that the technical committees responsible for the part 2 standards have determined that it is not necessary to specify particular requirements for the appliance in question over and above the general requirements.

This standard is a product family standard dealing with the safety of appliances and takes precedence over horizontal and generic standards covering the same subject.

NOTE 2 Horizontal and generic standards covering a hazard are not applicable since they have been taken into consideration when developing the general and particular requirements for the IEC 60335 series of standards. For example, in the case of temperature requirements for surfaces on many appliances, generic standards, such as ISO 13732-1 for hot surfaces, are not applicable in addition to Part 1 or part 2 standards.

An appliance that complies with the text of this standard will not necessarily be considered to comply with the safety principles of the standard if, when examined and tested, it is found to have other features which impair the level of safety covered by these requirements.

An appliance employing materials or having forms of construction differing from those detailed in the requirements of this standard may be examined and tested according to the intent of the requirements and, if found to be substantially equivalent, may be considered to comply with the standard.

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –

Part 2-110: Particular requirements for commercial microwave appliances with insertion or contacting applicators

1 Scope

This clause of Part 1 is replaced by the following.

This International Standard deals with the safety of microwave appliances intended for commercial use, their **rated voltage** being not more than 250 V for single-phase appliances connected between one phase and neutral and 480 V for other appliances.

In general, this standard does not take into account

– persons (including children) whose
  - physical, sensory or mental capabilities; or
  - lack of experience and knowledge

  prevents them from using the appliance safely without supervision or instruction;
– children playing with the appliance.

Appliances covered by this standard incorporate an open-ended **applicator** (as example an overview is given in Figure 103) for treatment of the **load**. They are divided into three types:

– with **insertion applicator**, typically for moisture removal by insertion into holes in floors, walls or ceilings (an example is given in Figure 106);
– with **large area contacting applicator**, typically for drying of floors, walls or ceilings (examples are given in Figure 104 and Figure 105);
– with **small area contacting applicator**, typically for paint removal and spot-heating (an example is given in Figure 107).

NOTE 101 Appliances with **insertion applicator** and with **large area contacting applicator** are **portable appliances**. Appliances with **small area contacting applicator** are **handheld appliances**.

NOTE 102 Appliances that use non-electrical energy are within the scope of this standard. The microwave-related portion is considered **motor-operated**.

NOTE 103 Attention is drawn to the fact that

– these appliances can radiate microwave energy outside a **restricted area** where they are used. The additional requirements specified by national authorities responsible for the protection for non-ionising radiation that the limit of power flux density is 10 W/m^2, averaged over any time period of 6 min, outside this **restricted area** is taken into consideration in this standard;
– these appliances are intended to exclusively treat the **load** in **normal operation**, i.e. this standard does not apply to appliances or systems employing free space microwave propagation;
– for appliances intended to be used in tropical countries, special requirements can be necessary;
– in many countries, additional requirements are specified by the national health authorities, and national authorities responsible for the protection of labour and for non-ionising radiation protection.

NOTE 104 This standard does not apply to

– household microwave ovens, including combination microwave ovens (IEC 60335-2-25);
– commercial microwave ovens with a cavity door, commercial combination microwave ovens with a cavity door and commercial microwave ovens without a cavity door and with transportation means (IEC 60335-2-90);
– industrial microwave heating equipment (IEC 60519-6);
– appliances for medical purposes (IEC 60601-1);

Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

– appliances and equipment for laboratory use (series of IEC 61010);

– appliances intended to be used in locations where special conditions prevail, such as the presence of a corrosive or explosive atmosphere (dust, vapour or gas).

NOTE 105 Some of the specifications and tests in this standard are not applicable for other than 2 450 MHz appliances.

2 Normative references

This clause of Part 1 is applicable except as follows.

Addition:

IEC 60335-2-90, *Household and similar electrical appliances – Safety – Part 2-90: Particular requirements for commercial microwave ovens*

ISO 3864-1, *Graphical symbols – Safety colours and safety signs – Part 1: Design principles for safety signs and safety markings*

ISO 7010, *Graphical symbols – Safety colours and safety signs – Registered safety signs*

3 Terms and definitions

This clause of Part 1 is applicable except as follows.

3.1.7 *Addition:*

Note 101 to entry: The **rated frequency** is the input frequency.

3.1.9 *Replacement:*
normal operation
heating operation of the **appliance** under the following conditions:

The **appliance** is operated according to the manufacturer's instructions for **intended use**. However, using a typical load for **intended use** may be impractical, since it may be part of a building, unless the manufacturer makes useful and realistic such **loads** available for the tests. If that is not the case, the appliance is operated under the following conditions:

The initial temperature of the test load which is used for microwave energy absorption shall be (20 ± 5) °C.

The highest generator power settings are to be used.

Appliances with an **insertion applicator** for moisture removal are operated by insertion into holes in floor, wall or ceiling structures under the following conditions:

a) The test load consists of a metal tank filled with water, having an open top water surface exceeding that of the horizontal dimensions of the appliance by at least 70 mm on all sides and having a water column height of at least 150 mm plus the length of the longest insertion distance of the **insertion applicator**. At the top sides of the tank there are horizontal supports of a **microwave-transparent** material, with a suitable opening for the applicator antenna. The water level is adjusted so that the distance from the housing of the appliance to the test load is the same as in its **intended use**.

Note 101 to entry: If it is obvious that good microwave impedance matching of the **insertion applicator** can be obtained only if the hole into which it is inserted is not water-filled, a sleeve or similar of a highly **microwave transparent** material such as PTFE is used around the **insertion applicator**. If wave propagation in the axial direction occurs in the test set-up and the manufacturer can show that it is not possible in actual use, or monitoring devices then shut down the **insertion applicator**, a thin-wall plastic tube with inner diameter corresponding to the maximum hole diameter according to the manufacturer's specification can be used.

AVA Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

b) Appliances with **large area contacting applicator** for drying of floor, wall or ceiling structures are operated under the following conditions: the test load consists of a metal tank filled with water, having an open top water surface exceeding that of the horizontal dimensions of the appliance by at least 70 mm on all sides and having a water column height of at least 150 mm. At the top of two opposite tank sides there are horizontal supports of a **microwave-transparent** material, extending just so far inwards that the **traction drive** rests on the support. The water level is adjusted so that the distance from the **applicator** to the test load is the same as in its **intended use**. The proper reversal function of the **traction drive** is tested under the following conditions: the appliance is operated on a horizontal plywood surface with a thickness of 20 mm and an area sufficient to allow back and forth movement between blocks representing walls.

Note 102 to entry: If needed for representative operation of the appliance, the horizontal supports are extended as to activate the mechanical **microwave interlocks**.

Appliances with **small area contacting applicator** for paint removal and spot-heating are operated under the following conditions:

The test load consists of a grinding wheel or grinding block made of fine-grained silicon carbide at least 15 mm in thickness, and its length and width exceeding the corresponding dimensions of the applicator opening by at least 30 mm; however this test load shall be so large that it can be air-cooled from the underside without the appliance being influenced.

3.101
microwave appliance with insertion, large or small area contacting applicator
commercial appliance using electromagnetic energy in one or several of the ISM frequency bands between 300 MHz and 30 GHz, for supplying energy to an external **load** which is heated so that a resulting process of drying, moisture transport which may result in forces due to formation of steam, decomposition or chemical modification, melting, or termination of organisms such as bacteria or fungus occurs

Note 1 to entry: ISM frequency bands are the electromagnetic frequencies established by the ITU and reproduced in CISPR 11.

Note 2 to entry: Food and beverages are not **loads** in the meaning of this standard.

3.102
applicator
structure which applies the microwave energy to the **load**

3.103
load
object to be treated into which the **applicator** is introduced or put in close position to

3.104
microwave transparency
property of a material having negligible absorption and reflection of microwaves

Note 1 to entry: The relative permittivity of a **microwave transparent** material is less than 7 and the relative loss factor is less than 0,015.

3.105
insertion applicator
applicator for insertion into the **load**, in which all **available microwave power** is intended to be absorbed

3.106
large area contacting applicator
applicator with a metallic enclosure, having at least one geometric non-metallic opening through which microwave energy is applied to a closely located external **load** in which all **available microwave power** is intended to be absorbed

Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

3.107
small area contacting applicator
applicator with a metallic enclosure, having at least one geometric non-metallic opening or appropriate device through which microwave energy is applied to a very closely located external **load** in which all **rated microwave power** is intended to be absorbed

3.108
rated microwave power output
microwave power output assigned to the appliance by the manufacturer

Note 1 to entry: This can be lower than the **available microwave power**, due to intentional microwave power losses in microwave absorbers (see Note in 101.1) and coaxial cables acting for protection of the microwave generator of **small area contacting applicators** (see 22.101).

3.109
available microwave power
the microwave generator nominal output under impedance matched condition which is obtained by the generator manufacturer specification and measurement of its electrical input to the generator in the appliance during the first 10 s of operation at maximum power

Note 1 to entry: Magnetrons will typically have a stationary power output 3 s after energising.

3.110
instructed person
person who is sufficiently instructed and monitored to know how to avoid any danger caused by the operation of a microwave appliance with **insertion applicator**, **large area contacting applicator**, or **small area contacting applicator**

3.111
skilled person
person with suitable professional education, knowledge and experience to discern and to avoid any danger caused by the operation of a microwave appliance with **insertion applicator**, **large area contacting applicator**, or **small area contacting applicator**

3.112
ordinary person
person who is neither a **skilled person** nor an **instructed person**

3.113
traction drive
means or system used to accomplish movement of an appliance with **large area contacting applicator** on a floor

3.114
microwave enclosure
overall structure that is intended to confine the microwave energy

Note 1 to entry: Barriers mounted outside the **microwave enclosure** are not considered a part of it.

3.115
microwave barrier
microwave transparent part of the microwave appliance that is mounted outside the **microwave enclosure** for limiting access into it and can only be removed with the aid of **tools**

Note 1 to entry: A **microwave barrier** can be mounted between the **microwave enclosure** and the external cover of the appliance.

Note 2 to entry: Devices such as an array of metal chains or hinged metal plates at the periphery of the opening of an **applicator** intended to reduce microwave leakage are not considered **microwave barriers**.

Note 3 to entry: **Microwave barriers** cannot be hinged or flexed.

Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

3.116
microwave guard
constructive part of the appliance that is mounted outside or at the **microwave enclosure** for reducing microwave leakage by shielding and/or absorption and can only be removed with the aid of **tools**

Note 1 to entry: **Microwave guards** can move or open when the **applicator** is brought into contact with the **load**.

Note 2 to entry: Devices such as an array of metal chains or hinged metal plates at the periphery of the opening of an **applicator** intended to reduce microwave leakage are considered **microwave guards**.

3.117
maintenance door
constructive part of the appliance that can be opened or removed with the aid of **tools** to get access for service and repair

3.118
microwave interlock
device or system that prevents the operation of the microwave generator if conditions of excessive microwave leakage occur or are likely to occur

Note 1 to entry: Examples of **microwave interlock** are switches which stop the microwave power when a contacting **applicator** is lifted up or an **insertion applicator** is removed from its **load** during operation, and an integral leakage monitor which does the same if there is insufficient proximity between an **applicator** and the **load** or if an attempt is made to start the appliance without a **load**.

3.119
intended use
any use of the appliance which is reasonably foreseeable, as described in the user instructions, and which is consistent with such activities as operating, starting, stopping, connecting to or disconnecting from the supply mains

3.120
control
any control device requiring the operator's actuation to perform specific functions

3.121
viewing opening
opening into the **applicator** through which the treatment can be visually monitored

3.122
restricted area
the space where the operation of the equipment takes place, plus any area outside this where the exposure level from the equipment may exceed 10 W/m^2, averaged over any 6 min

Note 1 to entry: The **restricted area** is determined by measuring the microwave leakage through floor, wall or ceiling structures of the treatment zone. The thickness of the **load** in the radially outgoing direction from the **applicator** is considered only if the **load** is accessible from behind for microwave leakage measurements in **normal operation**.

3.123
biased-off switch
switch that automatically returns to the **off-position** when its actuating member is released

3.124
start switch
biased-off switch that shall be actuated by the operator before the **operation switch** will function

Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

3.125
operation switch
biased-off switch designed so that it will automatically disconnect the microwave generator or the supply main circuit when the operator's actuating force is removed

4 General requirement

This clause of Part 1 is applicable except as follows.

4.101 *Instead of the requirements on supervision of the **microwave interlocks** by monitored microwave interlocks as in IEC 60335-2-90, this standard applies the concepts of **restricted area** and microwave leakage checks of **microwave interlock** function for l**arge area contacting applicators** and **insertion applicators** – and **start switch** as well as **operation switch** for **small area contacting applicators**.*

5 General conditions for the tests

This clause of Part 1 is applicable except as follows.

5.3 *Modification:*

Instead of carrying out the tests in the order of clauses, the following sequence of clauses and subclauses applies: 32, 22.107, 101, 7 to 17, 20, 21, 18, 19, 22 (except 22.107), 23 to 31.

NOTE 101 Clause 101 deals with the protection against leakage by basic design of **microwave enclosures**; Clause 22 deals with the additional requirements applicable when handling and against improper handling of the appliance, and against other hazards caused by the microwaves; Clause 32 deals with the leakage measurement instrumentation and handling, plus limiting values.

5.101 *Addition:*

The microwave-related portion of the appliance is considered **motor-operated**.

6 Classification

This clause of Part 1 is applicable except as follows.

6.1 *Modification:*

Microwave appliances shall be **class I**.

6.2 *Addition:*

Large area contacting applicators and **insertion applicators** shall be at least IPX1. **Small area contacting applicators** shall be at least IPX5.

7 Marking and instructions

This clause of Part 1 is applicable except as follows.

7.1 *Modification:*

Add the following new dashed item and text before the last dashed item of Part 1:

– substance of the following warnings, if applicable:

Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

– WARNING: Switch off and remove plug from mains before adjusting, cleaning or if the cord is entangled or damaged.
– WARNING: Read the instruction sheet.
– WARNING: Keep the flexible supply cord away from the microwave-energised parts.

Where appropriate IEC/ISO symbols or pictograms are available, they may be used.

Add the following new text before the compliance paragraph of Part 2-110:

Where appropriate, appliances shall be marked with symbols ISO 7000-0434A (2004-01) and IEC 60417-6167 (2012-07).

Addition:

Appliances shall be marked with the nominal frequency in megahertz of the ISM band in which they operate.

Appliances shall be marked with the **rated microwave power output**.

Appliances shall be marked on an affixed inspection tag or similar, with the date when the latest complying microwave leakage and function test in accordance with the service manual was carried out.

Compliance is checked by inspection.

7.6 *Addition:*

[symbol IEC 60417-6166 (2012-07)] caution, non-ionizing radiation

[symbol IEC 60417-6167 (2012-07)] keep out of microwave radiation

[symbol ISO 7010-P004 (2011-05)] no thoroughfare

7.12 *Addition:*

The instructions shall include the substance of the following.

– WARNING: If **microwave barriers** or **microwave guards** are damaged, the appliance must not be operated until repairs by a **skilled person** have been carried out;
– WARNING: It is hazardous for anyone other than a **skilled person** to carry out any service or repair operation that involves the removal of any cover or barrier which gives protection against exposure to microwave energy;
– if smoke is observed, switch off or unplug the appliance;

AVA Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

– failure to maintain the appliance in a clean condition could lead to deterioration that could adversely affect the life of the appliance and possibly result in a hazardous situation;

– the appliance shall not be cleaned with a water jet.

~~The substance of the following warnings, if applicable, shall be placed in a prominent position on the appliance. The letters, which may be in upper or lower case, shall be a minimum of 3 mm high, in black on a yellow background. Where appropriate IEC/ISO symbols or pictograms are available, they may be used. Markings or symbols giving cautionary information shall be located close to the hazard.~~

~~– WARNING: Switch off and remove plug from mains before adjusting, cleaning or if the cord is entangled or damaged.~~

~~– WARNING: Read the instruction sheet.~~

~~– WARNING: Keep the flexible supply cord away from the microwave-energised parts.~~

~~A microwave warning sign (IEC 60417-5140 (2003-04)) of a size specified in IEC 60417, shall be placed in a location where any **microwave barrier** or **microwave guard** is visible, or near the opening in the **microwave barrier** of a **contacting applicator** under which there is a **load**.~~

~~The warning text shall include the substance of the following:~~

~~WARNING~~

~~MICROWAVE ENERGY~~

~~DO NOT INSERT THE HAND OR FOREIGN OBJECTS~~

~~The same type of warning sign shall be placed at **viewing openings** with holes larger than diameter 12 mm and which are not protected by visually transparent protective devices. A warning not to insert objects shall also be given.~~

Appliances shall be operated only by **instructed persons** or **skilled persons**.

An instruction sheet shall be supplied with the appliance.

The instructions shall include:

a) those warnings required to be marked on the appliance together with further explanation, where appropriate;

b) specifications of the **load** surface irregularities (non-flatness) with which the appliance may be used;

c) that the appliance shall not be used in standing water;

d) advice on the use and type of extension cords to be used (not lighter than required in 25.7);

e) instructions for fitting and use of attachments, if any;

f) the substance of the following, where appropriate:

WARNING: If parts of **viewing openings**, **microwave barriers**, **microwave guards**, the housing or any other means named by the manufacturer are damaged, the appliance shall not be operated until it is repaired by a **skilled person**. Until repairs are carried out, the

Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

appliance shall be set in a permanent non-operational condition (e.g. with key switch, code-card or similar devices). Further details are included in the instructions for use.

The **instructed persons** shall regularly, but at a minimum of once a year, be instructed by a **skilled person**. A record of the instruction provided shall be required.

1) Training
   - Read the instructions carefully. Be familiar with the **controls** and the proper use of the appliance.
   - Never allow people unfamiliar with these instructions to use the appliance.
2) Preparation
   - Thoroughly inspect the area where the appliance is to be used and remove all foreign objects.
3) Operation
   - Operate the appliance only in daylight or in good artificial light.
   - The main switch key shall not be left with the appliance when it is unattended.
   - The key shall be stored in a safe place.
   - Use extreme caution when reversing or pulling an operating **insertion applicator** or **large area contacting applicator** towards you.
   - Overheating of potentially flammable **loads** such as wood and some composite materials may be locally and internally heated to charring, which may in turn cause the microwave absorption rate to increase so that a fire occurs. The microwave power setting may need to be reduced and the treatment shall be constantly attended. Attention shall also be paid to the risk of a delayed hazardous condition.
   - If smoke is observed, switch off the appliance, contain the fire by an extinguisher, pay attention to the risk of recurrence and see to it that the overheated region does not expand to unattended spaces.
   - Never operate the appliance with defective **microwave barriers** or **microwave guards**, or without other safety devices in place.
   - Switch on the appliance according to instructions and with all parts of your body which are not used for correct handling of the appliance well away from the applicator.
   - Do not put hands or feet near or under applicators, **microwave barriers** or **microwave guards**.
   - Pull the plug from the socket:
     – before clearing a blockage;
     – before checking, cleaning or working on the appliance;
     – after striking a foreign object. Inspect the appliance and if damaged do not operate it until it has been repaired by a **skilled person**.

7.14 *Addition:*

The warning specified in 7.12 shall be in lettering at least 3 mm high.

The warning specified in 7.101 and 7.102 shall be in lettering at least 5 mm high.

The letters of the substance of the warnings of the penultimate dashed item of 7.1, which may be in upper or lower case, shall be a minimum of 5 mm high, in black on a yellow background.

The height of the triangle of symbol ISO 7000-0434A (2004-01) and the height of symbol IEC 60417-6167 (2012-07) shall be at least 50 mm.

Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

The diameter of symbol ISO 7010-P004 (2011-05) and the height of the triangle of symbol IEC 60417-6166 (2012-07) required by 7.102 shall be at least 150 mm.

Symbols ISO 7000-0434A (2004-01), IEC 60417-6166 (2012-07) and ISO 7010-P004 (2011-05) shall comply with ISO 3864-1, but only with the specified colour requirements.

7.15 *Addition:*

The substance of the warnings of the penultimate dashed item shall be placed in a prominent position on the appliance.

Symbol ISO 7000-0434A (2004-01) and symbol IEC 60417-6167 (2012-07) shall be placed adjacent to each other in a location where any **microwave barrier** or **microwave guard** is visible, or near the opening in the **microwave barrier** of a **contacting applicator** under which there is a **load**.

The same symbols shall be placed at **viewing openings** with holes larger than diameter 12 mm and which are not protected by visually transparent protective devices.

Markings or symbols giving cautionary information shall be located close to the hazard.

7.101 The service or repair manual shall include the substance of the following:

– WARNING: The appliance shall comply with requirements of Clauses 101 and 32 after every repair and according to the instructions of the manufacturer.

Attention: Persons shall not be exposed to excessive emitted microwave energy from the microwave generator. All connections, waveguides, flanges, seals, contacts, etc. of the **applicator**, **microwave enclosure**, **microwave barriers** and **microwave guards** shall be safely constructed so that the microwave leakage does not exceed the allowed limit. Operation of the appliance without a microwave absorbing **load** shall be avoided. The appliance shall be regularly maintained and kept in a good condition to ensure that microwave leakage does not exceed the allowed limit.

In addition, the service manual shall specify the following:

– the presence of user instructions is to be checked;
– a microwave leakage check is to be made at least every 100 h of usage or at shorter intervals, which shall be stated in the service manual;
– when the microwave leakage check is made, all **microwave interlocks** are to be checked and a test of the proper function of any built-in leakage monitor being a part of a **microwave interlock** is also made according to instructions which shall be given in the service manual;
– that the appliance shall be marked on an affixed inspection tag or similar, with the date when the latest complying microwave leakage and function test in accordance with the paragraph above was carried out.

NOTE A test of a built-in leakage monitor can be made firstly by disabling its 20 s time constant, then making other **microwave interlocks** inoperable and then finally slowly lifting the **large area contacting applicator** during **normal operation**. **Insertion applicators** are tested in the same manner.

7.102 The following operator instructions apply for protection of the general public against excessive microwave exposure when operating appliances with **insertion applicator** or **large area contacting applicator**:

– The operator shall have access to an instrument according to Clause 32.
– Inspect the walls, floors or ceilings that are to be treated for the presence of metal objects such as long nails, electrical cables, water pipes and air ducts. These may firstly create local overheating and secondly act as antennas and transport microwave energy along

AVA Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

The microwave power setting may need to be reduced and particular attention is to be paid to possible microwave leakage outside what is typically considered the **restricted area**.

– Ensure that only the operator can be present in the **restricted area**.

– The boundaries of the **restricted area** are determined by measuring the power flux density with an instrument as specified in Clause 32. An initial measurement series is made with the appliance located in the most onerous position with respect to expected boundaries of the **restricted area**. The instrument time constant of 2 s to 3 s is then used. The locations where the largest readings have been made are then to be re-examined, using a longer averaging time up to 6 min.

– Any measurement results shall be recorded in a journal for each job in the same building. In addition to the journal, a plot of the location(s) of the appliance shall be included as well as the point of measurements. For this purpose a copy of the plan drawing may be used.

– Since the boundaries of the **restricted area** may change during **normal operation** the boundaries shall be re-determined by several measurements of power flux density with an instrument as specified in Clause 32.

– In case of doubt or missing relevant information about the construction of the building the **restricted area** shall be enlarged.

~~– The **restricted area** shall be made inaccessible and be clearly marked. The symbol (see IEC 60417-5140 (2003-04)) below shall be used and the substance of the following shall also be included along with the symbol:~~

NOTE Examples for how to make the **restricted area** inaccessible are: locking of doors of rooms lying in the **restricted area** or setting up a barrier installation. The mechanical stability requirements on barrier installations are under consideration. However, it is not possible to insert test probe B of IEC 61032 through the barrier installation.



~~WARNING~~

~~MICROWAVE ENERGY~~

~~DO NOT ENTER~~

– The **restricted area** shall be made inaccessible and be clearly marked with symbol ISO 7010-P004 (2011-05) and symbol IEC 60417-6166 (2012-07).

Compliance is checked by inspection.

8 Protection against access to live parts

This clause of Part 1 is applicable.

9 Starting of motor-operated appliances

This clause of Part 1 is applicable except as follows.

9.1 *Addition:*

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

Motors of the **traction drive** shall start under all voltage conditions that may occur in use.

Compliance is checked by starting the motor three times at a voltage equal to 0,85 times ***rated voltage****, the motor being at room temperature at the beginning of the test.*

The motor is started each time under the conditions occurring at the beginning of ***normal operation*** *or, for automatic appliances, at the beginning of the normal cycle of operation. The motor shall be allowed to stop between successive starts. For appliances provided with motors having other than centrifugal starting switches, the test is repeated at a voltage equal to 1,06 times* ***rated voltage****.*

In all cases, the motor shall start and it shall function in such a way that safety is not affected and overload protection devices of the motor shall not operate.

10 Power input and current

This clause of Part 1 is applicable.

11 Heating

This clause of Part 1 is applicable except as follows.

11.7 *Modification:*

Appliances with a ***contacting applicator*** *for drying of floor, wall or ceiling structures, and appliances with an* ***insertion applicator*** *for moisture removal by insertion into holes in floor, wall or ceiling structures are operated as specified in 3.1.9 until steady conditions are established.*

12 Void

13 Leakage current and electric strength at operating temperature

This clause of Part 1 is applicable except as follows.

13.2 *Modification:*

The last sentence of the fourth paragraph beginning with "*For appliances intended to be connected in star connection only, …*" is deleted.

NOTE 101 An electronic power converter with a supply of more than one phase can be damaged in most cases.

14 Transient overvoltages

This clause of Part 1 is applicable.

15 Moisture resistance

This clause of Part 1 is applicable.

Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

16 Leakage current and electric strength

This clause of Part 1 is applicable except as follows.

16.101 The windings of the power transformer that supplies the magnetron shall have adequate insulation.

Compliance is checked by the test of 16.101.1 for switch mode power supplies and by the test of 16.101.2 for other power transformers.

16.101.1 *The insulation between the primary and secondary windings of switch mode power supply transformers is subjected for 1 min to a voltage of substantially sinusoidal waveform and having a frequency of 50 Hz or 60 Hz. The value of the voltage 1,414 times the peak value of the secondary* ***working voltage*** *plus 750 V, with a minimum of 1 250 V.*

There shall be no breakdown between windings or between adjacent turns of the same winding.

16.101.2 *Twice the* ***working voltage*** *is induced in the secondary winding of the transformer by applying a sinusoidal voltage having a frequency higher than* ***rated frequency*** *to the primary terminals.*

The duration of the test is

– *60 s, for frequencies up to twice the* ***rated frequency****, or*

– $120 \times \frac{\text{rated frequency}}{\text{test frequency}}$ s *, with a minimum of 15 s, for higher frequencies.*

NOTE The frequency of the test voltage is higher than the **rated frequency** to avoid excessive excitation current.

A maximum of one-third of the test voltage is applied and is then rapidly increased without creating transients. At the end of the test, the voltage is decreased in a similar manner to approximately one-third of its full value before switching off.

There shall be no breakdown between windings or between adjacent turns of the same winding.

17 Overload protection of transformers and associated circuits

This clause of Part 1 is applicable except as follows.

Addition:

The tests are not carried out on the power transformer that supplies the magnetron and its associated circuits, these are checked during the tests of Clause 19.

18 Endurance

This clause of Part 1 is replaced by the following.

Microwave barriers, **microwave guards** and other associated parts shall be constructed to withstand wear that may be expected in normal use.

Compliance is checked by the following test.

Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

__Microwave barriers__, __microwave guards__ and other associated parts that are manipulated or accessed by an __instructed person__ multiple times on a daily basis for inspection, __load__ correction or similar shall be subjected to 10 000 cycles of operation.

__Microwave barriers__, __microwave guards__ and other associated parts that are regularly manipulated or accessed for servicing purposes on a daily basis or less shall be subjected to 300 cycles of operation.

If there are more than one identical such barrier, guard or similar, only one is tested.

The number of operations is 6 cycles per 1 min or the maximum quantity that is given for the construction.

After the test, the microwave leakage shall not exceed the limit specified in Clause 32 and __microwave barriers__, __microwave guards__ and other associated parts shall still function.

NOTE 101 **Controls** can be rendered inoperative in order to carry out the test.

NOTE 102 Components, the deterioration of which does not impair compliance with this standard, can be replaced in order to complete the test.

19 Abnormal operation

This clause of Part 1 is applicable except as follows.

19.11.2 *Addition:*

The cathode to anode circuit of a magnetron is open-circuited and short-circuited in turn. If one of these fault conditions results in an input current that increases with decreasing voltage, the test is carried out with the appliance supplied at 0,94 times __rated voltage__. However, if the input current increases more than proportionally with voltage, the appliance is supplied at 1,06 times __rated voltage__.

The filament of a magnetron is not short-circuited.

19.101 *The __traction drive__ of appliances with __contacting applicator__ is defeated and the appliance is then operated on a horizontal metal surface exceeding that of the horizontal dimensions of the appliance by at least 70 mm on all sides, instead of the normal load.*

The period of operation is the maximum time allowed by the timer or until steady conditions are established, whichever is shorter.

The test in 32.101 is then made, without rod.

19.102 *Appliances with __large area contacting applicator__ or __small area contacting applicator__ are operated with __controls__ set at the most unfavourable position and placed on a horizontal metal surface exceeding that of the horizontal dimensions of the appliance by at least 70 mm on all sides, instead of the normal load.*

Appliances with __small area contacting applicator__ are in addition operated with __controls__ set at the most unfavourable position and held in free space, instead of at the normal load.

Appliances with __insertion applicator__ are operated with __controls__ set at the most unfavourable position and placed in a metal tube with a metal bottom and a metal ring at the side of insertion with a diameter and length exceeding the dimensions of the part of the appliance intended to be inserted, instead of the normal load.

AVA Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

The period of operation of appliances is the maximum time allowed by the timer or until steady conditions are established, whichever is shorter.

The test in 32.101 is then made, without rod.

19.103 *Appliances are operated under **normal operation** with the timer or other **controls** that operate in normal use short-circuited.*

NOTE If the appliance is provided with more than one **control**, these are short-circuited in turn.

19.104 *Appliances are operated under **normal operation** and with any single-fault condition simulated that is likely to occur. The **controls** are adjusted to their most unfavourable setting and appliances with **contacting applicator** and **insertion applicator** are operated for the maximum time allowed by the timer or stationary conditions or 90 min, whichever is shorter.*

NOTE Examples of fault conditions are

– blocking of air openings in the same plane;
– locking the rotor of motors if the locked rotor torque is smaller than the full load torque;
– locking moving parts liable to be jammed.

19.105 *The position switches of the reversal control of the **traction drive** of appliances with **large area contacting applicator** are defeated and the appliance is then operated as in 3.1.9.*

The period of operation is the maximum time allowed by the timer or until steady conditions are established, whichever is shorter.

20 Stability and mechanical hazards

This clause of Part 1 is applicable except as follows.

20.1 *Addition:*

***Maintenance doors** which can be opened, lids and accessories shall be placed in the most unfavourable position.*

20.2 *Addition after the first paragraph:*

This is also to be applied on operating elements i.e. handles or hand wheels.

20.101 Protective enclosures according to 20.2 shall not be **detachable** except where

– an appropriate interlock prevents operation of motors or fans without protective enclosures;
– it is a solid part of the housing of the appliance.

Compliance is checked by inspection.

21 Mechanical strength

This clause of Part 1 is applicable except as follows.

21.101 *Appliances with **large area contacting applicator** for a horizontal **load**, and with **insertion applicator** intended for vertical insertion are placed on a rigid floor, as in normal use.*

Documents
Document Sharing Hub
Full document details: IEC 60335-2-110-2019

A force of 140 N or the maximum force that can be applied without tilting the appliance, whichever is smaller, is then applied in a direction perpendicular to the ***load*** *surface, to the free edges of* ***microwave barriers*** *and non-movable* ***microwave guards****.*

This test is carried out 10 times. There shall be no mechanical deformation.

Appliances with ***large area contacting applicator*** *for a vertical* ***load****, and with* ***insertion applicator*** *intended for horizontal insertion are placed against a rigid wall, as in normal use. A force corresponding to 4 times the mass of the appliance is then applied vertically to the outer part of the appliance and then vertically to the free edges of* ***microwave barriers*** *and non-movable* ***microwave guards****, for 1 min.*

The appliance shall not fall down. It shall also comply with Clause 32.

Handheld ***small area contacting applicators*** *are placed against a rigid object, as in normal use. A force of 140 N is then applied axially, for 1 min.*

There shall be no mechanical deformation.

21.102 *The outside surface of* ***microwave barriers*** *and* ***microwave guards*** *and visually transparent protective devices over or inside* ***viewing openings*** *of appliances with* ***large area contacting applicator*** *and with* ***insertion applicator*** *are subjected to three impacts, each having an energy of 3 J. These impacts are applied to the central parts of the barriers and may be at the same point.*

The impact is applied by means of a steel ball having a diameter of 50 mm and a mass of approximately 0,5 kg. The ball is suspended by a suitable cord that is held in the plane of the barrier. The ball is allowed to fall as a pendulum through the distance required to strike the surface with the specified impact energy.

Openable ***microwave guards*** *are then opened and their inner surfaces are subjected to three similar impacts.*

NOTE The test is not made at accessible locations with removed **microwave barriers**.

Any chokes and microwave absorbers on ***microwave guards*** *are further tested by being subjected to three similar impacts. The impacts are made at three different locations.*

Appliances with ***small area contacting applicator*** *are held as in normal use. The outside surface of* ***microwave guards*** *of appliances with* ***small area contacting applicator*** *is subjected to a force of corresponding to 5 times the mass of the appliance or 20 N, whichever is smaller.*

The appliance shall then comply with Clause 32.

21.103 *The power supply of the* ***small area contacting applicator*** *is placed in any position up to 1 m above the floor allowing the* ***small area contacting applicator*** *to fall down on a hardwood base having a thickness of 50 mm and being located where the* ***applicator*** *will hit it when dropped from a height of 1 m above the floor, with the cord to the power supply intact.*

The ***applicator*** *is then dropped onto the hardwood base.*

This test is carried out five times, attempting to position the ***applicator*** *so that its major axis is horizontal and so that a different part of it is exposed to the impact each time.*

The ***applicator*** *is then dropped five times attempting to position with its major axis vertically, with its active end pointing downwards.*

AVA Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

*The **applicator** shall not be damaged to such an extent that compliance with this standard is impaired, and in particular with regard to Clauses 8 and 32.*

21.104 *The outside surface of **large area contacting applicators** and accessible **insertion applicators** positioned as in normal use are subjected to three impacts, each having an energy of 3 J. These impacts are applied to the most onerous parts and may be at the same point.*

The impact is applied by means of a steel ball having a diameter of 50 mm and a mass of approximately 0,5 kg. The ball is suspended by a suitable cord. The ball is allowed to fall as a pendulum through the distance required to strike the surface with the specified impact energy.

The appliance shall then comply with Clause 32.

22 Construction

This clause of Part 1 is applicable except as follows.

22.40 *Addition:*

The switch shall have provisions for locking, such as a key or a key switch.

22.101 **Insertion applicators** and **large area contacting applicators** shall have an **available microwave power** of 2 000 W or less.

Small area contacting applicators shall have an effective microwave power of 200 W or less.

Compliance is checked by inspection and relevant measurements.

The effective microwave power is calculated or measured at the feedthrough for coaxial line and control wiring (see key 9 in Figure 107) as follows:

– *if there is a coaxial line between the microwave power generator and the **small area contacting applicator**, the losses in this coaxial line are to be measured or calculated under the condition of 25 % reflected power by means of conventional microwave methods;*
– *if there is a microwave isolator or a protective two-port attenuator between the microwave power generator and the **small area contacting applicator**, the manufacturer is allowed to use such data to increase the **available microwave power** under conditions of **normal operation**.*

22.102 **Large area contacting applicators** for drying of floor, wall or ceiling structures shall not have a smaller applicator opening than 1 cm^2 per W **of available microwave power**.

NOTE A minimum square opening is thus 35 × 35 cm for 1 200 W **available microwave power**.

Compliance is checked by inspection.

22.103 **Small area contacting applicators** shall not have a smaller applicator opening than 0,05 cm^2 per W of effective microwave power.

NOTE A minimum rectangular opening is thus 8 cm × 1 cm for 160 W effective microwave power.

Compliance is checked by inspection.

AVA Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019

22.104 Contacting applicators for drying of floor, wall or ceiling structures equipped with automatic movement means of operation shall be provided with controls so that microwave generation is stopped when the appliance movement stops.

Compliance is checked by inspection of the appliance and its circuit diagram, and by relevant measurements and tests.

22.105 Appliances with **large area contacting applicator** and **insertion applicator** shall be provided with a means such that damage to the **supply cord** due to movement of the appliance, and appliance movement over **the supply cord**, are prevented as far as possible. The means provided shall be re-usable.

This requirement is considered to be met by, for example,

– a cord-retaining device to keep the **supply cord** out of the vicinity of the **microwave enclosure**, with the **supply cord** being adequately fastened to the appliance,
– the **supply cord** entry or attachment being at least 0,6 m from the nearest point of the **microwave enclosure**,
– mechanical guards being designed into the **microwave barrier**,
– expandable springs to which the cord is fastened or automatic cord reels or equivalent which are fixed above the floor.

Compliance is checked by inspection and by the following test procedure, except for automatic cord reel-in devices.

*The **supply cord** as delivered with the appliance is attached to the device in accordance with the instruction manual. The **supply cord** is then subjected 10 times to a pull of 100 N, the pull being applied in the most unfavourable direction, without jerks, for 1 s.*

*After the test, the power **supply cord** shall show no damage within the meaning of this standard and it shall not have been displaced longitudinally, in the device, by more than 2 mm.*

Appliances with **small area contacting applicator** shall be provided with a means such that damage to the grounded flexible cable containing a coaxial line and control wiring due to moving and turning the appliance is prevented as far as possible.

This requirement is considered to be met by, for example,

– a cord-retaining device to keep the grounded flexible cable containing coaxial line and control wiring out of the vicinity of the guard, with the grounded flexible cable containing coaxial line and control wiring being adequately fastened to the appliance, or
– the grounded flexible cable containing coaxial line and control wiring entry or attachment being at least 0,2 m from the nearest point of the guard.

Compliance is checked by inspection.

22.106 Maintenance doors and lids with hinges shall be constructed so that they cannot fall down unintentionally.

Compliance is checked by inspection.

22.107 Appliances **with large area contacting applicator** and with **insertion applicator** shall incorporate at least two **microwave interlocks** that are operated when the **applicator** is moved away from the **load**. Each of these interlocks shall operate before undue microwave leakage occurs and at least one of the interlocks shall operate by mechanical means.

AVA Documents
Document Sharing Hub

Full document details: IEC 60335-2-110-2019