IEC 60683

Edition 2.0 2011-10

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Industrial electroheating equipment – Test methods for submerged-arc furnaces

Chauffage électrique industriel – Méthodes d'essai des fours à arc submergé

IEC 60683:2011

Documents
Document Sharing Hub

Full document details: IEC 60683 2011

THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.
If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.
Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub
The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, withdrawn and replaced publications.
- IEC Just Published: www.iec.ch/online_news/justpub
Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.
- Electropedia: www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.
- Customer Service Centre: www.iec.ch/webstore/custserv
If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:
Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm
Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,…). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.
- Just Published CEI: www.iec.ch/online_news/justpub
Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.
- Electropedia: www.electropedia.org
Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.
- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:
Email: csc@iec.ch
Tél.: +41 22 919 02 11
Fax: +41 22 919 03 00

Documents
Document Sharing Hub

Full document details: IEC 60683 2011

IEC 60683

Edition 2.0 2011-10

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Industrial electroheating equipment – Test methods for submerged-arc furnaces

Chauffage électrique industriel – Méthodes d'essai des fours à arc submergé

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX **N**

ICS 25.180.10

ISBN 978-2-88912-753-5

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

Documents
Document Sharing Hub

Full document details: IEC 60683 2011

CONTENTS

FOREWORD ... 3
1 Scope and object ... 5
2 Normative references ... 5
3 Terms and definitions ... 5
4 Features of the SAF system ... 8
4.1 Electrical assembly of SAF ... 8
4.2 Star-delta switch ... 9
4.3 Types of SAF ... 9
4.4 SAF process principles ... 9
4.5 Types of electrodes ... 9
4.6 Electrode system ... 10
4.7 Water cooling ... 10
4.8 Electrical connection ... 10
5 Tests and general conditions ... 10
5.1 General ... 10
5.2 List of tests during cold state ... 11
5.3 List of tests during hot commissioning and hot state ... 11
6 Technical tests ... 11
6.1 Electrical insulation resistance ... 11
6.1.1 General ... 11
6.1.2 Electrical insulation during erection ... 11
6.1.3 Electrical insulation during cold test ... 11
6.1.4 Electrical insulation during hot state ... 12
6.2 Cooling water system ... 12
6.3 Characteristics of electrode regulation ... 12
6.3.1 Speed of electrode motion ... 12
6.3.2 Electrode regulator dead band ... 12
6.3.3 Electrode motion response time ... 12
6.3.4 Current control of semiconductor converter (if applicable) ... 13
6.4 Determination of electrical characteristics during operation ... 13
6.5 Determination of secondary voltage ... 13
6.6 Operational parameters ... 13
Bibliography ... 14

Documents
Document Sharing Hub
Full document details: IEC 60683 2011

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL ELECTROHEATING EQUIPMENT – TEST METHODS FOR SUBMERGED-ARC FURNACES

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60683 has been prepared by IEC technical committee 27: Industrial electroheating.

This second edition cancels and replaces the previous edition published in 1980 and constitutes a technical revision.

Significant technical changes with respect to the previous edition are as follows:

– Clause 1 (*Scope and object*) – the types of furnaces covered by this standard are more clearly defined.
– Clause 2 (*Normative references*) and Clause 3 (*Terms and definitions*) have been updated and completed.
– A new Clause 4 (*Features of the SAF sytem*) has been added; it mainly concentrates on the tests necessary for high voltage/high current electrical equipment in the installation.
– Clause 5 (*Tests and general conditions*) and Clause 6 (*Technical tests*) have been modified according to today's requirements for safe operation of a SAF.

Documents
Document Sharing Hub
Full document details: IEC 60683 2011

The text of this standard is based on the following documents:

CDV	Report on voting
27/780/CDV	27/797/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

Documents
Document Sharing Hub

Full document details: IEC 60683 2011

INDUSTRIAL ELECTROHEATING EQUIPMENT – TEST METHODS FOR SUBMERGED-ARC FURNACES

1 Scope and object

This International Standard specifies test procedures, conditions and methods according to which the main parameters and the main operational characteristics of a submerged-arc furnace (SAF) with rated electrical power levels above 500 kVA are established.

This standard is applicable to SAF with one or more electrodes.

In order to determine further technical or economic assessments, additional tests may be necessary.

Tests for some special equipment for semiconductor converter controlled furnaces, such as controlled rectifiers or controlled a.c. converters, are covered by IEC 60146-1-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60398, *Industrial electroheating installations – General test methods*

IEC 60519-1:2010, *Safety in electroheating installations – Part 1: General requirements*

IEC 60519-4, *Safety in electroheat installations – Part 4: Particular requirements for arc furnace installations*

3 Terms and definitions

For the purposes of this document the terms and definitions given in IEC 600519-1:2010 and the following apply.

NOTE Refer to International Electrotechnical Vocabulary, IEC 60050, for general definitions. Terms relating to industrial electroheat are defined in IEC 60050-841.

3.1
active power
P
mean value of the instantaneous power p (in kW) taken under periodic conditions over one period of time T (in h):

$$P = \frac{1}{T}\int_0^T p\,dt$$

NOTE Active power instantaneous value (r.m.s.) measured at any time, including all phases.

[IEC 60050-131:2002, 131-11-42, modified]

Documents
Document Sharing Hub
Full document details: IEC 60683 2011

3.2
apparent power
S
power rating of the transformer, energizing the SAF (in MVA)

$$S = UI = \sqrt{P^2 + Q^2} \quad \text{(for single-phase SAF)}$$

$$S = \sqrt{3}\ UI \quad \text{(for three-phase SAF)}$$

where

U is the voltage, r.m.s., sinusoidal value (in kV)

I is the current, r.m.s. sinusoidal value (in kA)

[IEC 60050-131:2002, 131-11-41, modified]

3.3
bottom electrode
SAFdc electrical conductive elements integrated in the SAF bottom (mainly connected as anode)

3.4
cold state
thermal state of a furnace and its installation, when the temperature of all parts is equal to ambient temperature

3.5
cold test
test of the entire furnace installation, including functions, connections, movements and instrumentation, prior hot commissioning, following erection

3.6
dead band
finite range of electrical values within which a variation of the input variable does not produce any measurable change in the output variable

[IEC 60050-351:2006, 351-24-14, modified]

3.7
electrode
part produced from conductive material to transfer the electric current to the process

NOTE For types of electrodes, see 4.5.

[IEC 60050-841:2004, 841-26-38, modified]

3.8
furnace transformer
transformer feeding the SAF with electrical energy, supplied from the high-voltage network with suitable voltage and current ranges for operation

NOTE 1 Secondary voltage is controlled by on-load tap changer or adjusted during off-circuit.

NOTE 2 There are designs using three or more single phase transformers per furnace.

[IEC 60050-841:2004, 841-26-55, modified]

Documents
Document Sharing Hub

Full document details: IEC 60683 2011

3.9
furnace electrical losses
P_{loss}
losses caused by the parts of the main electrical circuit, outside the furnace vessel

NOTE Electrical losses of high voltage supply, power factor compensation (when used) or prebaking electrodes are not included in the furnace electrical losses.

3.10
furnace
vessel which consists of bottom, shell and roof, into which the process material is charged

NOTE SAF, constructed from steel, clad with refractory, can be circular / rectangular in open, semi-closed or closed form.

[IEC 60050-841:2004, 841-26-16, modified]

3.11
high-current line
assembly to conduct high current between transformer secondary bus bars and electrode(s), connected in series- (and/or parallel), comprising flexible connections, bus bar system or high current tubes, cables, electrode arms (when used) and contact clamps

3.12
hot commissioning
heating up of the furnace till a defined production is reached

3.13
hot state
thermal condition of the furnace as soon as hot commissioning is finished

3.14
main electrical circuit
electrical equipment for SAF comprising high voltage supply, power factor compensation (when used), switchgear, transformer(s), semiconductor convertors (a.c. or d.c.) (when used), d.c. reactor (when used), high current line, electrode systems with electrodes and burden

3.15
power factor
cos φ
ratio of the active power to the apparent power, measured on the primary side of the transformer

$$\cos\varphi = \frac{P}{S}$$

where

P is the active power (in MW)

S is the apparent power (in MVA)

NOTE In case of harmonics, power factor is determined according to IEC 60146-1-1.

[IEC 60050-131:2002, 131-11-46, modified]

3.16
reactive power
Q
total reactive electrical power (in MVAr) generated by the main electrical circuit of a SAF, measured on all phases at the primary side of the transformer

Documents
Document Sharing Hub
Full document details: IEC 60683 2011

NOTE 1 Instantaneous value of the reactive power measured at any time, including all phases.

NOTE 2 Mean value within a time interval: i.e. generated reactive energy (in MVArh) by the power-on time (in h).

[IEC 60050-131:2002, 131-11-44, modified]

3.17
reactive power compensation
action to optimize the transmission of reactive power during operation

[IEC 60050-603:1986, 603-04-28, modified]

3.18
rectifier
device by means of which alternating current is changed into direct current for SAFdc

[IEC 60050-881:1983, 881-08-11, modified]

3.19
semiconductor converter
electronic converter for electrical power with semiconductor valve devices

NOTE SAFdc: converter to control the direct current (rectifier); SAFac: converter to control alternating current to smooth the power input (graduator).

[IEC 60050-551:1998, 551-12-42, modified]

3.20
smoothing reactor
reactor used to reduce alternating components of a pulsating current, to minimise arc impacts and to ensure arc stability during the process

[IEC 60050-811:1991, 811-26-21, modified]

3.21
specific electric energy consumption
quantity of electrical energy (in kWh) consumed by the SAF for the production of the final product (in t), charging a defined mixture of specified raw materials or for the (s)melting of charged material (in t)

3.22
submerged arc-resistance furnace
SAF
vessel in which a combined arc / resistance heating is used to melt the charged material

[IEC 60050-841:2004, 841-26-12, modified]

4 Features of the SAF system

4.1 Electrical assembly of SAF

In the electrical assembly of a SAF, the following equipment is included:

– high-voltage supply line,
– high voltage switchgear, by which the SAF can be connected/disconnected from the electrical supply under load,
– furnace transformer(s),
– secondary bus bar system,
– semiconductor converter (a.c. or d.c.),

Documents
Document Sharing Hub
Full document details: IEC 60683 2011

– equipment for reactive power compensation and/or voltage stabilization (if supplied),
– automatic power regulation system,
– boards, panels and desks,
– control, measuring and signalling devices.

4.2 Star-delta switch

Star-delta switch(es) is/are arranged on transformer(s) HV side. It connects the transformer HV windings to wye – or delta connection in order to modify the transformer(s) secondary voltage range by $\sqrt{3}$. Any star-delta switch can be operated in off-circuit condition only.

NOTE When three single-phase transformers are used, the star-delta switch is installed normally inside the transformer vessel. On single-phase transformers, the star-delta switches are installed at the high voltage switchgear.

4.3 Types of SAF

In general the SAF is operated using the a.c. or d.c. technology.

In the SAFac, the electrical energy is conducted to the process via 3 to 6 electrodes. In some SAFac applications (e.g. FeNi furnaces) semiconductor convertors are used for alternating current control.

In the SAFdc, electrical energy is conducted via the anode in the bottom of the furnace through the charge material to the cathode (electrode).

Electrical energy normally forms arcs between the electrode and the charge material or heats up the charge material by the resistance heating (Joule effect).

4.4 SAF process principles

Processing of nonferrous metal, iron alloys, waste recycling, slag and cleaning of slag is possible in the SAF.

It shall be differentiated between the following modes using the SAF for production:

a) 100 % burden resistance mode (electrodes submerged in the burden), e.g. for the production of FeCr, FeSi;
b) mix of burden and slag resistance mode (electrodes submerged in burden and slag), e.g. for slag cleaning and settling furnaces for Cu, Pb, Zn;
c) shielded arc mode (arc below electrode tip is shielded with burden and is in touch with the slag), e.g. producing FeNi;
d) open arc mode (arc below electrode tip in direct contact with the slag), e.g. in the TiO_2-slag production and waste recycling.

4.5 Types of electrodes

There are different types of electrodes, i.e.:

a) prebaked electrodes,
b) self-baking electrodes (Soederberg electrodes),
c) extrusion/composite electrodes, which are a combination of Soederberg electrodes with a prebaked electrode as a core,
d) hollow electrode system, which allow charging of fines via the centre hole (prebaked, self-baking).

The selection of the type of electrode depends mainly on:

Documents
Document Sharing Hub
Full document details: IEC 60683 2011