

ECMA

Standardizing Information and Communication Systems

Alphabetical Reference Index to IEC 950

Withdrawn

ECMA

Standardizing Information and Communication Systems

Alphabetical Reference Index to IEC 950

**(IEC 950 second edition, including
amendments 1, 2, 3 and 4)**

Withdrawn

Brief history

IEC 950, the safety standard for Information Technology equipment, is a large and complex document dealing with subjects as diverse as electrical safety, chemical safety, protection from heat and connection to telecommunication networks. It was considered that an index would be useful to facilitate the use of IEC 950 for both designers and test agencies.

In April 1993, ECMA TC12 (Safety for ITE) had the opportunity to organise this work. It was agreed that the document should take the form of a formal ECMA Technical Report, and as such, once approved, it would be made available free to any person or organisation requesting it. Incorporation of the Index in other documents is permitted, and subject to quoting the origin of the document. To this effect, a soft version is available from ECMA.

This Index, modified as necessary, is also part of the second edition of Standard ECMA-129, "Information Technology Equipment - Safety".

Liaison was maintained with IEC/TC74, and this third edition of ECMA TR/63 takes into account Amendment 4 to IEC 950.

Comments by users of this index on its usefulness and completeness will assist ECMA in the preparation of any future edition, and will be welcomed.

Adopted as an ECMA Technical Report by the General Assembly of December 1995.

Withdrawn

Introduction

This index has been prepared under the auspices of ECMA/TC12 - Product Safety. It relates to IEC 950 - Safety of Information Technology Equipment, second edition (1991), including amendments 1, 2, 3 and 4.

This index is for information only and the selection of indexed items does not imply any particular importance.

Location references are clause or sub-clause numbers or annex letters.

Principal references are printed **Bold**.

References to the Introduction (Principles of Safety) are indicated as Introduction.

If a term is defined in the standard, its definition is indicated in the index by an asterisk, e.g. **RATED VOLTAGE** 1.2.1.1*.

A		with a TOOL	1.7.18
		see also RESTRICTED ACCESS LOCATIONS	
abnormal conditions	Introduction, 1.3.1, 5.4	accessibility <i>see</i> access	
heating elements	4.3.20	actuators, mechanical, in interlock systems	2.8.7
overload protection	5.4.1, 5.4.3	additional requirements outside the standard	1.1.2
sequence of testing	1.4.3	adhesive	
simulated	5.4.6	ageing test	4.3.22
fan not running	4.4.8	application	2.9.6
general	4.4.1	adjustment	
one at a time	1.4.12	marking	
tests under abnormal conditions of		for rated voltage	1.7.4
electrical components	5.4.6	for thermostats etc	1.7.13
electromechanical components	5.4.5	must not create a hazard	4.3.1, 4.3.2
heating thermoplastic parts	5.4.10	worst case conditions for tests	1.4.4, 1.4.9, 2.1.2, annex H
motors	5.4.2, B.2	air filters, flammability	4.4.3.1, 4.4.3.6
thermostats	K.6	air gaps	
thermal cutout operates	1.2.11.4	CLEARANCES applicable	2.5.1, 2.9.2 (table 3 condition 6, table 5 condition 7)
within FIRE ENCLOSURES	4.4.6	CLEARANCES not applicable	2.9.1
abnormal operating conditions <i>see</i> abnormal conditions		disconnect devices	2.6.2
abrasion resistance test	2.9.5	interlock switches	2.8.6
access, accessibility		tip of test finger if voltage is over 1 kV	2.1.2, annex F (figure F.14 point A)
by		altitude (elevation)	
OPERATORS <i>see</i> OPERATOR ACCESS AREAS		during operation	1.1.2
SERVICE PERSONNEL <i>see</i> SERVICE ACCESS AREAS		during testing	5.3.2
definitions	1.2.7	ampacity of	
means OPERATOR access (area)	1.2.7.1	protective earthing conductors	2.3.3.3, 2.5.11
prevention by interlock	1.2.7.6	power supply cords	3.2.4
restricted	1.2.8.8, 2.1.4.1, 2.1.4.2, 6.2.2	telecommunication wiring	6.5
through openings in ENCLOSURES	2.1.2, annex F (figure F.14, point A)	terminals	3.3.5, 3.3.6
to		wires and cables	3.1.1, 6.5
controls	4.3.2	apertures <i>see</i> openings	
ELV CIRCUITS <i>see</i> ELV CIRCUITS, accessibility		appliance couplers	annex P (IEC 320)
energized parts	2.1.1	as disconnect devices <i>see</i> disconnection for servicing	
handles, levers, knobs	2.1.8, 4.3.5	as means of connection to power	3.2.1
interlocks	2.8.3, 2.8.5	fault testing	5.4.6
internal wiring	2.1.3, 2.9.4.4	in PLUGGABLE EQUIPMENT	1.2.5.1, 1.2.5.2
lasers	4.3.12, IEC 825	on detachable power supply cords	1.2.5.4
plugs and sockets	4.3.17		
moving parts	2.8.2, 4.1.2, 4.1.3		
sharp edges	4.1.4		
TELECOMMUNICATION NETWORKS	6.3.1, 6.4.1		
terminals	3.2.8		
TNV CIRCUITS <i>see</i> TNV CIRCUITS, accessibility			

reversible (unpolarized)	2.6.6, 4.3.20	beads, ceramic	3.1.7
that fill aperture in ENCLOSURES	4.4.4	OPERATOR access	2.1.2
<i>see also</i> appliance couplers			
applicability		belts	2.1.2, 4.3.6, 4.4.3.3, A.6.2
of requirements and tests	1.4.1, 1.5.2	bibliography	annex Q
of standard 1.1.1		BODY (of equipment)	1.2.7.5*
arcing		insulation	1.6.3, 2.2.6 (table 0.1 condition 6)
as energy hazard	Introduction	body, current through a human	annex Q (IEC 479-1)
causing ignition of air filter	4.4.3.6	<i>see also</i> leakage current	
during tests for thermal controls	annex K	BOUNDING SURFACES	1.2.10.1, 1.2.10.2, 1.2.10.3*
FIRE ENCLOSURE required	4.4.4, 4.4.5.1	bridging of insulation	2.2.6, 2.2.8, 5.3.2 (note 3), 6.3.3.1
high current ignition tests	4.4.4, A.3	by	
asbestos, not to be used as insulation	2.2.2	capacitors	1.5.6, 1.6.4, 2.2.8.1
		resistors	2.2.8, 5.3.2 (note 3)
B		surge suppressors	6.3.3.1
backup		components removed for test	5.3.2 (note 3), 6.3.3.1
overcurrent protection	2.7.3	permitted with conditions	2.2.8, 2.3.5, 2.4.3, 6.2.1.5
sources of power	1.1.3, 2.6.12, 3.2.1, 5.2.2, G.2	under fault conditions	3.1.8, 3.3.2, 3.3.9, C.2
baffles in bottoms of FIRE ENCLOSURES	4.4.6	<i>see also</i> energy hazards	
ball-pressure test on thermoplastic parts	5.4.10, figure 21 (page 241)	building installations (fixed wiring)	1.2.5.1, 1.2.5.2, 1.2.5.3, 2.7.4 (note)
barriers	Introduction	disconnect device in	1.7.2, 2.7.1, 2.7.3
for electrical separation	2.3.3.1, 3.3.2	not in Scope of standard	1.1.3
for special power connections	3.3.2	building wiring <i>see</i> building installations	
in bottoms of FIRE ENCLOSURES	4.4.6	BUILDING-IN, EQUIPMENT FOR	1.2.3.5*, 2.1.2, 5.1
no mechanical strength test		bus-bars	
within MECHANICAL ENCLOSURES	4.2.1	as internal wiring	3.1.1
secured with adhesive	4.3.22	as protective earthing conductors	2.5.5
to prevent ignition	4.4.3.3, 4.4.3.6, 4.4.6	bushings	
BASIC INSULATION	Introduction, 1.2.9.2*, 1.2.9.3, 1.2.9.4, 1.2.9.5	in metal	3.1.2
application	2.1.1, 2.1.2, 2.1.8, 2.2.6	power cord	3.2.5, 3.2.6, 3.2.7
in		flammability	4.4.3.5
SELV CIRCUITS	2.3.3, 2.3.3.2, 2.3.3.3, 2.3.5	C	
TNV CIRCUITS	6.2.1.2, 6.2.1.4, 6.2.1.5	cables	
wound components	2.9.4.4	earthing conductors in multicore	2.5.5, 2.5.11
on coated printed boards	2.9.5, annex F (figure F.13)	earthing conductors in ribbon	2.5.5
bridging <i>see</i> bridging of insulation		power	3.2.2, 3.3.5, annex P (IEC 227, IEC 245, IEC 885)
consequences of failure	2.3.1, 2.3.3, 2.4.1, 2.5.11, 6.2.1.2	power, FIRE ENCLOSURES not required	4.4.5.2
dimensions	2.9.2, 2.9.3, 2.9.4, annex F, R.1, R.2	TV distribution	1.2.14.7
electric strength	5.3.2	CABLES, INTERCONNECTING	1.2.11.7*, 1.5.5, 2.10.1
failure to be simulated	1.4.12	calibre of conductors <i>see</i> ampacity	
integrity		capacitors	
after a test	5.4.4, 5.4.9	casings, isolation	2.1.9
in service	3.3.9	class U (IEC 364-14)	2.2.8.1
interchanged with SUPPLEMENTARY INSULATION	2.2.6	class X (IEC 364-14)	1.5.6
one element of DOUBLE INSULATION	2.2.7.1, 5.4.9	class Y (IEC 364-14)	1.6.4, 2.2.8.1
short-circuited before test	6.2.1.2	connected to IT POWER SYSTEMS	1.6.4
WORKING VOLTAGE	2.2.7	IEC 65	1.5.6
batteries		in FIRE ENCLOSURES	4.4.5.1
as SECONDARY CIRCUITS	1.2.8.2	mains filters	1.5.6, 1.6.4
in limited power sources	2.1.1	discharging	2.1.10
lithium and similar, requirements	4.3.21	motors	B.5, B.8
lithium, marking	1.7.17	not protected by fuses	5.4.8
battery backup systems, not in Scope of standard	1.1.3		
battery compartments, access to TNV CIRCUITS	6.2.2.2		

stored charge	2.1.10, 2.4	WORKING VOLTAGES	2.2.7
cathode ray tubes, mechanical strength	4.2.8	in PRIMARY CIRCUITS	2.2.7.2
CCITT Recommendations <i>see</i> ITU-T Recommendations		in SECONDARY CIRCUITS	2.2.7.3
cemented joints in insulation	2.9.7, figures F.5, F.6, F.7	coated printed boards	2.9.5, annex F (figure F.13), R.1
ceramic and glass insulation		colours	
on printed boards	2.9.4.3	controls and indicators	1.7.8.2, annex P (IEC 73, ISO 3864)
temperature during tests	2.9.3 (table 6 condition 6), 5.1 (table 16 part 2), 5.4.9	flexible printed wiring	2.5.5
<i>see also</i> beads, ceramic		protective earthing conductors	2.5.5, 3.1.6, 3.2.4
CFR 47, part 68	M.3, annex P	comparative tracking index <i>see</i> c.t.i.	
chemical hazards	Introduction	components (definitions)	1.2.11*
<i>see also</i> corrosion and ozone		bridging insulation <i>see</i> bridging of insulation	
circuit characteristics (definitions)	1.2.8*	electro-magnetic	2.8.4, 5.4.5
circuits		mains voltage rating	1.6.3, 1.6.4
interconnection	2.10.1, 2.10.2	selection	1.5, 4.4
ELV <i>see</i> ELV CIRCUITS		separate testing	1.4.3, 2.2.3
LIMITED CURRENT <i>see</i> LIMITED CURRENT CIRCUITS		wound	2.9.4.4, 2.9.6, annex U
PRIMARY <i>see</i> PRIMARY CIRCUITS		<i>see also</i> transformers	
SECONDARY <i>see</i> SECONDARY CIRCUITS		conductive liquids	1.4.10
SELV <i>see</i> SELV CIRCUITS		conductor sizes <i>see</i> ampacity	
TNV <i>see</i> TNV CIRCUITS		connection terminals	1.7.7, 3.3
CLASS I and CLASS II EQUIPMENT in same system	2.5.4	connections <i>see also</i> disconnection	
CLASS I EQUIPMENT	1.2.4.1*, 1.7.2, 2.3.2, 5.4.9 (note)	definitions	1.2.5, 1.2.8.1, 1.2.12
BASIC INSULATION to be tested	5.4.9	between circuits	2.3.5, 2.4.3, 6.2.1.2
earthing	2.5.1, 6.3.2	INTERCONNECTING CABLES	1.2.11.7, 1.5.5, 3.1.1
marking of earthing terminals	1.7.7.1	to	
leakage current	5.2.5, 6.3.4, G.5	functional earth	2.5.2
CLASS II EQUIPMENT	1.2.4.2*, 1.7.1	other equipment	2.5.4, 2.10, 6.4.1
different from IEC 536 term	1.2.4.2 (note)	power supply	1.4.9, 3.1, 3.2, 3.3
earthing	2.5.2	protective earth	2.5, 3.1.6
leakage current	5.2.2, 6.3.4, G.2	TELECOMMUNICATION NETWORKS	2.3.1, 2.3.2 (note), clause 6, annex P (CFR 47, part 68)
CLASS III EQUIPMENT	1.2.4.3*	connectors	2.3.4, 3.2.1, 3.2.3, 4.3.17
no requirement for electric shock	1.3.3	contact by test probe	6.2.2.1, 6.4.1
classification of equipment	1.3.3	protective earthing contacts in	2.5.6, 2.5.7
CLEARANCES	1.2.10.2*, 2.2.1, 2.9.1, 2.9.2, annex F	<i>see also</i> appliance couplers, mains plugs, plugs, socket-outlets, and sockets	
<i>see also</i> IEC 664, interpolation, and separation distances		construction details	4.3
1.5 kV transients assumed	2.9.2.2 (note)	contact	
as OPERATIONAL INSULATION	5.4.4	gaps <i>see</i> air gaps	
at high altitudes	5.3.2 (table 18 condition 2)	pressure	3.1.8, 3.1.9, 3.1.10, 3.3.7
behind conductive ENCLOSURES	2.1.6	reliability	K.1
between uninsulated conductors	3.1.4	touching <i>see</i> access	
divided by floating parts	2.9.1, annex F (figure F.15)	CONTINUOUS OPERATION	1.2.2.3*, 5.1
in		control, quality <i>see</i> quality control	
encapsulated parts	2.9.7	controls	
enclosed parts	2.9.6	<i>see also</i> colours	
PRIMARY CIRCUITS	2.9.2.1	mains voltage adjustment	1.7.8, 4.3.1
SECONDARY CIRCUITS	2.9.2.2	manual	
increased by coatings	2.9.8	accessibility	4.3.2
integrity in service	2.9.1, C.2	fixing	4.3.5
measured through openings	2.9.1, annex F (figure F.14 point B)	isolation	2.1.7, 2.1.8
must be adequate	2.2.4	operated during test	5.2.3, 5.2.4, G.3.2, G.4.2, annex H
reduced	R.2	marking	1.7.8
variable	2.9.9, 5.3.2	temperature	5.3.2 (table 16 part 2)