IEC 61000-6-4

Edition 3.0 2018-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

BASIC EMC PUBLICATION

PUBLICATION FONDAMENTALE EN CEM

Electromagnetic compatibility (EMC) – Part 6-4: Generic standards – Emission standard for industrial environments

Compatibilité électromagnétique (CEM) – Partie 6-4: Normes génériques – Norme sur l'émission pour les environnements industriels

IEC 61000-6-4:2018-02(en-fr)

AVA Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2018 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue
Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,…). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 21 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary
67 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

IEC 61000-6-4

Edition 3.0 2018-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

BASIC EMC PUBLICATION

PUBLICATION FONDAMENTALE EN CEM

Electromagnetic compatibility (EMC) – Part 6-4: Generic standards – Emission standard for industrial environments

Compatibilité électromagnétique (CEM) – Partie 6-4: Normes génériques – Norme sur l'émission pour les environnements industriels

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 33.100.10

ISBN 978-2-8322-5371-7

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

AVA Documents
Document Sharing Hub

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

Full document details: IEC 61000-6-4-2018

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions and abbreviated terms 8
3.1 Terms and definitions 8
3.2 Abbreviated terms 10
4 Conditions during testing 11
5 Product documentation 12
6 Applicability 12
7 Measurement uncertainty 12
8 Compliance with this document 12
9 Emission requirements 13
Annex A (informative) Testing of DC powered systems 17
Annex B (informative) Further information on measurements using a FAR 19
B.1 General 19
B.2 Analysis 19
B.2.1 Theoretical analysis of simple radiators 19
B.2.2 Limitations with the basic model 20
B.2.3 Measurements on an EUT 23
B.2.4 Derivation of limits 24
B.3 Requirements 24
Bibliography 26

Figure 1 – Example of ports 9
Figure B.1 – Geometrical optics model for OATS measurements 19
Figure B.2 – Field attenuation between two half-wave dipoles above ground plane with fixed transmit antenna height and variable receive antenna height 20
Figure B.3 – Equivalent circuit diagram of a typical EUT 21
Figure B.4 – 10 m distance, horizontal polarization, calculated differences for an electrically short straight wire above the ground plane on an OATS compared with a FAR ($E_{OATS} - E_{FAR}$) 21
Figure B.5 – 10 m distance, vertical polarization, calculated differences for an electrically short straight wire above the ground plane on an OATS compared with a FAR ($E_{OATS} - E_{FAR}$) 22
Figure B.6 – 3 m distance, horizontal polarization, calculated differences for an electrically short straight wire above the ground plane on an OATS compared with a FAR ($E_{OATS} - E_{FAR}$) 22
Figure B.7 – 3 m distance, vertical polarization, calculated differences for an electrically short straight wire above the ground plane on an OATS compared with a FAR ($E_{OATS} - E_{FAR}$) 23
Figure B.8 – Differences of the horizontal polarised emission of the small EUT with mains lead in the 3 m FARs and on 10 m OATS 24

Table 1 – Test arrangements of EUT 11

AVA Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

Table 2 – Required highest frequency for radiated measurement 14
Table 3 – Requirements for radiated emissions – enclosure port 15
Table 4 – Requirements for conducted emissions – low voltage AC mains port 16
Table 5 – Requirements for conducted emissions – wired network port 16
Table A.1 – Proposed requirements for conducted emissions – DC power port 17
Table A.2 – Conducted testing of DC powered equipment 18
Table B.1 – Proposed requirements for radiated emissions, FAR 25

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTROMAGNETIC COMPATIBILITY (EMC) –

Part 6-4: Generic standards – Emission standard for industrial environments

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61000-6-4 has been prepared by CISPR subcommittee H: Limits for the protection of radio services.

This third edition cancels and replaces the second edition published in 2006 and Amendment 1:2010 This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) possible future requirements on DC ports;
b) possible future radiated polarity specific emission limits within a FAR;
c) the definition of which average detector is used for emission measurements at frequencies above 1GHz and that results using a peak detector are acceptable for all measurements;
d) the definition of different EUT test arrangements.

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

The text of this International Standard is based on the following documents:

FDIS	Report on voting
CIS/H/339A/FDIS	CIS/H/350/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

It forms Part 6-4 of the IEC 61000 series of standards. It has the status of a basic EMC publication in accordance with IEC Guide 107.

A list of all parts in the CISPR 61000 series, published under the general title *Electromagnetic compatibility*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

INTRODUCTION

IEC 61000 is published in separate parts according to the following structure:

Part 1: General

General considerations (introduction, fundamental principles)

Definitions, terminology

Part 2: Environment

Description of the environment

Classification of the environment

Compatibility levels

Part 3: Limits

Emission limits

Immunity limits (insofar as they do not fall under the responsibility of the product committees)

Part 4: Testing and measurement techniques

Measurement techniques

Testing techniques

Part 5: Installation and mitigation guidelines

Installation guidelines

Mitigation methods and devices

Part 6: Generic standards

Part 9: Miscellaneous

Each part is further subdivided into several parts published either as International Standards or technical reports/specifications, some of which have already been published as sections. Others will be published with the part number followed by a dash and a second number identifying the subdivision (example: IEC 61000-6-1).

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

ELECTROMAGNETIC COMPATIBILITY (EMC) –

Part 6-4: Generic standards – Emission standard for industrial environments

1 Scope

This part of IEC 61000 for emission requirements applies to electrical and electronic equipment intended for use within the environment existing at industrial (see 3.1.12) locations.

This document does not apply to equipment that fall within the scope of IEC 61000-6-3.

The environments encompassed by this document cover both indoor and outdoor locations.

Emission requirements in the frequency range 9 kHz to 400 GHz are covered in this document and have been selected to provide an adequate level of protection of radio reception in the defined electromagnetic environment. No measurement needs to be performed at frequencies where no requirement is specified. These requirements are considered essential to provide an adequate level of protection to radio services.

Not all disturbance phenomena have been included for testing purposes but only those considered relevant for the equipment intended to operate within the environments included within this document.

Requirements are specified for each port considered.

This generic EMC emission standard is to be used where no applicable product or product-family EMC emission standard is available.

NOTE 1 Safety considerations are not covered by this document.

NOTE 2 In special cases, situations will arise where the levels specified in this document will not offer adequate protection; for example where a sensitive receiver is used in close proximity to an equipment. In these instances, special mitigation measures may have to be employed.

NOTE 3 Disturbances generated in fault conditions of equipment are not covered by this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-161, *International Electrotechnical Vocabulary – Chapter 161: Electromagnetic compatibility*

IEC 61000-4-20:2010, *Electromagnetic compatibility (EMC) – Part 4-20: Testing and measurement techniques – Emission and immunity testing in transverse electromagnetic (TEM) waveguide*

CISPR 11:2015, *Industrial, scientific and medical equipment – Radio-frequency disturbance characteristics – Limits and methods of measurement*
CISPR 11:2015/AMD1:2016

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

CISPR 14-1:2016, *Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus – Part 1: Emission*

CISPR 16-1-1:2015, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

CISPR 16-1-2:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-2: Radio disturbance and immunity measuring apparatus – Coupling devices for conducted disturbance measurements*

CISPR 16-1-4:2010, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements*
CISPR 16-1-4:2010/AMD1:2012
CISPR 16-1-4:2010/AMD2:2017

CISPR 16-1-6:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna calibration*
CISPR 16-1-6:2014/AMD1:2017

CISPR 16-2-1:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 2-1: Methods of measurement of disturbances and immunity – Conducted disturbance measurements*
CISPR 16-2-1:2014/AMD1:2017

CISPR 16-2-3:2016, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 2-3: Methods of measurement of disturbances and immunity – Radiated disturbance measurements*

CISPR 16-4-2:2011, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modelling – Measurement instrumentation uncertainty*
CISPR 16-4-2:2011/AMD1:2014

CISPR 32:2015, *Electromagnetic compatibility of multimedia equipment – Emission requirements*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-161 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1.1
port
physical interface of the specified equipment with the external electromagnetic environment

Note 1 to entry: See Figure 1.

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018



Figure 1 – Example of ports

3.1.2
enclosure port
physical boundary of the equipment which electromagnetic fields may radiate through or impinge on

3.1.3
cable port
port at which a conductor or a cable is connected to the equipment

Note 1 to entry: Examples are signal, wired network, control and power ports.

3.1.4
wired network port
point of connection for voice, data and signalling transfers intended to interconnect widely-dispersed systems by direct connection to a single-user or multi-user communication network

Note 1 to entry: Examples of these include CATV, PSTN, ISDN, xDSL, LAN and similar networks.

Note 2 to entry: These ports may support screened or unscreened cables and may also carry AC or DC power where this is an integral part of the telecommunication specification.

Note 3 to entry: A port generally intended for interconnection of components of a system under test (e.g. RS-232, RS-485, field buses in the scope of IEC 61158, IEEE Standard 1284 (parallel printer), Universal Serial Bus (USB), IEEE Standard 1394 (“Fire Wire”), etc.) and used in accordance with its functional specifications (e.g. for the maximum length of cable connected to it), is not considered to be a wired network port.

Note 4 to entry: In previous editions of this document and many product standards, this port was defined as a telecommunications or network port.

3.1.5
power port
port for the connection of the equipment to the primary electrical power supply

3.1.6
public mains network
electricity lines to which all categories of consumers have access and which are operated by a supply or distribution undertaking for the purpose of supplying electrical energy

3.1.7
low voltage
LV
a set of voltage levels used for the distribution of electricity and whose upper limit is generally accepted to be 1 000 V AC or 1 500 V DC

[SOURCE: IEC 60050-601:1985, 601-01-26, modified – addition of the words "or 1 500 V DC"]

3.1.8
DC distribution network
local supply network in the infrastructure of a site or building intended for use by one or more different types of equipment and providing power independent of the public mains network

Documents
Document Sharing Hub
Full document details: IEC 61000-6-4-2018

Note 1 to entry: Connection to a remote local battery is not regarded as a DC distribution network, if such a link comprises only power supply for a single piece of equipment.

3.1.9
low voltage AC mains port
port used to connect to the low voltage AC mains supply network to power the equipment

Note 1 to entry: Equipment with a DC power port is considered low voltage AC mains powered if it is powered from an AC/DC power converter.

Note 2 to entry: The low voltage AC mains supply could be public or non-public.

3.1.10
highest internal frequency F_x
highest fundamental frequency generated or used within the EUT, or the highest frequency at which it operates

3.1.11
small equipment
equipment, either positioned on a table top or standing on the floor which, including its cables fits in a cylindrical test volume of 1,2 m in diameter and 1,5 m above the ground plane

Note 1 to entry: These dimensions are currently under discussion in CISPR.

3.1.12
industrial location
location characterized by a separate power network, supplied from a high- or medium-voltage transformer, dedicated for the supply of the installation

Note 1 to entry: Industrial locations can generally be described by the existence of an installation with one or more of the following characteristics:

- items of equipment installed and connected together and working simultaneously;
- significant amount of electrical power generated, transmitted and/or consumed;
- frequent switching of heavy inductive or capacitive loads;
- high currents and associated magnetic fields;
- presence of industrial, high power scientific and medical (ISM) equipment (for example, welding machines).

The electromagnetic environment at an industrial location is predominantly produced by the equipment and installation present at the location. There are types of industrial locations where some of the electromagnetic phenomena appear in a more severe degree than in other installations.

Example locations include metalworking, pulp and paper, chemical plants, car production, farm building, high-voltage areas of airports

Note 2 to entry: The connection between location and electromagnetic environment is given in 3.1.13.

3.1.13
electromagnetic environment
totality of electromagnetic phenomena existing at a given location

Note 1 to entry: In general, the electromagnetic environment is time-dependent and its description may need a statistical approach.

Note 2 to entry: It is very important not to confuse the electromagnetic environment and the location itself.

[SOURCE IEC 60050-161:1990, 161-01-01, modified – Note 2 to entry has been added.]

3.2 Abbreviated terms

AAN Asymmetric Artificial Network

AC Alternating Current

AMN Artificial Mains Network

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

CATV	Cable TV network
DC	Direct Current
DSL	Digital Subscriber Line
EUT	Equipment Under Test
FAR	Fully Anechoic Room
FSOATS	Free Space Open Area Test Site
ISDN	Integrated Services Digital Network
ITE	Information Technology Equipment
LAN	Local Area Network
MME	Multi Media Equipment
OATS	Open Area Test Site
PSTN	Public Switched Telephone Network
SAC	Semi Anechoic Chamber
TEM	Transverse Electromagnetic Mode
USB	Universal Serial Bus
xDSL	Generic term for all types of DSL technology

4 Conditions during testing

The EUT shall be tested in the operating mode producing the largest emission in the frequency band being measured, consistent with normal applications. The configuration of the test sample shall be varied to achieve maximum emission consistent with typical applications and installation practice. Pre-testing may be used to reduce test time.

If the EUT is part of a system, or can be connected to associated equipment, the EUT shall be tested while connected to the minimum representative configuration of associated equipment necessary to exercise the ports in a similar manner to that described in CISPR 11 or CISPR 32.

The EUT shall be arranged in accordance with the requirements of Table 1.

Table 1 – Test arrangements of EUT

Intended operational arrangement(s) of EUT	Test arrangement	Remarks
Table-top only	Table-top	
Floor-standing only	Floor-standing	
Can be floor-standing or table-top	Table-top	
Rack mounted	In a rack or table-top	
Other, for example wall mounted, ceiling mounted, handheld, body worn	Table-top	With normal orientation If the equipment is designed to be mounted on a ceiling, the downward-facing portion of the EUT may be oriented facing upward.
If a physical hazard would be caused by testing the device on a table-top, then it can be tested as floor standing and the test report shall document the decision and justification.		

In cases where a manufacturer's specification requires external filtering and/or shielding devices or measures that are clearly specified in the user's manual, the test requirements of this document shall be applied with the specified devices or measures in place.

Documents
Document Sharing Hub
Full document details: IEC 61000-6-4-2018

The configuration and mode of operation during the measurements shall be precisely noted in the test report. If the EUT has a large number of similar ports or ports with many similar connections, a sufficient number shall be selected to simulate actual operating conditions and to ensure that all the different types of termination are covered.

The measurements shall be carried out at one single set of parameters within the operating ranges of temperature, humidity and atmospheric pressure specified for the product and at the rated supply voltage, unless otherwise indicated in the basic standard. The relevant conditions shall be recorded in the test report.

Where applicable, additional information on EUT configuration can be found in CISPR 16-2-1, CISPR 16-2-3, CISPR 11 or CISPR 32 as referenced in Table 3 to Table 5.

5 Product documentation

The purchaser/user/installer shall be informed within the product documentation if special measures have to be taken to achieve compliance. One example, would be the need to use shielded or special cables.

6 Applicability

The application of measurements for emission(s) depends on the particular equipment, its configuration, its ports, its technology and its operating conditions.

Measurements shall be applied to the relevant ports of the equipment according to the requirements defined in Table 3 to Table 5. Measurements shall only be carried out where the relevant ports exist.

It may be determined from consideration of the electrical characteristics and usage of particular equipment that some of the measurements are inappropriate and therefore unnecessary. In such a case it is required that the decision and justification not to measure shall be recorded in the test report.

7 Measurement uncertainty

Where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in CISPR 16-4-2 this shall be followed, and for these measurements the determination of compliance with the limits in this document shall take into consideration the measurement instrumentation uncertainty in accordance with CISPR 16-4-2. Calculations to determine the measurement result and any adjustment of the test result required when the test laboratory uncertainty is larger than the value for U_{cispr} given in CISPR 16-4-2 shall be included in the test report.

8 Compliance with this document

Where this document gives options for testing particular requirements with a choice of test methods, compliance can be shown against any of the relevant test methods, using the specific limits with the restrictions provided in the relevant tables clauses. For example, floor standing shall be assessed against table clause 3.1, considering table clause 3.2 is limited to small equipment and table clause 3.3 is limited to table top equipment.

In any situation where it is necessary to retest the equipment the test method originally chosen shall be used in order to ensure consistency of the results.

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

Equipment which fulfils the requirements across the frequency ranges specified in Table 3 to Table 5 in this document is deemed to fulfil the requirements in the entire frequency range from 9 kHz to 400 GHz.

Measurements do not need to be performed at frequencies where no limits are specified.

NOTE CISPR TR 16-4-3 provides guidance on the applicability of limits to series produced equipment.

9 Emission requirements

The emission requirements for equipment covered by this document are given on a port by port basis and defined in Table 3 to Table 5. Annex A is provided for information purposes only and lists proposed limits for DC power ports.

The measurements shall be conducted in a well-defined and reproducible manner and performed in any order.

The description of the measurement, the measurement instrumentation, the measurement methods, and the measurement set-up to be used are given in the standards, which are referred to in Table 3 to Table 5. These standards are not repeated here, however modifications or additional information needed for the practical application of the measurements are given in this document.

The following shall be taken into account during the application of the measurements defined in Table 3 to Table 5.

- At transitional frequencies, the lower limit applies.
- Where the limit value varies over a given frequency range, it changes linearly with respect to the logarithm of the frequency.
- The test site shall be validated for the measurement distance chosen.
- Where the table clause defines more than one detector, then the measurements shall be performed using both types of detector. Results obtained using a peak detector may be used instead of the other defined detectors.
- Where a different measurement distance is chosen, other than the reference distance defined in the limit column of Table 3, the limits shall be offset based upon the following formula:

  new limit = defined limit – 20 log (measurement distance/reference distance)

  The unit of metres shall be used for distance and dB(μV/m) for the limits.

  With regard to each table clause, the measurements shall be performed at only one distance.
- For radiated emission measurements, Table 2 shows the highest frequency up to which radiated emission measurements shall be performed based up the value of F_x.

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

Table 2 – Required highest frequency for radiated measurement

Highest internal frequency (F_x)	Highest measured frequency
$F_x \leq$ 108 MHz	1 GHz
108 MHz $< F_x \leq$ 500 MHz	2 GHz
500 MHz $< F_x \leq$ 1 GHz	5 GHz
$F_x >$ 1 GHz	5 × F_x up to a maximum of 6 GHz
NOTE 1 Where the highest internal frequency is not known, tests are performed up to 6 GHz.	
NOTE 2 F_x is defined in 3.1.10.	

- For emission measurements above 1 GHz, the peak detector limits shall not be applied to disturbances produced by arcs or sparks that are high voltage breakdown events. Such disturbances arise when devices contain or control mechanical switches that control current in inductors, or when devices contain or control subsystems that create static electricity (such as paper handling devices). The average limits apply to disturbances from arcs or sparks, and both peak and average limits will apply to other disturbances from such devices.
- For radiated emission measurements using a FSOATS, FAR or SAC, the measurement distance is the horizontal distance between the vertical projections of the calibration point of the receiving antenna and the boundary of the EUT. The boundary of the EUT is the smallest imaginary circular periphery around the most compact arrangement of the EUT, using typical spacing.
- Where this document specifies the use of an average detector, the linear average detector defined in Clause 6 of CISPR 16-1-1:2015 shall be used.

NOTE In the measurement specifics columns of Table 3 to Table 5, where relevant, the format is as follows: characteristic, basic standard, clause. For example, from table clause 3.1, Instrumentation, CISPR 16-1-1:2015, Clause 4.

Documents
Document Sharing Hub

Full document details: IEC 61000-6-4-2018

Table 3 – Requirements for radiated emissions – enclosure port

Table clause	Test facility	Frequency range MHz	Limits dB(µV/m) Detector / measurement distance	Measurement specifics [a]	Limitations and restrictions [a]
3.1	OATS or SAC	30 to 230	40 Quasi-peak / 10 m	Instrumentation, CISPR 16-1-1, Clause 4 Antennas, CISPR 16-1-4, 4.5 Test site, CISPR 16-1-4, Clause 5 Method, CISPR 16-2-3, 7.3	Allowed measurement distances: 3 m, 5 m, 10 m or 30 m For equipment meeting the size criterion defined in 3.1.11, the measurements may be performed at the 3 m distance. Note this size criterion is currently under discussion. For measurement distances less than 30 m, the receiving antenna height shall be varied between 1 m to 4 m, else 1 m to 6 m shall be used. Additional guidance on the test method can be found in CISPR 16-2-3, 7.3 and Clause 8.
		230 to 1 000	47 Quasi-peak / 10 m		
3.2	TEM	30 to 230	40 Quasi-peak / n/a	IEC 61000-4-20	Only applicable to battery powered equipment not intended to have external cables attached. Restricted to equipment complying with the definition of small equipment within 6.2 in IEC 61000-4-20.
		230 to 1 000	47 Quasi-peak / n/a		
3.3	FAR	30 to 230	52 to 45 Quasi-peak / 3 m	Instrumentation, CISPR 16-1-1, Clause 4 Antennas, CISPR 16-1-4, 4.5 Test site, CISPR 16-1-4, 5.4.7 Method, CISPR 16-2-3, 7.4.	Restricted to table top equipment, and floor-standing equipment which can be placed on table during the test. Allowed measurement distances: 3 m, 5 m or 10 m The limitations on EUT size in CISPR 16-2-3 apply.
		230 to 1 000	52 Quasi-peak / 3 m		
3.4	FSOATS OATS FAR SAC (see limitations)	1 000 to 3 000	76 Peak / 3 m	Instrumentation, CISPR 16-1-1, Clauses 5 and 6 Antennas, CISPR 16-1-4, Clause 4.5 Test site, CISPR 16-1-4, Clause 8 Method, CISPR 16-2-3, Clause 7.6.	Allowed measurement distances: 3 m, 5 m or 10 m. Other facilities, such as FAR, SAC or OATS may be used provided they satisfy the free space conditions as defined in CISPR 16-1-4. For SAC and OATS, additional absorber may be required.
			56 Average / 3 m		
		3 000 to 6 000	80 Peak / 3 m		
			60 Average / 3 m		

The equipment is deemed to comply with the enclosure port requirement below 1 GHz if it meets the requirements defined in one or more of the table clauses 3.1, 3.2 or 3.3.

Antenna calibration shall be in accordance with CISPR 16-1-6:2014/AMD1:2017.

[a] Within this table, the version of the references are as follows:

CISPR 16-1-1 is CISPR 16-1-1:2015, CISPR 16-1-4 is CISPR 16-1-4:2010, CISPR 16-1-4:2010/AMD1:2012 and CISPR 16-1-4:2010/AMD1:2012/AMD2:2017, CISPR 16-2-3 is CISPR 16-2-3:2016 and IEC 61000-4-20 is IEC 61000-4-20:2010.

Documents
Document Sharing Hub
Full document details: IEC 61000-6-4-2018