IEC 61189-2-808

Edition 1.0 2024-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Test methods for electrical materials, printed board and other interconnection structures and assemblies – Part 2-808: Thermal resistance of an assembly by thermal transient method

Méthodes d'essai pour les matériaux électriques, les cartes imprimées et autres structures et assemblages d'interconnexion – Partie 2-808 : Résistance thermique d'un assemblage par la méthode du transitoire thermique

IEC 61189-2-808:2024-04(en-fr)

Documents
Document Sharing Hub
Full document details: IEC 61189-2-808-2024

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC - webstore.iec.ch/advsearchform
La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, …). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished
Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org
Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

AVA Documents
Document Sharing Hub

Full document details: IEC 61189-2-808-2024

IEC 61189-2-808

Edition 1.0 2024-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Test methods for electrical materials, printed board and other interconnection structures and assemblies – Part 2-808: Thermal resistance of an assembly by thermal transient method

Méthodes d'essai pour les matériaux électriques, les cartes imprimées et autres structures et assemblages d'interconnexion – Partie 2-808 : Résistance thermique d'un assemblage par la méthode du transitoire thermique

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 31.180

ISBN 978-2-8322-8804-7

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

AVA Documents
Document Sharing Hub

Full document details: IEC 61189-2-808-2024

CONTENTS

FOREWORD 3
1 Scope 5
2 Normative references 5
3 Terms and definitions 5
4 Objective 5
5 Test specimen 6
6 Test equipment and procedures 7
6.1 Test method and recommended test parameters 7
6.2 Test equipment 7
6.3 Test procedure 8
7 Test result 8
8 Report 9
Annex A (informative) Additional test methods for thermal resistance 11
Annex B (informative) Thermal resistance of die attach materials 13
B.1 Test specimen 13
B.2 Die attach materials 13
B.3 Test result 14
Annex C (informative) Uncertainty and repeatability for thermal resistance test 16
C.1 Test specimen 16
C.2 Test result 16
Annex D (informative) Thermostat equipment 18
Bibliography 20

Figure 1 – Structure of an assembly 6
Figure 2 – The fabricated test sample 6
Figure 3 – Test structure for measuring thermal resistance 8
Figure 4 – Test result for thermal resistance of an assembly 9
Figure B.1 –Structure of test sample using die attach material 13
Figure B.2 –The fabricated test sample using die attach material 13
Figure B.3 – Test graph for die attach materials 15
Figure C.1 – Test structure for measuring thermal resistance 16
Figure C.2 – Test result for thermal resistance of assembly 16
Figure D.1 – Connection of the thermostat unit to the T3Ster® main system unit 18
Figure D.2 –Calibration diagram recorded by the T3Ster® thermostat 19

Table 1 – Test result for thermal resistance of an assembly 9
Table A.1 – ASTM C1113 11
Table A.2 – ASTM E1461 11
Table A.3 – ASTM D5470 12
Table B.1 – Properties for die attach materials 14
Table B.2 – Test result for die attach materials 15
Table C.1 – Test result for thermal resistance of assembly 17

AVA Documents
Document Sharing Hub

Full document details: IEC 61189-2-808-2024

INTERNATIONAL ELECTROTECHNICAL COMMISSION

TEST METHODS FOR ELECTRICAL MATERIALS, PRINTED BOARD AND OTHER INTERCONNECTION STRUCTURES AND ASSEMBLIES –

Part 2-808: Thermal resistance of an assembly by thermal transient method

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61189-2-808 has been prepared by IEC technical committee 91: Electronics assembly technology. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
91/1935/FDIS	91/1955/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

Documents
Document Sharing Hub

Full document details: IEC 61189-2-808-2024

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61189 series, published under the general title *Test methods for electrical materials, printed board and other interconnection structures and assemblies*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: IEC 61189-2-808-2024

TEST METHODS FOR ELECTRICAL MATERIALS, PRINTED BOARD AND OTHER INTERCONNECTION STRUCTURES AND ASSEMBLIES –

Part 2-808: Thermal resistance of an assembly by thermal transient method

1 Scope

This part of IEC 61189 describes the thermal transient method to characterize the thermal resistance of an assembly consisting of a heat source (e.g. power device), an attachment material (e.g. solder) and a dielectric layer with electrode. This method is suitable to determine the thermal resistance of materials and assembly methods as well as to optimize the thermal flux to a heat sink.

NOTE This method is not intended to measure and specify the value of the thermal resistance of a dielectric material. For that purpose, other standards exist. Examples are given in Annex A.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60194-2, *Printed boards design, manufacture and assembly – Vocabulary – Part 2: Common usage in electronic technologies as well as printed board and electronic assembly technologies*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60194-2 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

4 Objective

The increasing power consumption of devices such as LED require a close examination of the heat dissipating path within thermal conductive printed circuit boards (Annex A). Therefore, effective removal of heat to maintain a safe junction temperature is the key to meeting the heat flux by using thermal conductive material for printed circuit boards. Thermal resistance is the crucial factor of heat dissipation dielectric materials in printed circuit board. Therefore, with the aim to reduce the thermal resistance in circuit boards, it is proposed to determine the thermal resistance by measuring the thermal transient characteristics of an assembly.

Documents
Document Sharing Hub

Full document details: IEC 61189-2-808-2024

5 Test specimen

To test the thermal resistance of an assembly, at first a test specimen shall be built, which consists of a heat source (e.g. power device), an attachment material (e.g. solder) and a dielectric layer with metal electrode. See Figure 1 for the structure. In the next step, the thermal resistance of the assembly can be determined by comparison of the thermal transient characteristics obtained when testing the assembly attached to a thermostat with or without a thermal interface material (TIM). See Figure 3 and Clause 6 for the test description.



Key

1 Heat source

2 Solder

3 Electrode layer

4 Dielectric layer

Figure 1 – Structure of an assembly

To obtain an adequate thermal resistance, a layer of around 200 µm thick solder shall be used for the die attach. The power source is a chip type device of the size 3,45 mm × 3,45 mm, powered with 1 W through voltage common collector (VCC) and ground (GND). The dielectric layer is a 2 cm × 2 cm substrate of 1 mm thickness. Figure 2 shows an example of such a test specimen.



Key

1 Voltage common collector (VCC)

2 Ground (GND)

Figure 2 – The fabricated test sample

Documents
Document Sharing Hub
Full document details: IEC 61189-2-808-2024

6 Test equipment and procedures

6.1 Test method and recommended test parameters

The thermal transient test equipment is a unique equipment for performing thermal measurements on semiconductor devices like ICs, transistors, diodes, etc. The thermal transient test equipment is most suitable for analyzing their thermal behavior, evaluating packages and device mounting, and detecting defects. This equipment is a computer-controlled equipment that can be used along with a PC hosting a special control and evaluation software. This equipment as a mandatory part of configuration can apply programmed thermal excitations and record complex thermal responses and provides built-in results evaluation procedures. Results of these post-processing procedures include the pulse thermal resistance diagram, time-constant spectrum, complex locus of the thermal impedance, differential and integral structure or profile function (Annex B).

6.2 Test equipment

The thermal transient measurements can be performed using a commercially available test equipment and specifically built test fixtures (Annex C). The test sample is mounted on the temperature-controlled heat sink. The heat sink is maintained at a temperature of 25 °C and controlled by a Keithley temperature controller. Initially, a junction-to-case thermal equilibrium is ensured by applying a drive current (I_{drive}) for a sufficiently long duration; then the I_{drive} is switched off and a small sense current (I_{sense}) is applied. When the system shifts to its new thermal equilibrium, the cooling down of the junction is measured.

From the transient time curves, the duration of cooling down can be taken to be how long the heating current I_{drive} needs to be applied to load the thermal capacities. The same time must be measured applying I_{sense} to resolve the thermal path downstream to the respective capacity. One approach to determine the required measurement time is to modify the thermal interface between the heat sink and the module. The time value at which the curve with the best possible thermal interface and one with a bad thermal interface separate is approximately the appropriate time duration for I_{drive} and I_{sense} when the thermal path upstream of the varied thermal interface is to be investigated. One can stepwise shorten the heat-up and cool-down time afterward and observe at what setting, and at which time, values change in the logarithmic time-derived curve. The shortest time for which the deviation of the time curves is still within the signal-to-noise range of the curve with long heating and cooling times is still acceptable. The thermal response at initial ‘0’ cycles and after 'n' cycles was measured. The measurement time of 40 s is unnecessarily long. For the second test run with test samples B, the measurement time was reduced to 5 s. In principle, this allowed us to reduce the heating up and cooling down time further to 0,5 s, because data later than 300 ms are not included for data analysis. The shape of the transient signal does not change when the cycle of heating up and cooling down times is shortened. In this experiment, the thermal tape (thermal conductivity: 6,5 W/mK) with the thickness of 500 µm is used. Thermal tape as a thermal interface material is used for separating the interface of the test sample through the comparison of thermal transient characteristics depending on whether or not the test sample has thermal interface material.

Documents
Document Sharing Hub
Full document details: IEC 61189-2-808-2024



Key

1 Heat source (1 W)

2 SAC305 solder (T: 200 µm)

3 Electrode layer (T: 35 µm)

4 Dielectric layer (T: 500 µm)

5 Thermal interface material (T: 500 µm)

6 Thermostat

NOTE The thermostat is the temperature-controlled system (Annex D). The thermostat has the thermocouples inside system.

Figure 3 – Test structure for measuring thermal resistance

6.3 Test procedure

The test sequences to test the thermal resistance of an assembly are as follows:

1) cleaning the contamination on the thermostat;
2) firstly, attaching the test sample on the thermostat without the thermal interface material;
3) testing the thermal transient characteristics of the test sample by biasing the power;
   - driving current (I_{drive}): 1 500 mA
   - sensor current (I_{sense}) for test: 10 mA
   - total power: 4,548 W
   - TIM: thermal pad (thickness: 500 µm)
   - temperature coefficient: −1,272 mV/°C
4) repeat the sequence 1);
5) secondly, attaching the test sample on the thermostat by using thermal interface material;
6) testing the thermal transient characteristics of the test sample by biasing the power;
7) comparing the thermal transient characteristics of the test sample depending on with or without the thermal interface material;
8) extracting the thermal resistance value of an assembly with test results.

7 Test result

From the cumulative structure function of the thermal transient characteristics, after converting to the cumulative structure function because it is eased to look for the separation point, the thermal resistance value is extracted by looking for the separated point from the measurement excel sheet instead of the visible graph (see Figure 4 and Table 1). Detailed information can be found in JESD-51-14(Published: Nov 2010), clause 4, Junction-to-Case Thermal Resistance Measurement (Test Method).

Documents
Document Sharing Hub
Full document details: IEC 61189-2-808-2024



Key

1 The measured of thermal resistance of an assembly

2 The measured thermal resistance of assembly without TIM

3 The measured thermal resistance of assembly with TIM

NOTE C_{th} is thermal capacitance and K is temperature (Kelvin).

Figure 4 – Test result for thermal resistance of an assembly

In order to extract value for thermal resistance of assembly, the separated value from the measurement results, depending on with TIM and without TIM, should be looked for.

Table 1 – Test result for thermal resistance of an assembly

Total thermal resistance (without TIM) K/W	Total thermal resistance (with TIM) K/W	Thermal resistance of an assembly K/W
10,86	9,68	9,2

8 Report

This test report shall include:

a) structure of the test specimen;

b) thermal tape used as TIM;

c) the used power sources;

d) the date of the test;

e) the room temperature under which the test was conducted;

f) the test sequences;

g) the graph of the cumulative structure function;

h) the total thermal resistance of the test specimen with or without TIM;

i) the thermal resistance of an assembly.

Documents
Document Sharing Hub
Full document details: IEC 61189-2-808-2024

The result value of an assembly separated differently from the measurement results, depending on the presence or absence of TIM, is defined as the thermal resistance and assembly. Detailed information can be found in JESD-51-14 (Published: Nov 2010), clause 4, Junction-to-Case Thermal Resistance Measurement (Test Method).

Documents
Document Sharing Hub

Full document details: IEC 61189-2-808-2024

Annex A
(informative)

Additional test methods for thermal resistance

Table A.1, Table A.2 and Table A.3 show additional test methods for thermal resistance.

Table A.1 – ASTM C1113

Measuring method	Hot wire type (ASTM C1113)
Principle of measurement	 $\lambda = (q / 4\pi)\ \ln(t2 - t1) / (T2 - T1)$ where λ thermal conductivity t time q heat value T temperature
Features	Thin film sample : > 300 µm Contact measuring (Low precision because of the contact thermal resistance at probe/sample)

Table A.2 – ASTM E1461

Measuring method	Laser flash type (ASTM E1461)
Principle of measurement	 Calculate the thermal conductivity from temperature rising curve by simulation fitting.
Features	Thin film sample OK Non-contact measuring (high precision) Multi-layer sample OK (CCL etc.)

Documents
Document Sharing Hub
Full document details: IEC 61189-2-808-2024

Table A.3 – ASTM D5470

Measuring method	Thermal resistance type (ASTM D5470)
Principle of measurement	 Calculate the thermal resistance from amount of heat (W) and temperature rising (ΔT) at heat insulating box. Convert the thermal conductivity: $\lambda = h / (R \cdot A)$ Where h thickness R thermal resistance A sample area
Features	Standard for thermal resistance measuring (Have a tendency to show high thermal conductivity)

Documents
Document Sharing Hub
Full document details: IEC 61189-2-808-2024