



INTERNATIONAL
STANDARD



Coaxial communication cables –
Part 1-111: Electrical test methods – Stability of phase test methods



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



IEC 61196-1-111

Edition 3.0 2024-09

INTERNATIONAL STANDARD



**Coaxial communication cables –
Part 1-111: Electrical test methods – Stability of phase test methods**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.10

ISBN 978-2-8322-9609-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....4

1 Scope.....6

2 Normative references 6

3 Terms and definitions 6

4 Phase variation with temperature.....9

 4.1 Purpose 9

 4.2 Test equipment.....9

 4.3 Preparation of test sample (TS) 9

 4.4 Test environment 9

 4.5 Preconditioning.....10

 4.6 Test procedure.....10

 4.7 Test result.....12

 4.7.1 Calculation of temperature coefficient of phase.....12

 4.7.2 Graph of phase temperature change.....13

 4.7.3 Maximum variation value of phase variation with temperature.....13

 4.7.4 Ratio of the relative phase temperature coefficient 13

 4.8 Test report 13

 4.9 Requirement 13

5 Phase constant variation with temperature 13

 5.1 Purpose 13

 5.2 Test equipment.....14

 5.3 Test sample 14

 5.4 Test environment 14

 5.5 Preconditioning.....14

 5.6 Test procedure.....14

 5.7 Test result.....14

 5.8 Test report 15

 5.9 Requirement 15

6 Phase stability with bending 15

 6.1 Purpose 15

 6.2 Test environment 15

 6.3 Test sample 16

 6.4 Test equipment.....16

 6.5 Test procedure.....16

 6.6 Test report 17

 6.7 Requirement 18

7 Phase stability with twisting 18

 7.1 Purpose 18

 7.2 Test environment.....18

 7.3 Test sample 18

 7.4 Test equipment.....19

 7.5 Test procedure.....19

 7.6 Test report 20

 7.7 Requirement 20

Annex A (normative) Phase consistency test for two or more cables.....21

 A.1 Purpose 21

A.2	Test equipment	21
A.3	The preparation of test sample (TS).....	21
A.4	Test environment	21
A.5	Test procedure.....	22
A.6	Test report	22
A.7	Requirement	22
Annex B (normative)	Phase variation with temperature test between two cables	23
B.1	Purpose	23
B.2	Preparation of test sample	23
B.3	Test environment	23
B.4	Preconditioning	23
B.5	Test procedure.....	23
B.6	Test results	23
B.7	Test report	24
B.8	Requirement	24
Annex C (informative)	Example for recording and calculating the phase variation with temperature	25
C.1	Purpose	25
C.2	Test sample	25
C.3	Test conditions	25
C.4	Test record and calculation	25
C.5	Test result calculation	27
Figure 1	– Test sample (TS)	9
Figure 2	– Preconditioning	10
Figure 3	– TS placement diagram	11
Figure 4	– Phase–Frequency graph schematic diagram	12
Figure 5	– Test sample (TS)	16
Figure 6	– Bending test.....	17
Figure 7	– Test graph schematic diagram	18
Figure 8	– Twist test	19
Figure 9	– Test graph schematic diagram	20
Figure A.1	– Cable	21
Figure A.2	– Cable assembly (TS)	21
Figure B.1	– $\eta_{t,f} - T$ (°C) contrast graph	23
Figure C.1	– $\eta_{t,f} - T$ (°C) graph	26
Table C.1	– Test record and calculation	26

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COAXIAL COMMUNICATION CABLES –

Part 1-111: Electrical test methods – Stability of phase test methods

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61196-1-111 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

This second edition cancels and replaces the first edition published in 2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) addition of the list of test methods in the Scope;
- b) addition of "the number of scanning points" in every test method;
- c) addition of Annex A, Phase consistency test for two or more cables;
- d) addition of Annex B, Phase variation with temperature test between two cables.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46A/1666/CDV	46A/1680/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61196 series, published under the general title *Coaxial communication cables*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

COAXIAL COMMUNICATION CABLES –

Part 1-111: Electrical test methods – Stability of phase test methods

1 Scope

This part of IEC 61196 provides test methods to determine the stability of phase of coaxial communication cables.

This document is applicable to RF coaxial cables. RF coaxial cable assemblies can also use this document for reference.

This part of IEC 61196 comprises following test methods:

- a) phase variation with temperature (Clause 4);
- b) phase constant variation with temperature (Clause 5);
- c) phase stability with bending (Clause 6);
- d) phase stability with twisting (Clause 7);
- e) phase consistency test for two or more cables (Annex A);
- f) phase variation with temperature test between two cables (Annex B).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61196-1, *Coaxial communication cables – Part 1: Generic specification – General, definitions and requirements*

IEC 61196-1-108:2011, *Coaxial communication cables – Part 1-108: Electrical test methods – Test for characteristic impedance, phase and group delay, electrical length and propagation velocity*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61196-1 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1
temperature coefficient of phase

$\eta_{t,f}$
coefficient defined as at the specified frequency f , as the ratio of the phase difference $\Delta\varphi_{t,f}$ between $\varphi_{25^\circ\text{C},f}$ at 25 °C and $\varphi_{t,f}$ at temperature t , and the total phase $\Phi_{25^\circ\text{C},f}$ at 25 °C

$$\eta_{t,f} = \frac{\varphi_{25^\circ\text{C},f} - \varphi_{t,f}}{\Phi_{25^\circ\text{C},f}} = \frac{\Delta\varphi_{t,f}}{\Phi_{25^\circ\text{C},f}} \tag{1}$$

where:

$\varphi_{t,f}$ is the phase at temperature t and frequency f , in (°);

$\varphi_{25^\circ\text{C},f}$ is the phase at 25 °C and frequency f , in (°);

$\Delta\varphi_{t,f}$ is the phase difference between $\varphi_{25^\circ\text{C},f}$ and $\varphi_{t,f}$ at frequency f , in (°);

$\Phi_{25^\circ\text{C},f}$ is the total phase at 25 °C and frequency f , in (°)

3.2
maximum variation of temperature coefficient of phase

$|\Delta\eta|_{\text{max}}$
maximum value η_{max} minus the minimum value η_{min}

$$\Delta\eta_{\text{max}} = |\eta_{\text{max}} - \eta_{\text{min}}| \tag{2}$$

3.3
ratio of relative temperature coefficient of phase PT

ratio of the relative temperature coefficient of phase PT , when the relationship between phase and temperature is sufficiently linear

$$PT = \frac{|\varphi_{t_1,f} - \varphi_{t_2,f}|}{\Phi_{25^\circ\text{C},f} \times (t_2 - t_1)} \tag{3}$$

where:

$\varphi_{t_1,f}$ is the phase value at t_1 and frequency f , in (°);

$\varphi_{t_2,f}$ is the phase value at t_2 and frequency f , in (°);

$\Phi_{25^\circ\text{C},f}$ is the total phase at 25 °C and frequency f , in (°);

t_1 and t_2 are any two temperatures within a specified temperature range in which the relationship between phase and temperature is sufficiently linear ($t_2 > t_1$), in °C

3.4

total relative variation of phase constant

total relative variation of the phase constant

$$\delta\beta = \frac{\beta_2 - \beta_1}{\beta_{\text{nom}}} \quad (4)$$

$$\delta\beta = \frac{l_{e,2} - l_{e,1}}{l_{\text{mech}}} \times v_{r,\text{nom}} = (\tau_{p,2} - \tau_{p,1}) \times c \times v_{r,\text{nom}} \quad (5)$$

where:

- β_1 is the phase constant at temperature t_1 , in radians/m;
- β_2 is the phase constant at temperature $t_2 > t_1$, in radians/m;
- β_{nom} is the nominal phase constant, in radians/m;
- $\tau_{p,1}$ is the phase delay at temperature t_1 , in s/m;
- $\tau_{p,2}$ is the phase delay at temperature $t_2 > t_1$, in s/m;
- c is the propagation velocity in free space (3×10^8 m/s);
- $l_{e,1}$ is the electrical length at temperature t_1 , in m;
- $l_{e,2}$ is the electrical length at temperature $t_2 > t_1$, in m;
- l_{mech} is the mechanical length, in m;
- $v_{r,\text{nom}}$ is the nominal relative propagation velocity

Note 1 to entry: For unidirectional variation, t_1 and t_2 are the limits of a specified temperature range. In the case of changing signs of variation, t_1 and t_2 become the temperatures at which the extreme value of l_e or τ_p occur.

3.5

temperature coefficient of phase constant, CT

temperature coefficient of the phase constant

$$CT = \frac{\delta\beta}{t_2 - t_1} \quad (6)$$

where:

- CT is the temperature coefficient of phase constant, in K^{-1} ;
- $\delta\beta$ is the total relative variation of the phase constant;