IEC 61196-1-127

Edition 1.0 2024-03

INTERNATIONAL STANDARD

colour inside

Coaxial communication cables –
Part 1-127: Electrical test methods – Link loss of radiating cable

IEC 61196-1-127:2024-03(en)

Documents
Document Sharing Hub

Full document details: IEC 61196-1-127 2024

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Documents
Document Sharing Hub

Full document details: IEC 61196-1-127 2024

IEC 61196-1-127

Edition 1.0 2024-03

INTERNATIONAL STANDARD

colour inside

Coaxial communication cables –
Part 1-127: Electrical test methods – Link loss of radiating cable

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.10

ISBN 978-2-8322-8314-1

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: IEC 61196-1-127 2024

CONTENTS

FOREWORD 3
1 Scope 5
2 Normative references 5
3 Terms and definitions 5
4 Test equipment 6
4.1 Signal generator 6
4.2 Receiver 6
4.3 Trolley 6
4.4 Antenna 6
4.5 Load 6
4.6 Connecting cables and connectors 6
4.7 Data collection system and calculations 7
5 Test arrangements 10
5.1 General 10
5.2 Free-space method 10
5.3 Ground-level method 12
6 Test conditions 14
7 Test methods 14
7.1 General 14
7.2 Complete sample test method 14
7.2.1 Test sample (TS) preparation 14
7.2.2 Test procedure 14
7.3 Segmented samples test method 14
7.3.1 Test sample (TS) preparation 14
7.3.2 Test procedure 15
7.4 Attenuation and coupling loss test method 16
7.4.1 General 16
7.4.2 Test sample (TS) preparation 18
7.4.3 Test procedure 18
8 Requirement 18
9 Test report 19

Figure 1 – Illustration of section-wise link loss calculation of 50 % reception probability 8
Figure 2 – Illustration of link loss calculation of 50 % reception probability of entire tested length 9
Figure 3 – Test arrangement for free-space method 11
Figure 4 – Antenna orientations with free-space method 12
Figure 5 – Test arrangement for ground-level method 13
Figure 6 – Antenna orientations with ground-level method 13
Figure 7 – Segmented test samples 15
Figure 8 – Segmented samples test 16
Figure 9 – Schematic diagram of the link loss of the radiating cable 17
Figure 10 – Segmented test samples for attenuation + coupling loss test method 17

Documents
Document Sharing Hub
Full document details: IEC 61196-1-127 2024

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COAXIAL COMMUNICATION CABLES –

Part 1-127: Electrical test methods – Link loss of radiating cable

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users shall ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61196-1-127 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46A/1661/FDIS	46A/1670/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English

Documents
Document Sharing Hub

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61196 series, published under the general title *Coaxial communication cables*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: IEC 61196-1-127 2024

COAXIAL COMMUNICATION CABLES –

Part 1-127: Electrical test methods – Link loss of radiating cable

1 Scope

This part of IEC 61196 applies to radiating cables. It specifies a test method for determining the link loss of radiating cables for use in communication systems.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1:2013, *Environmental testing – Part 1: General and guidance*

IEC 61196-1, *Coaxial communication cables – Part 1: Generic specification − General, definitions and requirements*

IEC 61196-1-123, *Coaxial communication cables – Part 1-123: Electrical test methods – Test for attenuation constant of radiating cable*

IEC 61196-1-124, *Coaxial communication cables – Part 1-124: Electrical test methods – Test for coupling loss of radiating cable*

IEC 61196-4, *Coaxial communication cables – Part 4: Sectional specification for radiating cables*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61196-1, IEC 61196-4 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1
link loss
ratio of the input power P_{in} transmitted into the transceiver end of the radiating cable from signal source to the power P_{r} received by a half-wavelength dipole antenna located at a distance from the radiating cable, expressed by Formula (1):

$$L_L(X) = 10log_{10}\frac{P_{in}}{P_r(X)} \quad (1)$$

where

Documents
Document Sharing Hub
Full document details: IEC 61196-1-127 2024

$L_L(X)$ is the link loss at the axial antenna position X, in dB;

P_{in} is the input power transmitted into the transceiver end of the radiating cable from the signal source, in W;

$P_r(X)$ is the receiving power of the half-wavelength dipole antenna at the axial antenna position X and at a radial distance from the radiating cable, in W;

X is the axial distance of the dipole from the transceiver end of the cable, in m.

4 Test equipment

4.1 Signal generator

A signal generator or other suitable signal source shall be used. Its output power, frequency range and bandwidth shall meet the measurement requirements. In order to ensure the repeatability of measurement, the frequency stability of signal generator or other signal source should be better than 10^{-6}.

4.2 Receiver

The frequency range, bandwidth, sampling rate, sensitivity and port type of the receiver shall meet the test requirements. If equivalent equipment can achieve the same function, it can also be used. In order to ensure the repeatability of measurement, the measurement uncertainty of the receiver or equivalent equipment (such as the vector network analyser) should be better than 0,5 dB.

4.3 Trolley

The trolley can move freely along the track on one side of the cable to be tested.

4.4 Antenna

Generally, a half-wave dipole antenna shall be used; if other antenna types are used, the frequency range and the port type of antenna shall meet the test requirements. The accuracy of the antenna gain shall comply with the relevant specifications.

NOTE Not only the gain of an antenna has an impact on the test result but also its directivity. Highly directive antennas for instance enable different orientations to the cable compared with dipoles as described in Figure 4 and Figure 6. If other antenna types than dipoles are used, the antenna orientation relative to the cable needs to be clearly described in the test report.

4.5 Load

The frequency range, return loss, absorbed power and port type of the load shall comply with the test requirements.

4.6 Connecting cables and connectors

Connecting cables can be used to connect the signal generator to the tested cable, and the receiver to the antenna. The return losses of test leads, test connectors, adapters and other devices for connection shall at least be 2 dB better than the required value of the test sample.

Documents
Document Sharing Hub
Full document details: IEC 61196-1-127 2024