IEC 62435-2

Edition 1.0 2017-01

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Electronic components – Long-term storage of electronic semiconductor devices – Part 2: Deterioration mechanisms

Composants électroniques – Stockage de longue durée des dispositifs électroniques à semiconducteurs – Partie 2: Mécanismes de détérioration

IEC 62435-2:2017-01(en-fr)

Documents
Document Sharing Hub
Full document details: IEC 62435-2 2017

THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue
Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,…). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary
65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

Documents
Document Sharing Hub

Full document details: IEC 62435-2 2017

IEC 62435-2

Edition 1.0 2017-01

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Electronic components – Long-term storage of electronic semiconductor devices –
Part 2: Deterioration mechanisms

Composants électroniques – Stockage de longue durée des dispositifs électroniques à semiconducteurs –
Partie 2: Mécanismes de détérioration

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 31.020

ISBN 978-2-8322-3836-3

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

AVA Documents
Document Sharing Hub

Full document details: IEC 62435-2 2017

CONTENTS

FOREWORD 3
INTRODUCTION 5
1 Scope 7
2 Normative references 7
3 Terms, definitions and abbreviated terms 7
3.1 Terms and definitions 7
3.2 Abbreviated terms 8
4 Principles of deterioration 8
4.1 General 8
4.2 Solderability and oxidisation of lead finishes 8
4.3 Popcorning 8
4.4 Delamination 8
4.5 Corrosion and tarnishing 8
4.6 Electrical effects 9
4.7 High-energy ionizing radiation damage 9
4.8 Storage temperature risks to semiconductor devices 9
4.9 Noble metal finishes 9
4.10 Matte tin and other finishes 9
4.11 Solder ball and solder bump 9
4.12 Devices containing programmable memory – flash, programmable logic and other devices containing non-volatile memory cells 10
5 Technical validation of the components 10
5.1 Purpose 10
5.2 Test selection criteria 10
5.3 Measurements and tests 11
5.3.1 Assessment of the supplied batch reliability 11
5.3.2 List of test methods 11
5.4 Periodic assessment 12
Annex A (normative) Failure mechanisms – Encapsulated and non-encapsulated active components 14
Bibliography 17

Table 1 – List of tests 11
Table A.1 – Failure mechanisms: encapsulated and non-encapsulated active components 14

Documents
Document Sharing Hub
Full document details: IEC 62435-2 2017

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRONIC COMPONENTS – LONG-TERM STORAGE OF ELECTRONIC SEMICONDUCTOR DEVICES –

Part 2: Deterioration mechanisms

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62435-2 has been prepared by IEC technical committee 47: Semiconductor devices.

The text of this standard is based on the following documents:

FDIS	Report on voting
47/2327/FDIS	47/2350/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

Documents
Document Sharing Hub

Full document details: IEC 62435-2 2017

A list of all parts in the IEC 62435 series, published under the general title *Electronic components – Long-term storage of electronic semiconductor devices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

Documents
Document Sharing Hub

Full document details: IEC 62435-2 2017

INTRODUCTION

This document applies to the long-term storage of electronic components.

This is a document for long-term storage (LTS) of electronic devices drawing on the best long-term storage practices currently known. For the purposes of this document, LTS is defined as any device storage whose duration can be more than 12 months for product scheduled for long duration storage. While intended to address the storage of unpackaged semiconductors and packaged electronic devices, nothing in this standard precludes the storage of other items under the storage levels defined herein.

Although it has always existed to some extent, obsolescence of electronic components and particularly of integrated circuits, has become increasingly intense over the last few years.

Indeed, with the existing technological boom, the commercial life of a component has become very short compared with the life of industrial equipment such as that encountered in the aeronautical field, the railway industry or the energy sector.

The many solutions enabling obsolescence to be resolved are now identified. However, selecting one of these solutions should be preceded by a case-by-case technical and economic feasibility study, depending on whether storage is envisaged for field service or production, for example:

- remedial storage as soon as components are no longer marketed;
- preventive storage anticipating declaration of obsolescence.

Taking into account the expected life of some installations, sometimes covering several decades, the qualification times, and the unavailability costs, which can also be very high, the solution to be adopted to resolve obsolescence should often be rapidly implemented. This is why the solution retained in most cases consists in systematically storing components which are in the process of becoming obsolescent.

The technical risks of this solution are, a priori, fairly low. However, it requires perfect mastery of the implemented process and especially of the storage environment, although this mastery becomes critical when it comes to long-term storage.

All handling, protection, storage and test operations are recommended to be performed according to the state of the art.

The application of the approach proposed in this standard in no way guarantees that the stored components are in perfect operating condition at the end of this storage. It only comprises a means of minimizing potential and probable degradation factors.

Some electronic device users have the need to store electronic devices for long periods of time. Lifetime buys are commonly made to support production runs of assemblies that well exceed the production timeframe of its individual parts. This puts the user in a situation requiring careful and adequate storage of such parts to maintain the as-received solderability and minimize any degradation effects to the part over time. Major degradation concerns are moisture, electrostatic fields, ultra-violet light, large variations in temperature, air-borne contaminants, and outgassing.

Warranties and sparing also present a challenge for the user or repair agency as some systems have been designated to be used for long periods of time, in some cases for up to 40 years or more. Some of the devices needed for repair of these systems will not be available from the original supplier for the lifetime of the system or the spare assembly may be built with the original production run but then require long-term storage. This document was developed to provide a standard for storing electronic devices for long periods of time.

AVA Documents
Document Sharing Hub

Full document details: IEC 62435-2 2017

For storage of devices that are moisture sensitive but that do not need to be stored for long periods of time, refer to IEC TR 62258-3.

Long-term storage assumes that the device is going to be placed in uninterrupted storage for a number of years. It is essential that it is useable after storage. Particular attention should be paid to storage media surrounding the devices together with the local environment.

These guidelines do not imply any warranty of product or guarantee of operation beyond the storage time given by the manufacturer.

The IEC 62435 series is intended to ensure that adequate reliability is achieved for devices in user applications after long-term storage. Users are encouraged to request data from suppliers to these specifications to demonstrate a successful storage life as requested by the user. These standards are not intended to address built-in failure mechanisms that would take place regardless of storage conditions

These standards are intended to give practical guide to methods of long-duration storage of electronic components where this is intentional or planned storage of product for a number of years. Storage regimes for work-in-progress production are managed according to company internal process requirements and are not detailed in this series of standards.

The overall standard includes a number of parts. Parts 1 to 4 apply to any long-term storage and contain general requirements and guidance, whereas Parts 5 to 9 are specific to the type of product being stored. It is intended that the product specific part should be read alongside the general requirements of Parts 1 to 4.

Electronic components requiring different storage conditions are covered separately starting with Part 5.

The structure of the IEC 62435 series as currently conceived is as follows:

Part 1 – General

Part 2 – Deterioration mechanisms

Part 3 – Data

Part 4 – Storage

Part 5 – Die and wafer devices

Part 6 – Packaged or finished devices

Part 7 – MEMS

Part 8 – Passive electronic devices

Part 9 – Special cases

Documents
Document Sharing Hub

Full document details: IEC 62435-2 2017

ELECTRONIC COMPONENTS – LONG-TERM STORAGE OF ELECTRONIC SEMICONDUCTOR DEVICES –

Part 2: Deterioration mechanisms

1 Scope

This part of IEC 62435 is related to deterioration mechanisms and is concerned with the way that components degrade over time depending on the storage conditions applied. This part also includes guidance on test methods that may be used to assess generic deterioration mechanisms. Typically, this part is used in conjunction with IEC 62435-1 for any device long-term storage whose duration may be more than 12 months for product scheduled for long duration storage. Mechanisms that apply to specific component types are detailed in IEC 62435-5 to IEC 62435-9 (proposed)[1].

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60749-20-1, *Semiconductor devices – Mechanical and climatic test methods – Part 20-1: Handling, packing, labelling and shipping of surface-mount devices sensitive to the combined effect of moisture and soldering heat*

3 Terms, definitions and abbreviated terms

For the purposes of this document, the following terms, definitions and abbreviated terms apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1 Terms and definitions

3.1.1
storage environment
specially controlled storage area, with particular control of temperature, humidity, atmosphere and any other conditions depending on the product requirements

3.1.2
long-term storage
LTS
planned storage of components to extend the life-cycle for a duration with the intention of supporting future use

[1] Under preparation.

Documents
Document Sharing Hub

Full document details: IEC 62435-2 2017

3.1.3
MBB
moisture barrier bag
storage bag manufactured with a flexible laminated vapour barrier film that restricts the transmission of water vapour

Note 1 to entry: Refer to IEC 60749-20-1 for packaging of moisture sensitive products.

3.2 Abbreviated terms

BGA ball grid array

ES electro-static

ESD electro-static discharge

MSD moisture sensitive device

PWB printed wiring board

rH relative humidity

4 Principles of deterioration

4.1 General

In determining the deterioration mechanisms for products stored under LTS, it is important to consider not only the deterioration of the product itself (see Annex A) but also any deterioration mechanism that can affect the subsequent processing and use of the product.

4.2 Solderability and oxidisation of lead finishes

Device surfaces that will be soldered to another surface using reflow and/or wave soldering operations should join successfully. Solderability determines whether the surfaces intended to be joined metallurgically can perform as expected. Failure to form a complete metallurgical joint can result in conditions known as non-wets or de-wets; oxides typically contribute to solderability degradation. LTS factors that can impact the ability for a part to form a good metallurgical joint include humidity, oxygen exposure, cleanliness, foreign material, and contamination.

4.3 Popcorning

Moisture content within a material when heated rapidly results in expansion of the moisture in form of vapour. This vapour occupies greater space than the moisture from which it was derived. If this vapour is not allowed to dissipate, then the materials within which it is contained will increase in size and exceed the strength or ability of the material to contain the vapour. Subsequently an electronic device that was manufactured correctly (i.e., all materials were properly adhered) may then develop a loss of adhesion. This may lead to interface delamination, package blistering, cracking, and bubbling.

4.4 Delamination

Delamination can occur when moisture accumulates in the materials, voids or at the interface between layers. Subsequent exposure to cycling or thermal processing can cause a separation of materials. Dies with organic passivation, organic substrates, polymer encapsulants, and PWBs tend to absorb moisture which could subsequently outgas during high-temperature processing. The primary failure mode is interfacial disbanding and cohesive separation.

4.5 Corrosion and tarnishing

Corrosion is a chemical reaction that results in the oxidation and/or structural decomposition of metals. Metal migration is also a form of corrosion. Moisture, chemical attack and contamination enhances corrosion mechanisms; contaminants (including fluorine and chlorine)

AVA Documents Document Sharing Hub

Full document details: IEC 62435-2 2017

may be hydrated with atmospheric moisture or pollutants during shipment, handling and ambient storage and act as corrosion catalyst. Eliminating the moisture is key to inhibiting corrosion. Corrosion can lead to opens, shorts, dendrites, and discoloration.

Tarnishing of some metal finishes can lead to solderability issues, notably the tarnishing of silver and silver alloys predominantly caused by chemical reaction to oxygen and/or sulphur.

4.6 Electrical effects

Conductive or electro-static (ES) dissipative materials should be used when required for ESD protection. ESD may be caused by using inappropriate packing materials, too low relative humidity (rH), or proximity to ES field sources. This may lead to p-n junction damage, oxide breakdown/puncturing, or other sensitive parameter effects.

4.7 High-energy ionizing radiation damage

Where the product is known to be susceptible to damage caused by ionizing radiation (e.g., as from x-rays or other high energy radiation sources), exposure to such radiation shall be qualified and quantified to understand the potential damage. Some die types can be particularly sensitive to damage and parameter drift caused by radiation. Care should be taken to ensure protection from ionizing radiation sources for those products that are sensitive.

4.8 Storage temperature risks to semiconductor devices

Exposure to heat over time can accelerate some semiconductor failure mechanisms, including stress voiding in metallization and data loss in some non-volatile memory cell types that have been written to a desired state prior to storage. Refer to JEP-122 for further details on such mechanisms..

4.9 Noble metal finishes

No failure mechanisms have been identified that would compromise the reliability of plastic encapsulated solid state devices with lead finishes containing Au or Pd owing to storage. The best practise for long-duration storage is associated with a warehouse environment as described in IEC 60721-3-1 and as required by IEC 60749-20-1.

4.10 Matte tin and other finishes

Assuming proper MSD protection for the term of storage, lead finishes not containing Au or Pd may require tests such as solderability on aged units to confirm long-term storage integrity.

Consideration should be given to the likelihood of the creation of tin whiskers and oxide degradation that gives rise to solderability issues. Refer to lead finish guidelines in IEC 60749-21.

4.11 Solder ball and solder bump

Assuming proper MSD protection for the term of storage and that the solder balls or bumps are fully reflowed, no failure mechanisms have been identified that compromise the reliability of solder balled or bumped BGA packages stored for extended periods of time in a warehouse environment per IEC TR 62258-3. However, if the solder balls or bumps are not reflowed but are attached with an adhesive or a solder paste that has a lower melting point, the solder balls or bumps shall be examined for oxide growth that could affect adhesion or solderability. Surface analysis of the balls/bumps and solderability testing on aged units can be required to confirm acceptance for attach of the next level of assembly after long-term storage.

Documents
Document Sharing Hub

Full document details: IEC 62435-2 2017

4.12 Devices containing programmable memory – flash, programmable logic and other devices containing non-volatile memory cells

Devices that contain memory cells may contain certain locations that are factory programmed. These may be used to contain identification information and code that the device uses during normal component use or user programming. It is important to check that these types of components will not lose essential data during storage which can render the component non-functional after storage. The original component manufacturer may recommend special storage conditions, such as temperature maxima and minima to ensure that this data is not corrupted.

Subject to original component manufacturers' recommendations, it is recommended that such devices are stored in the un-programmed state. However, care should be taken to ensure that equipment to programme the devices will also be available when the components are taken out of storage. This may require storage of special programming equipment.

Where programmable devices are stored in the programmed state, then removal from storage should also include a test to check that the programming is not corrupted.

5 Technical validation of the components

5.1 Purpose

The purpose of the technical validation of the components with a view to their storage is to detect *a priori* the batches which do not offer proper reliability and life-time guarantees.

In designing the tests, consideration should be given to the application mission profile and the storage mission profile.

5.2 Test selection criteria

The first thing to be taken into account to select the tests to be implemented for storing components is to have these components previously qualified, depending on the profile of their expected mission.

In addition, in the case of multiple-source components, the selection of the sources shall have been validated by a method capable of evidencing "false" second sources.

The selection of the required tests and measurements will depend on the storage strategy adopted. It can cover a range from a minimal utilization with no tests to a maximal utilization, where all tests described in Table 1 would be performed.

As a whole, the technical validation of the components requires the following items to be checked:

a) compliance with the visual inspection criteria;

b) solderability checking;

c) sealing/hermeticity checking (for components with hermetic packages);

d) compliance with the electrical specifications in the temperature range;

e) checking of manufacturing control (technological analysis);

f) checking the supplied batch reliability.

The criteria for sanctions and the number of tested components may vary depending on the requirements and level of reliability, as well as the data collected from the original component manufacturer. At the end of the technical validation, a status is established for this batch in order to decide on its storage capability.

AVA Documents
Document Sharing Hub

Full document details: IEC 62435-2 2017