IEC 62629-62-11

Edition 1.0 2022-11

INTERNATIONAL STANDARD

colour inside

3D display devices –
Part 62-11: Measurement methods for virtual-image type – Optical

IEC 62629-62-11:2022-11(en)

Documents
Document Sharing Hub

Full document details: IEC 62629-62-11-2022

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2022 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Documents
Document Sharing Hub

Full document details: IEC 62629-62-11-2022

IEC 62629-62-11

Edition 1.0 2022-11

INTERNATIONAL STANDARD

colour inside

3D display devices –
Part 62-11: Measurement methods for virtual-image type – Optical

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.120; 31.260

ISBN 978-2-8322-6006-7

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: IEC 62629-62-11-2022

CONTENTS

FOREWORD 5
1 Scope 7
2 Normative references 7
3 Terms, definitions, and abbreviated terms 7
3.1 Terms and definitions 7
3.2 Abbreviated terms 8
4 Measurement systems 8
4.1 Measuring device 8
4.2 Measuring setup 9
4.2.1 Eye-box and virtual image plane 9
4.2.2 Determination of the eye-box 9
4.2.3 Measuring configuration for geometric property 11
4.2.4 Test image and denotation for the captured test image 12
5 Common measurement applied for 3D virtual-image geometry 13
5.1 General 13
5.2 Position estimation of measuring points 13
6 Measurement method for the geometry property of the virtual image plane 16
6.1 Measurement of virtual image distance 16
6.1.1 Conditions 16
6.1.2 Procedures 16
6.1.3 Reports 16
6.2 Measurement of look down/over angle 17
6.2.1 Conditions 17
6.2.2 Procedures 17
6.2.3 Reports 17
6.3 Measurement of field of view 18
6.3.1 Conditions 18
6.3.2 Procedures 18
6.3.3 Reports 19
7 Measurement methods for the geometric distortion of the virtual image plane 19
7.1 General 19
7.2 Measurement of static distortion 19
7.2.1 Conditions 19
7.2.2 Procedures 20
7.2.3 Reports 20
8 Measurement method for the distance between a user and a 3D virtual object 21
8.1 General 21
8.2 Measurement method 21
8.2.1 Conditions 21
8.2.2 Procedures 21
8.2.3 Reports 22
9 Measurement methods for luminance and chromaticity 22
9.1 General 22
9.2 Measurement for luminance drop over the eye-box 22
9.2.1 Conditions 22
9.2.2 Procedures 22

AVA Documents
Document Sharing Hub

Full document details: IEC 62629-62-11-2022

9.2.3 Reports 25
9.3 Measurement of the luminance and chromaticity for the virtual-image plane 25
9.3.1 Conditions 25
9.3.2 Procedures 26
9.3.3 Reports 28
Annex A (informative) Comparison of measurement items between the conventional 3D display and the virtual-image type 3D display 29
Annex B (informative) Comparison of the optical-property measurement methods for virtual images 31
Annex C (informative) Additional information for geometric property measurement of 3D virtual images using imaging LMDs 34
C.1 General 34
C.2 Reasons for the necessity of using three imaging LMDs 34
C.3 Geometric calibration process for the imaging LMDs 35
Annex D (informative) Measurement for static crosstalk 38
D.1 General 38
D.2 Preparations 38
D.3 Procedures 39
D.4 Reports 42
Bibliography 43

Figure 1 – Geometric relationship between an eye-box and a virtual-image plane 9
Figure 2 – Configuration for determination of the eye-box 10
Figure 3 – Measuring setup for geometric property 11
Figure 4 – Test image with nine measuring points (top) and the three corresponding images captured by three imaging LMDs (bottom) 12
Figure 5 – Denotation for each of the three corresponding images captured by three imaging LMDs 13
Figure 6 – Geometric relationship of the black circle of P_{11} in the test image, two imaging LMDs, and the captured P_{11} (indicated by m_{11}^{L} and m_{11}^{R}) by the two imaging LMDs of LMD_L and LMD_R 15
Figure 7 – Denotation for the black circle indicated by P_{11} (i and j = 1) in the three corresponding images captured by three imaging LMDs 15
Figure 8 – Measuring condition for the virtual image distance 16
Figure 9 – Measuring conditions for look down and look over angles 17
Figure 10 – Measuring conditions for field of view (FOV) 19
Figure 11 – Measuring conditions for evaluating static distortion 20
Figure 12 – Measuring conditions for the distance of the 3D virtual object 21
Figure 13 – Three images captured by three imaging LMDs for the 3D virtual object located at the back of the virtual plane 22
Figure 14 – Measuring location representation in the eye-box 23
Figure 15 – Measuring condition for luminance and chromaticity from the centre point in the eye-box 25
Figure A.1 – Example of 3D displays 29
Figure B.1 – Illustration of the measurement concept applied for this documenta 32
Figure B.2 – Illustration of the measurement concept applied for ISO 9241-305:2008, 6.11.1 [5] 33

AVA Documents
Document Sharing Hub
Full document details: IEC 62629-62-11-2022

Figure B.3 – Illustration of the measurement concept applied for SAE J 1757-2 [3] 33
Figure C.1 – Limit in the determination of the location of a 3D virtual object using two imaging LMDs 34
Figure C.2 – Determination of the location of a 3D virtual object using three imaging LMDs 35
Figure C.3 – World, imaging LMD and 2D image (pixel) coordinates for calibration 37
Figure D.1 – Example of luminance profile created by four perspective images 38
Figure D.2 – Measuring layout for the 3D crosstalk of a 3D HUD 39
Figure D.3 – Example of luminance angular profile for 21 perspective images 41

Table 1 – Example of reported specification of an imaging LMD 8
Table 2 – Example of measurement results for the average of luminance drop for white colour over the eye-box shown in Figure 14 25
Table 3 – Example of measurement results for white (black) luminance, contrast, uniformity of white (black) luminance, and chromaticity coordinates in the measurement configuration of Figure 15 28
Table A.1 – Comparison of measurement items 30
Table B.1 – Comparison of the optical-property measurement methods for virtual images 32
Table D.1 – Example of measurement results for 3D crosstalk value 42

Documents
Document Sharing Hub
Full document details: IEC 62629-62-11-2022

INTERNATIONAL ELECTROTECHNICAL COMMISSION

3D DISPLAY DEVICES –

Part 62-11: Measurement methods for virtual-image type – Optical

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62629-62-11 has been prepared by IEC technical committee 110: Electronic displays. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
110/1459/FDIS	110/1473/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

AVA Documents
Document Sharing Hub

A list of all parts in the IEC 62629 series, published under the general title: *3D display devices*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: IEC 62629-62-11-2022

3D DISPLAY DEVICES –

Part 62-11: Measurement methods for virtual-image type – Optical

1 Scope

This part of IEC 62629 specifies the standard measuring conditions and measurement methods for determining the optical properties of the image created by 3D display devices and virtual-image optics such as head-up displays. The virtual image refers to an image in which the 3D visual information is superimposed with the outside world. Eye-wear type displays are however beyond the scope of this document.

NOTE The meaning of a virtual image in optics is in general an image formed when the outgoing rays from a point on an object always diverge. With regard to display application, a virtual image can be interpreted according to a real viewing case. When an image is viewed, even though there is no physical display (monitor, TV, screen), in front of a person's eyes, it is called virtual image.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendment-s) applies.

IEC 62629-1-2, *3D display devices – Part 1-2: Generic – Terminology and letter symbols*

3 Terms, definitions, and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62629-1-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1.1
virtual image distance
distance from the centre between both eyes to the centre of a virtual image

Note 1 to entry: The eye-centre corresponds to the point where the half of the binocular spacing is located.

3.1.2
field of view
angle subtending the area of the virtual image as observed from the centre between both eyes

3.1.3
eye-box
<3D display devices – virtual-image type> three-dimensional space within which the users place both their eyes and properly see the entire virtual image

Documents
Document Sharing Hub

Full document details: IEC 62629-62-11-2022

3.1.4
look down angle
angle in a downward direction between the normal line and viewing direction from which the virtual image is viewed at the centre between both eyes

Note 1 to entry: The normal line represents a line forming a vertical angle of 90° from the centre of the eye to the virtual image plane.

3.1.5
look over angle
angle in a sideway direction between the normal line and viewing direction from which the virtual image is viewed at the centre between both eyes

3.2 Abbreviated terms

CCD charge-coupled device

CMOS complementary metal-oxide semiconductor

FOV field of view

HUD head-up display

IPD inter pupil distance

LMD light measuring device

4 Measurement systems

4.1 Measuring device

A spot LMD or an imaging LMD such as a 2D imaging colorimeter should be applied for measuring light and colour properties, for example luminance value, chromaticity coordinates, etc. The specification of the LMD applied should be described in the report as in the example given in Table 1.

NOTE If a 3D display has the characteristics of multi-view, which is explained in IEC 62629-22-1 [1][1], the aperture size of 2 mm to 5 mm is suggested and is not larger than 6 mm.

Table 1 – Example of reported specification of an imaging LMD

Image sensor type	CCD, CMOS
Resolution	1 380 × 1 030, 2 448 × 2 050,
Luminance range	0,05 cd/m^2 to 100 000 cd/m^2
Repeatability	ΔL (luminance) < 0,1 % $\Delta x, y$ (chromaticity coordinate) < 0,001
Measuring accuracy	ΔL < 3 % (for Standard Illuminant A) $\Delta x, y$ < 0,002 (for Standard Illuminant A)

The geometric property of the 3D virtual image can be estimated using the imaging LMD (multiple imaging LMDs or one imaging LMD with movement). Annex A shows a comparison of measurement items between the conventional 3D display and the virtual-image type 3D display.

[1] Numbers in square brackets refer to the Bibliography.

Documents
Document Sharing Hub
Full document details: IEC 62629-62-11-2022

4.2 Measuring setup

4.2.1 Eye-box and virtual image plane

The geometric relationship between an eye-box and a virtual image plane is shown in Figure 1.



Figure 1 – Geometric relationship between an eye-box and a virtual-image plane

If users' eyes are placed in the eye-box, it is assumed that the users can view the entire virtual image without moving their head or making any other adjustment. The eye-box position can be specified by a supplier since this is varied by the application. The designed viewing distance shown in Figure 1 is the distance between the centre of the eye-box and the position on the half mirror, which should be suggested by the supplier. For the measurement, the designed viewing distance should be applied as the measuring distance.

If the eye-box location information is not provided by the supplier, this can be determined according to the method presented in 4.2.2. The measuring devices of the imaging LMD should be set up within the eye-box position. When the same left and right images without parallax are input, the plane on which the image is displayed is referred to as the virtual image plane. A 3D virtual object can be presented in the front or the back of the virtual image plane. A 3D coordinate system of xyz indicated in Figure 1 is defined in order to figure out the positions of the 3D virtual object and the virtual image plane from the eye-box of the users. The centre of the eye-box is defined as the zero position (xyz = 0).

NOTE If the supplier does not provide the eye-box position, this can be estimated by checking the geometric location where observers can view the entire virtual image plane. In general, the eye-box location is defined by the manufacturer according to the application. For example, it is determined by considering the distance from the windshield or combiner to the driver for automotive application, and the distance from the user to the half mirror for the exhibition application.

4.2.2 Determination of the eye-box

If the eye-box position is not provided by the supplier, the following method can be applied to determine the eye-box:

NOTE H1 to H9 and V1 to V7 in Figure 2 indicate examples of the position of the imaging LMD to determine the eye-box.

Documents
Document Sharing Hub
Full document details: IEC 62629-62-11-2022



Figure 2 – Configuration for determination of the eye-box

a) a full grey input image (e.g. RGB = 50) with a white outline and a centre grey square (1 / 5 input image size in the horizontal and vertical position, e.g. RGB = 200) can be used as shown in Figure 2;

b) an imaging LMD is located at the designed viewing distance (z = 0) and should be directed to the centre point of the input image;

c) the virtual image of full grey input is captured, and the luminance of the centre grey square is measured by moving the imaging LMD in an increment of 5 mm from left to right;

NOTE 1 When the experimenter visually observes the virtual image (in Figure 2) at the designed viewing distance, the left border of the target virtual image starts to be viewed. The LMD is placed at position H1.

d) find the maximum luminance value from those measured while moving the imaging LMD, and calculate the percentage of the maximum luminance value at all imaging LMD locations;

e) the leftmost and rightmost positions, at which the full grey image with the white outline is acquired and the percentage of the maximum luminance value is greater than 50 %, are determined in the x-axis (for instance, almost half of the virtual image plane and 40 % of the percentage of the maximum luminance value are only acquired by the imaging LMD at the H1 position);

NOTE 2 The percentage of the maximum luminance value applied to find the eye-box boundary can be selected as 50 % or something else, but the value will be recorded in the report.

f) for example, the leftmost and rightmost horizontal positions to be determined are H3 and H8 in Figure 2;

NOTE 3 The left eye and right eye are located at the leftmost and rightmost positions determined through the procedures (a) to (e). Both eyes are free to be located inside the leftmost and rightmost positions.

g) the horizontal centre (x = 0) is found from the middle position of H3 and H8;

h) the virtual image of full grey input is captured and the luminance of the centre grey square is measured by moving the imaging LMD in an increment of 5 mm from the bottom through the horizontal centre (x = 0) to the top;

i) find the maximum luminance value from those measured while moving the imaging LMD, and calculate the percentage of the maximum luminance value at all imaging LMD locations;

j) the bottommost and topmost positions, at which the full grey image with the white outline is acquired and the percentage of the maximum luminance value is greater than 50 %, are determined in the y-axis;

k) for example, the bottommost and topmost vertical positions to be determined are V2 and V6 in Figure 2;

AVA Documents Document Sharing Hub

l) the vertical centre (y = 0) is found from the middle position of V2 and V6; and

m) the zero position (xyz = 0) is finally determined.

4.2.3 Measuring configuration for geometric property

Figure 3 illustrates the configuration of three imaging LMDs and the test pattern displayed on the virtual-image plane in the three-dimensional xyz−coordinate system for evaluating geometric characteristics of the virtual projected image.



Figure 3 – Measuring setup for geometric property

The measurement items for assessing the virtual image geometry relative to a user's eyes are the look down/over angle, virtual image distance, and field of view. To ensure that projections are properly aligned, geometric distortion is also measured. The centre of the eye-box is defined to be the origin (x = 0, y = 0 and z = 0) at which the centre imaging LMD (LMD_C) is placed. The gap between the left (LMD_L) and right (LMD_R) imaging LMDs is assumed to be the same as the inter pupil distance (IPD) of a user. The average IPD of 60 mm or 65 mm can be used for this gap. The IPDs are selected to reflect mean values among both male and female examinees found in previous research [2]. The distance between the $LMD_{L(R)}$ and LMD_C is the half of the distance between the LMD_L and LMD_R. If one imaging LMD instead of three imaging LMDs is applied, the measurement can be conducted by moving the imaging LMD. The measuring point for each of the nine black circles in the test pattern is named P_{ij} (i and j = 1, 2, 3). P_{ij} can be expressed as (x_{ij}, y_{ij}, z_{ij}) in the xyz-coordinate system.

The 3D virtual image/object to be evaluated can be located on the virtual image plane or in the front/rear of the virtual image plane (Figure 1). If the 3D virtual image/object is placed on the virtual image plane, there is no parallax. On the other hand, if the 3D virtual image/object to be evaluated is located in the front or rear of the virtual image plane, there is negative or positive parallax.

Annex B describes the principle of the geometric-property measurement method applied for this document and comparisons with other measurement methods. Annex C provides the geometric calibration process for the imaging LMD. The required calibration level should satisfy the following condition.

The rotation matrix R in the calibration result of three imaging LMDs (LMD_L, LMD_C and LMD_R) in Figure 3 should be $R_L = R_C = R_R$ in theory. For the practical case, if $R_L \neq R_C \neq R_R$, there is then nonzero for the difference in the vertical pixel index of $\left|n_{ij}^{L} - n_{ij}^{R}\right|$ between the captured images by LMD_L and LMD_R where the n is vertical pixel index of the captured image of the test pattern ij. To obtain reliable results, the value of $\left|n_{ij}^{L} - n_{ij}^{R}\right|$ should be less than 1 %, that is, the difference in the vertical pixel index between the captured images by LMD_L and LMD_R should

AVA Documents Document Sharing Hub

be less than the number of vertical pixels in the captured image/100. Details related to imaging LMD calibration are described in Annex C.

4.2.4 Test image and denotation for the captured test image

Figure 4 shows the test image composed of nine black circles and the three corresponding captured images by three imaging LMDs (LMD_L, LMD_C and LMD_R) placed in the left, centre and right positions of the eye-box. Every black circle includes a white cross in the centre. The distance between LMD_L and LMD_R is indicated by a. The measuring point(s) can be selected from the nine points of P_{11} to P_{33} as necessary.



Figure 4 – Test image with nine measuring points (top right) and the three corresponding images (bottom) captured by three imaging LMDs (top left)

Documents
Document Sharing Hub
Full document details: IEC 62629-62-11-2022



captured image by LMD_L captured image by LMD_C captured image by LMD_R

$P^L_{ij} = (m^L_{ij}, n^L_{ij})$ $P^C_{ij} = (m^C_{ij}, n^C_{ij})$ $P^R_{ij} = (m^R_{ij}, n^R_{ij})$

NOTE m, n: pixel index of the captured image, which is an integer.

Figure 5 – Denotation for each of the three corresponding images captured by three imaging LMDs

Figure 5 shows the denotation in terms of P^L_{ij}, P^C_{ij}, and P^R_{ij} for the test patterns in the three corresponding captured images by three imaging LMDs, that is LMD_L, LMD_C and LMD_R. Since P^L_{ij}, P^C_{ij}, and P^R_{ij} are the two-dimensional coordinates on the captured images, $P^{L,C,R}_{ij}$ is represented by ($m^{L,C,R}_{ij}$, $n^{L,C,R}_{ij}$) where m and n are pixel indexes of the captured image of the test pattern.

5 Common measurement applied for 3D virtual-image geometry

5.1 General

The 3D virtual images should be properly aligned relative to a user's eyes. The geometric property therefore shall be evaluated for the projected virtual-image plane and the 3D virtual objects (see Figure 1) that can be located in front or in back of the virtual image plane. Clause 5 introduces the common measurement method applied for the geometric property evaluation. Clause 6 and Clause 7 describe the specific procedures for evaluating the degree to which a virtual image is aligned from a user's location by focusing on four aspects: look down/over angle, field of view, distance between the user, and virtual image plane, and the distortion. Clause 8 describes the detailed procedures for determining the distance between the user and the 3D virtual object.

There is no parallax for the 3D virtual object placed on the virtual image plane, whereas there is negative or positive parallax for the 3D virtual object located in front or in back of the virtual image plane. The geometric properties for the virtual image plane (Figure 8 to Figure 11) and the 3D virtual object (Figure 12) are obtained based on the triangulation methodology. The input factors in the application of triangulation are the binocular disparity information acquired by the multiple imaging LMDs and the field of view of the imaging LMD.

If the geometric property measurement is made using other methods than that proposed by this document, these other methods shall be mentioned in the report.

5.2 Position estimation of measuring points

If the positions (P_{ij} = x_{ij}, y_{ij}, z_{ij}) for the nine points P_{11} to P_{33} on the captured image are determined in the xyz-coordinate system of Figure 3, the geometric information for the virtual

AVA Documents Document Sharing Hub