IEC 62891

Edition 1.0 2020-07

INTERNATIONAL STANDARD

colour inside

Maximum power point tracking efficiency of grid connected photovoltaic inverters

IEC 62891:2020-07(en)

Documents
Document Sharing Hub

Full document details: IEC 62891-2020

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

Documents
Document Sharing Hub

Full document details: IEC 62891-2020

IEC 62891

Edition 1.0 2020-07

INTERNATIONAL STANDARD

colour inside

Maximum power point tracking efficiency of grid connected photovoltaic inverters

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 27.160

ISBN 978-2-8322-8470-4

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: IEC 62891-2020

CONTENTS

FOREWORD 4
1 Scope 6
2 Normative references 6
3 Terms and definitions 6
3.1 Inverter input (PV generator) 6
3.2 Inverter output (grid) 7
3.3 Measured quantities 7
3.4 Calculated quantities 8
4 MPPT efficiencies 9
4.1 General description 9
4.2 Test set-up 10
4.3 Static MPPT efficiency 11
4.3.1 Test conditions 11
4.3.2 Measurement procedure 12
4.3.3 Evaluation – Calculation of static MPPT efficiency 13
4.4 Test conditions for dynamic MPPT efficiency 13
4.4.1 Dynamic MPPT efficiency 13
4.4.2 Measurement procedure 14
4.4.3 Evaluation – Calculation of the dynamic MPPT efficiency 14
5 Calculation of the overall efficiency 15
Annex A (normative) Requirements on the measuring apparatus 16
A.1 PV generator simulator 16
A.1.1 General 16
A.1.2 Requirements on the static characteristic 16
A.1.3 Requirement on the transient stability 17
A.1.4 Requirements on the dynamic characteristic 17
A.1.5 Requirements on electrical characteristic 17
A.1.6 Calibration – Uncertainty 17
A.2 AC power supply 17
Annex B (normative) Test conditions for dynamic MPPT efficiency 18
B.1 Test profiles 18
B.2 Test sequence with ramps 10 % – 50 % G_{STC} (See Table B.1) 20
B.3 Test sequence with ramps 30 % – 100 % G_{STC} (See Table B.2) 21
B.4 Start-up and shut-down test with slow ramps (See Table B.3 and Figure B.3) 21
B.5 Total test duration 22
Annex C (normative) Models of current/voltage characteristic of PV generator 23
C.1 PV generator model for MPPT performance tests 23
C.2 Alternative PV generator model for MPPT performance tests 27
Annex D (normative) Efficiency weighting factors 29
D.1 European efficiency 29
D.2 CEC efficiency 29
Annex E (normative) Specification of the static MPPT and conversion efficiency in terms of normalised rated AC power 30
E.1 General 30
E.2 Re-normalisation of output power P_{AC} to the rated output power $P_{AC,r}$ 30

AVA Documents
Document Sharing Hub

Full document details: IEC 62891-2020

E.3 Representation of the conversion efficiency in terms of normalised rated output power 30
E.4 Interpolation on normative nodes 31
E.5 Result 33
Bibliography 34

Figure 1 – Example test set-up for MPPT efficiency measurements 11
Figure B.1 – Test sequence for fluctuations between small and medium irradiation intensities 18
Figure B.2 – Test sequence for fluctuations between medium and high irradiation intensities 19
Figure B.3 – Test sequence for the start-up and shut-down test of grid connected inverters 22
Figure C.1 – Irradiation-dependent V-I- and V-P characteristic of a c-Si PV generator 25
Figure C.2 – Irradiation-dependent V-I- and V-P characteristic of a thin-film PV generator 26

Table 1 – Test specifications for static MPPT efficiency 12
Table A.1 – General requirements on the simulated I/V characteristic of the PV generator 16
Table B.1 – Dynamic MPPT-Test 10 % → 50 % G_{STC} (valid for the evaluation of $\eta_{MPPTdyn}$) 20
Table B.2 – Dynamic MPPT-Test 30 % → 100 % G_{STC} (valid for the evaluation of $\eta_{MPPTdyn}$) 21
Table B.3 – Dynamic MPPT- Slow Ramp 1 % → 10 % G_{STC} (valid for the evaluation of $\eta_{MPPTdyn}$) 21
Table C.1 – Technology-dependent parameters 24
Table C.2 – MPP-values obtained with the cSi PV model 25
Table C.3 – MPP-values obtained with the TF-PV mode 27
Table D.1 – Weighting factors and partial MPP power levels for the calculation of the European efficiency 29
Table D.2 – Weighting factors and partial MPP power levels for the calculation of the CEC efficiency (California Energy Commission) 29
Table E.1 – Measured quantities at the conversion efficiency test 30
Table E.2 – Conversion efficiency in term of rated AC power 31
Table E.3 – Allowed limits for the nodes of the normalised AC power 31
Table E.4 – Sought values by means of interpolation 32
Table E.5 – Interpolated conversion efficiencies 33

Documents
Document Sharing Hub
Full document details: IEC 62891-2020

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MAXIMUM POWER POINT TRACKING EFFICIENCY OF GRID CONNECTED PHOTOVOLTAIC INVERTERS

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62891 has been prepared by IEC technical committee 82: Solar photovoltaic energy systems.

The text of this standard is based on the following documents:

FDIS	Report on voting
82/1723/FDIS	82/1736/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

Documents
Document Sharing Hub

Full document details: IEC 62891-2020

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: IEC 62891-2020

MAXIMUM POWER POINT TRACKING EFFICIENCY OF GRID CONNECTED PHOTOVOLTAIC INVERTERS

1 Scope

This document provides a procedure for the measurement of the efficiency of the maximum power point tracking (MPPT) of inverters used in grid-connected photovoltaic (PV) systems. Both the static and dynamic MPPT efficiency are considered. Based on the static MPPT efficiency calculated in this document and steady state conversion efficiency determined in IEC 61683 the overall efficiency can be calculated.

The dynamic MPPT efficiency is indicated separately.

NOTE This document addresses PV inverters connected to an AC grid. However, this procedure may also be used for other power conversion devices with MPPT functionality used in PV systems, such as charge controllers or optimizers.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61683, *Photovoltaic systems – Power conditioners – Procedure for measuring efficiency*

IEC TS 61836, *Solar photovoltaic energy systems – Terms, definitions and symbols*

EN 50160, *Voltage characteristics of electricity supplied by public distribution networks*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC TS 61836 apply, as well as the following:

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1 Inverter input (PV generator)

3.1.1
maximum input voltage
$V_{\mathbf{DCmax}}$
allowed maximum voltage at the inverter input

Note 1 to entry: Exceeding of V_{DCmax} may destroy the equipment under test.

Documents
Document Sharing Hub
Full document details: IEC 62891-2020

3.1.2
minimum input voltage
V_{DCmin}
minimum input voltage for the inverter to energize the utility grid, independent of mode of operation

3.1.3
rated input voltage
$V_{DC,r}$
input voltage specified by the manufacturer, to which other data sheet information refers

3.1.4
maximum MPP voltage
V_{MPPmax}
maximum voltage at which the inverter can convert its rated power under MPPT conditions

3.1.5
minimum MPP voltage
V_{MPPmin}
minimum voltage at which the inverter can convert its rated power under MPPT conditions

Note 1 to entry: The actual minimum MPP voltage may depend on the grid voltage level.

3.1.6
rated input power
$P_{DC,r}$
rated input power of the inverter, which can be converted under continuous operating conditions

3.1.7
maximum input current
$I_{DC,max}$
maximum input current of the inverter under continuous operating conditions

Note 1 to entry: At inverters with several independent inputs, this value may depend on the chosen input configuration.

3.2 Inverter output (grid)

3.2.1
rated grid voltage
$V_{AC,r}$
utility grid voltage to which other data sheet information refers

3.2.2
rated power
$P_{AC,r}$
active power the inverter can deliver in continuous operation

3.3 Measured quantities

3.3.1
PV simulator MPP-Power
$P_{MPP,\ PVS}$
MPP power provided by the PV simulator

3.3.2
input power
P_{DC}
measured input power of the device under test

Documents
Document Sharing Hub
Full document details: IEC 62891-2020

3.3.3
PV simulator MPP voltage
$V_{\mathrm{MPP,\ PVS}}$
MPP voltage provided by the PV simulator

3.3.4
input voltage
V_{DC}
measured input voltage of the device under test

3.3.5
PV simulator MPP current
$I_{\mathrm{MPP,\ PVS}}$
MPP current provided by the PV simulator

3.3.6
input current
I_{DC}
measured input current of the device under test

3.3.7
output power
P_{AC}
measured AC output power of the device under test

3.3.8
output voltage
V_{AC}
measured AC voltage

3.3.9
output current
I_{AC}
measured AC output current of the device under test

3.4 Calculated quantities

3.4.1
MPPT efficiency, energetic
η_{MPPT}
ratio of the energy drawn by the device under test within a defined measuring period T_M to the energy provided theoretically by the PV simulator at the maximum power point (MPP):

$$\eta_{\mathrm{MPPT}} = \frac{\int_0^{T_{\mathrm{M}}} p_{\mathrm{DC}}(t) \cdot dt}{\int_0^{T_{\mathrm{M}}} p_{\mathrm{MPP}}(t) \cdot dt} \tag{1}$$

where

$P_{\mathrm{DC}}(t)$ is the instantaneous value of the power drawn by the device under test;

$P_{\mathrm{MPP}}(t)$ is the instantaneous value of the MPP power provided theoretically by the PV simulator.

Documents
Document Sharing Hub
Full document details: IEC 62891-2020

3.4.2
conversion efficiency, energetic
η_{conv}
.ratio of the energy delivered by the device under test at the AC terminal within a defined measuring period T_M to the energy accepted by the device under test at the DC terminal:

$$\eta_{conv} = \frac{\int_0^{T_M} p_{AC}(t) \cdot dt}{\int_0^{T_M} p_{DC}(t) \cdot dt} \tag{2}$$

where

$P_{AC}(t)$ is the instantaneous value of the delivered power at the AC terminal of the device under test;

$P_{DC}(t)$ is the instantaneous value of the accepted power at the DC terminal of the device under test.

3.4.3
overall efficiency, energetic
η_t
ratio of the energy delivered by the device under test at the AC terminals within a defined measuring period T_M to the energy provided theoretically by the PV simulator:

$$\eta_t = \frac{\int_0^{T_M} p_{AC}(t) \cdot dt}{\int_0^{T_M} p_{MPP}(t) \cdot dt} \text{ respectively } \eta_t = \eta_{conv} \cdot \eta_{MPPT} \tag{3}$$

3.5
photovoltaic array simulator
current source emulating the static and dynamic behaviour of a PV array, in particular the current-voltage characteristic (see IEC TS 61836).

Note 1 to entry: The requirements are outlined in Clause A.1.

4 MPPT efficiencies

4.1 General description

The MPPT efficiency describes the accuracy of an inverter to set its operating conditions to match the maximum power point on the characteristic curve of a PV generator. The overall MPPT efficiency is divided into static and dynamic efficiency components.

Because inverters with poor MPPT performance operate at a DC input voltage that is different from MPP voltage, and static power conversion efficiency depends on DC input voltage, the measurements of static MPPT efficiency and static power conversion efficiency according to 4.3 shall be performed simultaneously.

a) Static MPPT efficiency

Documents
Document Sharing Hub
Full document details: IEC 62891-2020

The static MPPT efficiency is determined by means of measurement as follows:

$$\eta_{\text{MPPTstat}} = \frac{1}{P_{\text{MPP,PVS}} \cdot T_{\text{M}}} \sum_i V_{\text{DC},i} \cdot I_{\text{DC},i} \cdot \Delta T \tag{4}$$

where

$V_{\text{DC},i}$ is the sampled value of the inverter's input voltage;

$I_{\text{DC},i}$ is the sampled value of the inverter's input current;

T_{M} is the overall measuring period;

ΔT is the period between two subsequent sample values.

The static MPPT efficiency describes the accuracy of an inverter to regulate on the maximum power point on a given static characteristic curve of a PV generator.

$V_{\text{DC},i}$ and $I_{\text{DC},i}$ shall be sampled at the same time.

b) Dynamic MPPT efficiency

Variations of the irradiation intensity and the resulting transition of the inverter to the new operation point are not considered with the static MPPT efficiency. For the evaluation of this transient characteristic the dynamic MPPT efficiency is specified. The dynamic MPPT efficiency is defined as:

$$\eta_{\text{MPPTdyn}} = \frac{1}{\sum_j P_{\text{MPP,PVS},j} \cdot \Delta T_j} \sum_i V_{\text{DC},i} \cdot I_{\text{DC},i} \cdot \Delta T_i \tag{5}$$

where

ΔT_j is the period in which the power $P_{\text{MPP,PVS},j}$ is provided;

ΔT_i is the period in which the power $V_{\text{DC},i}$ and $I_{\text{DC},i}$ are sampled.

4.2 Test set-up

The generic test set-up for single phase grid connected inverters is depicted in Figure 1. The diagram can also be considered as a single-phase representation of a test-circuit for multi phase inverters.

Documents
Document Sharing Hub
Full document details: IEC 62891-2020