



IEC 80000-13

Edition 2.0 2025-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Quantities and units –
Part 13: Information science and technology**

**Grandeurs et unités –
Partie 13: Science et technologies de l'information**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



IEC 80000-13

Edition 2.0 2025-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Quantities and units –
Part 13: Information science and technology**

**Grandeurs et unités –
Partie 13: Science et technologies de l'information**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 01.060; 01.040.35

ISBN 978-2-8327-0160-7

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

AVA Documents
Document Sharing Hub

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
0.1 Tables of quantities	5
0.2 General	5
0.3 Remark on units for quantities whose dimensional exponents are all equal to zero.....	5
0.4 Numerical statements in this International Standard	5
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	6
4 Prefixes for binary multiples	17
Alphabetical index	18
Bibliography.....	20
Table 1 – Quantities and units in information science and technology	7
Table 2 – Prefixes for binary multiples	17

INTERNATIONAL ELECTROTECHNICAL COMMISSION

QUANTITIES AND UNITS –

Part 13: Information science and technology

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC and ISO draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC and ISO take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC and ISO had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch> or www.iso.org/patents. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

IEC 80000-13 has been prepared by IEC technical committee 25: Quantities and units in close cooperation with ISO/TC 12 Quantities and units. It is an International Standard.

This second edition cancels and replaces the first edition published in 2008. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) addition of new prefixes for binary multiples.

The text of this International Standard is based on the following documents:

Draft	Report on voting
25/811/FDIS	25/823/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

A list of all parts in the ISO 80000 and IEC 80000 series, published under the general title *Quantities and units*, can be found on the ISO and IEC websites.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

0.1 Tables of quantities

In most cases, only one name and only one symbol for the quantity are given; where two or more names or two or more symbols are given for one quantity and no special distinction is made, they are on an equal footing. When two types of italic letters exist (for example as with ϑ and θ ; $\wp$ and ϕ ; a and α ; g and g), only one of these is given. This does not mean that the other is not equally acceptable. It is recommended that such variants should not be given different meanings. A symbol within parenthesis implies that it is a reserve symbol, to be used when, in a particular context, the main symbol is in use with a different meaning.

0.2 General

The names of units for the corresponding quantities are given together with the international symbols and the definitions. These unit names are language-dependent, but the symbols are international and the same in all languages. For further information, see the SI Brochure (9th edition 2019, updated in 2024) from BIPM and ISO 80000-1.

The units are arranged in the following way:

- The coherent SI units are given first. The SI units have been adopted by the General Conference on Weights and Measures (Conférence Générale des Poids et Mesures, CGPM). The use of coherent SI units, and their decimal multiples and submultiples formed with the SI prefixes are recommended, although the decimal multiples and submultiples are not explicitly mentioned.
- Some non-SI units are then given, being those accepted by the International Committee for Weights and Measures (Comité International des Poids et Mesures, CIPM), or by the International Organization of Legal Metrology (Organisation Internationale de Métrologie Légale, OIML), or by ISO and IEC, for use with the SI. Such units are separated from the SI units in the item by use of a broken line between the SI units and the other units.

0.3 Remark on units for quantities whose dimensional exponents are all equal to zero

The coherent unit for any quantity whose dimensional exponents are equal to zero is the number one, symbol 1. When the value of such a quantity is expressed, the unit symbol 1 is generally not written out explicitly. Quantities that are ratios of quantities of the same kind (for example length ratios and amount fractions) have the option of being expressed with units (m/m, mol/mol) to aid the understanding of the quantity being expressed and also allow the use of SI prefixes, if this is desirable ($\mu\text{m}/\text{m}$, nmol/mol).

EXAMPLE 1

Refractive index $n = 1,53 \times 1 = 1,53$

Prefixes shall not be used to form multiples or submultiples of this unit. Instead of prefixes, powers of 10 are recommended.

EXAMPLE 2

Reynolds number $Re = 1,32 \times 10^3$

0.4 Numerical statements in this International Standard

The sign = is used to denote "is exactly equal to", the sign $\approx$ is used to denote "is approximately equal to", and the sign := is used to denote "is by definition equal to".

QUANTITIES AND UNITS –

Part 13: Information science and technology

1 Scope

This document specifies names, symbols and definitions for quantities and units used in information science and technology. Where appropriate, conversion factors are also given. Prefixes for binary multiples are also given.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

The names, definitions and symbols for quantities and units of information science and technology are given in Table 1 on the following pages.

Table 1 – Quantities and units in information science and technology

Item No.	Quantity			Unit		Remarks
	Name	Symbol	Definition	Name	Symbol	
13-1	traffic intensity	A	number of simultaneously busy resources in a particular pool of resources	erlang	E	1 E corresponds to the occupancy of one resource. The name "erlang" was given to the traffic intensity unit in 1946 by the International Telephone Consultative Committee (CCIF), in honour of the Danish mathematician, A. K. Erlang (1878-1929), who was the founder of traffic theory in telephony. See IEV 715-05-02.
13-2	traffic offered intensity	A_o	traffic intensity (item 13-1) of the traffic that would have been generated by the users of a pool of resources if their use had not been limited by the size of the pool	erlang	E	1 E corresponds to the occupancy of one resource. See IEV 715-05-05.
13-3	traffic carried intensity, traffic load	Y	traffic intensity (item 13-1) of the traffic served by a particular pool of resources	erlang	E	1 E corresponds to the occupancy of one resource. General practice is to estimate the traffic intensity as an average over a specified time interval, e.g. the busy hour. See IEV 715-05-04.
13-4	mean queue length	$L, (\Omega)$	time average of queue length	one	1	For the unit one, see the Introduction. See IEV 171-02-34.
13-5	loss probability	B	probability for losing a call attempt	one	1	For the unit one, see the Introduction.
13-6	waiting probability	W	probability for waiting for a resource	one	1	For the unit one, see the Introduction.
13-7	call intensity, calling rate	λ	number of call attempts over a specified time interval divided by the duration (ISO 80000-3:2019, item 3-9) of this interval	second to the power of minus one inverse second	s ⁻¹	See IEV 715-03-13.
13-8	completed call intensity	μ	call intensity (item 13-7) for the call attempts that result in the transmission of an answer signal	second to the power of minus one inverse second	s ⁻¹	For a definition of the complete call attempt, see IEV 715-03-11.

Item No.	Quantity			Unit		Remarks
	Name	Symbol	Definition	Name	Symbol	
13-9	storage capacity, storage size	M	amount of data that can be contained in a storage device, expressed as a number of specified data elements	one bit octet byte	1 bit o B	For the unit one, see the Introduction. The specified data elements depend on the organization of the storage device, for example, binary elements (also called "bits"), octets (also called "bytes"), words of a given number of bits, blocks. A subscript referring to a specified data element can be added to the symbol. EXAMPLES: storage capacity for bits, M_{bit} storage capacity for octets, M_{o} or M_{B}. For registers, the term "register length" is used with the same meaning. Although in this context the designation "bit", symbol bit, is not really a unit, it is often used like a unit, e.g. $M_{\text{bit}} = 32\,000$, where the unit one is implicit, is often written as $M = 32\,000$ bit. Similarly, although the designation octet or byte, symbols o and B, respectively, are not units, they are often used like units, e.g., $M_{\text{o}} = 4\,000$ or $M_{\text{B}} = 4\,000$, where the unit one is implicit, are often written $M = 4\,000$ o or $M = 4\,000$ B. When used to express a storage capacity or an equivalent binary storage capacity, the bit and the octet (or byte) may be combined with SI prefixes or prefixes for binary multiples. In English, the name "byte", symbol B, is used as a synonym for "octet". Here, "byte" means an eight-bit byte. However, "byte" has been used for numbers of bits other than eight. To avoid the risk of confusion, it is strongly recommended that the name "byte" and the symbol B be used only for eight-bit bytes. The symbol B for byte is not international and is not to be confused with the symbol B for bel.

Item No.	Quantity			Unit		Remarks
	Name	Symbol	Definition	Name	Symbol	
13-10	equivalent binary storage capacity	M_e	$M_e = \lg n$ where n is the number of possible states of the given device	one bit	1 bit	For the unit one, see the Introduction. The minimum storage capacity of a bit-organized storage device which would contain the amount of data in the given storage device is equal to the smallest integer greater than or equal to the equivalent binary storage capacity. When used to express a storage capacity or an equivalent binary storage capacity, the bit may be combined with SI prefixes or prefixes for binary multiples (see Clause 4). In this context, "bit" is a special name as well as symbol for the coherent unit one. For the unit one, see the Introduction.
13-11	transfer rate	$r, (v)$	quotient of the number of specified data elements transferred in a time interval by the duration of this interval	second to the power of minus one inverse second	s^{-1}	The symbol v is the Greek letter nu. A subscript referring to a specified data element can be added to the symbol. EXAMPLES: digit rate, r_d or v_d (see IEC 702-05-23 and IEC 704-16-06); transfer rate for octets (or bytes), r_o, r_B, v_o, v_B ; binary digit rate or bit rate (item 13-13). In English, the name "byte", symbol B, is used as a synonym for "octet". Here "byte" means an eight-bit byte. See remarks in item 13-9. The octet per second (or byte per second) may be combined with prefixes, for example kilooctet per second, symbol ko/s (or kilobyte per second, symbol kB/s).
				digit per second octet per second, byte per second	o/s, B/s	

Item No.	Quantity			Unit		Remarks
	Name	Symbol	Definition	Name	Symbol	
13-12	period of data elements, period duration of data elements	T	$T = 1 / r$ where r is the transfer rate (item 13-11) when the data elements are transmitted in series	second	s	A subscript referring to a specified data element can be added to the symbol. EXAMPLES: period of digits, T_d ; period of octets (or bytes), T_o or T_B . For the unit second, see IEC 112-02-04. See IEC 171-06-05.
13-13	binary digit rate, bit rate	$r_{\text{bit}}, (v_{\text{bit}})$	transfer rate (item 13-11) where the data elements are binary digits	second to the power of minus one inverse second	s^{-1}	In English, the systematic name would be "transfer rate for binary digits". The bit per second may be combined with prefixes, for example megabit per second, symbol Mbit/s.
13-14	period of binary digits, period duration of binary digits, bit period	T_{bit}	$T_{\text{bit}} = 1 / r_{\text{bit}}$ where r_{bit} is the binary digit rate (item 13-13) when the binary digits are transmitted in series	bit per second	bit/s	See IEC 704-16-07.
13-15	equivalent binary digit rate, equivalent bit rate	$r_e, (v_e)$	binary digit rate (item 13-13) equivalent to a transfer rate (item 13-11) for specified data elements	second to the power of minus one inverse second	s^{-1}	In English, the systematic name would be "equivalent binary transfer rate". See IEC 704-17-05.
13-16	modulation rate, line digit rate	r_m, μ	inverse of the shortest duration of a signal element	bit per second	bit/s	The term "modulation rate" is used in conventional telegraphy and data transmission. In isochronous digital transmission, the term "line digit rate" is generally used. $1 \text{ Bd} := \text{s}^{-1}$
				baud	Bd	Baud is a special name for the second to the power of minus one for this quantity. The baud may be combined with prefixes, for example kilobaud, symbol kBd, megabaud, symbol MBd. See IEC 704-17-03.

Item No.	Quantity			Unit		Remarks
	Name	Symbol	Definition	Name	Symbol	
13-17	quantizing distortion	T_Q	distortion of a signal resulting from the process of quantizing an original signal when the values to be quantized are within the working range of the quantizer	watt	W	For the unit watt, see IEC 113-03-55. See IEC 704-24-13. The unit of the quantizing distortion is the same as the unit of the signal. This may not always be the watt.
13-18	carrier power	P_c, C	power supplied to the antenna feed line by a radio transmitter taken under the condition of no modulation	watt	W	See IEC 713-09-20.
13-19	signal energy per binary digit	E_{bit}	$E_{\text{bit}} = P_c T_{\text{bit}}$ where P_c is carrier power (item 13-18) and T_{bit} is period of binary digits (item 13-14)	joule	J	For the unit joule, see IEC 113-03-46. See IEC 171-06-07.
13-20	error probability	P	probability that a data element be incorrectly received	one	1	For the unit one, see the Introduction. A subscript referring to a specified data element can be added to the symbol. EXAMPLES: error probability for binary digits or bit error probability, P_{bit} block error probability, P_{bl} The measured value is designated as "error ratio", whereas "error rate" is deprecated, for example, "bit error ratio" (BER), "block error ratio". See IEC 171-06-08.
13-21	Hamming distance	d_n	number of digit positions in which the corresponding digits of two words of the same length are different	one	1	For the unit one, see the Introduction. See IEC 721-08-25.
13-22	clock frequency, clock rate	f_{cl}	frequency at which a clock oscillates	hertz	Hz	For the unit hertz, see IEC 103-06-18.
13-23	decision content	D_a	$D_a = \log_a n$ where a is the number of possibilities at each decision and n the number of events	one	1	For the unit one, see the Introduction. When the same base is used for the same number of events then $D_a = H_0$, where H_0 is maximum entropy (item 13-26). See IEC 171-07-10.

Item No.	Quantity			Unit		Remarks
	Name	Symbol	Definition	Name	Symbol	
13-24	information content	$I(x)$	$I(x) = \lg \frac{1}{p(x)} \text{ Sh}$ $= \lg \frac{1}{p(x)} \text{ Hart}$ $= \ln \frac{1}{p(x)} \text{ nat}$ where $p(x)$ is the probability of event x	shannon hartley natural unit of information	Sh Hart nat	One shannon is the quantity value when the argument is equal to two. 1 Sh $\approx$ 0,693 nat $\approx$ 0,301 Hart One hartley is the quantity value when the argument is equal to ten. 1 Hart $\approx$ 3,322 Sh $\approx$ 2,303 nat One natural unit of information is the quantity value when the argument is equal to e, Euler's number. 1 nat $\approx$ 1,433 Sh $\approx$ 0,434 Hart See IEV 171-07-14.
13-25	entropy	H	$H(X) = \sum_{i=1}^n p(x_i) I(x_i) \text{ for the set}$ $X = \{X_1, \dots, X_n\}$ where $p(x_i)$ is the probability, and $I(x_i)$ is the information content of event x_i	shannon hartley natural unit of information	Sh Hart nat	See IEV 171-07-15.
13-26	maximum entropy	$H_0, (H_{\max})$	maximum entropy occurs when $p(x_i) = 1/n$ for $i = 1, \dots, n$	shannon hartley natural unit of information	Sh Hart nat	The maximum entropy is sometimes called "decision content" because the value is the same when the base is an integer, for the same number of events. See item 13-23. See IEV 171-07-16.
13-27	relative entropy	H_r	$H_r = H / H_0$ where H is entropy (item 13-25) and H_0 is maximum entropy (item 13-26)	one	1	See IEV 171-07-17.
13-28	redundancy	R	$R = H_0 - H$ where H is entropy (item 13-25) and H_0 is maximum entropy (item 13-26)	shannon hartley natural unit of information	Sh Hart nat	See IEV 171-07-18.