IEC TR 61292-4

Edition 4.0 2023-01

TECHNICAL REPORT

colour inside

Optical amplifiers –
Part 4: Maximum permissible optical power for the damage-free and safe use of optical amplifiers, including Raman amplifiers

Documents
Document Sharing Hub

IEC TR 61292-4:2023-01(en)

Full document details: IEC TR 61292-4-2023

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, …). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch
Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Documents
Document Sharing Hub

Full document details: IEC TR 61292-4-2023

IEC TR 61292-4

Edition 4.0 2023-01

TECHNICAL REPORT

colour inside

Optical amplifiers –
Part 4: Maximum permissible optical power for the damage-free and safe use of optical amplifiers, including Raman amplifiers

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.10; 33.180.30

ISBN 978-2-8322-6339-6

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: IEC TR 61292-4-2023

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions, and abbreviated terms 8
3.1 Terms and definitions 8
3.2 Abbreviated terms 8
4 Maximum transmissible optical power to keep fibres damage-free 8
4.1 General 8
4.2 Fibre fuse and its propagation 9
4.3 Loss-induced heating at connectors or splices 10
4.4 Connector endface damage induced by dust/contamination 11
4.5 Fibre coat burn/melt induced by tight fibre bending 13
4.6 Summary of the fibre damage 14
5 Maximum transmissible optical power to keep eyes and skin safe 15
5.1 Maximum transmissible exposure (MPE) on the surface of eye and skin 15
5.2 Maximum permissible optical power in the fibre for the safety of eye and skin 15
5.2.1 Power limit 15
5.2.2 Need for APR 16
5.2.3 Wavelengths 17
5.2.4 Locations 17
5.2.5 Nominal ocular hazard distance (NOHD) 17
5.2.6 Power reduction times 17
5.2.7 Medical aspects of the safety of eyes and skin in existing standards 18
6 Maximum optical power permissible for optical amplifiers from the viewpoint of fibre damage as well as eye and skin safety 19
7 Conclusion 19
Annex A (informative) General information for optical fibre fuse 20
A.1 Introductory remark 20
A.2 Generating mechanism 20
A.3 Void formation mechanism 24
A.4 Propagation characteristic of a fibre fuse 24
A.5 Prevention and termination 26
A.5.1 General 26
A.5.2 Prevention methods 26
A.5.3 Termination methods 27
A.6 Additional safety information 29
A.7 Conclusion 29
Bibliography 30

Figure 1 – Experimental set-up for fibre fuse propagation 9
Figure 2 – Connection loss versus temperature increase 11
Figure 3 – Test set-up 11
Figure 4 – Surface condition contaminated with metal filings, before the test 12
Figure 5 – Variation of power attenuation during test at several power input values for plugs contaminated with metal filings 13

AVA Documents
Document Sharing Hub

Full document details: IEC TR 61292-4-2023

Figure 6 – Polishing surface condition contaminated with metal filing, after test 13
Figure 7 – Thermo viewer image of tightly bent SMF with optical power of 3 W at 1 480 nm 14
Figure 8 – Temperature of the coating surface of SMFs against bending with optical power of 3 W at 1 480 nm 14
Figure 9 – Maximum permissible power in the fibre against APR power reduction time 18
Figure A.1 – Front part of the fibre fuse damage generated in the optical fibre 20
Figure A.2 – SiO absorption model 22
Figure A.3 – Calculated fibre fuse propagation behaviour simulated with the SiO absorption model 23
Figure A.4 – Series of optical micrographs showing damage generated by 9,0 W 1 480 nm laser light suggesting a mechanism of periodic void formation 24
Figure A.5 – Images of fibre fuse ignition taken with an ultra-high-speed camera and an optical micrograph of the damaged fibre 25
Figure A.6 – Power density dependence of the fibre-fuse propagation velocity 26
Figure A.7 – Optical micrographs showing front part of the fibre fuse damage generated in SMF-28 fibres with various laser intensities (1 480 nm) 26
Figure A.8 – Principle of the optical fibre fuse passive termination method and photograph of a fibre fuse terminator using a TEC structure 27
Figure A.9 – Photograph of hole-assisted fibre and fibre fuse termination using a hole-assisted fibre 28
Figure A.10 – Example of fibre fuse active termination scheme 29
Figure A.11 – Transformation of electrical signal by optical fibre fuse 29

Table 1 – Threshold power of fibre fuse propagation for various fibres 9
Table 2 – Measurement conditions 10
Table 3 – Examples of power limits for optical fibre communication systems having automatic power reduction to reduce emissions to a lower hazard level 16
Table 4 – Location types within an optical fibre communication system and their typical installations 17

Documents
Document Sharing Hub

Full document details: IEC TR 61292-4-2023

INTERNATIONAL ELECTROTECHNICAL COMMISSION

OPTICAL AMPLIFIERS –

Part 4: Maximum permissible optical power for the damage-free and safe use of optical amplifiers, including Raman amplifiers

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 61292-4 has been prepared by subcommittee 86C: Fibre optic systems and active devices, of IEC technical committee 86: Fibre optics. It is a Technical Report.

This fourth edition cancels and replaces the third edition published in 2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition.

a) The technical information has been updated to reflect revisions of the relevant references.
b) In particular, the descriptions provided in Clause 5 and Clause 6 have been modified significantly to reflect changes in the cited references. Unnecessary formulas and explanations that overlap with the references have been removed to simplify the document.
c) New information has been added to Annex A on optical fibre burning when light enters an optical fibre with a bubble train formed by a fibre fuse.

Documents
Document Sharing Hub

Full document details: IEC TR 61292-4-2023

The text of this Technical Report is based on the following documents:

Draft	Report on voting
86C/1821/DTR	86C/1832/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 61292 series, published under the general title *Optical amplifiers* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: IEC TR 61292-4-2023

INTRODUCTION

This document is dedicated to the subject of maximally permissible optical power for damage-free and safe use of optical amplifiers, including Raman amplifiers. Since the technology is quite new and still evolving, amendments and new editions to this document can be expected.

Many new types of optical amplifiers are entering the marketplace, and research is also stimulating the development of many new types of fibre and non-fibre based optical amplifiers. With the introduction of new technologies, such as long-haul, beyond 100 Gb/s, WDM transmission, digital coherent transmission and Raman amplification, some optical amplifiers employ optical pump sources with extremely high optical power – possibly up to several Watts. For example, erbium doped fibre amplifiers that provide extremely high output power are described in IEC TR 61292-8 [1][1], and Raman amplifiers in IEC TR 61292-6 [2].

Excessively high optical power can cause physical damage to the optical fibres, components and equipment, in addition to presenting a medical hazard to the human eye and skin.

The possibility of fibre damage caused by high optical intensity has been discussed at technical conferences and in technical reports for many years. The use of high intensity optical amplifiers can cause problems in optical fibres, which include fibre fuse, heating in the splice points (connection points), fibre endface damage due to dust, and fibre coat burning due to tight fibre bending. For example, IEC TR 62547 [3] provides guidelines for the measurement of high-power damage sensitivity of single-mode fibre to bends, and IEC TR 62627-01 [4] describes cleaning methods for fibre optic connectors to reduce the risk of fibre endface damage. In addition, other standard groups are discussing the risk of ignition of hazardous environments caused by high-power radiation from optical equipment.

The medical aspects of high-power optical radiation have also been addressed by standards. IEC 60825-2 defines the concept of hazard levels and corresponding labelling, which addresses the safety aspects of lasers specifically in relation to tissue damage.

In addition, IEC TR 60825-17 [5] describes safety measures to protect against effects caused exclusively by thermal, opto-mechanical and related effects in passive optical components and optical cables used in high power optical fibre communication systems. Moreover, ITU-T Recommendation G.664 [6] discusses the safety feature of automatic laser power reduction.

With the recently growing interest in high power fibre amplifiers and fibre Raman amplifiers, however, some difficulties have been identified among optical amplifier users and manufacturers in fully understanding the technical details and requirements across all such standards and agreements.

This document provides a simple informative guideline on the maximum optical power permissible for optical amplifiers for optical amplifier users and manufacturers.

[1] Numbers in square brackets refer to the Bibliography.

Documents
Document Sharing Hub

Full document details: IEC TR 61292-4-2023

OPTICAL AMPLIFIERS –

Part 4: Maximum permissible optical power for the damage-free and safe use of optical amplifiers, including Raman amplifiers

1 Scope

This part of IEC 61292, which is a Technical Report, applies to all commercially available optical amplifiers (OAs), including optical fibre amplifiers (OFAs) using active fibres as well as Raman amplifiers. Semiconductor optical amplifiers (SOAs) using semiconductor gain media are also included.

This document provides informative guidelines on the threshold of high optical power that can cause high-temperature damage of the fibre. Also discussed is optical safety for manufacturers and users of optical amplifiers by quoting parts of existing standards and agreements on eye and skin safety.

This document identifies the following values for maximum permissible optical power in the optical amplifier for damage-free and safe operation:

a) the optical power limit that causes thermal damage to the fibre, such as fibre fuse and fibre-coat burning;

b) the maximum permissible exposure (MPE) to which the eyes/skin can be exposed without consequent injury;

c) the optical power limit in the fibre that causes MPE on the eyes/skin after free-space propagation from the fibre;

d) the absolute allowable optical power level for damage-free and safe operation of the optical amplifier by comparing a) and c).

The objective of this document is to minimize potential confusion and misunderstanding in the industry that can cause unnecessary alarms and hinder the progress and acceptance of advancing optical amplifier technologies in the market.

It is important that the reader always refers to the latest international standards and agreements, because the technologies concerned are rapidly evolving.

The present document will be frequently reviewed and updated in a timely manner by incorporating the results of various studies related to OAs and OA-supported optical systems.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61291-1:2018, *Optical amplifiers – Part 1: Generic specification*

Documents
Document Sharing Hub

Full document details: IEC TR 61292-4-2023

3 Terms, definitions, and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61291-1:2018 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.2 Abbreviated terms

ALS automatic laser shutdown

APR automatic power reduction

DSF dispersion shifted fibre

LOS loss of signal

MFD mode field diameter

MPE maximum permissible exposure

MPI-R single channel receive main path Interface reference point

MPI-S single channel source main path interface reference point

NOHD nominal ocular hazard distance

NZ-DSF non-zero dispersion shifted single-mode fibre

OA optical amplifier

OFA optical fibre amplifier

OFCS optical fibre communication system

SMF single-mode fibre

SOA semiconductor optical amplifier

4 Maximum transmissible optical power to keep fibres damage-free

4.1 General

The use and reasonably foreseeable misuse of high intensity optical amplifiers can cause problems in the fibre such as

a) fibre fuse and its propagation,

b) heating in splice points/connection points,

c) fibre endface damage due to dust and other contamination, and

d) fibre coat burning and ignition of hazardous environments due to tight fibre bending or breakage.

Subclauses 4.2 to 4.5 introduce results concerning the above issues to give guidelines for the damage-free use of optical amplifiers. However, the following results are only valid under the conditions tested, and a higher power could be applied under different conditions.

Documents
Document Sharing Hub

Full document details: IEC TR 61292-4-2023

4.2 Fibre fuse and its propagation

The safety of optical amplifiers is discussed from the viewpoint of laser hazard to the eyes and skin and from the viewpoint of fibre damage such as fibre-coat burning and fibre fusing. Subclause 4.2 experimentally analyses the fibre fuse and its propagation caused by high optical power and discusses the threshold power of fibre fuse propagation [7]. Fibre fuse is defined as the phenomenon in which an intense blue-white flash occurs and runs along the fibre toward the high-power light source while forming periodic and/or non-periodic voids.

Figure 1 shows a typical measurement set-up for measuring the threshold power of fibre fuse propagation. The fibre fuse is initiated by heating the optical fibre from outside of the fibre with an independent heat source, while light at high optical power is continuously launched into the fibre. Once the fibre fuse begins propagating, the optical source power is continuously reduced until the fuse propagation stops. Table 1 shows the threshold powers which were measured at various wavelengths of the high-power optical source and for various fibres. Although the threshold power depends on the wavelength of the high-power optical source, the power for the fuse propagation is less than 1,4 W and 1,2 W for a standard single-mode fibre (SMF) and a dispersion shifted fibre (DSF) respectively, which are used as the optical fibre for typical optical fibre communication systems.



Figure 1 – Experimental set-up for fibre fuse propagation

Table 1 – Threshold power of fibre fuse propagation for various fibres

Fibre type	Measurement wavelength µm	Threshold power of fibre fuse propagation W
Standard single-mode fibre	1,064	1 [8]
	1,467	1,4 [8]
	1,48	~1,2 [9]
	1,55	1,39 [10]
Dispersion shifted fibre	1,064	1,2 [8]
	1,467	0,65 [8]
	1,55	~1,1 [11]
Dispersion compensation fibre	1,55	~0,7 [11]

The difference in fibre mode-field diameter has been identified as the major reason for the difference in the threshold powers because the fibre fuse depends on the power density [7], [8].

On the other hand, it is difficult to identify the threshold power for self-initiated fibre fuse (without any external cause) because it varies significantly. The threshold powers for self-initiated fibre fuse significantly exceed 1,4 W and 1,2 W for standard single-mode fibre (SMF) and dispersion shifted fibre (DSF) respectively.

Further information on the generating mechanism, the characteristics of fibre fuse and the prevention and termination of the fibre fuse are described in Annex A.

AVA Documents
Document Sharing Hub
Full document details: IEC TR 61292-4-2023