IEC TR 63037

Edition 1.0 2016-11

TECHNICAL REPORT

Withdrawn

Electrical interface specifications for self ballasted lamps and controlgear in phase-cut dimmed lighting systems

IEC TR 63037:2016-11(en)

Documents
Document Sharing Hub

Full document details: IEC TR 63037 2016

THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

Withdrawn

Documents
Document Sharing Hub

Full document details: IEC TR 63037 2016

IEC TR 63037

Edition 1.0 2016-11

TECHNICAL REPORT

withdrawn

Electrical interface specifications for self ballasted lamps and controlgear in phase-cut dimmed lighting systems

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.140.99

ISBN 978-2-8322-3711-3

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: IEC TR 63037 2016

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions and abbreviated terms 7
3.1 Terms and definitions 7
3.2 Abbreviated terms 9
4 General description 10
5 General requirements 10
5.1 Voltage rating 10
5.2 Frequency rating 11
5.3 Marking of controlgear 11
6 Description of the lighting system and its components 11
6.1 Wiring method 11
6.2 Wiring diagram 11
7 Electrical specification 12
7.1 General 12
7.2 Electrical characteristics during the on state of a phase-cut dimming system 12
7.2.1 General 12
7.2.2 Electrical characteristics for leading edge dimming method 12
7.2.3 Electrical characteristics for trailing edge dimming method 17
7.3 Electrical characteristics during the off state of a phase-cut dimming system 23
8 Test procedures 24
8.1 General 24
8.2 Tests for leading edge dimmable devices 24
8.2.1 General 24
8.2.2 Test related to the non-conducting phase 25
8.2.3 Test related to the transition from the non-conducting to the conducting phase and to the conducting phase 25
8.3 Tests for trailing edge dimmable devices 25
8.3.1 General 25
8.3.2 Test related to the conducting phase 25
8.3.3 Test related to the transition from the conducting phase to the non-conducting phase 26
8.3.4 Test related to the non-conducting phase 26
8.4 Tests for characteristics during electronic off state 27
Annex A (informative) Voltage shapes to be used with the tests in IEC TR 63037 28
A.1 General 28
A.2 Waveform description 28
A.3 Waveform description 28
Annex B (informative) Equivalent phase-cut dimmer circuit 29
Bibliography 30

Figure 1 – Example of wiring diagram 11
Figure 2 – Timing leading edge dimming method 14

Withdrawn

AVA Documents Document Sharing Hub

Full document details: IEC TR 63037 2016

Figure 3 – Timing trailing edge dimming method 18
Figure 4 – Test setup for testing the conducting phase 24
Figure 5 – Test setup for the transition from the conducting to the non-conducting phase 26
Figure 6 – Test setup for the non-conducting phase 27
Figure A.1 – Waveform of AC voltage source 28
Figure A.2 – Waveform of AC voltage source 28
Figure B.1 – Scheme of the EC_D 29

Table 1 – Nominal mains voltage 100 V; frequency 50 Hz or 60 Hz 14
Table 2 – Nominal mains voltage 120 V; frequency 50 Hz or 60 Hz 14
Table 3 – Nominal mains voltage 200 V; frequency 50 Hz or 60 Hz 14
Table 4 – Nominal mains voltage 230 V; frequency 50 Hz or 60 Hz 15
Table 5 – Nominal mains voltage 277 V; frequency 50 Hz or 60 Hz 15
Table 6 – Slew rate for voltage decrease across the phase-cut dimmer 16
Table 7 – Nominal mains voltage 100 V; frequency 50 Hz or 60 Hz 16
Table 8 – Nominal mains voltage 120 V; frequency 50 Hz or 60 Hz 16
Table 9 – Nominal mains voltage 200 V; frequency 50 Hz or 60 Hz 17
Table 10 – Nominal mains voltage 230 V; frequency 50 Hz or 60 Hz 17
Table 11 – Nominal mains voltage 277 V; frequency 50 Hz or 60 Hz 17
Table 12 – Nominal mains voltage from 100 V to 277 V; frequency 50 Hz or 60 Hz 19
Table 13 – Nominal mains voltage 100 V; frequency 50 Hz or 60 Hz 20
Table 14 – Nominal mains voltage 120 V; frequency 50 Hz or 60 Hz 21
Table 15 – Nominal mains voltage 200 V; frequency 50 Hz or 60 Hz 21
Table 16 – Nominal mains voltage 230 V; frequency 50 Hz or 60 Hz 22
Table 17 – Nominal mains voltage 277 V; frequency 50 Hz or 60 Hz 22
Table 18 – Currents and voltages for controlgear during the electronic off state 23
Table 19 – Parameters for testing purposes 24

Withdrawn

Documents
Document Sharing Hub
Full document details: IEC TR 63037 2016

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRICAL INTERFACE SPECIFICATIONS FOR SELF BALLASTED LAMPS AND CONTROLGEAR IN PHASE-CUT DIMMED LIGHTING SYSTEMS

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.

2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.

3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.

4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.

5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.

6) All users should ensure that they have the latest edition of this publication.

7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.

8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 63037, which is a Technical Report, has been prepared by IEC technical committee 34: Lamps and related equipment.

The text of this Technical Report is based on the following documents:

Enquiry draft	Report on voting
34/305/DTR	34/325/RVC

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

Withdrawn

AVA Documents Document Sharing Hub

Full document details: IEC TR 63037 2016

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

withdrawn

Documents
Document Sharing Hub

Full document details: IEC TR 63037 2016

INTRODUCTION

This document describes the technical requirements for self-ballasted lamps and controlgear to work with phase-cut dimmers. For a complete picture of the technical requirements the user should also refer to the companion document that contains technical requirements and testing methods for phase-cut dimmers (IEC TR 63036).

withdrawn

Documents
Document Sharing Hub

Full document details: IEC TR 63037 2016

ELECTRICAL INTERFACE SPECIFICATIONS FOR SELF BALLASTED LAMPS AND CONTROLGEAR IN PHASE-CUT DIMMED LIGHTING SYSTEMS

Withdrawn

1 Scope

This document specifies the electrical interface between phase-cut dimming equipment and lighting equipment, such as LED integrated lamps and light sources with external controlgear, with the intention of helping designers of both types of equipment to develop products that will work together properly.

This document describes both the dimming phase and the off phase. In addition to the specification of the interface, test procedures are given for testing the proper operation.

It may be expected that controlgear fulfilling the requirements of this document are also suited to be used with electronic switches that use a circuitry comparable with that of a phase-cut dimmer, but do not contain means for the adjustability of the phase-cut angle.

Safety requirements are not covered by this document, but by respective product standards

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-845, *International Electrotechnical Vocabulary. Lighting* (available at http://www.electropedia.org)

IEC 62504, *General lighting – Light emitting diode (LED) products and related equipment - Terms and definitions*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62504 and IEC 60050-845 as well as the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1.1
phase-cut dimmed lighting system
combination of a phase-cut dimmer and one or more controlgear and light sources

Documents
Document Sharing Hub

Full document details: IEC TR 63037 2016

3.1.2
off state
state of a phase-cut dimming system when no light is emitted

3.1.3
on state
state of a phase-cut dimming system when light is emitted

3.1.4
phase-cut dimmer
electronic switch which is connected in series with a load and changes the supply voltage waveform applied to the load from the pure mains voltage waveform to a leading edge (forward phase) or a trailing edge (reverse phase) AC voltage waveform or is capable of switching between both waveforms

Note 1 to entry: The output voltage waveform of a phase-cut dimmer is applied to one or more loads. The conduction angle of the voltage waveform is adjustable.

Note 2 to entry: Within this document, where the term “dimmer” is used the term “phase-cut dimmer” is meant.

3.1.5
two-wire phase-cut dimmer
phase-cut dimmer which is connected in series with the load and has no connection to neutral

3.1.6
three-wire phase-cut dimmer
phase-cut dimmer which is connected in series with the load and has in addition a connection to neutral

3.1.7
controlgear
device between the phase-cut dimmer and one or more lamps which may serve to transform the AC mains power, limit the current of the lamp(s) to the required value, provide starting voltage and preheating current, prevent cold starting, correct power factor or reduce radio interference

Note 1 to entry: Lamps may have integrated controlgear such as an integrated LED lamp. Any references to controlgear will include any such integrated lamps.

3.1.8
load side
connection from the output of the phase-cut dimmer to the supply input of one or more controlgear

3.1.9
conducting period
time period during which the phase-cut dimmer supplies power to a controlgear

3.1.10
non-conducting period
time period during which the phase-cut dimmer does not supply power to a controlgear

3.1.11
half-wave
positive or negative 180 degrees of an AC sine wave starting and ending at the zero crossing point

Withdrawn

Documents
Document Sharing Hub
Full document details: IEC TR 63037 2016

3.1.12
phase angle
position within a half-wave expressed in degree, being in the range of 0° to 180°, referred to the beginning of the half-wave

3.2 Abbreviated terms

To describe the electrical characteristics of the phase-cut interface, the following abbreviations are used:

α_x Angle where the test voltage starts rising with the given slew rate SR as shown in Figure A.1

β_x Angle where the test voltage starts falling with the given slew rate SR as shown in Figure A.2

C_f Filter capacitor to reduce high frequency disturbances

EC_CG Equivalent circuit that represents a controlgear for phase-cut dimmer testing purposes

EC_D Equivalent circuit that represents a phase-cut dimmer for controlgear testing purposes

I_{CG} Current through the input terminals of the controlgear

I_{CG_pk} Repetitive peak current of the controlgear in leading edge mode

I_{CG_SL} Current-carrying capability of the controlgear with $V_{CG} \leq V_{SW}$ in leading edge mode

I_{CG_STH} Current-carrying capability of the controlgear with $V_{CG} \leq V_{SW}$ in trailing edge mode

I_{CG_STL} Current-carrying capability of the controlgear with $V_{CG} > V_{SW}$ in trailing edge mode

I_D Current through the load side terminal of the phase-cut dimmer

I_{D_nc} Maximum current through the phase-cut dimmer during the non-conducting period, limited by the phase-cut dimmer

I_{EC_CG} Value of test current of EC_CG in the test circuit in Figure A.1

I_{PO} Minimum current carrying capability of the controlgear during the electronic off state

I_{trans} Current sourced by the phase-cut dimmer during the transition from the conducting to the non-conducting state in trailing edge mode.

n Required minimum number of controlgear connected with one phase-cut dimmer (named in phase-cut dimmer installation sheet)

P_{CG} Rated input power of the controlgear (as marked)

P_{max} Maximum permissible nominal load of phase-cut dimmer (according to installation sheet)

P_{min} Minimum nominal load required by phase-cut dimmer (according to installation sheet)

R_R Resistance value of resistive load R of the test circuit of Figure 5 (according to 8.3.3), dependent on maximum permissible load of phase-cut dimmer P_{max}

SR The absolute value of the slew rate of the decrease of the voltage across the input terminals of a controlgear in trailing edge dimming mode when the phase-cut dimmer switches off at time t_{s1} (see Figure 3).

SR_L The absolute value of the slew rate of the increase of the voltage across the input terminals of a controlgear in leading edge dimming mode when the phase-cut dimmer under test switches on (according to Clause 8)

SR_T The absolute value of the slew rate of the decrease of the voltage across the input terminals of a controlgear in trailing edge dimming mode when the phase-cut dimmer under test switches off (according to Clause 8)

t_{HW} Time related to previous zero crossing of the mains to the subsequent zero crossing of the mains (duration of a half-wave)

Withdrawn

AVA Documents Document Sharing Hub