

IEEE Standard for Information Technology—Portable Operating System Interface (POSIX™)

Base Specifications, Issue 7— Technical Corrigendum 1

IEEE Computer Society

and

The Open Group

Sponsored by the
Portable Applications Standards Committee

IEEE
3 Park Avenue
New York, NY 10016-5997
USA

IEEE Std 1003.1™-2008/Cor 1-2013
(Corrigendum to
IEEE Std 1003.1-2008)

15 March 2013

IEEE Standard for Information Technology—Portable Operating System Interface (POSIX™)

Base Specifications, Issue 7— Technical Corrigendum 1

Sponsor

**Portable Applications Standards Committee
of the
IEEE Computer Society**

and
The Open Group

Approved 6 February 2013

IEEE-SA Standards Board

Approved 25 October 2012

The Open Group

Abstract: This Technical Corrigendum addresses problems discovered since the approval of IEEE Std 1003.1™-2008.

Keywords: application program interface (API), argument, asynchronous, basic regular expression (BRE), batch job, batch system, built-in utility, byte, child, command language interpreter, CPU, extended regular expression (ERE), FIFO, file access control mechanism, IEEE 1003.1™, input/output (I/O), job control, network, portable operating system interface (POSIX™)

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2013 by The Institute of Electrical and Electronics Engineers, Inc. and The Open Group.
All rights reserved. Published 15 March 2013. Printed in the United States of America.

Published 15 March 2013 by The Open Group. Printed in the United Kingdom by The Open Group.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

POSIX is a trademark of IEEE.

The Open Group
Apex Plaza, Forbury Road, Reading, Berkshire RG1 1AX, U.K.

PDF: ISBN 978-0-7381-8265-0 STD698161

This standard has been prepared by the Austin Group. Feedback relating to the material contained within this standard may be submitted by using the Austin Group web site at www.opengroup.org/austin/defectform.html.

IEEE prohibits discrimination, harassment, and bullying. For more information, visit www.ieee.org/web/aboutus/whatis/policies/p9-26.html.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher. Permission to reproduce all or any part of this standard must be with the consent of both copyright holders and may be subject to a license fee. Both copyright holders will need to be satisfied that the other has granted permission. Requests should be sent by email to austin-group-permissions@opengroup.org.

The Open Group is a global consortium that enables the achievement of business objectives through IT standards. With more than 400 member organizations, The Open Group has a diverse membership that spans all sectors of the IT community – customers, systems and solutions suppliers, tool vendors, integrators, and consultants, as well as academics and researchers – to:

- Capture, understand, and address current and emerging requirements, and establish policies and share best practices
- Facilitate interoperability, develop consensus, and evolve and integrate specifications and open source technologies
- Offer a comprehensive set of services to enhance the operational efficiency of consortia
- Operate the industry's premier certification service

Further information on The Open Group is available at www.opengroup.org.

The Open Group publishes a wide range of technical documentation, most of which is focused on development of Open Group Standards and Guides, but which also includes white papers, technical studies, certification and testing documentation, and business titles. Full details and a catalog are available at www.opengroup.org/bookstore.

Readers should note that updates – in the form of Corrigenda – may apply to any publication. This information is published at www.opengroup.org/corrigenda.

Notice and Disclaimer of Liability Concerning the Use of IEEE Documents: IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

Use of an IEEE Standard is wholly voluntary. IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon any IEEE Standard document.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained in its standards is free from patent infringement. IEEE Standards documents are supplied “AS IS”.

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

Translations: The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official Statements: A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on Standards: Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important to ensure that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. Any person who would like to participate in evaluating comments or revisions to an IEEE standard is welcome to join the relevant IEEE working group at <http://standards.ieee.org/develop/wg/>.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Photocopies: Authorization to photocopy portions of any individual standard for internal or personal use is granted by The Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to the Copyright Clearance Center. To arrange for payment of the licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Notice to users

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

This document is copyrighted by the IEEE. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making this document available for use and adoption by public authorities and private users, the IEEE does not waive any rights in copyright to this document.

Updating of IEEE documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA website at <http://standards.ieee.org/index.html> or contact the IEEE at the address listed previously. For more information about the IEEE Standards Association or the IEEE standards development process, visit the IEEE-SA website at <http://standards.ieee.org/index.html>.

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.



Participants

IEEE Std 1003.1™-2008/Cor 1-2013 was prepared by the Austin Group, sponsored by the Portable Applications Standards Committee of the IEEE Computer Society, The Open Group, and ISO/IEC JTC 1/SC22.

The Austin Group

At the time this IEEE standard was completed, the Austin Group had the following membership:

Andrew Josey, *Chair*

Donald W. Cragun, *Organizational Representative, IEEE PASC*
Nicholas Stoughton, *Organizational Representative, ISO/IEC JTC 1/SC22*
Mark S. Brown, *Organizational Representative, The Open Group*

Cathy Fox, *Technical Editor*

Austin Group Technical Reviewers

Eric Blake
Paolo Bonzini
Mark S. Brown
Geoff Clare
Donald W. Cragun
Ulrich Drepper
Laszlo Ersek
Hal Finkel
Mark Harris
Tom Honermann

Ross Johnson
Andrew Josey
Alexey Khoroshilov
Antoine Leca
Vincent Lefèvre
Matt McCutchen
Christoph Anton Mitterer
Peter O'Gorman
Peter Petrov
James C. Pugsley

Jörg Schilling
Ed Schouten
Konrad Schwarz
Martin Sebor
Nicolas Sitbon
Nicholas Stoughton
Jilles Tjoelker
Nathan Weeks
David A. Wheeler

Austin Group Working Group Members

Hans Aberg
Eitan Adler
Tanaka Akira
Matthias Andree
Matt W. Benjamin
Guido Berhoerster
Eric Blake
Hans Boehm
Paolo Bonzini
Davide Brini
Andries E. Brouwer
Mark S. Brown
David Butenhof
Albert Cahalan
Stephane Chazelas
Geoff Clare
Garrett Cooper
Donald W. Cragun
Matthew Dempsky
Casper Dik
Niall Douglas
Ulrich Drepper

Lawrence D.K.B. Dwyer
Paul Eggert
Julian Elischer
Laszlo Ersek
Bruce Evans
Sean C. Farley
Hal Finkel
Glenn Fowler
Mike Frysinger
Pierre Gaston
Thorsten Glaser
Philip Guenther
Bruno Haible
Mark Harris
David Holland
Tom Honermann
Ross Johnson
Andrew Josey
Dan Kegel
Michael Kerrisk
Alexey Khoroshilov
Josh Knight

Jonathan A. Kollasch
Bruce Korb
David Korn
Terry Lambert
Antoine Leca
Vincent Lefèvre
Wojtek Lerch
Scott Lurndal
Roger Marquis
Matt McCutchen
Esmaeil Mirzaee
Christoph Anton Mitterer
Joseph S. Myers
Alexander Nasonov
Jonathan Nieder
Carlos O'Donnell
Peter O'Gorman
Peter Petrov
Wayne Pollock
James C. Pugsley
Chet Ramey
Xavier Roche

Jeroen Ruigrok van der Werven
Bart Schaefer
Jörg Schilling
Nico Schottelius
Ed Schouten
Konrad Schwarz
Jens Schweikhardt
Martin Sebor

Glen Seeds
Thor Lancelot Simon
Keld Simonsen
Nicolas Sitbon
Johannes Sixt
Paul Smith
Nicholas Stoughton
Marcel Telka

Jilles Tjoelker
Fred J. Tydeman
Nathan Weeks
David A. Wheeler
Mats D Wichmann
Garrett Wollman
Jörg Wunsch

The Open Group

When The Open Group approved the Base Specifications, Issue 7, Technical Corrigendum 1 on **25 October 2012**, the membership of The Open Group Base Working Group was as follows:

Andrew Josey, *Chair*
Mark S. Brown, *Austin Group Liaison*

Cathy Fox, *Technical Editor*

Base Working Group Members

Eric Blake
Mark S. Brown
David Butenhof
Geoff Clare

Donald W. Cragun
Lawrence D.K.B. Dwyer
Darrin Johnson
James C. Pugsley

William L. Toth
Kevin Van Vechten

Portable Applications Standards Committee (PASC)

Joseph M. Gwinn, *Chair*
Andrew Josey, *Functional Chair (Interpretations)*
Curtis Royster Jr., *Functional Chair (Logistics)*
Nicholas Stoughton, *Secretary*

IEEE

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Mark S. Brown
Michael Browne
Keith Chow
Donald W. Cragun
Thomas Dineen
Andrew Fieldsend
David Fuschi

Randall Groves
Joseph Gwinn
Werner Hoelzl
Andrew Josey
Piotr Karocki
Fernando Lucas Rodriguez
Greg Luri

Peter Petrov
Bartien Sayogo
Stephen Schwarm
Gil Shultz
Walter Struppler
Oren Yuen

When the IEEE-SA Standards Board approved this standard on 6 February 2013, it had the following membership:

John Kulick, *Chair*
Richard H. Hulett, *Past Chair*
Konstantinos Karachalios, *Secretary*

Masayuki Ariyoshi
Peter Balma
Farooq Bari
Ted Burse
Wael William Diab
Stephen Dukes
Jean-Philippe Faure
Alexander Gelman

Mark Halpin
Gary Hoffman
Paul Houzé
Jim Hughes
Michael Janezic
Joseph L. Koepfinger*
David J. Law
Oleg Logvinov

Ron Petersen
Gary Robinson
Jon Walter Rosdahl
Adrian Stephens
Peter Sutherland
Yatin Trivedi
Phil Winston
Yu Yuan

*Member Emeritus

Also included are the following nonvoting IEEE-SA Standards Board liaisons:

Richard DeBlasio, *DOE Representative*
Michael Janezic, *NIST Representative*

Don Messina, *IEEE Standards Program Manager, Document Development*

Michael Kipness, *IEEE Standards Program Manager, Technical Program Development*

Introduction

This introduction is not part of IEEE Std 1003.1TM-2008/Cor1-2013 IEEE Standard for Information Technology—Portable Operating System Interface (POSIXTM) Base Specifications, Issue 7—Technical Corrigendum 1.

This Technical Corrigendum addresses issues raised in defect reports and interpretation requests submitted up to 17 May 2011 that meet all of the following criteria: (a) They are in the scope of the approved standard. (b) They contain no new APIs (functions/utilities); however, they may add enumeration symbols, non-function #defines, and reserve additional namespaces. (c) They address contradictions between different parts of the standard, or add consistency between the standard and overriding standards, or address security-related problems.

Contents

1. Changes to Base Definitions.....	2
2. Changes to System Interfaces.....	27
3. Changes to Shell and Utilities	260
4. Changes to Rationale.....	311



IEEE Standard for Information Technology—Portable Operating System Interface (POSIX™)

Base Specifications, Issue 7— Technical Corrigendum 1

IMPORTANT NOTICE: IEEE Standards documents are not intended to ensure safety, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

This IEEE document is made available for use subject to important notices and legal disclaimers.

These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents”. They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

NOTE: The editing instructions contained in this corrigendum define how to merge the material contained therein into the existing base standard to form the comprehensive standard.

1. Changes to Base Definitions

This section contains the set of changes to the text of the Base Definitions.

[Note to reviewers: References to defect reports are provided to aid reviewers.]

Change Number: Frontmatter/TC1/D5/0001 [246]

On Page: ix Line: 0 Section: Typographical Conventions

In the table of conventions, first column, change from:

Filename

to:

Filename, Pathname

Rationale: Austin Group Defect Report(s) applied: 246.

See <http://austingroupbugs.net/view.php?id=246>

Change Number: Frontmatter/TC1/D5/0002 [341]

On Page: ix Line: none Section: Typographical Conventions

Change:

'\'

in Note 2 to:

'\''

Rationale: Austin Group Defect Report(s) applied: 341.

See <http://austingroupbugs.net/view.php?id=341>

Change Number: XBD/TC1/D5/0001 [68]

On Page: 9 Line: 247 Section: 1.7.1 Codes

Change from:

[MX]IEC 60559 Floating-Point

The functionality described is optional. The functionality described is also an extension to the ISO C standard.

Where applicable, functions are marked with the MX margin legend in the SYNOPSIS section. Where additional semantics apply to a function, the material is identified by use of the MX margin legend.[/MX]

to:

[MX]IEC 60559 Floating-Point

The functionality described is optional. The functionality described is mandated by the ISO C standard only for implementations that define __STDC_IEC_559__.[/MX]

[MXX]IEC 60559 Floating-Point Extension
The functionality described is part of the IEC 60559 Floating-Point
option, but is an extension to the ISO C standard.[/MXX]

Rationale: Austin Group Defect Report(s) applied: 68.
See <http://austingroupbugs.net/view.php?id=68>

Change Number: XBD/TC1/D5/0002 [291]

On Page: 21 Line: 730 Section: 2.1.5.1 Subprofiling Considerations

Change from:

filename argument

to:

pathname argument

Rationale: Austin Group Defect Report(s) applied: 291.
See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0003 [82]

On Page: 24 Line: 830,839 Section: 2.1.5.2 XSI Option Groups

Add to the list of options (in alphabetical order):

_POSIX_THREAD_ROBUST_PRIO_INHERIT

_POSIX_THREAD_ROBUST_PRIO_PROTECT

Rationale: Austin Group Defect Report(s) applied: 82.
See <http://austingroupbugs.net/view.php?id=82>

Change Number: XBD/TC1/D5/0004 [291]

On Page: 54 Line: 1647 Section: 3.136 Dot

Change from:

In the context of naming files, the filename consisting of a single dot
character ('.').

to:

In the context of naming files, the filename consisting of a single
<period> character ('.').

Rationale: Austin Group Defect Report(s) applied: 291.
See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0005 [291]

On Page: 55 Line: 1650 Section: 3.137 Dot-Dot

Change from:

The filename consisting solely of two dot characters ("..").

to:

The filename consisting solely of two <period> characters ("..").

Rationale: Austin Group Defect Report(s) applied: 291.

See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0006 [371,425]

On Page: 60 Line: 1763 Section: 3.166 File Descriptor

Change from:

The value of a file descriptor is from zero to {OPEN_MAX}. A process can have no more than {OPEN_MAX} file descriptors open simultaneously.

to:

The value of a newly-created file descriptor is from zero to {OPEN_MAX}-1. A file descriptor can have a value greater than or equal to {OPEN_MAX} if the value of {OPEN_MAX} has decreased (see `sysconf()`) since the file descriptor was opened.

Rationale: Austin Group Defect Report(s) applied: 371,425.

See <http://austingroupbugs.net/view.php?id=371>

See <http://austingroupbugs.net/view.php?id=425>

Change Number: XBD/TC1/D5/0007 [291]

On Page: 60 Line: 1782 Section: 3.170 Filename

Change from:

A name consisting of 1 to {NAME_MAX} bytes used to name a file. The characters composing the name may be selected from the set of all character values excluding the <slash> character and the null byte. The filenames dot and dot-dot have special meaning. A filename is sometimes referred to as a "pathname component".

to:

A sequence of bytes consisting of 1 to {NAME_MAX} bytes used to name a file. The bytes composing the name shall not contain the <NUL> or <slash> characters. In the context of a pathname, each filename shall be followed by a <slash> or a <NUL> character; elsewhere, a filename followed by a <NUL> character forms a string (but not necessarily a character string). The filenames dot and dot-dot have special meaning. A filename is sometimes referred to as a "pathname component". See also XBD Section 3.266 Pathname.

Rationale: Austin Group Defect Report(s) applied: 291.

See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0008 [291]

On Page: 60 Line: 1786 Section: 3.170

After Section 3.170, add a new section and then renumber existing sections:

3.1xx Filename String

A string consisting of a filename followed by a <NUL> character.

Rationale: Austin Group Defect Report(s) applied: 291.

See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0009 [291]

On Page: 75 Line: 2145 Section: 3.266 Pathname

Change from:

A character string that is used to identify a file. In the context of POSIX.1-2008, a pathname may be limited to {PATH_MAX} bytes, including the terminating null byte. It has an optional beginning <slash>, followed by zero or more filenames separated by <slash> characters. A pathname may optionally contain one or more trailing <slash> characters. Multiple successive <slash> characters are considered to be the same as one <slash>, except for the case of exactly two leading <slash> characters.

to:

A string that is used to identify a file. In the context of <current version>, a pathname may be limited to {PATH_MAX} bytes, including the terminating null byte. It has optional beginning <slash> characters, followed by zero or more filenames separated by <slash> characters. A pathname can optionally contain one or more trailing <slash> characters. Multiple successive <slash> characters are considered to be the same as one <slash>, except for the case of exactly two leading <slash> characters.

Note: If a pathname consists of only bytes corresponding to characters from the portable filename character set (see XBD Section 3.276), <slash> characters, and a single terminating <NUL> character, the pathname will be usable as a character string in all supported locales; otherwise, the pathname might only be a string (rather than a character string). Additionally, since the single-byte encoding of the <slash> character is required to be the same across all locales and to not occur within a multi-byte character, references to a <slash> character within a pathname are well-defined even when the pathname is not a character string. However, this property does not necessarily hold for the remaining characters within the portable filename character set.

Rationale: Austin Group Defect Report(s) applied: 291.

See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0010 [291]

On Page: 77 Line: 2193 Section: 3.275

After Section 3.275, add a new section and then renumber existing

sections:

3.2xx Portable Filename

A filename consisting only of characters from the portable filename character set.

Note: Applications should avoid using filenames that have the <hyphen> character as the first character since this may cause problems when filenames are passed as command line arguments.

Rationale: Austin Group Defect Report(s) applied: 291.
See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0011 [291]

On Page: 77 Line: 2199 Section: 3.276 Portable Filename Character Set

Add a sentence at the end of the section:

See also XBD Section 3.266 Pathname.

Rationale: Austin Group Defect Report(s) applied: 291.
See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0012 [181]

On Page: 97 Line: 2670 Section: 3.396 Thread

Change from:

Each thread has its own thread ID, scheduling priority and policy, errno value, thread-specific key/value bindings, and the required system resources to support a flow of control.

to:

Each thread has its own thread ID, scheduling priority and policy, errno value, floating point environment, thread-specific key/value bindings, and the required system resources to support a flow of control.

Rationale: Austin Group Defect Report(s) applied: 181.
See <http://austingroupbugs.net/view.php?id=181>

Change Number: XBD/TC1/D5/0013 [186]

On Page: 98 Line: 2685 Section: 3.399 Thread-Safe

Change from:

A function that may be safely invoked concurrently by multiple threads.

to:

A thread-safe function can be safely invoked concurrently with other calls to the same function, or with calls to any other thread-safe functions, by multiple threads.

Rationale: Austin Group Defect Report(s) applied: 186.
See <http://austingroupbugs.net/view.php?id=186>

Change Number: XBD/TC1/D5/0014 [135]

On Page: 108 Line: 2900 Section: 4.4 File Access Permissions

Delete the last paragraph in the section:

POSIX.1-2008 does not provide a way to open a directory for searching. It is unspecified whether directory search permission is granted based on the file access modes of the directory's file descriptor or on the mode of the directory at the time the directory is searched.

Rationale: Austin Group Defect Report(s) applied: 135.
See <http://austingroupbugs.net/view.php?id=135>
Text is removed that predated the addition of the `O_SEARCH` flag.

Change Number: XBD/TC1/D5/0015 [291]

On Page: 109 Line: 2915 Section: 4.7 Filename Portability

Change from:

Portable filenames shall not have the <hyphen> character as the first character since this may cause problems when filenames are passed as command line arguments.

to:

Note: Applications should avoid using filenames that have the <hyphen> character as the first character since this may cause problems when filenames are passed as command line arguments.

Rationale: Austin Group Defect Report(s) applied: 291.
See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0016 [83]

On Page: 112 Line: 3040 Section: 4.12 Pathname Resolution

Change from:

A pathname that begins with two successive <slash> characters may be interpreted in an implementation-defined manner, although ...

to:

If a pathname begins with two successive <slash> characters, the first component following the leading <slash> characters may be interpreted in an implementation-defined manner, although ...

Rationale: Austin Group Defect Report(s) applied: 83.
See <http://austingroupbugs.net/view.php?id=83>

Change Number: XBD/TC1/D5/0017 [340]

On Page: 121 Line: 3303 Section: 5 File Format Notation

Change from:

Escape Sequences represent non-graphic characters.

to:

Escape Sequences represent non-graphic characters and the escape character (<backslash>).

Rationale: Austin Group Defect Report(s) applied: 340.

See <http://austingroupbugs.net/view.php?id=340>

Change Number: XBD/TC1/D5/0018 [302]

On Page: 127 Line: 3583 Section: 6.1 Portable Character Set

Change from:

... if an application accesses any pair of locales where the character encodings differ, or accesses data from an application running in a locale which has different encodings from the application's current locale, the results are unspecified.

to:

... if an application uses any pair of locales where the character encodings differ, or accesses data from an application using a locale which has different encodings from the locales used by the application, the results are unspecified.

Rationale: Austin Group Defect Report(s) applied: 302.

See <http://austingroupbugs.net/view.php?id=302>

Change Number: XBD/TC1/D5/0019 [291]

On Page: 128 Line: 3589 Section: 6.1 Portable Character Set

After L3589 insert a new bullet:

* The encoded values associated with <slash> and <period> shall be invariant across all locales supported by the implementation.

Rationale: Austin Group Defect Report(s) applied: 291.

See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0020 [216]

On Page: 128 Line: 3596 Section: 6.2 Character Encoding

Change from:

The POSIX locale contains the characters in Table 6-1 (on page 125), ...

to:

The POSIX locale contains the characters in Table 6-1 (on page 125)
and Table 6-2 (on page 130), ...

Rationale: Austin Group Defect Report(s) applied: 216.
See <http://austingroupbugs.net/view.php?id=216>

Change Number: XBD/TC1/D5/0021 [291]

On Page: 128 Line: 3619 Section: 6.2 Character Encoding

Add a sentence:

Likewise, the byte values used to encode <period> and <slash> shall not
occur as part of any other character in any locale.

Rationale: Austin Group Defect Report(s) applied: 291.
See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0022 [216]

On Page: 129 Line: 3661 Section: 6.4 Character Set Description File

Change from:

... the symbolic names and their corresponding encoding values shall be
included in the file.

to:

... the symbolic names and their corresponding encoding values shall be
included in the file. The encoding values shall each be represented in
a single byte.

Rationale: Austin Group Defect Report(s) applied: 216.
See <http://austingroupbugs.net/view.php?id=216>

Change Number: XBD/TC1/D5/0023 [302]

On Page: 135 Line: 3820-3822 Section: 7.1 General

Change from:

The behavior of some of the C-language functions defined in the System
Interfaces volume of POSIX.1-2008 shall also be modified based on the
current locale, as defined by the last call to `setlocale()`.

to:

The behavior of some of the C-language functions defined in the System
Interfaces volume of POSIX.1-2008 shall also be modified based on a locale
selection. The locale to be used by these functions can be selected in
the following ways:

1. For functions such as `isalnum_l()` that take a locale object as an argument, a locale object can be obtained from `newlocale()` or `duplocale()` and passed to the function.

2. For functions that do not take a locale object as an argument, the current locale for the thread can be set by calling `uselocale()` or the global locale for the process can be set by calling `setlocale()`. Such functions shall use the current locale of the calling thread if one has been set for that thread; otherwise, they shall use the global locale.

Rationale: Austin Group Defect Report(s) applied: 302.
See <http://austingroupbugs.net/view.php?id=302>
These changes were overlooked during the revision when per-thread locales were added.

Change Number: XBD/TC1/D5/0024 [302]

On Page: 135 Line: 3839 Section: 7.1 General

Change from:

Applications can select the desired locale by invoking the `setlocale()` function (or equivalent) with the appropriate value. If the function is invoked with an empty string, such as:

```
setlocale(LC_ALL, "");
```

the value of the corresponding environment variable is used.

to:

Applications can select the desired locale by calling the `newlocale()` or `setlocale()` function with the appropriate value. If the function is invoked with an empty string, such as:

```
newlocale(LC_ALL_MASK, "", (locale_t)0);
```

or:

```
setlocale(LC_ALL, "");
```

the value of the corresponding environment variable is used.

Rationale: Austin Group Defect Report(s) applied: 302.
See <http://austingroupbugs.net/view.php?id=302>
These changes were overlooked during the revision when per-thread locales were added.

Change Number: XBD/TC1/D5/0025 [22,427]

On Page: 164 Line: 5141-5146 Section: 7.3.6 LC_MESSAGES

On L5142 in the description of the `yesexpr` keyword, change from:

... the acceptable affirmative response ...

to:

... acceptable affirmative responses ...

On L5144-5145 in the description of the noexpr keyword, change from:

... the acceptable negative response ...

to:

... acceptable negative responses ...

Rationale: Austin Group Defect Report(s) applied: 22,427.

See <http://austingroupbugs.net/view.php?id=22>

See <http://austingroupbugs.net/view.php?id=427>

Change Number: XBD/TC1/D5/0026 [167]

On Page: 173 Line: 5476 Section: 8.1 Environment Variable Definition

Change from:

... manipulating the environ variable ...

to:

... assigning a new value to the environ variable ...

Rationale: Austin Group Defect Report(s) applied: 167.

See <http://austingroupbugs.net/view.php?id=167>

Change Number: XBD/TC1/D5/0027 [167]

On Page: 173 Line: 5478 Section: 8.1 Environment Variable Definition

Add a new paragraph after L5478:

If the application modifies the pointers to which environ points, the behavior of all interfaces described in the System Interfaces volume of POSIX.1-2008 is undefined.

Rationale: Austin Group Defect Report(s) applied: 167.

See <http://austingroupbugs.net/view.php?id=167>

Change Number: XBD/TC1/D5/0028 [291]

On Page: 175 Line: 5566 Section: 8.2 Internationalization Variables

In the description of NLSPATH, change from:

filename

to:

pathname

Rationale: Austin Group Defect Report(s) applied: 291.

See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0029 [302]

On Page: 177 Line: 5636 Section: 8.2 Internationalization Variables

Change from:

At runtime, these values are bound to the locale of a process by calling the `setlocale()` function.

to:

These environment variables are used by the `newlocale()` and `setlocale()` functions, and by the standard utilities.

Rationale: Austin Group Defect Report(s) applied: 302.

See <http://austingroupbugs.net/view.php?id=302>

Change Number: XBD/TC1/D5/0030 [139]

On Page: 178 Line: 5674 Section: 8.3 Other Environment Variables

In the description of the `PATH` variable, change from:

When a non-zero-length prefix is applied to this filename, a `<slash>` shall be inserted between the prefix and the filename.

to:

When a non-zero-length prefix is applied to this filename, a `<slash>` shall be inserted between the prefix and the filename if the prefix did not end in `<slash>`.

Rationale: Austin Group Defect Report(s) applied: 139.

See <http://austingroupbugs.net/view.php?id=139>

This change is for consistency with the previous change to `CDPATH` made in Interpretation 1003.1-2001 #199

Change Number: XBD/TC1/D5/0031 [84]

On Page: 178 Line: 5687 Section: 8.3 Other Environment Variables

At the end of the `PATH` variable, add a new paragraph:

Since colon is a separator in this context, directory names that might be used in `PATH` should not include a colon character.

Rationale: Austin Group Defect Report(s) applied: 84.

See <http://austingroupbugs.net/view.php?id=84>

Change Number: XBD/TC1/D5/0032 [305,427]

On Page: 186 Line: 5995 Section: 9.3.5 RE Bracket Expression

At L5995, add a new paragraph:

8. If a bracket expression contains at least three list elements, where

the first and last list element are the same single-character element of
<period>, <equals-sign>, or <colon>, then it is unspecified whether the
bracket expression will be treated as a collating symbol, equivalence
class, or character class, respectively; treated as a matching list
expression; or rejected as an error.

Rationale: Austin Group Defect Report(s) applied: 305,427.
See <http://austingroupbugs.net/view.php?id=305>
See <http://austingroupbugs.net/view.php?id=427>

Change Number: XBD/TC1/D5/0033 [134]

On Page: 197 Line: 6402 Section: 10.1 Directory Structure and Files

Change from:

/dev/null An infinite data source and data sink. ...

to:

/dev/null An empty data source and infinite data sink. ...

Rationale: Austin Group Defect Report(s) applied: 134.
See <http://austingroupbugs.net/view.php?id=134>
Improve the description of /dev/null.

Change Number: XBD/TC1/D5/0034 [79]

On Page: 201 Line: 6531-6542 Section: 11.1.4 Terminal Access Control

On L6531 change from:

... if the reading process is ignoring or blocking the SIGTTIN signal, ...

to:

... if the reading process is ignoring the SIGTTIN signal or the reading
thread is blocking the SIGTTIN signal, ...

On L6539 change from:

... and the process is ignoring or blocking the SIGTTOU signal, ...

to:

... and the process is ignoring the SIGTTOU signal or the writing thread
is blocking the SIGTTOU signal, ...

On L6540 change from:

If TOSTOP is set, and the process group of the writing process is
orphaned, and the writing process is not ignoring or blocking the SIGTTOU
signal, ...

to:

If TOSTOP is set, the process group of the writing process is orphaned,
the writing process is not ignoring the SIGTTOU signal, and the writing
thread is not blocking the SIGTTOU signal, ...

Rationale: Austin Group Defect Report(s) applied: 79.
See <http://austingroupbugs.net/view.php?id=79>

Change Number: XBD/TC1/D5/0035 [271]

On Page: 205 Line: 6710 Section: 11.1.11 Closing A Terminal Device File

Change from:

The last process to close a terminal device file shall cause any output to be sent to the device and any input to be discarded.

to:

The last process to close a terminal device file shall cause any output to be sent to the device and shall cause any input to be discarded.

Rationale: Austin Group Defect Report(s) applied: 271.
See <http://austingroupbugs.net/view.php?id=271>

The text can mean two things:

1. "any output to be sent" and "any input" shall be discarded.
2. "any output" will be sent and "any input" shall be discarded.

Change Number: XBD/TC1/D5/0036 [79]

On Page: 211 Line: 6962 Section: 11.2.5 Local Modes

Change from:

Processes that are blocking or ignoring SIGTTOU signals are excepted and allowed to produce output, and the SIGTTOU signal shall not be sent.

to:

If the writing process is ignoring the SIGTTOU signal or the writing thread is blocking the SIGTTOU signal, the process is allowed to produce output, and the SIGTTOU signal shall not be sent.

Rationale: Austin Group Defect Report(s) applied: 79.
See <http://austingroupbugs.net/view.php?id=79>

Change Number: XBD/TC1/D5/0037 [171]

On Page: 216 Line: 7120 Section: 12.2 Utility Syntax Guidelines

In Guideline 5 change from:

Options without option-arguments should be accepted when grouped behind one '-' delimiter.

to:

One or more options without option-arguments, followed by at most one option that takes an option-argument, should be accepted when grouped behind one '-' delimiter.

Rationale: Austin Group Defect Report(s) applied: 171.
See <http://austingroupbugs.net/view.php?id=171>

Change Number: XBD/TC1/D5/0038 [98]

On Page: 220 Line: 7234 Section: <aio.h>

In the DESCRIPTION section, add FSC|SIO shading to the declaration
of aio_fsync().

Rationale: Austin Group Defect Report(s) applied: 98.
See <http://austingroupbugs.net/view.php?id=98>

Change Number: XBD/TC1/D5/0039 [291]

On Page: 231 Line: 7575 Section: <dirent.h>

In the DESCRIPTION section, change from:

d_name[] Name of entry.

to:

d_name[] Filename string of entry.

Rationale: Austin Group Defect Report(s) applied: 291.
See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0040 [291]

On Page: 231 Line: 7577 Section: <dirent.h>

In the DESCRIPTION section, change from:

The character array d_name is of unspecified size, but the number of
bytes preceding the terminating null byte shall not exceed {NAME_MAX}.

to:

The array d_name is of unspecified size, but shall contain a filename
of at most {NAME_MAX} bytes followed by a terminating null byte.

Rationale: Austin Group Defect Report(s) applied: 291.
See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0041 [291]

On Page: 232 Line: 7612 Section: <dirent.h>

In the RATIONALE section, change from:

... number of characters provided matches (or only slightly exceeds)
the length of the filename.

to:

... number of bytes provided matches (or only slightly exceeds) the length of the filename string.

Rationale: Austin Group Defect Report(s) applied: 291.
See <http://austingroupbugs.net/view.php?id=291>

Change Number: XBD/TC1/D5/0042 [206]

On Page: 232 Line: 7629 Section: <dirent.h>

In the CHANGE HISTORY section, change from:

... `fopendir()` ...

to:

... `fdopendir()` ...

Rationale: Austin Group Defect Report(s) applied: 206.
See <http://austingroupbugs.net/view.php?id=206>

Change Number: XBD/TC1/D5/0043 [324]

On Page: 236 Line: 7739 Section: <errno.h>

In the DESCRIPTION section, change from:

[ENOTDIR] Not a directory.

to:

[ENOTDIR] Not a directory or a symbolic link to a directory.

Rationale: Austin Group Defect Report(s) applied: 324.
See <http://austingroupbugs.net/view.php?id=324>

Change Number: XBD/TC1/D5/0044 [274]

On Page: 239 Line: 7848 Section: <fcntl.h>

In the DESCRIPTION section, after:

The <fcntl.h> header shall define the following symbolic constants for use as the file access modes for `open()`, `openat()`, and `fcntl()`.

add:

The values shall be unique, except that `O_EXEC` and `O_SEARCH` may have equal values.

Rationale: Austin Group Defect Report(s) applied: 274.
See <http://austingroupbugs.net/view.php?id=274>

Change Number: XBD/TC1/D5/0045 [78,432]

On Page: 240 Line: 7874-7879 Section: <fcntl.h>

In the DESCRIPTION section, delete L7874 to L7875.

The <fcntl.h> header shall define the following symbolic constants as values for the flag used by open() and openat():

In the DESCRIPTION section, move L7876 to L7879:

O_CLOEXEC The FD_CLOEXEC flag associated with the new descriptor shall be set to close the file descriptor upon execution of an exec family function.

O_DIRECTORY Fail if not a directory.

O_NOFOLLOW Do not follow symbolic links.

into the section at L7829 to L7834, so that it reads:

The <fcntl.h> header shall define the following symbolic constants as file creation flags for use in the oflag value to open() and openat(). The values shall be bitwise-distinct and shall be suitable for use in #if preprocessing directives.

O_CLOEXEC The FD_CLOEXEC flag associated with the new descriptor shall be set to close the file descriptor upon execution of an exec family function.

O_CREAT Create file if it does not exist.

O_DIRECTORY Fail if not a directory.

O_EXCL Exclusive use flag.

O_NOCTTY Do not assign controlling terminal.

O_NOFOLLOW Do not follow symbolic links.

O_TRUNC Truncate flag.

Rationale: Austin Group Defect Report(s) applied: 78,432.

See <http://austingroupbugs.net/view.php?id=78>

See <http://austingroupbugs.net/view.php?id=432>

Change Number: XBD/TC1/D5/0046 [346]

On Page: 249 Line: 8198 Section: <float.h>

In the DESCRIPTION section, add a paragraph within the *_MAX_EXP bullet:

[CX]Additionally, FLT_MAX_EXP shall be at least as large as FLT_MANT_DIG, DBL_MAX_EXP shall be at least as large as DBL_MANT_DIG, and LDBL_MAX_EXP shall be at least as large as LDBL_MANT_DIG; which has the effect that FLT_MAX, DBL_MAX, and LDBL_MAX are integral.[/CX]

Rationale: Austin Group Defect Report(s) applied: 346.

See <http://austingroupbugs.net/view.php?id=346>

Change Number: XBD/TC1/D5/0047 [346]

1030
1031 On Page: 250 Line: 8224 Section: <float.h>
1032
1033 In the RATIONALE section, change from:
1034
1035 None.
1036
1037 to:
1038
1039 All known hardware floating-point formats satisfy the property that
1040 the exponent range is larger than the number of mantissa digits. The
1041 ISO C standard permits a floating-point format where this property is
1042 not true, such that the largest finite value would not be integral;
1043 however, it is unlikely that there will ever be hardware support for
1044 such a floating-point format, and it introduces boundary cases that
1045 portable programs should not have to be concerned with (for example,
1046 a non-integral DBL_MAX means that ceil() would have to worry about
1047 overflow). Therefore, this standard imposes an additional requirement
1048 that the largest representable finite value is integral.
1049
1050 *Rationale:* Austin Group Defect Report(s) applied: 346.
1051 See <http://austingroupbugs.net/view.php?id=346>
1052
1053
1054 **Change Number: XBD/TC1/D5/0048 [403]**
1055
1056
1057 On Page: 254 Line: 8333 Section: <ftw.h>
1058
1059 In the DESCRIPTION section, change from:
1060
1061 FTW_F File.
1062
1063 to:
1064
1065 FTW_F Non-directory file.
1066
1067 *Rationale:* Austin Group Defect Report(s) applied: 403.
1068 See <http://austingroupbugs.net/view.php?id=403>
1069
1070
1071 **Change Number: XBD/TC1/D5/0049 [24]**
1072
1073
1074 On Page: 258 Line: 8441-8442 Section: <grp.h>
1075
1076 In the DESCRIPTION, add XSI shading to endgrent() and getgrent().
1077
1078 *Rationale:* Austin Group Defect Report(s) applied: 24.
1079 See <http://austingroupbugs.net/view.php?id=24>
1080
1081
1082 **Change Number: XBD/TC1/D5/0050 [211]**
1083
1084
1085 On Page: 261 Line: 8510- Section: <inttypes.h>
1086
1087 In the DESCRIPTION section change from:
1088
1089 The <inttypes.h> header shall define at least the following type:
1090
1091 imaxdiv_t Structure type that is the type of the value returned by the
1092 imaxdiv() function.

1093
1094 to:
1095
1096 The <inttypes.h> header shall define at least the following types:
1097
1098 `imaxdiv_t` Structure type that is the type of the value returned by the
1099 `imaxdiv()` function.
1100
1101 [CX]`wchar_t` As described in <stddef.h>. [/CX]
1102
1103 *Rationale:* Austin Group Defect Report(s) applied: 211.
1104 See <http://austingroupbugs.net/view.php?id=211>
1105
1106
1107 **Change Number: XBD/TC1/D5/0051** [107]
1108
1109
1110 On Page: 264 Line: 8623 Section: <langinfo.h>
1111
1112 In the DESCRIPTION section, replace <nl/types.h> with <nl_types.h>.
1113
1114 *Rationale:* Austin Group Defect Report(s) applied: 107.
1115 See <http://austingroupbugs.net/view.php?id=107>
1116 Corrected an editorial error in referencing <nl_types.h>.
1117
1118
1119 **Change Number: XBD/TC1/D5/0052** [108]
1120
1121
1122 On Page: 268 Line: 8756 Section: <limits.h>
1123
1124 In the DESCRIPTION section, change from:
1125
1126 Many of the symbols listed here are not defined by the ISO/IEC 9899:
1127 1999 standard. Such symbols are not shown as CX shaded.
1128
1129 to:
1130
1131 (Shading block as follows on L8756-8757)
1132
1133 Many of the symbols listed here are not defined by the ISO/IEC 9899:
1134 1999 standard. Such symbols are not shown as CX shaded, except under
1135 the heading "Numerical Limits".
1136
1137 *Rationale:* Austin Group Defect Report(s) applied: 108.
1138 See <http://austingroupbugs.net/view.php?id=108>
1139
1140
1141 **Change Number: XBD/TC1/D5/0053** [291]
1142
1143
1144 On Page: 272 Line: 8933 Section: <limits.h>
1145
1146 In the DESCRIPTION (<limits.h> {NAME_MAX}) change from:
1147
1148 ... bytes in a filename (not including the terminating null).
1149
1150 to:
1151
1152 ... bytes in a filename (not including the terminating null of a filename
1153 string).
1154
1155 *Rationale:* Austin Group Defect Report(s) applied: 291.

1156 See <http://austingroupbugs.net/view.php?id=291>

1157

1158

1159 **Change Number: XBD/TC1/D5/0054** [182,427]

1160

1161

1162 On Page: 274 Line: 9020 Section: <limits.h>

1163

1164 In the DESCRIPTION section, Minimum Values, change from:

1165

1166 A conforming implementation shall provide values at least this large.

1167

1168 to:

1169

1170 For each of these limits, a conforming implementation shall provide a

1171 value at least this large or shall have no limit.

1172

1173 *Rationale:* Austin Group Defect Report(s) applied: 182,427.

1174 See <http://austingroupbugs.net/view.php?id=182>

1175 See <http://austingroupbugs.net/view.php?id=427>

1176

1177

1178 **Change Number: XBD/TC1/D5/0055** [291]

1179

1180

1181 On Page: 275 Line: 9060 Section: <limits.h>

1182

1183 In the DESCRIPTION ({_POSIX_NAME_MAX}), change from:

1184

1185 ... bytes in a filename (not including the terminating null).

1186

1187 to:

1188

1189 ... bytes in a filename (not including the terminating null of a filename
1190 string).

1191

1192 *Rationale:* Austin Group Defect Report(s) applied: 291.

1193 See <http://austingroupbugs.net/view.php?id=291>

1194

1195

1196 **Change Number: XBD/TC1/D5/0056** [371]

1197

1198

1199 On Page: 275 Line: 9066 Section: <limits.h>

1200

1201 In the DESCRIPTION section, change from:

1202

1203 Maximum number of files that one process can have open at any one time.

1204

1205 to:

1206

1207 A value one greater than the maximum value that the system may assign
1208 to a newly-created file descriptor.

1209

1210 *Rationale:* Austin Group Defect Report(s) applied: 371.

1211 See <http://austingroupbugs.net/view.php?id=371>

1212

1213

1214 **Change Number: XBD/TC1/D5/0057** [291]

1215

1216

1217 On Page: 277 Line: 9182 Section: <limits.h>

1218

1219 In the DESCRIPTION ({_XOPEN_NAME_MAX}), change from:
1220
1221 ... bytes in a filename (not including the terminating null).
1222
1223 to:
1224
1225 ... bytes in a filename (not including the terminating null of a filename
1226 string).
1227
1228 *Rationale:* Austin Group Defect Report(s) applied: 291.
1229 See <http://austingroupbugs.net/view.php?id=291>
1230
1231
1232 **Change Number: XBD/TC1/D5/0058** [108]
1233
1234
1235 On Page: 278 Line: 9218 Section: <limits.h>
1236
1237 In the DESCRIPTION section, add CX shading to:
1238
1239 LONG_BIT (P278 L9218-9220)
1240 WORD_BIT (P279 L9260-9262)
1241 SSIZE_MAX (P279 L9242-9244)
1242
1243 *Rationale:* Austin Group Defect Report(s) applied: 108.
1244 See <http://austingroupbugs.net/view.php?id=108>
1245
1246
1247 **Change Number: XBD/TC1/D5/0059** [291]
1248
1249
1250 On Page: 280 Line: 9311 Section: <limits.h>
1251
1252 In the RATIONALE section, change "filenames" to "pathnames".
1253
1254 *Rationale:* Austin Group Defect Report(s) applied: 291.
1255 See <http://austingroupbugs.net/view.php?id=291>
1256
1257
1258 **Change Number: XBD/TC1/D5/0060** [301,427]
1259
1260
1261 On Page: 284 Line: 9450 Section: <locale.h>
1262
1263 In the DESCRIPTION section change from:
1264
1265 ... a special object descriptor used by the uselocale() function.
1266
1267 to:
1268
1269 ... a special object descriptor used by the duplocale() and uselocale()
1270 functions.
1271
1272 *Rationale:* Austin Group Defect Report(s) applied: 301,427.
1273 See <http://austingroupbugs.net/view.php?id=301>
1274 See <http://austingroupbugs.net/view.php?id=427>
1275
1276
1277 **Change Number: XBD/TC1/D5/0061** [355]
1278
1279
1280 On Page: 303 Line: 10141 Section: <netinet/in.h>
1281

1282 In the DESCRIPTION section, change from:
1283
1284 Values of this type shall be cast by applications to struct sockaddr
1285 for use with socket functions.
1286
1287 to:
1288
1289 Pointers to this type shall be cast by applications to struct sockaddr *
1290 for use with socket functions.
1291
1292 *Rationale:* Austin Group Defect Report(s) applied: 355.
1293 See <http://austingroupbugs.net/view.php?id=355>
1294
1295
1296 **Change Number: XBD/TC1/D5/0062 [208]**
1297
1298
1299 On Page: 328 Line: 10963 Section: <signal.h>
1300
1301 In the DESCRIPTION section, change the margin marker notation for the
1302 SIG_HOLD macro from:
1303
1304 OB CX
1305
1306 to:
1307
1308 OB XSI
1309
1310 *Rationale:* Austin Group Defect Report(s) applied: 208.
1311 See <http://austingroupbugs.net/view.php?id=208>
1312 SIG_HOLD shading and margin marker notation is updated from
1313 OB CX to OB XSI as it is used with the sigset function which is an
1314 XSI function.
1315
1316
1317 **Change Number: XBD/TC1/D5/0063 [80]**
1318
1319
1320 On Page: 330 Line: 11032 Section: <signal.h>
1321
1322 In the DESCRIPTION section, in the table of signals, change the shading
1323 on SIGPROF from OB XSR to OB XSI.
1324
1325 *Rationale:* Austin Group Defect Report(s) applied: 80.
1326 See <http://austingroupbugs.net/view.php?id=80>
1327
1328
1329 **Change Number: XBD/TC1/D5/0064 [157]**
1330
1331
1332 On Page: 331 Line: 11055 Section: <signal.h>
1333
1334 In the DESCRIPTION section, change the shading margin marker from XSI
1335 to CX on the following text:
1336
1337 The storage occupied by sa_handler and sa_sigaction may overlap, and a
1338 conforming application shall not use both simultaneously.
1339
1340 *Rationale:* Austin Group Defect Report(s) applied: 157.
1341 See <http://austingroupbugs.net/view.php?id=157>
1342
1343
1344 **Change Number: XBD/TC1/D5/0065 [291,427]**

1345
1346
1347 On Page: 351 Line: 11796 Section: <stdio.h>
1348
1349 In the DESCRIPTION section, at P351 L11796 (XBD <stdio.h> FILENAME_MAX),
1350 change from "filename string" to "pathname".
1351
1352 *Rationale:* Austin Group Defect Report(s) applied: 291,427.
1353 See <http://austingroupbugs.net/view.php?id=291>
1354 See <http://austingroupbugs.net/view.php?id=427>
1355
1356
1357 **Change Number: XBD/TC1/D5/0066** [197]
1358
1359
1360 On Page: 356 Line: 11992 Section: <stdlib.h>
1361
1362 In the DESCRIPTION section, add the CX margin marker and shading to the
1363 getsubopt() function prototype.
1364
1365 *Rationale:* Austin Group Defect Report(s) applied: 197.
1366 See <http://austingroupbugs.net/view.php?id=197>
1367 The getsubopt() function is an extension to the ISO C standard.
1368
1369
1370 **Change Number: XBD/TC1/D5/0067** [355]
1371
1372
1373 On Page: 382 Line: 12813-12817 Section: <sys/socket.h>
1374
1375 In the DESCRIPTION section, change from:
1376
1377 When a sockaddr_storage structure is cast as a sockaddr structure,
1378 the ss_family field of the sockaddr_storage structure shall map onto
1379 the sa_family field of the sockaddr structure. When a sockaddr_storage
1380 structure is cast as a protocol-specific address structure, the ss_family
1381 field shall map onto a field of that structure that is of type sa_family_t
1382 and that identifies the protocol's address family.
1383
1384 to:
1385
1386 When a pointer to a sockaddr_storage structure is cast as a pointer to a
1387 sockaddr structure, the ss_family field of the sockaddr_storage structure
1388 shall map onto the sa_family field of the sockaddr structure. When
1389 a pointer to a sockaddr_storage structure is cast as a pointer to a
1390 protocol-specific address structure, the ss_family field shall map onto
1391 a field of that structure that is of type sa_family_t and that identifies
1392 the protocol's address family.
1393
1394 *Rationale:* Austin Group Defect Report(s) applied: 355.
1395 See <http://austingroupbugs.net/view.php?id=355>
1396
1397
1398 **Change Number: XBD/TC1/D5/0068** [207]
1399
1400
1401 On Page: 388 Line: 13042 Section: <sys/stat.h>
1402
1403 In the DESCRIPTION section, add the XSI margin marker, and shade blkcnt_t
1404 and blksize_t.
1405
1406 *Rationale:* Austin Group Defect Report(s) applied: 207.
1407 See <http://austingroupbugs.net/view.php?id=207>

1408 Add notation to show that blkcnt_t and blksize_t are XSI
1409 extensions.
1410
1411
1412 **Change Number: XBD/TC1/D5/0069** [210]
1413
1414
1415 On Page: 398 Line: 13360f Section: <sys/types.h>
1416
1417 In the DESCRIPTION section, remove the XSI margin marker and shading
1418 from fsblkcnt_t and fsfilcnt_t.
1419
1420 *Rationale:* Austin Group Defect Report(s) applied: 210.
1421 See <http://austingroupbugs.net/view.php?id=210>
1422 The statvfs structure, where fsblkcnt_t and fsfilcnt_t are
1423 used, is now in base.
1424
1425
1426 **Change Number: XBD/TC1/D5/0070** [28]
1427
1428
1429 On Page: 399 Line: 13389 Section: <sys/types.h>
1430
1431 In the DESCRIPTION section, change from:
1432
1433 <blank name> Also used to identify a trace stream attributes object
1434
1435 to:
1436
1437 trace_attr_t Used to identify a trace stream attributes object
1438
1439 (The existing OB TRC shading should apply to the whole line.)
1440
1441 *Rationale:* Austin Group Defect Report(s) applied: 28.
1442 See <http://austingroupbugs.net/view.php?id=28>
1443
1444
1445 **Change Number: XBD/TC1/D5/0071** [376]
1446
1447
1448 On Page: 399 Line: 13415 Section: <sys/types.h>
1449
1450 In the DESCRIPTION section, between L13415 and 13416, add a bullet:
1451
1452 * dev_t shall be an integer type.
1453
1454 *Rationale:* Austin Group Defect Report(s) applied: 376.
1455 See <http://austingroupbugs.net/view.php?id=376>
1456
1457
1458 **Change Number: XBD/TC1/D5/0072** [210]
1459
1460
1461 On Page: 399 Line: 13417 Section: <sys/types.h>
1462
1463 In the DESCRIPTION section, remove the XSI margin marker and shading
1464 from fsblkcnt_t and fsfilcnt_t.
1465
1466 *Rationale:* Austin Group Defect Report(s) applied: 210.
1467 See <http://austingroupbugs.net/view.php?id=210>
1468 The statvfs structure, where fsblkcnt_t and fsfilcnt_t are
1469 used, is now in base.
1470

1471
1472 **Change Number: XBD/TC1/D5/0073** [327]
1473
1474
1475 On Page: 399 Line: 13420 Section: <sys/types.h>
1476
1477 In the DESCRIPTION section, change from:
1478
1479 time_t and clock_t shall be integer or real-floating types.
1480
1481 to:
1482
1483 clock_t shall be an integer or real-floating type. [CX]time_t shall be
1484 an integer type.[/CX]
1485
1486 *Rationale:* Austin Group Defect Report(s) applied: 327.
1487 See <http://austingroupbugs.net/view.php?id=327>
1488
1489
1490 **Change Number: XBD/TC1/D5/0074** [355]
1491
1492
1493 On Page: 403 Line: 13517 Section: <sys/un.h>
1494
1495 In the DESCRIPTION section, change from:
1496
1497 Values of this type shall be cast by applications to struct sockaddr
1498 for use with socket functions.
1499
1500 to:
1501
1502 Pointers to this type shall be cast by applications to struct sockaddr *
1503 for use with socket functions.
1504
1505 *Rationale:* Austin Group Defect Report(s) applied: 355.
1506 See <http://austingroupbugs.net/view.php?id=355>
1507
1508
1509 **Change Number: XBD/TC1/D5/0075** [357,427]
1510
1511
1512 On Page: 418 Line: 13996 Section: <tgmath.h>
1513
1514 In the DESCRIPTION section, in the table at L13996-13997, scalbln()
1515 should sort before scalbn().
1516
1517 *Rationale:* Austin Group Defect Report(s) applied: 357,427.
1518 See <http://austingroupbugs.net/view.php?id=357>
1519 See <http://austingroupbugs.net/view.php?id=427>
1520
1521
1522 **Change Number: XBD/TC1/D5/0076** [212]
1523
1524
1525 On Page: 422 Line: 14153 Section: <time.h>
1526
1527 In the DESCRIPTION section, add the CX margin marker notation and shading
1528 to L14153-14155. (The <time.h> header.... TIMER_ABSTIME ...)
1529
1530 *Rationale:* Austin Group Defect Report(s) applied: 212.
1531 See <http://austingroupbugs.net/view.php?id=212>
1532
1533

Change Number: XBD/TC1/D5/0077 [212]

On Page: 422 Line: 14159 Section: <time.h>

In the DESCRIPTION section, change from:

... a progrm defines ...

to:

... a program defines ...

Rationale: Austin Group Defect Report(s) applied: 212.

See <http://austingroupbugs.net/view.php?id=212>

This is an editorial correction.

Change Number: XBD/TC1/D5/0078 [311]

On Page: 430 Line: 14446 Section: <unistd.h>

In the DESCRIPTION section, after:

For implementations conforming to POSIX.1-2008, the value shall be 200809L.

add (to the same paragraph):

For profile implementations that define _POSIX_SUBPROFILE (see Section 2.1.5.1) in <unistd.h>, _POSIX2_VERSION may be left undefined or be defined with the value -1 to indicate that the Shell and Utilities volume is not supported. In this case a call to sysconf(_SC_2_VERSION) shall return either 200809L or -1 indicating that the Shell and Utilities volume is or is not, respectively, supported at runtime.

At L14455 after:

The following symbolic constants, if defined in <unistd.h>, shall have a value of -1, 0, or greater, unless otherwise specified below.

add:

For profile implementations that define _POSIX_SUBPROFILE (see Section 2.1.5.1) in <unistd.h>, constants described below as always having a value greater than zero need not be defined and, if defined, may have a value of -1, 0, or greater.

Rationale: Austin Group Defect Report(s) applied: 311.

See <http://austingroupbugs.net/view.php?id=311>

Change Number: XBD/TC1/D5/0079 [209]

On Page: 439-440 Line: 14870-14875 Section: <unistd.h>

In the DESCRIPTION section, add the XSI margin marker and shading for L14870 to 14875 (symbolic constants F_LOCK ... F_ULOCK).

Rationale: Austin Group Defect Report(s) applied: 209.

See <http://austingroupbugs.net/view.php?id=209>

Change Number: XBD/TC1/D5/0080 [360]

On Page: 443 Line: 15048 Section: <unistd.h>

In the DESCRIPTION section, delete L15048 (ctermid() declaration in XBD <unistd.h>).

At L15124 (<unistd.h>), add a sentence:

Implementations may also include the ctermid() prototype as defined in <stdio.h>.

Tag the entire paragraph starting on L15124 including the above new sentence with the OB margin marking.

Rationale: Austin Group Defect Report(s) applied: 360.

See <http://austingroupbugs.net/view.php?id=360>

Some implementations have had a declaration for ctermid() and this should still be allowed in Issue 7. Having ctermid() and pthread_atfork() prototypes in <unistd.h>, however, are namespace pollution issues that should be corrected in the next revision.

Change Number: XBD/TC1/D5/0081 [380]

On Page: 455 Line: 15531-15532 Section: <wchar.h>

In the DESCRIPTION section, in the wcpcpy() and wcpncpy() prototype declarations change from:

restrict*

to:

*restrict

Rationale: Austin Group Defect Report(s) applied: 380.

See <http://austingroupbugs.net/view.php?id=380>

2. Changes to System Interfaces

This section contains the set of changes to the text of the System Interfaces.

[Note to reviewers: References to defect reports are provided to aid reviewers.]

Change Number: XSH/TC1/D5/0001 [316]

On Page: 477 Line: 16210 Section: 2.3 Error Numbers

Change from:

The ERRORS section on each reference page specifies which error conditions shall be detected by all implementations ("shall fail") and which may be optionally detected by an implementation ("may fail"). If no error condition is detected, the action requested shall be successful.

to:

The ERRORS section on each reference page specifies which error conditions shall be detected by all implementations ("shall fail") and which may be optionally detected by an implementation ("may fail"). If no error condition is detected, the action requested shall be successful. If an error condition is detected, the action requested may have been partially performed, unless otherwise stated.

Rationale: Austin Group Defect Report(s) applied: 316.
See <http://austingroupbugs.net/view.php?id=316>

Change Number: XSH/TC1/D5/0002 [146]

On Page: 482 Line: 16419 Section: 2.3 Error Numbers

For the [ENOTDIR] description, change from:

[ENOTDIR] Not a directory. A component of the specified pathname exists, but it is not a directory, when a directory was expected.

to:

[ENOTDIR] Not a directory. A component of the specified pathname exists, but it is not a directory, when a directory was expected; or an attempt was made to create a non-directory file, and the specified pathname contains at least one non-`<slash>` character and ends with one or more trailing `<slash>` characters.

Rationale: Austin Group Defect Report(s) applied: 146.
See <http://austingroupbugs.net/view.php?id=146>

Change Number: XSH/TC1/D5/0003 [112]

On Page: 482 Line: 16430 Section: 2.3 Error Numbers

Change from:

[ENOTSUP] Not supported. The implementation does not support this feature of the Realtime Option Group.

to:

[ENOTSUP] Not supported. The implementation does not support the requested feature or value.

Rationale: Austin Group Defect Report(s) applied: 112.
See <http://austingroupbugs.net/view.php?id=112>

Change Number: XSH/TC1/D5/0004 [77]

On Page: 485 Line: 16549 Section: 2.4.1 Signal Generation and Delivery

Change from:

When any stop signal (SIGSTOP, SIGTSTP, SIGTTIN, SIGTTOU) is generated for a process, any pending SIGCONT signals for that process shall be

discarded. Conversely, when SIGCONT is generated for a process, all pending stop signals for that process shall be discarded. When SIGCONT is generated for a process that is stopped, the process shall be continued, even if the SIGCONT signal is blocked or ignored. If SIGCONT is blocked and not ignored, it shall remain pending until it is either unblocked or a stop signal is generated for the process.

to:

When any stop signal (SIGSTOP, SIGTSTP, SIGTTIN, SIGTTOU) is generated for a process or thread, all pending SIGCONT signals for that process or any of the threads within that process shall be discarded. Conversely, when SIGCONT is generated for a process or thread, all pending stop signals for that process or any of the threads within that process shall be discarded. When SIGCONT is generated for a process that is stopped, the process shall be continued, even if the SIGCONT signal is ignored by the process or is blocked by all threads within the process and there are no threads in a call to a `sigwait()` function selecting SIGCONT. If SIGCONT is blocked by all threads within the process, there are no threads in a call to a `sigwait()` function selecting SIGCONT, and SIGCONT is not ignored by the process, the SIGCONT signal shall remain pending on the process until it is either unblocked by a thread or a thread calls a `sigwait()` function selecting SIGCONT, or a stop signal is generated for the process or any of the threads within the process.

Rationale: Austin Group Defect Report(s) applied: 77.
See <http://austingroupbugs.net/view.php?id=77>

Change Number: XSH/TC1/D5/0005 [66]

On Page: 489 Line: 16717 Section: 2.4.3 Signal Actions

In the section "Pointer to a Function", change from:

When signal-catching functions are invoked asynchronously with process execution, the behavior of some of the functions defined by this volume of POSIX.1-200x is unspecified if they are called from a signal-catching function.

to:

If the process is multi-threaded, or if the process is single threaded and a signal handler is executed other than as the result of:

- * The process calling `abort()`, `raise()`, `kill()`, `pthread_kill()`, or `sigqueue()` to generate a signal that is not blocked

- * A pending signal being unblocked and being delivered before the call that unblocked it returns

the behavior is undefined if the signal handler refers to any object other than `errno` with static storage duration other than by assigning a value to an object declared as `volatile sig_atomic_t`, or if the signal handler calls any function defined in this standard other than one of the functions listed in the following table.

Rationale: Austin Group Defect Report(s) applied: 66.
See <http://austingroupbugs.net/view.php?id=66>

Change Number: XSH/TC1/D5/0006 [102]

1780
1781
1782 On Page: 489 Line: 16722 Section: 2.4.3 Signal Actions
1783
1784 Add pthread_self() and pthread_kill() to the list of async-signal-safe
1785 functions.
1786
1787 *Rationale:* Austin Group Defect Report(s) applied: 102.
1788 See <http://austingroupbugs.net/view.php?id=102>
1789
1790
1791 **Change Number: XSH/TC1/D5/0007 [103]**
1792
1793
1794 On Page: 489 Line: 16722 Section: 2.4.3 Signal Actions
1795
1796 Add pthread_sigmask() to the list of async-signal-safe functions.
1797
1798 *Rationale:* Austin Group Defect Report(s) applied: 103.
1799 See <http://austingroupbugs.net/view.php?id=103>
1800
1801
1802 **Change Number: XSH/TC1/D5/0008 [234]**
1803
1804
1805 On Page: 489 Line: 16750 Section: 2.4.3 Signal Actions
1806
1807 In the table of functions that shall be async-signal-safe, add fchdir()
1808 to the list.
1809
1810 *Rationale:* Austin Group Defect Report(s) applied: 234.
1811 See <http://austingroupbugs.net/view.php?id=234>
1812
1813
1814 **Change Number: XSH/TC1/D5/0009 [312]**
1815
1816
1817 On Page: 492 Line: 16878 Section: 2.5.1 Interaction of File Descriptors
1818 and Standard I/O Streams
1819
1820 Delete the text:
1821
1822 Otherwise, the result is undefined.
1823
1824 *Rationale:* Austin Group Defect Report(s) applied: 312.
1825 See <http://austingroupbugs.net/view.php?id=312>
1826 Since L16842-16843 cover both handles, it is clear that the
1827 statements on L16878 and L16893 are redundant (as well as contradictory).
1828
1829
1830 **Change Number: XSH/TC1/D5/0010 [312]**
1831
1832
1833 On Page: 493 Line: 16893 Section: 2.5.1 Interaction of File Descriptors
1834 and Standard I/O Streams
1835
1836 Delete the text:
1837
1838 If the rules above are not followed, the result is unspecified.
1839
1840 *Rationale:* Austin Group Defect Report(s) applied: 312.
1841 See <http://austingroupbugs.net/view.php?id=312>
1842 Since L16842-16843 cover both handles, it is clear that the

statements on L16878 and L16893 are redundant (as well as contradictory).

Change Number: XSH/TC1/D5/0011 [345,428]

On Page: 497 Line: 17067 Section: 2.7.1 IPC General Description

Add a new paragraph:

In addition to the `ipc_perm` structure, each associated data structure includes several `time_t` fields for recording timestamps of particular operations. When an operation is described as setting a timestamp to the current time, that particular timestamp member of the associated data structure shall be set to the largest `time_t` value which is not greater than the current time.

Rationale: Austin Group Defect Report(s) applied: 345,428.

See <http://austingroupbugs.net/view.php?id=345>

See <http://austingroupbugs.net/view.php?id=428>

Change Number: XSH/TC1/D5/0012 [109,429]

On Page: 507 Line: 17490 Section: 2.9.1 Thread-Safety

Add `mblen()` and `mbtowc()` in alphabetic order to the list of functions that need not be thread-safe in the table on P507 L17490-17510; remove `wcstombs()` from the same table.

On L17511, change from:

The `wcrtomb()` and `wcsrtombs()` functions need not be thread-safe if passed a NULL `ps` argument.

to:

The `mbrlen()`, `mbrtowc()`, `mbsnrtowcs()`, `mbsrtowcs()`, `wcrtomb()`, `wcsnrtombs()`, and `wcsrtombs()` functions need not be thread-safe if passed a NULL `ps` argument.

Rationale: Austin Group Defect Report(s) applied: 109,429.

See <http://austingroupbugs.net/view.php?id=109>

See <http://austingroupbugs.net/view.php?id=429>

Change Number: XSH/TC1/D5/0013 [89]

On Page: 508 Line: 17536-17542 Section: 2.9.3 Thread Mutexes

On L17536-L17538, change from:

* It returns successfully from [...] with `m` as the mutex argument.

to:

* It calls [...] with `m` as the mutex argument and the call returns zero or `EOWNERDEAD`.

On L17538 (after the 3rd bullet item) add a new bullet item:

1906 * It calls `pthread_mutex_setprioceiling()` with `m` as the mutex argument
1907 and the call returns `[EOWNERDEAD]`.
1908
1909 On L17539-17542 (last 2 bullet items), change from:
1910
1911 * It returns (successfully or not) from `pthread_cond_wait()` with `m`
1912 as the mutex argument (except as explicitly indicated otherwise for
1913 certain errors).
1914
1915 * It returns (successfully or not) from `pthread_cond_timedwait()` with
1916 `m` as the mutex argument (except as explicitly indicated otherwise for
1917 certain errors).
1918
1919 to:
1920
1921 * It calls `pthread_cond_wait()` with `m` as the mutex argument and the call
1922 returns zero or certain error numbers (see `pthread_cond_timedwait()`).
1923
1924 * It calls `pthread_cond_timedwait()` with `m` as the mutex argument and the
1925 call returns zero or certain error numbers (see `pthread_cond_timedwait()`).
1926
1927 *Rationale:* Austin Group Defect Report(s) applied: 89.
1928 See <http://austingroupbugs.net/view.php?id=89>
1929
1930
1931 **Change Number: XSH/TC1/D5/0014** [410]
1932
1933
1934 On Page: 514 Line: 17760 Section: 2.9.5.2 Cancellation Points
1935
1936 Add `strerror_l()` to the list, between `strerror()` and `strerror_r()`.
1937
1938 Add `strftime_l()` to the list, between `strftime()` and `symlink()`.
1939
1940 *Rationale:* Austin Group Defect Report(s) applied: 410.
1941 See <http://austingroupbugs.net/view.php?id=410>
1942
1943
1944 **Change Number: XSH/TC1/D5/0015** [376]
1945
1946
1947 On Page: 540 Line: 18820 Section: 2.12.1 Defined Types
1948
1949 In the table, change from:
1950
1951 `dev_t` Arithmetic type used for device numbers.
1952
1953 to:
1954
1955 `dev_t` Integer type used for device numbers.
1956
1957 *Rationale:* Austin Group Defect Report(s) applied: 376.
1958 See <http://austingroupbugs.net/view.php?id=376>
1959
1960
1961 **Change Number: XSH/TC1/D5/0016** [327]
1962
1963
1964 On Page: 541 Line: 18867 Section: 2.12.1 Defined Types
1965
1966 Change from:
1967
1968 `time_t` Integer or real-floating type used for time in seconds, as defined

1969 in the ISO C standard.
1970
1971 to:
1972
1973 time_t Integer type used for time in seconds, as defined in the ISO
1974 C standard.
1975
1976 *Rationale:* Austin Group Defect Report(s) applied: 327.
1977 See <http://austingroupbugs.net/view.php?id=327>
1978
1979
1980 **Change Number: XSH/TC1/D5/0017** [74]
1981
1982
1983 On Page: 541 Line: 18881-18886 Section: 2.12.3 Pointer Types
1984
1985 Delete Section 2.12.3:
1986
1987 2.12.3 Pointer Types
1988
1989 All function pointer types shall have the same representation as the
1990 type pointer to void. Conversion of a function pointer to void * shall
1991 not alter the representation. A void * value resulting from such a
1992 conversion can be converted back to the original function pointer type,
1993 using an explicit cast, without loss of information.
1994
1995 Note: The ISO C standard does not require this, but it is required for
1996 POSIX conformance.
1997
1998 *Rationale:* Austin Group Defect Report(s) applied: 74.
1999 See <http://austingroupbugs.net/view.php?id=74>
2000
2001
2002 **Change Number: XSH/TC1/D5/0018** [464]
2003
2004
2005 On Page: 559 Line: 19380 Section: accept()
2006
2007 In the DESCRIPTION section, change from:
2008
2009 address_len Points to a socklen_t structure ...
2010
2011 to:
2012
2013 address_len Either a null pointer, if address is a null pointer,
2014 or a pointer to a socklen_t object ...
2015
2016 *Rationale:* Austin Group Defect Report(s) applied: 464.
2017 See <http://austingroupbugs.net/view.php?id=464>
2018
2019
2020 **Change Number: XSH/TC1/D5/0019** [461]
2021
2022
2023 On Page: 561 Line: 19464 Section: access()
2024
2025 In the DESCRIPTION section, change from:
2026
2027 ... the current working directory is used ...
2028
2029 to:
2030
2031 ... the current working directory shall be used ...

2032
2033 *Rationale:* Austin Group Defect Report(s) applied: 461.
2034 See <http://austingroupbugs.net/view.php?id=461>
2035
2036
2037 **Change Number: XSH/TC1/D5/0020 [324]**
2038
2039
2040 On Page: 561 Line: 19482 Section: `access()`
2041
2042 In the ERRORS section, for the `[ENOTDIR]` error, change from:
2043
2044 A component of the path prefix is not a directory, ...
2045
2046 to:
2047
2048 A component of the path prefix names an existing file that is neither
2049 a directory nor a symbolic link to a directory, ...
2050
2051 *Rationale:* Austin Group Defect Report(s) applied: 324.
2052 See <http://austingroupbugs.net/view.php?id=324>
2053 This is an editorial issue clarifying the intent of the
2054 standard.
2055
2056
2057 **Change Number: XSH/TC1/D5/0021 [278]**
2058
2059
2060 On Page: 562 Line: 19491 `access()`
2061
2062 In the ERRORS section, add (after the `[EBADF]` error):
2063
2064 `[ENOTDIR]` The path argument is not an absolute path and `fd` is a file
2065 descriptor associated with a non-directory file.
2066
2067 *Rationale:* Austin Group Defect Report(s) applied: 278.
2068 See <http://austingroupbugs.net/view.php?id=278>
2069
2070
2071 **Change Number: XSH/TC1/D5/0022 [278]**
2072
2073
2074 On Page: 562 Line: 19504 Section: `access()`
2075
2076 In the ERRORS section, delete:
2077
2078 `[ENOTDIR]` The path argument is not an absolute path and `fd` is neither
2079 `AT_FDCWD` nor a file descriptor associated with a directory.
2080
2081 *Rationale:* Austin Group Defect Report(s) applied: 278.
2082 See <http://austingroupbugs.net/view.php?id=278>
2083
2084
2085 **Change Number: XSH/TC1/D5/0023 [291]**
2086
2087
2088 On Page: 562 Line: 19512–19513 Section: `access()`
2089
2090 In the EXAMPLES section, change both instances of "filename" to
2091 "pathname".
2092
2093 *Rationale:* Austin Group Defect Report(s) applied: 291.
2094 See <http://austingroupbugs.net/view.php?id=291>

2095

2096

2097 **Change Number: XSH/TC1/D5/0024** [320]

2098

2099

2100 On Page: 564 Line: 19589 Section: `acos()`

2101

2102 Change:

2103

2104 ... and either a NaN (if supported), or an implementation-defined
2105 value shall be returned.

2106

2107 to:

2108

2109 ... and a NaN shall be returned.

2110

2111 *Rationale:* Austin Group Defect Report(s) applied: 320.

2112 See <http://austingroupbugs.net/view.php?id=320>

2113

2114

2115 **Change Number: XSH/TC1/D5/0025** [320]

2116

2117

2118 On Page: 566 Line: 19645 Section: `acosh()`

2119

2120 In the RETURN VALUE section, change from:

2121

2122 ... and either a NaN (if supported), or an implementation-defined
2123 value shall be returned.

2124

2125 to:

2126

2127 ... and a NaN shall be returned.

2128

2129 *Rationale:* Austin Group Defect Report(s) applied: 320.

2130 See <http://austingroupbugs.net/view.php?id=320>

2131

2132

2133 **Change Number: XSH/TC1/D5/0026** [98]

2134

2135

2136 On Page: 573 Line: 19785 Section: `aio_fsync()`

2137

2138 In the SYNOPSIS section, shade the synopsis and add the margin code
2139 `FSC|SIO`.

2140

2141 On L19788, in the DESCRIPTION section, change from:

2142

2143 The `aio_fsync()` function shall asynchronously force all I/O operations
2144 associated with the file indicated by the file descriptor `aio_fildes`
2145 member of the `aiocb` structure referenced by the `aiocbp` argument and
2146 queued at the time of the call to `aio_fsync()` to the synchronized I/O
2147 completion state.

2148

2149 to:

2150

2151 The `aio_fsync()` function shall asynchronously perform a file
2152 synchronization operation, as specified by the `op` argument, for I/O
2153 operations associated with the file indicated by the file descriptor
2154 `aio_fildes` member of the `aiocb` structure referenced by the `aiocbp` argument
2155 and queued at the time of the call to `aio_fsync()`.

2156

2157 On L19793, in the DESCRIPTION section, add SIO shading to:

2158
2159 If `op` is `O_DSYNC`, all currently queued I/O operations shall be completed
2160 as if by a call to `fdatsync()`; that is, as defined for synchronized
2161 I/O data integrity completion.
2162
2163 On L19794, in the DESCRIPTION section, add FSC shading to:
2164
2165 If `op` is `O_SYNC`, all currently queued I/O operations shall be completed
2166 as if by a call to `fsync()`;
2167
2168 and add FSC SIO shading to:
2169
2170 ... that is, as defined for synchronized I/O file integrity completion.
2171
2172 On L19797, in the DESCRIPTION section, change from:
2173
2174 ... operation queued by `aio_fsync()` fails, then, as for `fsync()` and
2175 `fdatsync()`, outstanding I/O operations are not guaranteed to have
2176 been completed.
2177
2178 to:
2179
2180 ... operation queued by `aio_fsync()` fails, then outstanding I/O operations
2181 are not guaranteed to have been completed.
2182
2183 On L19825, in the ERRORS section, add SIO shading to:
2184
2185 [EINVAL] This implementation does not support synchronized I/O for
2186 this file.
2187
2188 and add another [EINVAL] error after it, shaded FSC:
2189
2190 [EINVAL] The `aio_fildes` member of the `aio_cb` structure refers to a file
2191 on which an `fsync()` operation is not possible.
2192
2193 *Rationale:* Austin Group Defect Report(s) applied: 98.
2194 See <http://austingroupbugs.net/view.php?id=98>
2195
2196
2197 **Change Number: XSH/TC1/D5/0027** [98]
2198
2199
2200 On Page: 574 Line: 19826 Section: `aio_fsync()`
2201
2202 In the ERRORS section, change from:
2203
2204 [EINVAL] A value of `op` other than `O_DSYNC` or `O_SYNC` was specified.
2205
2206 to:
2207
2208 [EINVAL] A value of `op` other than `O_DSYNC` or `O_SYNC` was specified, or
2209 `O_DSYNC` was specified and the implementation does not provide runtime
2210 support for the Synchronized Input and Output option, or `O_SYNC` was
2211 specified and the implementation does not provide runtime support for
2212 the File Synchronization option.
2213
2214 On L19829, in the ERRORS section, change from:
2215
2216 The error is returned in the error status for the asynchronous `fsync()`
2217 operation.
2218
2219 to:
2220