



IEEE Standard for Harmonic Control in Electric Power Systems

IEEE Power and Energy Society

Developed by the
Transmission and Distribution Committee

IEEE Std 519™-2022
(Revision of IEEE Std 519-2014)



IEEE Standard for Harmonic Control in Electric Power Systems

Developed by the

Transmission and Distribution Committee
of the
IEEE Power and Energy Society

Approved 13 May 2022

IEEE SA Standards Board

THIS IS A REDLINE DOCUMENT PRODUCED BY TECHSTREET, AN ASME COMPANY.

This document is intended to provide users with an indication of changes from one edition to the next. It includes a full-text version of the new document, plus an indication of changes from the previous version.

Redlines are designed to save time and improve efficiencies by using the latest software technology to find and highlight document changes. More professionals are using valuable new technologies like redlines, to help improve outcomes in a fast paced global business world.

Because it may not be technically possible to capture all changes accurately, it is recommended that users consult previous editions as appropriate. In all cases, only the current base version of this publication is to be considered the official document.

This Redline is produced solely by Techstreet. IEEE has not prepared this Redline and is not responsible for its accuracy.

Redline Processing Notes:

1. ~~Red Text~~ - Red strikethrough text denotes deletions.
2. Blue Text - Blue underlined text denotes modifications and additions.

Abstract: Goals for the design of electrical systems that include both linear and nonlinear loads are established in this standard. The voltage and current waveforms that may exist throughout the system are described, and waveform distortion goals for the system designer are established. The interface between sources and loads is described as the point of common coupling and observance of the design goals will reduce interference between electrical equipment.

This standard addresses steady-state limitations. Transient conditions exceeding these limitations may be encountered. This document sets the quality of power that is to be provided at the point of common coupling. This document does not cover the effects of radio-frequency interference; however, guidance is offered for wired telephone systems.

Keywords: harmonics, IEEE 519™, power quality, steady-state

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2022 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 5 August 2022. Printed in the United States of America.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-8727-6 STD25432
Print: ISBN 978-1-5044-8728-3 STDPD25432

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <https://www.ieee.org/about/corporate/governance/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE Standards documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>), appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards through an accredited consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed by volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers are not necessarily members of IEEE or IEEE SA and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE makes no warranties or representations concerning its standards, and expressly disclaims all warranties, express or implied, concerning this standard, including but not limited to the warranties of merchantability, fitness for a particular purpose and non-infringement. In addition, IEEE does not warrant or represent that the use of the material contained in its standards is free from patent infringement. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE is the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that the presenter's views should be considered the personal views of that individual rather than the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations, consulting information, or advice pertaining to IEEE Standards documents.**

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its Societies and Standards Coordinating Committees are not able to provide an instant response to comments, or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in evaluating comments or in revisions to an IEEE standard is welcome to join the relevant IEEE working group. You can indicate interest in a working group using the Interests tab in the Manage Profile & Interests area of the [IEEE SA myProject system](#).¹ An IEEE Account is needed to access the application.

Comments on standards should be submitted using the [Contact Us](#) form.²

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not constitute compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Data privacy

Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and data ownership in the context of assessing and using the standards in compliance with applicable laws and regulations.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

¹ Available at: <https://development.standards.ieee.org/myproject-web/public/view.html#landing>.

² Available at: <https://standards.ieee.org/content/ieee-standards/en/about/contact/index.html>.

Photocopies

Subject to payment of the appropriate licensing fees, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400; <https://www.copyright.com/>. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#).³ For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

Errata

Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#).⁴ Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to periodically check for errata.

Patents

IEEE Standards are developed in compliance with the [IEEE SA Patent Policy](#).⁵

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing

³ Available at: <https://ieeexplore.ieee.org/browse/standards/collection/ieee>.

⁴ Available at: <https://standards.ieee.org/standard/index.html>.

⁵ Available at: <https://standards.ieee.org/about/sasb/patcom/materials.html>.

agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

IMPORTANT NOTICE

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. IEEE Standards development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

Participants

At the time this standard was completed, the Harmonics Working Group had the following membership:

David Zech, *Chair*
S. Mark Halpin, *Vice Chair*
Nick Zagrodnik, *Secretary*

Julio Barros
Math Bollen
Marlin Browning
Gary Chang
Joseph Grappe
Bill Howe
Steven Johnston
Kevin Kittredge
Justin Kuhlers
Roberto Langella

Theo Laughner
Chester Li
Jan Meyer
Dave Mueller
Chris Mullins
Anthony Murphy
Matt Norwalk
Marty Page
Rey Ramos

Daniel Sabin
Kenn Sedziol
Nikunj Shah
Harish Sharma
Gaurav Singh
Joseph Sneed
Grazia Todeschini
Reigh Walling
Benno Weis
Francisc Zavoda

The following members of the individual Standards Association balloting group voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Mohamed Abouelella
Steven Ashmore
Thomas Barnes
Steven Bezner
Jon Bickel
Thomas Bishop
William Bloethe
Jon Brasher
Jeffrey Britton
Marlin Browning
Paul Cardinal
Sean Carr
Richard Carter
Wen-Kung Chang
Michael Chirico
Murphy Choy
Larry Conrad
Stephen Conrad
Thomas Cooke
Timothy Croushore
Gary Donner
Neal Dowling
Donald Dunn
Jorge Fernandez Daher
Jeffrey Fowler
Carl Fredericks
Kamal Garg
George Gela
David Gilmer
Joseph Grappe
S. Mark Halpin
Gordon Halt
Robert Hanna
Lee Herron
Werner Hoelzl
Robert Hoerauf
Ali Hooshyar

John Houdek
Yi Hu
Richard Jackson
John John
Brian Johnson
Steven Johnston
Laszlo Kadar
Innocent Kamwa
Haran Karmaker
John Kay
Irfan Khan
Yuri Khersonsky
James Kinney
Boris Kogan
Jacob Kulangara
Jim Kulchisky
Mikhail Lagoda
Chung-Yiu Lam
Benjamin Lanz
Theo Laughner
An Le
Wei-Jen Lee
Yung-chiang Lee
Ting Li
William Lockley
Tapan Manna
John McDaniel
Jeffrey McElray
Daleep Mohla
Daniel Mulkey
Jerry Murphy
Arun Narang
Dennis Neitzel
Arthur Neubauer
James Niemira
Joe Nims
Nayeem Ninad

Matthew Norwalk
Gearold O. H. Eidhin
Emre Ozsoy
Sivaraman P
Lorraine Padden
Marty Page
David Parman
Bansi Patel
Pathik Patel
Howard Penrose
Jim Phillips
John Rama
Moises Ramos
Reynaldo Ramos
Lakshman Raut
Bruce Rockwell
Charles Rogers
Daniel Sabin
Steven Sano
Sergio Santos
Bartien Sayogo
Kenneth Sedziol
Robert Seitz
Nikunj Shah
Harish Sharma
Nigel Shore
Hyeong Sim
Gaurav Singh
Jerry Smith
Gary Smullin
Wayne Stec
Steven Swindler
Eric Udren
Timothy Unruh
James Van De Ligt
Benton Vandiver
Sarat Chandra Vegunta

John Vergis
Quintin Verzosa
Reigh Walling
Daniel Ward

Keith Waters
Kenneth White
James Wikston
Larry Young

Nick Zagrodnik
Vahraz Zamani
Francisc Zavoda
David Zech

When the IEEE SA Standards Board approved this standard on 13 May 2022, it had the following membership:

David J. Law, *Chair*
Ted Burse, *Vice Chair*
Gary Hoffman, *Past Chair*
Konstantinos Karachalios, *Secretary*

Edward A. Addy
Ramy Ahmed Fathy
J. Travis Griffith
Guido R. Hiertz
Yousef Kimiagar
Joseph L. Koepfinger*
Thomas Koshy
John D. Kulick

Johnny Daozhuang Lin
Kevin Lu
Daleep C. Mohla
Andrew Myles
Damir Novosel
Annette D. Reilly
Robby Robson
Jon Walter Rosdahl

Mark Siira
Dorothy V. Stanley
Lei Wang
F. Keith Waters
Karl Weber
Sha Wei
Philip B. Winston
Daidi Zhong

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 519-2022, IEEE Standard for Harmonic Control in Electric Power Systems.

This standard shall be applied at interface points between system owners or operators and users in the power system. The limits in this standard shall apply at a point of common coupling (PCC) between the system owner or operator and a user, where the PCC is usually taken as the point in the power system closest to the user where the system owner or operator could offer service to other users. Frequently for service to industrial users (i.e., manufacturing plants) via a dedicated service transformer, the PCC is at the HV side of the transformer. For commercial users (office parks, shopping malls, etc.) supplied through a common service transformer, the PCC is commonly at the LV side of the service transformer.

The limits in this standard represent a shared responsibility for harmonic control between system owners or operators and users. Users produce harmonic currents that flow through the system owner's or operator's system, which lead to voltage harmonics in the voltages supplied to other users. The amount of harmonic voltage distortion supplied to other users is a function of the aggregate effects of the harmonic current producing loads of all users and the impedance characteristics of the supply system.

Harmonic voltage distortion limits are provided to reduce the potential negative effects on user and system equipment. Maintaining harmonic voltages below these levels necessitates that

- All users limit their harmonic current emissions to reasonable values determined in an equitable manner based on the inherent ownership stake each user has in the supply system.
- Each system owner or operator takes action to decrease voltage distortion levels by modifying the supply system impedance characteristics as necessary.

In order to allow the system owner or operator to control the system impedance characteristics to reduce voltage distortion when necessary, users should not add equipment that affects the impedance characteristic in a way such that voltage distortions are increased. In effect, such actions by a user could result in producing excessive voltage harmonic distortion. Such equipment additions (that lead to undesirable system impedance characteristics) should be controlled by the user in the same manner as current harmonic-producing devices operated by the user.

Contents

1. Overview	11
1.1 Scope	11
1.2 Purpose	12
1.3 Word usage	13
2. Normative references	13
3. Definitions, acronyms, and abbreviations	14
3.1 Definitions	14
3.2 Acronyms and abbreviations	15
4. Harmonic measurements	15
4.1 Measurement window width	15
4.2 Very short time harmonic measurements	16
4.3 Short time harmonic measurements	16
4.4 Statistical evaluation	16
5. Harmonic distortion limits	16
5.1 Voltage distortion limits	17
5.2 Current distortion limits	17
5.3 Current distortion limits for systems nominally rated 120 V through 69 kV	18
5.4 Current distortion limits for systems nominally rated above 69 kV through 161 kV	19
5.5 Current distortion limits for systems nominally rated above 161 kV	20
5.6 Recommendations for increasing harmonic current limits	21
Annex A (informative) Interharmonic voltage limits	23
A.1 Premise	23
A.2 Limits rationale	23
A.3 Summary of the work done by the interharmonic distortion task force	25
Annex B (informative) Telephone influence factor (TIF)	26
B.1 Guidelines for I - T product	27
Annex C (informative) Limits on commutation notches	28
C.1 Recommended limits on commutation notches	28
Annex D (informative) Bibliography	29

IEEE ~~Standard~~ **Recommended Practice and Requirements** for Harmonic Control in Electric Power Systems

~~IMPORTANT NOTICE: IEEE Standards documents are not intended to ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.~~

~~This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading "Important Notice" or "Important Notices and Disclaimers Concerning IEEE Documents." They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.~~

1. Overview

~~The uses of~~ Nonlinear loads connected to electric power systems include static power converters, arc discharge devices, saturated magnetic devices, and, to a lesser degree, rotating machines. Static power converters of electric power are the largest nonlinear loads and are used in industry for a variety of purposes, such as electrochemical power supplies, adjustable speed drives, and uninterruptible power supplies. These devices are useful because they can convert ac to dc, dc to dc, dc to ac, and ac to ac. [These nonlinear devices are key elements for energy savings.](#)

Nonlinear loads change the sinusoidal nature of the ac power current (and consequently the ac voltage drop), thereby resulting in the flow of harmonic currents in the ac power system that can cause interference with communication circuits and other types of equipment. These harmonic currents also lead to increased losses and heating in numerous electromagnetic devices (motors, transformers, etc.). When reactive power compensation, in the form of power factor improvement capacitors, is used, resonant conditions can occur that may result in high levels of harmonic voltage and current distortion when the resonant condition occurs at a harmonic associated with nonlinear loads.

Common sources of harmonic currents in power systems include power electronic converters, arc furnaces, static [volt-ampere reactive \(VAR\)](#) systems, inverters for distributed generation, ac phase controllers, cycloconverters, and ac-dc converters (rectifiers) commonly used in switched mode power supplies and pulse width modulated (PWM) motor drives. Each of these harmonic-producing devices can have fairly consistent harmonic current emission characteristics over time or each may present a widely-varying characteristic depending on the control of the device, the characteristics of the system, and other variables.

1.1 Scope

This [standard](#) ~~recommended practice~~ establishes goals for the design of electrical systems that include both linear and nonlinear loads. The voltage and current waveforms that may exist throughout the system are described, and waveform distortion goals for the system designer are established. The interface between sources and loads is described as the point of common coupling and observance of the design goals will [reduce](#) ~~minimize~~ interference between electrical equipment.

The voltage and current distortion limits in this standard shall apply at the user point of common coupling (PCC) to overall installation containing harmonic producing loads (nonlinear equipment). Users are directed to other applicable standards such as IEEE Std 1547™ or IEEE Std 2800™ for current distortion limits of inverter-based resources (IBR) installations.¹ When no other applicable standard exists, users shall continue to use footnote “c” under Table 2 through Table 4 in this standard for IBR connected to transmission systems.

If an installation has a mix of harmonic producing loads and IBR at the same facility, users are directed to use Figure 1 in this document to determine whether IEEE 519 limits apply at the PCC.

This [standard](#) ~~recommended practice~~ addresses steady-state limitations. Transient conditions exceeding these limitations may be encountered. This document sets the quality of power that is to be provided at the point of common coupling. This document does not cover the effects of radio-frequency interference; however, guidance is offered for wired telephone systems.

¹[Information on references can be found in Clause 2.](#)

The limits given in this document are based on assumptions that are technically justifiable at the PCC between the system owner/operator and user. These assumptions, and therefore the limits in this document, are not necessarily valid at any other point in the power system. For this reason, the limits given in this document are not intended to be used for the evaluation of equipment.

1.2 Purpose

This standard ~~recommended practice~~ is to be used for guidance in the design of power systems with nonlinear loads. The limits set are for steady state operating ~~operation and are recommended for “worst case”~~ conditions. ~~Transient conditions exceeding these limits may be encountered.~~ In any case, the limit values given in this document ~~are recommendations and~~ should not be considered binding in all cases. ~~Because of the nature of the recommendations,~~ Some conservatism is present that may not be necessary in all cases.

This standard shall ~~recommended practice should~~ be applied at a PCC ~~interface points~~ between system owners or operators and users in the power system. The limits in this standard ~~recommended practice~~ are intended for application at a ~~point of common coupling (PCC)~~ between the system owner or operator and a user, where the PCC is usually taken as the point in the power system closest to the user where the system owner or operator could offer service to another user. Frequently for service to industrial users (i.e., manufacturing plants) via a dedicated service transformer, the PCC is at the HV side of the transformer. For commercial users (office parks, shopping malls, etc.) supplied through a common service transformer, the PCC is commonly at the LV side of the service transformer.

The limits in this standard ~~recommended practice~~ represent a shared responsibility for harmonic control between system owners or operators and users. Users produce harmonic currents that flow through the ~~system~~ owner's or operator's system which lead to voltage harmonics in the voltages supplied to other users. The amount of harmonic voltage distortion supplied to other users is a function of the aggregate effects of the harmonic current producing loads of all users and the impedance characteristics of the supply system.