

---

---

**Telecommunications and exchange  
between information technology  
systems — Requirements for local and  
metropolitan area networks —**

**Part 3:  
Standard for Ethernet**

**AMENDMENT 3: Media access control  
parameters for 50 Gb/s and physical  
layers and management parameters  
for 50 Gb/s, 100 Gb/s, and 200 Gb/s  
operation**

*Télécommunications et échange entre systèmes informatiques —  
Exigences pour les réseaux locaux et métropolitains —*

*Partie 3: Norme pour Ethernet*

*AMENDEMENT 3: Paramètres de commande d'accès media pour  
50 Gb/s et couches physiques et paramètres de gestion pour  
fonctionnement à 50 Gb/s, 100 Gb/s et 200 Gb/s*



Reference number  
ISO/IEC/IEEE 8802-3:2021/Amd.3:2021(E)

**Documents**  
Document Sharing Hub  
© IEEE 2019



## **COPYRIGHT PROTECTED DOCUMENT**

© IEEE 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc  
3 Park Avenue, New York  
NY 10016-5997, USA

Email: [stds.ipr@ieee.org](mailto:stds.ipr@ieee.org)  
Website: [www.ieee.org](http://www.ieee.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO/IEC documents should be noted.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)) or the IEC list of patent declarations received (see [patents.iec.ch](http://patents.iec.ch)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html). In the IEC, see [www.iec.ch/understanding-standards](http://www.iec.ch/understanding-standards).

ISO/IEC/IEEE 8802-3:2021/Amd.3 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE Std 802.3cd-2018) and drafted in accordance with its editorial rules. It was adopted, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html) and [www.iec.ch/national-committees](http://www.iec.ch/national-committees).



# IEEE Standard for Ethernet

## **Amendment 3: Media Access Control Parameters for 50 Gb/s and Physical Layers and Management Parameters for 50 Gb/s, 100 Gb/s, and 200 Gb/s Operation**

Sponsor  
**LAN/MAN Standards Committee**  
of the  
**IEEE Computer Society**

Approved 5 December 2018  
**IEEE-SA Standards Board**

**Abstract:** Clause 131 through Clause 140 and Annex 135A through Annex 136D are added to IEEE Std 802.3-2018 by this amendment to specify IEEE 802.3 Media Access Control (MAC) parameters, Physical Layer specifications, and management parameters for the transfer of IEEE 802.3 format frames at 50 Gb/s, 100 Gb/s, and 200 Gb/s.

**Keywords:** 50GAUI-1, 50GAUI-2, 50GBASE-CR, 50GBASE-FR, 50GBASE-KR, 50GBASE-LR, 50GBASE-SR, 50 Gigabit Ethernet, 50GMII, 100GAUI-2, 100GAUI-4, 100GBASE-CR2, 100GBASE-DR, 100GBASE-KR2, 100GBASE-SR2, 100 Gigabit Ethernet, 200GBASE-CR4, 200GBASE-KR4, 200GBASE-SR4, 200 Gigabit Ethernet, amendment, EEE, Energy-Efficient Ethernet, Ethernet, FEC, forward error correction, IEEE 802.3™, IEEE 802.3cd™, LAUI-2, MMF, SMF

---

The Institute of Electrical and Electronics Engineers, Inc.  
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2019 by The Institute of Electrical and Electronics Engineers, Inc.  
All rights reserved. Published 15 February 2019. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-5357-8 STD23441  
Print: ISBN 978-1-5044-5358-5 STDPD23441

*IEEE prohibits discrimination, harassment and bullying.*

*For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.*

*No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.*

## Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/ipr/disclaimers.html>.

### Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

### Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

## Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

## Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board  
445 Hoes Lane  
Piscataway, NJ 08854 USA

## Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

## Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

## Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

## Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

## Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

## Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

## Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3cd Working Group ballot.

**David J. Law**, *IEEE 802.3 Working Group Chair*  
**Adam Healey**, *IEEE 802.3 Working Group Vice-Chair*  
**Pete Anslow**, *IEEE 802.3 Working Group Secretary*  
**Steven B. Carlson**, *IEEE 802.3 Working Group Executive Secretary*  
**Valerie Maguire**, *IEEE 802.3 Working Group Treasurer*

**Mark Nowell**, *IEEE P802.3cd Task Force Chair*  
**Matt Brown**, *IEEE P802.3cd Task Force Editor-in-Chief*  
**Arthur Marris**, *IEEE P802.3cd Task Force Editor*  
**Gary Nicholl**, *IEEE P802.3cd Task Force Editor*  
**Adee Ran**, *IEEE P802.3cd Task Force Editor*  
**Jonathan King**,<sup>1</sup> *IEEE P802.3cd Task Force Editor*  
**Peter Stassar**, *IEEE P802.3cd Task Force Editor*

Justin Abbott  
David Abramson  
Dale Amason  
Eric Baden  
Amrik Bains  
Thananya Baldwin  
Denis Beaudoin  
Christian Beia  
Vipul Bhatt  
William Bliss  
Mark Bohm  
Brad Booth  
Martin Bouda  
David Brandt  
Ralf-Peter Braun  
Theodore Brillhart  
Paul Brooks  
Phillip Brownlee  
Chris Bullock  
Jairo Bustos Heredia  
Adrian Butter  
Anthony Calbone  
Clark Carty  
Craig Chabot  
Mandeep Chadha  
David Chalupsky  
Jacky Chang  
Xin Chang  
Chan Chen  
Weiyang Cheng  
Golam Choudhury  
Keng Hua Chuang  
Christopher R. Cole  
John D'Ambrosia  
Piers J. G. Dawe  
Fred Dawson

Eric DiBiaso  
John Dillard  
Chris Diminico  
Curtis Donahue  
Michael Dudek  
Frank Effenberger  
John Ewen  
Ramin Farjad  
Shahar Feldman  
Matthias Fritsche  
Richard Frosch  
Andrew Gardner  
Ali Ghiasi  
Steven Gorshe  
Steffen Graber  
Olaf Grau  
Robert M. Grow  
Yong Guo  
Mark Gustlin  
Marek Hajduczenia  
Tomohiro Hashimoto  
Akinori Hayakawa  
Rajmohan Hegde  
David Hess  
Yasuo Hidaka  
David Hoglund  
Rita Horner  
Bernd Hormmeyer  
Xi Huang  
Xingang Huang  
Yasuhiro Hyakutake  
Jonathan Ingham  
Kazuhiko Ishibe  
Hideki Isono  
Tom Issenhuth  
Kenneth Jackson

Andrew Jimenez  
John Johnson  
Chad Jones  
Peter Jones  
Upen Kareti  
Yasuaki Kawatsu  
Yongbum Kim  
Mark Kimber  
Scott Kipp  
Michael Klempa  
Curtis Knittle  
Shigeru Kobayashi  
Paul Kolesar  
Toshihiko Kusano  
Hans Lackner  
Jeffrey Lapak  
Mark Laubach  
Greg Le Cheminant  
Hanan Leizerovich  
David Lewis  
Jon Lewis  
Mike Peng Li  
Robert Lingle  
Hai-Feng Liu  
Zhenyu Liu  
Moiz Lokhandwala  
Miklos Lukacs  
Kent Lusted  
Zahy Madgar  
Jeffery Maki  
David Malicoat  
Takeo Masuda  
Kirsten Matheus  
Erdem Matoglu

<sup>1</sup>Not a member of the IEEE 802.3 working group at the beginning of the working group ballot.

|                              |                    |                     |
|------------------------------|--------------------|---------------------|
| Mick McCarthy                | Alon Regev         | Yoshihiro Tsukamoto |
| Brett McClellan              | Duane Remein       | Ed Ulrichs          |
| Thomas McDermott             | Salvatore Rotolo   | Alexander Umnov     |
| John McDonough               | Sam Sambasivan     | Sterling A. Vaden   |
| Larry McMillan               | Edward Sayre       | Stefano Valle       |
| Greg McSorley                | Fred Schindler     | Paul Vanderlaan     |
| Marcel Medina                | Masood Shariff     | Dylan Walker        |
| Richard Mei                  | Kapil Shrikhande   | Roy Wang            |
| Richard Mellitz              | Jeff Slavick       | Tongtong Wang       |
| Phil Miguelez                | Daniel Smith       | Xinyuan Wang        |
| Paul Mooney                  | Scott Sommers      | Matthias Wendt      |
| Ron Muir Dale Murray         | Yoshiaki Sone      | Oded Wertheim       |
| Henry Muyschondt             | Bryan Sparrowhawk  | Natalie Wienckowski |
| Edward Nakamoto              | Atul Srivastava    | Ludwig Winkel       |
| Kevin Noll                   | Heath Stewart      | Peter Wu            |
| David Ofelt                  | David Stover       | Dayin Xu            |
| Thomas Palkert               | Ken-Ichi Suzuki    | Yu Xu               |
| Sujan Pandey                 | Steve Swanson      | Lennart Yseboodt    |
| Sesha Panguluri              | Andre Szczepanek   | Hayato Yuki         |
| Earl Parsons                 | William Szeto      | Andrew Zambell      |
| Wanquan Peng                 | Bharat Tailor      | Huanlin Zhang       |
| Ruben Perez De Aranda Alonso | Takayuki Tajima    | Qiwen Zhong         |
| Michael Peters               | Tomoo Takahara     | Yan Zhuang          |
| Jean Picard                  | Kohichi Tamura     | George Zimmerman    |
| David Piehler                | Nathan Tracy       | Helge Zinner        |
| Rick Pimpinella              | Matthew Traverso   | Pavel Zivny         |
| William Powell               | David Tremblay     |                     |
| Rick Rabinovich              | Stephen Trowbridge |                     |

The following members of the individual balloting committee voted on this amendment. Balloters may have voted for approval, disapproval, or abstention.

|                      |                   |                   |
|----------------------|-------------------|-------------------|
| Thomas Alexander     | Brian Franchuk    | Hyeong Ho Lee     |
| Richard Alfvén       | Avraham Freedman  | Hanan Leizerovich |
| Arne Alping          | Yukihiro Fujimoto | David Lewis       |
| Pete Anslow          | Zhigang Gong      | Jon Lewis         |
| Butch Anton          | Eric W. Gray      | Robert Lingle     |
| Eric Baden           | Randall Groves    | Hai-Feng Liu      |
| John Ballingall      | Mark Gustlin      | Kent Lusted       |
| Ralf-Peter Braun     | Adam Healey       | Michael Lynch     |
| Nancy Bravin         | Marco Hernandez   | Elvis Maculuba    |
| Theodore Brillhart   | David Hess        | Valerie Maguire   |
| Matt Brown           | Yasuo Hidaka      | Jeffery Maki      |
| Demetrio Bucaneg     | Werner Hoelzl     | Arthur Marris     |
| Gary Burrell         | Rita Horner       | Michael Maytum    |
| Jairo Bustos Heredia | Noriyuki Ikeuchi  | Mick McCarthy     |
| William Byrd         | Sergiu Iordanescu | Brett McClellan   |
| John Calvin          | Osamu Ishida      | Thomas McDermott  |
| Steven B. Carlson    | Atsushi Ito       | Richard Mellitz   |
| Juan Carreon         | Raj Jain          | Tremont Miao      |
| Clark Carty          | SangKwon Jeong    | Charles Moorwood  |
| Chan Chen            | Peter Jones       | Rick Murphy       |
| Keith Chow           | Manabu Kagami     | Michael Newman    |
| Keng Hua Chuang      | Piotr Karocki     | Charles Ngethe    |
| Charles Cook         | Stuart Kerry      | Gary Nicholl      |
| Piers J. G. Dawe     | Yongbum Kim       | Nick S. A. Nikjoo |
| Stephen Didde        | Jonathan King     | Mark Nowell       |
| Michael Dudek        | Paul Kolesar      | Satoshi Obara     |
| Sourav Dutta         | Mark Laubach      | Thomas Palkert    |
| Jason Ellison        | David J. Law      | Bansi Patel       |

Arumugam Paventhan  
Michael Peters  
David Piehler  
Rick Pimpinella  
Adee Ran  
R. K. Rannow  
Alon Regev  
Maximilian Riegel  
Robert Robinson  
Alexander Rysin  
Toshiaki Sakai  
Kapil Shrikhande  
Jason Shriver  
Jeff Slavick  
Daniel Smith  
Thomas Starai

Peter Stassar  
Robert Stone  
Walter Struppler  
Mitsutoshi Sugawara  
Junqing Sun  
Patrik Sundstrom  
Andre Szczepanek  
Kohichi Tamura  
David Thompson  
Geoffrey Thompson  
Michael Thompson  
David Tremblay  
Stephen Trowbridge  
Mark-Rene Uchida  
Alexander Umnov  
Paul Vanderlaan

Dmitri Varsanofiev  
George Vlantis  
Khurram Waheed  
Lisa Ward  
Keith Waters  
Oded Wertheim  
Andreas Wolf  
Chun Yu Charles Wong  
Peter Wu  
Xin Wu  
Jun Xu  
Adrian Young  
Oren Yuen  
Andrew Zambell  
Zhen Zhou  
Pavel Zivny

When the IEEE-SA Standards Board approved this amendment on 5 December 2018, it had the following membership:

**Jean-Philippe Faure**, *Chair*  
**Gary Hoffman**, *Vice Chair*  
**John D. Kulick**, *Past Chair*  
**Konstantinos Karachalios**, *Secretary*

Ted Burse  
Guido R. Hiertz  
Christel Hunter  
Joseph L. Koepfinger\*  
Thomas Koshy  
Hung Ling  
Dong Liu

Xiaohui Liu  
Kevin Lu  
Daleep Mohla  
Andrew Myles  
Paul Nikolich  
Ronald C. Petersen  
Annette D. Reilly

Robby Robson  
Dorothy Stanley  
Mehmet Ulema  
Phil Wennblom  
Philip Winston  
Howard Wolfman  
Jingyi Zhou

\*Member Emeritus

## Introduction

This introduction is not part of IEEE Std 802.3cd-2018, IEEE Standard for Ethernet. Amendment 3: Media Access Control Parameters for 50 Gb/s and Physical Layers and Management Parameters for 50 Gb/s, 100 Gb/s, and 200 Gb/s Operation.

IEEE Std 802.3™ was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile) and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2018 and are not maintained as separate documents.

At the date of publication for IEEE Std 802.3cd-2018, IEEE Std 802.3 was composed of the following documents:

### IEEE Std 802.3-2018

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber

access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines services and protocol elements that enable the exchange of IEEE Std 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well as 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

Section Seven—Includes Clause 96 through Clause 115 and Annex 97A through Annex 115A. Clause 96 through Clause 98, Clause 104, and associated annexes, specify Physical Layers and optional features for 100 Mb/s and 1000 Mb/s operation over a single twisted pair. Clause 100 through Clause 103, as well as associated annexes, specify Physical Layers for the operation of the EPON protocol over coaxial distribution networks. Clause 105 through Clause 114 and associated annexes include general information on 25 Gb/s operation as well as 25 Gb/s Physical Layer specifications. Clause 99 specifies a MAC merge sublayer for the interspersing of express traffic. Clause 115 and its associated annex specify a Physical Layer for 1000 Mb/s operation over plastic optical fiber.

Section Eight—Includes Clause 116 through Clause 126 and Annex 119A through Annex 120E. Clause 116 through Clause 124 and associated annexes include general information on 200 Gb/s and 400 Gb/s operation as well the 200 Gb/s and 400 Gb/s Physical Layer specifications. Clause 125 and Clause 126 include general information on 2.5 Gb/s and 5 Gb/s operation as well as 2.5 Gb/s and 5 Gb/s Physical Layer specifications.

#### IEEE Std 802.3cb-2018

Amendment 1—This amendment includes changes to IEEE Std 802.3-2018 and its amendments, and adds Clause 127 through Clause 130, Annex 127A, Annex 128A, Annex 128B, Annex 128C, and Annex 130A. This amendment adds new Physical Layers for operation at 2.5 Gb/s and 5 Gb/s over electrical backplanes.

#### IEEE Std 802.3bt-2018

Amendment 2—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 145, Annex 145A, Annex 145B, and Annex 145C. This amendment adds power delivery using all four pairs in the structured wiring plant, resulting in greater power being available to end devices. This amendment also allows for lower standby power consumption in end devices and adds a mechanism to better manage the available power budget.

#### IEEE Std 802.3cd™-2018

Amendment 3—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 131 through Clause 140 and Annex 135A through Annex 136D. This amendment adds MAC parameters, Physical Layers, and management parameters for the transfer of IEEE 802.3 format frames at 50 Gb/s, 100 Gb/s, and 200 Gb/s.

A companion document, IEEE Std 802.3.1, describes Ethernet management information base (MIB) modules for use with the Simple Network Management Protocol (SNMP). IEEE Std 802.3.1 is updated to add management capability for enhancements to IEEE Std 802.3 after approval of those enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.

## Contents

|                                                               |    |
|---------------------------------------------------------------|----|
| 1. Introduction.....                                          | 35 |
| 1.1 Overview.....                                             | 35 |
| 1.1.3 Architectural perspectives.....                         | 35 |
| 1.1.3.2 Compatibility interfaces.....                         | 35 |
| 1.3 Normative references.....                                 | 35 |
| 1.4 Definitions.....                                          | 36 |
| 1.5 Abbreviations.....                                        | 37 |
| 4. Media Access Control.....                                  | 38 |
| 4.4 Specific implementations.....                             | 38 |
| 4.4.2 MAC parameters.....                                     | 38 |
| 30. Management.....                                           | 39 |
| 30.3 Layer management for DTEs.....                           | 39 |
| 30.3.2 PHY device managed object class.....                   | 39 |
| 30.3.2.1 PHY device attributes.....                           | 39 |
| 30.3.2.1.2 aPhyType.....                                      | 39 |
| 30.3.2.1.3 aPhyTypeList.....                                  | 39 |
| 30.3.2.1.5 aSymbolErrorDuringCarrier.....                     | 39 |
| 30.5 Layer management for medium attachment units (MAUs)..... | 39 |
| 30.5.1 MAU managed object class.....                          | 39 |
| 30.5.1.1 MAU attributes.....                                  | 39 |
| 30.5.1.1.2 aMAUType.....                                      | 39 |
| 30.5.1.1.4 aMediaAvailable.....                               | 40 |
| 30.5.1.1.11 aBIPErrCount.....                                 | 41 |
| 30.5.1.1.12 aLaneMapping.....                                 | 41 |
| 30.5.1.1.17 aFECCorrectedBlocks.....                          | 41 |
| 30.5.1.1.18 aFECUncorrectableBlocks.....                      | 41 |
| 30.5.1.1.26 aRSFECBIPErrCount.....                            | 42 |
| 30.5.1.1.27 aRSFECLaneMapping.....                            | 42 |
| 30.5.1.1.29 aRSFECBypassIndicationAbility.....                | 42 |
| 30.5.1.1.31 aRSFECBypassIndicationEnable.....                 | 42 |
| 30.6 Management for link Auto-Negotiation.....                | 43 |
| 30.6.1 Auto-Negotiation managed object class.....             | 43 |
| 30.6.1.1 Auto-Negotiation attributes.....                     | 43 |
| 30.6.1.1.5 aAutoNegLocalTechnologyAbility.....                | 43 |
| 45. Management Data Input/Output (MDIO) Interface.....        | 44 |
| 45.2 MDIO Interface Registers.....                            | 44 |
| 45.2.1 PMA/PMD registers.....                                 | 44 |
| 45.2.1.1 PMA/PMD control 1 register (Register 1.0).....       | 46 |
| 45.2.1.1.3 Speed selection (1.0.13, 1.0.6, 1.0.5:2).....      | 46 |
| 45.2.1.2 PMA/PMD status 1 register (Register 1.1).....        | 46 |
| 45.2.1.2.3 Fault (1.1.7).....                                 | 46 |
| 45.2.1.4 PMA/PMD speed ability (Register 1.4).....            | 47 |
| 45.2.1.4.12a 50G capable (1.4.3).....                         | 47 |
| 45.2.1.6 PMA/PMD control 2 register (Register 1.7).....       | 47 |
| 45.2.1.6.3 PMA/PMD type selection (1.7.6:0).....              | 48 |

|                                                                                                                                                                                                |    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| 45.2.1.7 PMA/PMD status 2 register (Register 1.8).....                                                                                                                                         | 48 |
| 45.2.1.7.4 Transmit fault (1.8.11).....                                                                                                                                                        | 48 |
| 45.2.1.7.5 Receive fault (1.8.10).....                                                                                                                                                         | 49 |
| 45.2.1.8 PMD transmit disable register (Register 1.9).....                                                                                                                                     | 49 |
| 45.2.1.17a 50G PMA/PMD extended ability (Register 1.20).....                                                                                                                                   | 50 |
| 45.2.1.17a.1 50G PMA remote loopback ability (1.20.15).....                                                                                                                                    | 50 |
| 45.2.1.17a.2 50GBASE-LR ability (1.20.4).....                                                                                                                                                  | 50 |
| 45.2.1.17a.3 50GBASE-FR ability (1.20.3).....                                                                                                                                                  | 51 |
| 45.2.1.17a.4 50GBASE-SR ability (1.20.2).....                                                                                                                                                  | 51 |
| 45.2.1.17a.5 50GBASE-CR ability (1.20.1).....                                                                                                                                                  | 51 |
| 45.2.1.17a.6 50GBASE-KR ability (1.20.0).....                                                                                                                                                  | 51 |
| 45.2.1.21a PMA/PMD extended ability 2 (Register 1.25).....                                                                                                                                     | 51 |
| 45.2.1.21a.1 50G extended abilities (1.25.0).....                                                                                                                                              | 51 |
| 45.2.1.89 BASE-R PMD control register (Register 1.150).....                                                                                                                                    | 52 |
| 45.2.1.90 BASE-R PMD status register (Register 1.151).....                                                                                                                                     | 52 |
| 45.2.1.90.1 Receiver status 0 (1.151.0).....                                                                                                                                                   | 52 |
| 45.2.1.90.2 Frame lock 0 (1.151.1).....                                                                                                                                                        | 52 |
| 45.2.1.90.3 Start-up protocol status 0 (1.151.2).....                                                                                                                                          | 52 |
| 45.2.1.90.4 Training failure 0 (1.151.3).....                                                                                                                                                  | 52 |
| 45.2.1.110 RS-FEC control register (Register 1.200).....                                                                                                                                       | 53 |
| 45.2.1.110.a FEC degraded SER enable (1.200.4).....                                                                                                                                            | 53 |
| 45.2.1.110.b Four-lane PMD (1.200.3).....                                                                                                                                                      | 53 |
| 45.2.1.110.2 FEC bypass indication enable (1.200.1).....                                                                                                                                       | 54 |
| 45.2.1.111 RS-FEC status register (Register 1.201).....                                                                                                                                        | 54 |
| 45.2.1.111.1 PCS align status (1.201.15).....                                                                                                                                                  | 54 |
| 45.2.1.111.2 RS-FEC align status (1.201.14).....                                                                                                                                               | 54 |
| 45.2.1.111.5 FEC AM lock 1 (1.201.9).....                                                                                                                                                      | 55 |
| 45.2.1.111.6 FEC AM lock 0 (1.201.8).....                                                                                                                                                      | 55 |
| 45.2.1.111.7a FEC degraded SER (1.201.4).....                                                                                                                                                  | 55 |
| 45.2.1.111.7b FEC degraded SER ability (1.201.3).....                                                                                                                                          | 55 |
| 45.2.1.111.8 RS-FEC high SER (1.201.2).....                                                                                                                                                    | 55 |
| 45.2.1.111.9 FEC bypass indication ability (1.201.1).....                                                                                                                                      | 55 |
| 45.2.1.117 RS-FEC BIP error counter lane 0 (Register 1.230).....                                                                                                                               | 55 |
| 45.2.1.129 50GAUI-n, 100GAUI-2, 200GAUI-n, and 400GAUI-n chip-to-chip transmitter<br>equalization, receive direction, lane 0 register (Register 1.500).....                                    | 56 |
| 45.2.1.129.1 Request flag (1.500.15).....                                                                                                                                                      | 57 |
| 45.2.1.129.2 Post-cursor request (1.500.14:12).....                                                                                                                                            | 57 |
| 45.2.1.129.3 Pre-cursor request (1.500.11:10).....                                                                                                                                             | 57 |
| 45.2.1.129.4 Post-cursor remote setting (1.500.9:7).....                                                                                                                                       | 57 |
| 45.2.1.129.5 Pre-cursor remote setting (1.500.6:5).....                                                                                                                                        | 58 |
| 45.2.1.129.6 Post-cursor local setting (1.500.4:2).....                                                                                                                                        | 58 |
| 45.2.1.129.7 Pre-cursor local setting (1.500.1:0).....                                                                                                                                         | 58 |
| 45.2.1.130 50GAUI-n, 100GAUI-2, 200GAUI-n, and 400GAUI-n chip-to-chip transmitter<br>equalization, receive direction, lane 1 through lane 15 registers (Registers<br>1.501 through 1.515)..... | 58 |
| 45.2.1.131 50GAUI-n, 100GAUI-2, 200GAUI-n, and 400GAUI-n chip-to-chip transmitter<br>equalization, transmit direction, lane 0 register (Register 1.516).....                                   | 58 |
| 45.2.1.131.1 Request flag (1.516.15).....                                                                                                                                                      | 60 |
| 45.2.1.131.2 Post-cursor request (1.516.14:12).....                                                                                                                                            | 60 |
| 45.2.1.131.3 Pre-cursor request (1.516.11:10).....                                                                                                                                             | 60 |
| 45.2.1.131.4 Post-cursor remote setting (1.516.9:7).....                                                                                                                                       | 60 |
| 45.2.1.131.5 Pre-cursor remote setting (1.516.6:5).....                                                                                                                                        | 60 |
| 45.2.1.131.6 Post-cursor local setting (1.516.4:2).....                                                                                                                                        | 60 |
| 45.2.1.131.7 Pre-cursor local setting (1.516.1:0).....                                                                                                                                         | 61 |

|                                                                                                                                                                                           |    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| 45.2.1.132 50GAUI-n, 100GAUI-2, 200GAUI-n, and 400GAUI-n chip-to-chip transmitter equalization, transmit direction, lane 1 through lane 15 registers (Registers 1.517 through 1.531)..... | 61 |
| 45.2.1.132a PMA precoder control Tx output (Register 1.600).....                                                                                                                          | 61 |
| 45.2.1.132a.1 Lane 3 Tx output precoder enable (1.600.3).....                                                                                                                             | 61 |
| 45.2.1.132a.2 Lane 2 Tx output precoder enable (1.600.2).....                                                                                                                             | 61 |
| 45.2.1.132a.3 Lane 1 Tx output precoder enable (1.600.1).....                                                                                                                             | 62 |
| 45.2.1.132a.4 Lane 0 Tx output precoder enable (1.600.0).....                                                                                                                             | 62 |
| 45.2.1.132b PMA precoder control Rx input (Register 1.601).....                                                                                                                           | 62 |
| 45.2.1.132b.1 Lane 3 Rx input precoder enable (1.601.3).....                                                                                                                              | 62 |
| 45.2.1.132b.2 Lane 2 Rx input precoder enable (1.601.2).....                                                                                                                              | 62 |
| 45.2.1.132b.3 Lane 1 Rx input precoder enable (1.601.1).....                                                                                                                              | 62 |
| 45.2.1.132b.4 Lane 0 Rx input precoder enable (1.601.0).....                                                                                                                              | 62 |
| 45.2.1.132c PMA precoder control Rx output (Register 1.602).....                                                                                                                          | 63 |
| 45.2.1.132c.1 Lane 1 Rx output precoder enable (1.602.1).....                                                                                                                             | 63 |
| 45.2.1.132c.2 Lane 0 Rx output precoder enable (1.602.0).....                                                                                                                             | 63 |
| 45.2.1.132d PMA precoder control Tx input (Register 1.603).....                                                                                                                           | 63 |
| 45.2.1.132d.1 Lane 1 Tx input precoder enable (1.603.1).....                                                                                                                              | 63 |
| 45.2.1.132d.2 Lane 0 Tx input precoder enable (1.603.0).....                                                                                                                              | 63 |
| 45.2.1.132e PMA precoder request flag (Register 1.604).....                                                                                                                               | 64 |
| 45.2.1.132e.1 Tx input precoder request flag (1.604.1).....                                                                                                                               | 64 |
| 45.2.1.132e.2 Rx input precoder request flag (1.604.0).....                                                                                                                               | 64 |
| 45.2.1.132f PMA precoder request Rx input status (Register 1.605).....                                                                                                                    | 64 |
| 45.2.1.132f.1 Lane 1 Rx input precoder request status (1.605.1).....                                                                                                                      | 64 |
| 45.2.1.132f.2 Lane 0 Rx input precoder request status (1.605.0).....                                                                                                                      | 64 |
| 45.2.1.132g PMA precoder request Tx input status (Register 1.606).....                                                                                                                    | 65 |
| 45.2.1.132g.1 Lane 1 Tx input precoder request status(1.606.1).....                                                                                                                       | 65 |
| 45.2.1.132g.2 Lane 0 Tx input precoder request status (1.606.0).....                                                                                                                      | 65 |
| 45.2.1.132h RS-FEC degraded SER activate threshold register (Register 1.650, 1.651).....                                                                                                  | 65 |
| 45.2.1.132i RS-FEC degraded SER deactivate threshold register (Register 1.652, 1.653).....                                                                                                | 66 |
| 45.2.1.132j RS-FEC degraded SER interval register (Register 1.654, 1.655).....                                                                                                            | 66 |
| 45.2.1.135a BASE-R PAM4 PMD training LP control, lane 0 through lane 3 registers (Register 1.1120 through 1.1123).....                                                                    | 67 |
| 45.2.1.136a BASE-R PAM4 PMD training LP status, lane 0 through lane 3 registers (Register 1.1220 through 1.1223).....                                                                     | 68 |
| 45.2.1.137a BASE-R PAM4 PMD training LD control, lane 0 through lane 3 registers (Register 1.1320 through 1.1323).....                                                                    | 69 |
| 45.2.1.138a BASE-R PAM4 PMD training LD status, lane 0 through lane 3 registers (Register 1.1420 through 1.1423).....                                                                     | 70 |
| 45.2.1.139 PMD training pattern lanes 0 through 3 (Register 1.1450 through 1.1453).....                                                                                                   | 71 |
| 45.2.1.141 PRBS pattern testing control (Register 1.1501).....                                                                                                                            | 71 |
| 45.2.3 PCS registers.....                                                                                                                                                                 | 72 |
| 45.2.3.1 PCS control 1 register (Register 3.0).....                                                                                                                                       | 72 |
| 45.2.3.2 PCS status 1 register (Register 3.1).....                                                                                                                                        | 72 |
| 45.2.3.2.7 PCS receive link status (3.1.2).....                                                                                                                                           | 72 |
| 45.2.3.4 PCS speed ability (Register 3.4).....                                                                                                                                            | 73 |
| 45.2.3.4.5a 50G capable (3.4.5).....                                                                                                                                                      | 73 |
| 45.2.3.6 PCS control 2 register (Register 3.7).....                                                                                                                                       | 73 |
| 45.2.3.7 PCS status 2 register (Register 3.8).....                                                                                                                                        | 74 |
| 45.2.3.7.6a 50GBASE-R capable (3.8.8).....                                                                                                                                                | 74 |
| 45.2.3.10 EEE control and capability 1 (Register 3.20).....                                                                                                                               | 74 |
| 45.2.3.10.a 50GBASE-R EEE fast wake supported (3.20.14).....                                                                                                                              | 74 |
| 45.2.3.15 BASE-R and MultiGBASE-T PCS status 1 register (Register 3.32).....                                                                                                              | 75 |
| 45.2.3.15.1 BASE-R and MultiGBASE-T receive link status (3.32.12).....                                                                                                                    | 75 |

|                                                                                                                                                                                     |    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| 45.2.3.15.4 BASE-R and MultiGBASE-T PCS high BER (3.32.1) .....                                                                                                                     | 75 |
| 45.2.3.15.5 BASE-R and MultiGBASE-T PCS block lock (3.32.0) .....                                                                                                                   | 75 |
| 45.2.3.16 BASE-R and MultiGBASE-T PCS status 2 register (Register 3.33) .....                                                                                                       | 75 |
| 45.2.3.16.1 Latched block lock (3.33.15) .....                                                                                                                                      | 75 |
| 45.2.3.16.2 Latched high BER (3.33.14) .....                                                                                                                                        | 75 |
| 45.2.3.16.3 BER (3.33.13:8) .....                                                                                                                                                   | 76 |
| 45.2.3.16.4 Errored blocks (3.33.7:0) .....                                                                                                                                         | 76 |
| 45.2.3.19 BASE-R PCS test-pattern control register (Register 3.42) .....                                                                                                            | 76 |
| 45.2.7 Auto-Negotiation registers .....                                                                                                                                             | 76 |
| 45.2.7.12 Backplane Ethernet, BASE-R copper status (Register 7.48) .....                                                                                                            | 76 |
| 45.2.7.12.3 Negotiated Port Type (7.48.1, 7.48.2, 7.48.3, 7.48.5, 7.48.6, 7.48.8, 7.48.9,<br>7.48.10, 7.48.11, 7.48.12, 7.48.13, 7.48.14, 7.48.15, 7.49.0, 7.49.1,<br>7.49.2) ..... | 76 |
| 45.2.7.12a Backplane Ethernet, BASE-R copper status 2 (Register 7.49) .....                                                                                                         | 77 |
| 45.2.7.12a.1 Negotiated Port Type .....                                                                                                                                             | 77 |
| 69. Introduction to Ethernet operation over electrical backplanes .....                                                                                                             | 78 |
| 69.1 Overview .....                                                                                                                                                                 | 78 |
| 69.1.1 Scope .....                                                                                                                                                                  | 78 |
| 69.1.2 Relationship of Backplane Ethernet to the ISO OSI reference model .....                                                                                                      | 78 |
| 69.2 Summary of Backplane Ethernet Sublayers .....                                                                                                                                  | 80 |
| 69.2.1 Reconciliation sublayer and media independent interfaces .....                                                                                                               | 80 |
| 69.2.3 Physical Layer signaling systems .....                                                                                                                                       | 80 |
| 69.3 Delay constraints .....                                                                                                                                                        | 82 |
| 69.5 Protocol implementation conformance statement (PICS) proforma .....                                                                                                            | 82 |
| 73. Auto-Negotiation for backplane and copper cable assembly .....                                                                                                                  | 83 |
| 73.2 Relationship to the ISO/IEC Open Systems Interconnection (OSI) reference model .....                                                                                           | 83 |
| 73.5 DME transmission .....                                                                                                                                                         | 83 |
| 73.5.1 DME electrical specifications .....                                                                                                                                          | 83 |
| 73.6 Link codeword encoding .....                                                                                                                                                   | 84 |
| 73.6.4 Technology Ability Field .....                                                                                                                                               | 84 |
| 73.7 Receive function requirements .....                                                                                                                                            | 85 |
| 73.7.6 Priority Resolution function .....                                                                                                                                           | 85 |
| 73.10 State diagrams and variable definitions .....                                                                                                                                 | 86 |
| 73.10.1 State diagram variables .....                                                                                                                                               | 86 |
| 73.10.2 State diagram timers .....                                                                                                                                                  | 87 |
| 78. Energy-Efficient Ethernet (EEE) .....                                                                                                                                           | 88 |
| 78.1 Overview .....                                                                                                                                                                 | 88 |
| 78.1.4 PHY types optionally supporting EEE .....                                                                                                                                    | 88 |
| 78.5 Communication link access latency .....                                                                                                                                        | 89 |
| 80. Introduction to 40 Gb/s and 100 Gb/s networks .....                                                                                                                             | 90 |
| 80.1 Overview .....                                                                                                                                                                 | 90 |
| 80.1.3 Relationship of 40 Gigabit and 100 Gigabit Ethernet to the ISO OSI reference model .....                                                                                     | 90 |
| 80.1.4 Nomenclature .....                                                                                                                                                           | 91 |
| 80.1.5 Physical Layer signaling systems .....                                                                                                                                       | 92 |
| 80.2 Summary of 40 Gigabit and 100 Gigabit Ethernet sublayers .....                                                                                                                 | 93 |
| 80.2.2 Physical Coding Sublayer (PCS) .....                                                                                                                                         | 93 |

|                                                                                                                                                                    |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 80.2.3 Forward Error Correction (FEC) sublayers .....                                                                                                              | 93  |
| 80.2.4 Physical Medium Attachment (PMA) sublayer.....                                                                                                              | 94  |
| 80.2.5 Physical Medium Dependent (PMD) sublayer .....                                                                                                              | 94  |
| 80.2.6 Auto-Negotiation .....                                                                                                                                      | 94  |
| 80.4 Delay constraints.....                                                                                                                                        | 95  |
| 80.5 Skew constraints .....                                                                                                                                        | 96  |
| 80.7 Protocol implementation conformance statement (PICS) proforma.....                                                                                            | 99  |
| 82. Physical Coding Sublayer (PCS) for 64B/66B, type 40GBASE-R and 100GBASE-R .....                                                                                | 100 |
| 82.6 Auto-Negotiation .....                                                                                                                                        | 100 |
| 82.7 Protocol implementation conformance statement (PICS) proforma for Clause 82, Physical Coding Sublayer (PCS) for 64B/66B, type 40GBASE-R and 100GBASE-R.....   | 100 |
| 82.7.4 PICS proforma tables for PCS, type 40GBASE-R and 100GBASE-R .....                                                                                           | 100 |
| 82.7.4.11 Auto-Negotiation for Backplane Ethernet functions .....                                                                                                  | 100 |
| 90. Ethernet support for time synchronization protocols.....                                                                                                       | 101 |
| 90.1 Introduction.....                                                                                                                                             | 101 |
| 91. Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 100GBASE-R PHYs .....                                                                              | 102 |
| 91.3 PMA compatibility .....                                                                                                                                       | 102 |
| 91.5 Functions within the RS-FEC sublayer .....                                                                                                                    | 102 |
| 91.5.2 Transmit function.....                                                                                                                                      | 102 |
| 91.5.2.6 Alignment marker mapping and insertion .....                                                                                                              | 102 |
| 91.5.2.7 Reed-Solomon encoder.....                                                                                                                                 | 102 |
| 91.5.3 Receive function .....                                                                                                                                      | 103 |
| 91.5.3.3 Reed-Solomon decoder.....                                                                                                                                 | 103 |
| 91.5.3.3.1 FEC Degraded SER (optional) .....                                                                                                                       | 103 |
| 91.6 RS-FEC MDIO function mapping .....                                                                                                                            | 104 |
| 91.6.2a four_lane_pmd .....                                                                                                                                        | 104 |
| 91.6.2b FEC_degraded_SER_enable.....                                                                                                                               | 104 |
| 91.6.2c FEC_degraded_SER_activate_threshold .....                                                                                                                  | 105 |
| 91.6.2d FEC_degraded_SER_deactivate_threshold .....                                                                                                                | 105 |
| 91.6.2e FEC_degraded_SER_interval .....                                                                                                                            | 105 |
| 91.6.5a FEC_degraded_SER_ability .....                                                                                                                             | 105 |
| 91.6.5b FEC_degraded_SER .....                                                                                                                                     | 105 |
| 91.7 Protocol implementation conformance statement (PICS) proforma for Clause 91, Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 100GBASE-R PHYs..... | 105 |
| 91.7.3 Major capabilities/options.....                                                                                                                             | 105 |
| 91.7.4 PICS proforma tables for Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 100GBASE-R PHYs .....                                                  | 106 |
| 91.7.4.1 Transmit function.....                                                                                                                                    | 106 |
| 91.7.4.2 Receive function .....                                                                                                                                    | 106 |
| 116. Introduction to 200 Gb/s and 400 Gb/s networks .....                                                                                                          | 108 |
| 116.1 Overview.....                                                                                                                                                | 108 |
| 116.1.2 Relationship of 200 Gigabit and 400 Gigabit Ethernet to the ISO OSI reference model .....                                                                  | 108 |
| 116.1.3 Nomenclature.....                                                                                                                                          | 108 |
| 116.1.4 Physical Layer signaling systems .....                                                                                                                     | 108 |
| 116.2 Summary of 200 Gigabit and 400 Gigabit Ethernet sublayers .....                                                                                              | 110 |

|                                                                                                                                                                     |     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 116.2.5 Physical Medium Dependent (PMD) sublayer .....                                                                                                              | 110 |
| 116.4 Delay constraints.....                                                                                                                                        | 110 |
| 119. Physical Coding Sublayer (PCS) for 64B/66B, type 200GBASE-R and 400GBASE-R .....                                                                               | 111 |
| 119.5a Auto-Negotiation .....                                                                                                                                       | 111 |
| 119.6 Protocol implementation conformance statement (PICS) proforma for Clause 119, Physical Coding Sublayer (PCS) for 64B/66B, type 200GBASE-R and 400GBASE-R..... | 111 |
| 119.6.4 PICS proforma tables for Physical Coding Sublayer (PCS) 64B/66B, type 200GBASE-R and 400GBASE-R .....                                                       | 111 |
| 119.6.4.12 Auto-Negotiation for Backplane Ethernet functions .....                                                                                                  | 111 |
| 120. Physical Medium Attachment (PMA) sublayer, type 200GBASE-R and 400GBASE-R.....                                                                                 | 112 |
| 120.5 Functions within the PMA .....                                                                                                                                | 112 |
| 120.5.7 PAM4 Encoding Gray mapping for PAM4 encoded lanes.....                                                                                                      | 112 |
| 120.5.7.1 Gray mapping for PAM4 encoded lanes.....                                                                                                                  | 112 |
| 120.5.7.2 Precoding for PAM4 encoded lanes .....                                                                                                                    | 112 |
| 120.6 PMA MDIO function mapping.....                                                                                                                                | 112 |
| 120.7 Protocol implementation conformance statement (PICS) proforma for Clause 120, Physical Medium Attachment (PMA) sublayer, type 200GBASE-R and 400GBASE-R ..... | 113 |
| 120.7.7 Encoding .....                                                                                                                                              | 113 |
| 131. Introduction to 50 Gb/s networks .....                                                                                                                         | 114 |
| 131.1 Overview.....                                                                                                                                                 | 114 |
| 131.1.1 Scope.....                                                                                                                                                  | 114 |
| 131.1.2 Relationship of 50 Gigabit Ethernet to the ISO OSI reference model.....                                                                                     | 114 |
| 131.1.3 Nomenclature.....                                                                                                                                           | 114 |
| 131.1.4 Physical Layer signaling systems .....                                                                                                                      | 116 |
| 131.2 Summary of 50 Gigabit Ethernet sublayers .....                                                                                                                | 117 |
| 131.2.1 Reconciliation Sublayer (RS) and Media Independent Interface (50GMII).....                                                                                  | 117 |
| 131.2.2 Physical Coding Sublayer (PCS) .....                                                                                                                        | 117 |
| 131.2.3 Forward Error Correction (FEC) sublayer.....                                                                                                                | 117 |
| 131.2.4 Physical Medium Attachment (PMA) sublayer.....                                                                                                              | 117 |
| 131.2.5 Physical Medium Dependent (PMD) sublayer .....                                                                                                              | 117 |
| 131.2.6 Management interface (MDIO/MDC) .....                                                                                                                       | 117 |
| 131.2.7 Management.....                                                                                                                                             | 118 |
| 131.3 Service interface specification method and notation .....                                                                                                     | 118 |
| 131.3.1 Inter-sublayer service interface.....                                                                                                                       | 118 |
| 131.3.2 Instances of the Inter-sublayer service interface.....                                                                                                      | 118 |
| 131.3.3 Semantics of inter-sublayer service interface primitives .....                                                                                              | 118 |
| 131.4 Delay constraints.....                                                                                                                                        | 120 |
| 131.5 Skew constraints .....                                                                                                                                        | 120 |
| 131.6 State diagrams .....                                                                                                                                          | 123 |
| 131.7 Protocol implementation conformance statement (PICS) proforma.....                                                                                            | 123 |
| 132. Reconciliation Sublayer (RS) and Media Independent Interface (50GMII) for 50 Gb/s operation ...                                                                | 124 |
| 132.1 Overview.....                                                                                                                                                 | 124 |
| 132.1.1 Summary of major concepts .....                                                                                                                             | 124 |
| 132.1.2 Application.....                                                                                                                                            | 124 |
| 132.1.3 Rate of operation.....                                                                                                                                      | 124 |
| 132.1.4 Delay constraints.....                                                                                                                                      | 125 |

|                                                                                                                                                                                             |     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 132.1.5 Allocation of functions .....                                                                                                                                                       | 126 |
| 132.1.6 50GMII structure .....                                                                                                                                                              | 126 |
| 132.1.7 Mapping of 50GMII signals to PLS service primitives .....                                                                                                                           | 126 |
| 132.2 50GMII data stream .....                                                                                                                                                              | 126 |
| 132.3 50GMII functional specifications .....                                                                                                                                                | 126 |
| 132.4 LPI assertion and detection .....                                                                                                                                                     | 126 |
| 132.5 Protocol implementation conformance statement (PICS) proforma for Clause 132,<br>Reconciliation Sublayer (RS) and Media Independent Interface (50GMII) for 50 Gb/s<br>operation ..... | 127 |
| 132.5.1 Introduction .....                                                                                                                                                                  | 127 |
| 132.5.2 Identification .....                                                                                                                                                                | 127 |
| 132.5.2.1 Implementation identification .....                                                                                                                                               | 127 |
| 132.5.2.2 Protocol summary .....                                                                                                                                                            | 127 |
| 132.5.2.3 Major capabilities/options .....                                                                                                                                                  | 128 |
| 132.5.3 PICS proforma tables for Reconciliation Sublayer (RS) and Media Independent<br>Interface (50GMII) for 50 Gb/s operation .....                                                       | 128 |
| 132.5.3.1 General .....                                                                                                                                                                     | 128 |
| 132.5.3.2 Mapping of PLS service primitives .....                                                                                                                                           | 128 |
| 133. Physical Coding Sublayer (PCS) for 64B/66B, type 50GBASE-R .....                                                                                                                       | 129 |
| 133.1 Overview .....                                                                                                                                                                        | 129 |
| 133.1.1 Scope .....                                                                                                                                                                         | 129 |
| 133.1.2 Relationship of 50GBASE-R to other standards .....                                                                                                                                  | 129 |
| 133.1.3 Summary of 50GBASE-R sublayers .....                                                                                                                                                | 129 |
| 133.1.3.1 Physical Coding Sublayer (PCS) .....                                                                                                                                              | 129 |
| 133.1.4 Inter-sublayer interfaces .....                                                                                                                                                     | 129 |
| 133.1.4.1 PCS service interface (50GMII) .....                                                                                                                                              | 129 |
| 133.1.4.2 Forward Error Correction (FEC) or Physical Medium Attachment (PMA)<br>service interface .....                                                                                     | 130 |
| 133.1.5 Functional block diagram .....                                                                                                                                                      | 131 |
| 133.2 Physical Coding Sublayer (PCS) .....                                                                                                                                                  | 132 |
| 133.2.1 Functions within the PCS .....                                                                                                                                                      | 132 |
| 133.2.2 Alignment marker insertion .....                                                                                                                                                    | 132 |
| 133.2.3 PCS lane deskew .....                                                                                                                                                               | 133 |
| 133.2.4 Detailed functions and state diagrams .....                                                                                                                                         | 133 |
| 133.3 Delay constraints .....                                                                                                                                                               | 133 |
| 133.4 Auto-Negotiation .....                                                                                                                                                                | 133 |
| 133.5 Protocol implementation conformance statement (PICS) proforma for Clause 133, Physical<br>Coding Sublayer (PCS) for 64B/66B, type 50GBASE-R .....                                     | 134 |
| 133.5.1 Introduction .....                                                                                                                                                                  | 134 |
| 133.5.2 Identification .....                                                                                                                                                                | 134 |
| 133.5.2.1 Implementation identification .....                                                                                                                                               | 134 |
| 133.5.2.2 Protocol summary .....                                                                                                                                                            | 134 |
| 133.5.3 Major capabilities/options .....                                                                                                                                                    | 135 |
| 133.5.4 PICS proforma tables for Physical Coding Sublayer (PCS) for 64B/66B, type<br>50GBASE-R .....                                                                                        | 135 |
| 133.5.4.1 Coding rules .....                                                                                                                                                                | 135 |
| 133.5.4.2 Scrambler and Descrambler .....                                                                                                                                                   | 136 |
| 133.5.4.3 Deskew and Reordering .....                                                                                                                                                       | 136 |
| 133.5.4.4 Alignment Markers .....                                                                                                                                                           | 136 |
| 133.5.4.5 Test-pattern modes .....                                                                                                                                                          | 136 |
| 133.5.4.6 Bit order .....                                                                                                                                                                   | 137 |
| 133.5.4.7 Management .....                                                                                                                                                                  | 137 |

|                                                                                       |     |
|---------------------------------------------------------------------------------------|-----|
| 133.5.4.8 State diagrams.....                                                         | 137 |
| 133.5.4.9 Loopback .....                                                              | 138 |
| 133.5.4.10 Delay constraints.....                                                     | 138 |
| 133.5.4.11 Auto-Negotiation for Backplane Ethernet functions .....                    | 138 |
| 134. Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 50GBASE-R PHYs ..... | 139 |
| 134.1 Overview.....                                                                   | 139 |
| 134.1.1 Scope.....                                                                    | 139 |
| 134.1.2 Position of RS-FEC in the 50GBASE-R sublayers .....                           | 139 |
| 134.2 FEC service interface.....                                                      | 139 |
| 134.3 PMA compatibility .....                                                         | 140 |
| 134.4 Delay constraints.....                                                          | 141 |
| 134.5 Functions within the RS-FEC sublayer .....                                      | 141 |
| 134.5.1 Functional block diagram .....                                                | 141 |
| 134.5.2 Transmit function.....                                                        | 141 |
| 134.5.2.1 PCS Lane block synchronization.....                                         | 141 |
| 134.5.2.2 PCS Alignment lock and deskew.....                                          | 141 |
| 134.5.2.3 PCS Lane reorder.....                                                       | 141 |
| 134.5.2.4 Alignment marker removal.....                                               | 141 |
| 134.5.2.5 64B/66B to 256B/257B transcoder.....                                        | 142 |
| 134.5.2.6 Alignment marker mapping and insertion .....                                | 143 |
| 134.5.2.7 Reed-Solomon encoder.....                                                   | 144 |
| 134.5.2.8 Symbol distribution.....                                                    | 144 |
| 134.5.2.9 Transmit bit ordering .....                                                 | 144 |
| 134.5.3 Receive function .....                                                        | 144 |
| 134.5.3.1 Alignment lock and deskew .....                                             | 144 |
| 134.5.3.2 FEC Lane reorder.....                                                       | 146 |
| 134.5.3.3 Reed-Solomon decoder.....                                                   | 146 |
| 134.5.3.3.1 FEC Error indication bypass (optional) .....                              | 146 |
| 134.5.3.3.2 FEC Degraded SER (optional) .....                                         | 147 |
| 134.5.3.4 Alignment marker removal.....                                               | 147 |
| 134.5.3.5 256B/257B to 64B/66B transcoder.....                                        | 147 |
| 134.5.3.6 Block distribution .....                                                    | 147 |
| 134.5.3.7 Alignment marker mapping and insertion .....                                | 147 |
| 134.5.3.8 Receive bit ordering.....                                                   | 148 |
| 134.5.4 Detailed functions and state diagrams .....                                   | 148 |
| 134.5.4.1 State diagram conventions .....                                             | 148 |
| 134.5.4.2 State variables .....                                                       | 150 |
| 134.5.4.2.1 Variables .....                                                           | 150 |
| 134.5.4.2.2 Functions.....                                                            | 150 |
| 134.5.4.2.3 Counters .....                                                            | 150 |
| 134.5.4.3 State diagrams.....                                                         | 150 |
| 134.6 RS-FEC MDIO function mapping.....                                               | 151 |
| 134.6.1 FEC_bypass_indication_enable.....                                             | 152 |
| 134.6.2 FEC_degraded_SER_enable.....                                                  | 152 |
| 134.6.3 FEC_degraded_SER_activate_threshold.....                                      | 152 |
| 134.6.4 FEC_degraded_SER_deactivate_threshold.....                                    | 152 |
| 134.6.5 FEC_degraded_SER_interval.....                                                | 152 |
| 134.6.6 FEC_bypass_indication_ability.....                                            | 152 |
| 134.6.7 hi_ser.....                                                                   | 153 |
| 134.6.8 FEC_degraded_SER_ability.....                                                 | 153 |
| 134.6.9 FEC_degraded_SER.....                                                         | 153 |
| 134.6.10 fec_optional_states.....                                                     | 153 |

|            |                                                                                                                                                                |     |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 134.6.11   | amps_lock<x> .....                                                                                                                                             | 153 |
| 134.6.12   | fec_align_status .....                                                                                                                                         | 153 |
| 134.6.13   | FEC_corrected_cw_counter .....                                                                                                                                 | 153 |
| 134.6.14   | FEC_uncorrected_cw_counter .....                                                                                                                               | 153 |
| 134.6.15   | FEC_lane_mapping<x> .....                                                                                                                                      | 154 |
| 134.6.16   | FEC_symbol_error_counter_i .....                                                                                                                               | 154 |
| 134.6.17   | align_status .....                                                                                                                                             | 154 |
| 134.6.18   | BIP_error_counter_i .....                                                                                                                                      | 154 |
| 134.6.19   | lane_mapping<x> .....                                                                                                                                          | 154 |
| 134.6.20   | block_lock<x> .....                                                                                                                                            | 154 |
| 134.6.21   | am_lock<x> .....                                                                                                                                               | 154 |
| 134.7      | Protocol implementation conformance statement (PICS) proforma for Clause 134, Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 50GBASE-R PHYs ..... | 155 |
| 134.7.1    | Introduction .....                                                                                                                                             | 155 |
| 134.7.2    | Identification .....                                                                                                                                           | 155 |
| 134.7.2.1  | Implementation identification .....                                                                                                                            | 155 |
| 134.7.2.2  | Protocol summary .....                                                                                                                                         | 155 |
| 134.7.3    | Major capabilities/options .....                                                                                                                               | 156 |
| 134.7.4    | PICS proforma tables for Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 50GBASE-R PHYs .....                                                      | 156 |
| 134.7.4.1  | Transmit function .....                                                                                                                                        | 156 |
| 134.7.4.2  | Receive function .....                                                                                                                                         | 157 |
| 134.7.4.3  | State diagrams .....                                                                                                                                           | 158 |
| 134.7.4.4  | Delay Constraints .....                                                                                                                                        | 158 |
| 135.       | Physical Medium Attachment (PMA) sublayer, type 50GBASE-R and 100GBASE-P .....                                                                                 | 159 |
| 135.1      | Overview .....                                                                                                                                                 | 159 |
| 135.1.1    | Scope .....                                                                                                                                                    | 159 |
| 135.1.2    | Position of the PMA in the 50GBASE-R and 100GBASE-P sublayers .....                                                                                            | 159 |
| 135.1.3    | Summary of functions .....                                                                                                                                     | 159 |
| 135.1.4    | PMA sublayer positioning .....                                                                                                                                 | 160 |
| 135.2      | PMA interfaces .....                                                                                                                                           | 162 |
| 135.3      | PMA service interface .....                                                                                                                                    | 163 |
| 135.4      | Service interface below PMA .....                                                                                                                              | 164 |
| 135.5      | Functions within the PMA .....                                                                                                                                 | 165 |
| 135.5.1    | Per input-lane clock and data recovery .....                                                                                                                   | 166 |
| 135.5.2    | Bit-level multiplexing .....                                                                                                                                   | 167 |
| 135.5.3    | Skew and Skew Variation .....                                                                                                                                  | 167 |
| 135.5.3.1  | Skew generation toward SP0 .....                                                                                                                               | 168 |
| 135.5.3.2  | Skew tolerance at SP0 .....                                                                                                                                    | 168 |
| 135.5.3.3  | Skew generation toward SP1 .....                                                                                                                               | 168 |
| 135.5.3.4  | Skew tolerance at SP1 .....                                                                                                                                    | 169 |
| 135.5.3.5  | Skew generation toward SP2 .....                                                                                                                               | 169 |
| 135.5.3.6  | Skew tolerance at SP5 .....                                                                                                                                    | 169 |
| 135.5.3.7  | Skew generation at SP6 .....                                                                                                                                   | 169 |
| 135.5.3.8  | Skew tolerance at SP6 .....                                                                                                                                    | 169 |
| 135.5.3.9  | Skew generation at SP7 .....                                                                                                                                   | 169 |
| 135.5.3.10 | Skew tolerance at SP7 .....                                                                                                                                    | 169 |
| 135.5.4    | Delay constraints .....                                                                                                                                        | 170 |
| 135.5.5    | Clocking architecture .....                                                                                                                                    | 170 |
| 135.5.6    | Signal drivers .....                                                                                                                                           | 170 |
| 135.5.7    | PAM4 encoding .....                                                                                                                                            | 171 |
| 135.5.7.1  | Gray mapping for PAM4 encoded lanes .....                                                                                                                      | 171 |

|                                                                                                                                                                       |     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 135.5.7.2 Precoding for PAM4 encoded lanes .....                                                                                                                      | 171 |
| 135.5.8 PMA local loopback mode (optional).....                                                                                                                       | 172 |
| 135.5.9 PMA remote loopback mode (optional) .....                                                                                                                     | 173 |
| 135.5.10 PMA test patterns (optional).....                                                                                                                            | 173 |
| 135.5.10.1 Test patterns for NRZ encoded signals.....                                                                                                                 | 173 |
| 135.5.10.1.1 PRBS31 test pattern.....                                                                                                                                 | 173 |
| 135.5.10.1.2 PRBS9 test pattern.....                                                                                                                                  | 173 |
| 135.5.10.1.3 Square-wave test pattern.....                                                                                                                            | 173 |
| 135.5.10.2 Test patterns for PAM4 encoded signals .....                                                                                                               | 174 |
| 135.5.10.2.1 PRBS13Q test pattern.....                                                                                                                                | 174 |
| 135.5.10.2.2 PRBS31Q test pattern.....                                                                                                                                | 174 |
| 135.5.10.2.3 SSPRQ test pattern.....                                                                                                                                  | 174 |
| 135.5.10.2.4 Square wave (quaternary) test pattern .....                                                                                                              | 174 |
| 135.6 PMA MDIO function mapping.....                                                                                                                                  | 174 |
| 135.7 Protocol implementation conformance statement (PICS) proforma for Clause 135, Physical<br>Medium Attachment (PMA) sublayer, type 50GBASE-R and 100GBASE-P ..... | 178 |
| 135.7.1 Introduction.....                                                                                                                                             | 178 |
| 135.7.2 Identification .....                                                                                                                                          | 178 |
| 135.7.2.1 Implementation identification.....                                                                                                                          | 178 |
| 135.7.2.2 Protocol summary .....                                                                                                                                      | 178 |
| 135.7.3 Major capabilities/options.....                                                                                                                               | 179 |
| 135.7.4 PICS proforma tables for Physical Medium Attachment (PMA) sublayer, type<br>50GBASE-R and 100GBASE-P .....                                                    | 180 |
| 135.7.4.1 Functions.....                                                                                                                                              | 180 |
| 135.7.4.2 Timing.....                                                                                                                                                 | 180 |
| 135.7.4.3 Electrical .....                                                                                                                                            | 181 |
| 135.7.4.4 Diagnostics.....                                                                                                                                            | 182 |
| 135.7.7 Encoding .....                                                                                                                                                | 184 |
| 136. Physical Medium Dependent (PMD) sublayer and baseband medium, type 50GBASE-CR,<br>100GBASE-CR2, and 200GBASE-CR4 .....                                           | 185 |
| 136.1 Overview.....                                                                                                                                                   | 185 |
| 136.2 Conventions .....                                                                                                                                               | 187 |
| 136.3 PMD service interfaces.....                                                                                                                                     | 187 |
| 136.4 PCS requirements for Auto-Negotiation (AN) service interface.....                                                                                               | 189 |
| 136.5 Delay constraints.....                                                                                                                                          | 189 |
| 136.6 Skew constraints .....                                                                                                                                          | 190 |
| 136.6.1 Skew Constraints for 50GBASE-CR.....                                                                                                                          | 190 |
| 136.6.2 Skew Constraints for 100GBASE-CR2 and 200GBASE-CR4 .....                                                                                                      | 190 |
| 136.7 PMD MDIO function mapping.....                                                                                                                                  | 190 |
| 136.8 PMD functional specifications.....                                                                                                                              | 194 |
| 136.8.1 Link block diagram .....                                                                                                                                      | 194 |
| 136.8.2 PMD transmit function .....                                                                                                                                   | 195 |
| 136.8.3 PMD receive function.....                                                                                                                                     | 196 |
| 136.8.4 PMD global signal detect function .....                                                                                                                       | 196 |
| 136.8.5 PMD lane-by-lane signal detect function .....                                                                                                                 | 196 |
| 136.8.6 PMD global transmit disable function (optional) .....                                                                                                         | 196 |
| 136.8.7 PMD lane-by-lane transmit disable function (optional) .....                                                                                                   | 197 |
| 136.8.8 PMD fault function .....                                                                                                                                      | 197 |
| 136.8.9 PMD transmit fault function (optional) .....                                                                                                                  | 197 |
| 136.8.10 PMD receive fault function (optional).....                                                                                                                   | 197 |
| 136.8.11 PMD control function .....                                                                                                                                   | 197 |
| 136.8.11.1 Training frame structure .....                                                                                                                             | 197 |

|              |                                                                  |     |
|--------------|------------------------------------------------------------------|-----|
| 136.8.11.1.1 | Frame marker .....                                               | 198 |
| 136.8.11.1.2 | Control and status fields .....                                  | 198 |
| 136.8.11.1.3 | Training pattern .....                                           | 199 |
| 136.8.11.1.4 | Zero pad .....                                                   | 200 |
| 136.8.11.2   | Control field structure .....                                    | 200 |
| 136.8.11.2.1 | Initial condition request .....                                  | 201 |
| 136.8.11.2.2 | Modulation and precoding request .....                           | 201 |
| 136.8.11.2.3 | Coefficient select .....                                         | 201 |
| 136.8.11.2.4 | Coefficient request .....                                        | 201 |
| 136.8.11.3   | Status field structure .....                                     | 202 |
| 136.8.11.3.1 | Receiver ready .....                                             | 202 |
| 136.8.11.3.2 | Modulation and precoding status .....                            | 202 |
| 136.8.11.3.3 | Receiver frame lock .....                                        | 202 |
| 136.8.11.3.4 | Initial condition status .....                                   | 203 |
| 136.8.11.3.5 | Parity bit .....                                                 | 203 |
| 136.8.11.3.6 | Coefficient select echo .....                                    | 203 |
| 136.8.11.3.7 | Coefficient status .....                                         | 203 |
| 136.8.11.4   | Equalization control .....                                       | 203 |
| 136.8.11.4.1 | Initial condition setting request process .....                  | 203 |
| 136.8.11.4.2 | Initial condition setting response process .....                 | 203 |
| 136.8.11.4.3 | Coefficient update request process .....                         | 204 |
| 136.8.11.4.4 | Coefficient update response process .....                        | 204 |
| 136.8.11.5   | Modulation and precoding setting .....                           | 205 |
| 136.8.11.6   | Handshake timing .....                                           | 206 |
| 136.8.11.7   | Variables, functions, timers, counters, and state diagrams ..... | 206 |
| 136.8.11.7.1 | Variables .....                                                  | 206 |
| 136.8.11.7.2 | Functions .....                                                  | 208 |
| 136.8.11.7.3 | Timers .....                                                     | 209 |
| 136.8.11.7.4 | Counters .....                                                   | 209 |
| 136.8.11.7.5 | State diagrams .....                                             | 209 |
| 136.9        | PMD electrical characteristics .....                             | 213 |
| 136.9.1      | AC-coupling .....                                                | 213 |
| 136.9.2      | Signal paths .....                                               | 213 |
| 136.9.3      | Transmitter characteristics .....                                | 213 |
| 136.9.3.1    | Transmitter output waveform .....                                | 214 |
| 136.9.3.1.1  | Linear fit to the measured waveform .....                        | 214 |
| 136.9.3.1.2  | Steady-state voltage and linear fit pulse peak .....             | 216 |
| 136.9.3.1.3  | Coefficient initialization .....                                 | 216 |
| 136.9.3.1.4  | Coefficient step size .....                                      | 216 |
| 136.9.3.1.5  | Coefficient range .....                                          | 217 |
| 136.9.3.2    | Insertion loss, TP0 to TP2 or TP3 to TP5 .....                   | 217 |
| 136.9.3.3    | J3u jitter .....                                                 | 217 |
| 136.9.3.4    | Transmitter effective return loss (ERL) .....                    | 217 |
| 136.9.4      | Receiver characteristics .....                                   | 218 |
| 136.9.4.1    | Receiver input amplitude tolerance .....                         | 218 |
| 136.9.4.2    | Receiver interference tolerance .....                            | 219 |
| 136.9.4.2.1  | Test setup .....                                                 | 219 |
| 136.9.4.2.2  | Test channel .....                                               | 219 |
| 136.9.4.2.3  | Test channel calibration .....                                   | 219 |
| 136.9.4.2.4  | Pattern generator and noise injection .....                      | 220 |
| 136.9.4.2.5  | Test procedure .....                                             | 221 |
| 136.9.4.3    | Receiver jitter tolerance .....                                  | 221 |
| 136.9.4.3.1  | Test setup .....                                                 | 221 |
| 136.9.4.3.2  | Test procedure .....                                             | 221 |

|                                                                                                                                                                                                                |     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 136.9.4.4 Signaling rate range .....                                                                                                                                                                           | 222 |
| 136.9.4.5 Receiver ERL .....                                                                                                                                                                                   | 222 |
| 136.10 Channel characteristics .....                                                                                                                                                                           | 222 |
| 136.11 Cable assembly characteristics .....                                                                                                                                                                    | 222 |
| 136.11.1 Characteristic impedance and reference impedance .....                                                                                                                                                | 223 |
| 136.11.2 Cable assembly insertion loss .....                                                                                                                                                                   | 223 |
| 136.11.3 Cable assembly ERL .....                                                                                                                                                                              | 223 |
| 136.11.4 Differential to common-mode return loss .....                                                                                                                                                         | 224 |
| 136.11.5 Differential to common-mode conversion loss .....                                                                                                                                                     | 224 |
| 136.11.6 Common-mode to common-mode return loss .....                                                                                                                                                          | 224 |
| 136.11.7 Cable assembly Channel Operating Margin .....                                                                                                                                                         | 224 |
| 136.11.7.1 Channel signal and crosstalk path calculations .....                                                                                                                                                | 226 |
| 136.11.7.1.1 Channel signal path .....                                                                                                                                                                         | 226 |
| 136.11.7.1.2 Channel crosstalk paths .....                                                                                                                                                                     | 226 |
| 136.11.7.2 Signal and crosstalk paths used in calculation of COM .....                                                                                                                                         | 227 |
| 136.12 MDI specifications .....                                                                                                                                                                                | 228 |
| 136.13 Environmental specifications .....                                                                                                                                                                      | 228 |
| 136.14 Protocol implementation conformance statement (PICS) proforma for Clause 136,<br>Physical Medium Dependent (PMD) sublayer and baseband medium, type 50GBASE-CR,<br>100GBASE-CR2, and 200GBASE-CR4 ..... | 229 |
| 136.14.1 Introduction .....                                                                                                                                                                                    | 229 |
| 136.14.2 Identification .....                                                                                                                                                                                  | 229 |
| 136.14.2.1 Implementation identification .....                                                                                                                                                                 | 229 |
| 136.14.2.2 Protocol summary .....                                                                                                                                                                              | 229 |
| 136.14.3 Major capabilities/options .....                                                                                                                                                                      | 230 |
| 136.14.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and<br>baseband medium, type 50GBASE-CR, 100GBASE-CR2, and 200GBASE-CR4 .....                                                       | 231 |
| 136.14.4.1 PMD functional specifications .....                                                                                                                                                                 | 231 |
| 136.14.4.2 PMD control function .....                                                                                                                                                                          | 232 |
| 136.14.4.3 Transmitter specifications .....                                                                                                                                                                    | 232 |
| 136.14.4.4 Receiver specifications .....                                                                                                                                                                       | 233 |
| 136.14.4.5 Cable assembly specifications .....                                                                                                                                                                 | 233 |
| 136.14.4.6 Environmental specifications .....                                                                                                                                                                  | 234 |
| 137. Physical Medium Dependent (PMD) sublayer and baseband medium, type 50GBASE-KR,<br>100GBASE-KR2, and 200GBASE-KR4 .....                                                                                    | 235 |
| 137.1 Overview .....                                                                                                                                                                                           | 235 |
| 137.2 Conventions .....                                                                                                                                                                                        | 238 |
| 137.3 PMD service interfaces .....                                                                                                                                                                             | 238 |
| 137.4 PCS requirements for Auto-Negotiation (AN) service interface .....                                                                                                                                       | 238 |
| 137.5 Delay constraints .....                                                                                                                                                                                  | 238 |
| 137.6 Skew constraints .....                                                                                                                                                                                   | 239 |
| 137.6.1 Skew Constraints for 50GBASE-KR .....                                                                                                                                                                  | 239 |
| 137.6.2 Skew Constraints for 100GBASE-KR2 and 200GBASE-KR4 .....                                                                                                                                               | 239 |
| 137.7 PMD MDIO function mapping .....                                                                                                                                                                          | 239 |
| 137.8 PMD functional specifications .....                                                                                                                                                                      | 240 |
| 137.8.1 Link block diagram .....                                                                                                                                                                               | 240 |
| 137.8.2 PMD transmit function .....                                                                                                                                                                            | 240 |
| 137.8.3 PMD receive function .....                                                                                                                                                                             | 240 |
| 137.8.4 PMD global signal detect function .....                                                                                                                                                                | 240 |
| 137.8.5 PMD lane-by-lane signal detect function .....                                                                                                                                                          | 240 |
| 137.8.6 PMD global transmit disable function (optional) .....                                                                                                                                                  | 240 |
| 137.8.7 PMD lane-by-lane transmit disable function (optional) .....                                                                                                                                            | 240 |

|                                                                                                                                                                                                                |     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 137.8.8 PMD fault function .....                                                                                                                                                                               | 241 |
| 137.8.9 PMD transmit fault function (optional) .....                                                                                                                                                           | 241 |
| 137.8.10 PMD receive fault function (optional) .....                                                                                                                                                           | 241 |
| 137.8.11 PMD control function .....                                                                                                                                                                            | 241 |
| 137.9 Electrical characteristics .....                                                                                                                                                                         | 241 |
| 137.9.1 MDI .....                                                                                                                                                                                              | 241 |
| 137.9.2 Transmitter characteristics .....                                                                                                                                                                      | 241 |
| 137.9.2.1 Transmitter ERL .....                                                                                                                                                                                | 241 |
| 137.9.3 Receiver characteristics .....                                                                                                                                                                         | 242 |
| 137.9.3.1 Receiver ERL .....                                                                                                                                                                                   | 242 |
| 137.10 Channel characteristics .....                                                                                                                                                                           | 242 |
| 137.10.1 Channel insertion loss .....                                                                                                                                                                          | 244 |
| 137.10.2 Channel ERL .....                                                                                                                                                                                     | 245 |
| 137.11 Environmental specifications .....                                                                                                                                                                      | 245 |
| 137.12 Protocol implementation conformance statement (PICS) proforma for Clause 137,<br>Physical Medium Dependent (PMD) sublayer and baseband medium, type 50GBASE-KR,<br>100GBASE-KR2, and 200GBASE-KR4 ..... | 246 |
| 137.12.1 Introduction .....                                                                                                                                                                                    | 246 |
| 137.12.2 Identification .....                                                                                                                                                                                  | 246 |
| 137.12.2.1 Implementation identification .....                                                                                                                                                                 | 246 |
| 137.12.2.2 Protocol summary .....                                                                                                                                                                              | 246 |
| 137.12.3 Major capabilities/options .....                                                                                                                                                                      | 247 |
| 137.12.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and<br>baseband medium, type 50GBASE-KR, 100GBASE-KR2, and 200GBASE-KR4 .....                                                       | 248 |
| 137.12.4.1 Functional specifications .....                                                                                                                                                                     | 248 |
| 137.12.4.2 PMD control function .....                                                                                                                                                                          | 249 |
| 137.12.4.3 Transmitter characteristics .....                                                                                                                                                                   | 249 |
| 137.12.4.4 Receiver characteristics .....                                                                                                                                                                      | 250 |
| 137.12.4.5 Channel characteristics .....                                                                                                                                                                       | 250 |
| 137.12.4.6 Environmental specifications .....                                                                                                                                                                  | 250 |
| 138. Physical Medium Dependent (PMD) sublayer and medium, type 50GBASE-SR,<br>100GBASE-SR2, 200GBASE-SR4 .....                                                                                                 | 251 |
| 138.1 Overview .....                                                                                                                                                                                           | 251 |
| 138.1.1 Bit error ratio .....                                                                                                                                                                                  | 253 |
| 138.2 Physical Medium Dependent (PMD) service interface .....                                                                                                                                                  | 254 |
| 138.3 Delay and Skew .....                                                                                                                                                                                     | 255 |
| 138.3.1 Delay constraints .....                                                                                                                                                                                | 255 |
| 138.3.2 Skew constraints .....                                                                                                                                                                                 | 255 |
| 138.3.2.1 Skew Constraints for 50GBASE-SR .....                                                                                                                                                                | 255 |
| 138.3.2.2 Skew Constraints for 100GBASE-SR2 and 200GBASE-SR4 .....                                                                                                                                             | 256 |
| 138.4 PMD MDIO function mapping .....                                                                                                                                                                          | 256 |
| 138.5 PMD functional specifications .....                                                                                                                                                                      | 257 |
| 138.5.1 PMD block diagram .....                                                                                                                                                                                | 257 |
| 138.5.2 PMD transmit function .....                                                                                                                                                                            | 257 |
| 138.5.3 PMD receive function .....                                                                                                                                                                             | 258 |
| 138.5.4 PMD global signal detect function .....                                                                                                                                                                | 258 |
| 138.5.5 PMD lane-by-lane signal detect function .....                                                                                                                                                          | 259 |
| 138.5.6 PMD reset function .....                                                                                                                                                                               | 259 |
| 138.5.7 PMD global transmit disable function (optional) .....                                                                                                                                                  | 259 |
| 138.5.8 PMD lane-by-lane transmit disable function (optional) .....                                                                                                                                            | 259 |
| 138.5.9 PMD fault function (optional) .....                                                                                                                                                                    | 260 |
| 138.5.10 PMD transmit fault function (optional) .....                                                                                                                                                          | 260 |

|                                                                                                                                                                                                  |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 138.5.11 PMD receive fault function (optional).....                                                                                                                                              | 260 |
| 138.6 Lane assignments.....                                                                                                                                                                      | 260 |
| 138.7 PMD to MDI optical specifications for 50GBASE-SR, 100GBASE-SR2, and<br>200GBASE-SR4.....                                                                                                   | 260 |
| 138.7.1 Transmitter optical specifications.....                                                                                                                                                  | 261 |
| 138.7.2 Receiver optical specifications.....                                                                                                                                                     | 261 |
| 138.7.3 Illustrative link power budget.....                                                                                                                                                      | 262 |
| 138.8 Definition of optical parameters and measurement methods.....                                                                                                                              | 263 |
| 138.8.1 Test patterns for optical parameters.....                                                                                                                                                | 263 |
| 138.8.1.1 Multi-lane testing considerations.....                                                                                                                                                 | 264 |
| 138.8.2 Center wavelength and spectral width.....                                                                                                                                                | 264 |
| 138.8.3 Average optical power.....                                                                                                                                                               | 264 |
| 138.8.4 Outer Optical Modulation Amplitude (OMA <sub>outer</sub> ).....                                                                                                                          | 264 |
| 138.8.5 Transmitter and dispersion eye closure for PAM4 (TDECQ).....                                                                                                                             | 264 |
| 138.8.5.1 TDECQ reference equalizer.....                                                                                                                                                         | 265 |
| 138.8.6 Extinction ratio.....                                                                                                                                                                    | 265 |
| 138.8.7 Transmitter transition time.....                                                                                                                                                         | 265 |
| 138.8.8 Relative intensity noise (RIN <sub>12OMA</sub> ).....                                                                                                                                    | 265 |
| 138.8.9 Receiver sensitivity.....                                                                                                                                                                | 266 |
| 138.8.10 Stressed receiver sensitivity.....                                                                                                                                                      | 266 |
| 138.8.10.1 Sinusoidal jitter for receiver conformance test.....                                                                                                                                  | 267 |
| 138.9 Safety, installation, environment, and labeling.....                                                                                                                                       | 267 |
| 138.9.1 General safety.....                                                                                                                                                                      | 267 |
| 138.9.2 Laser safety.....                                                                                                                                                                        | 267 |
| 138.9.3 Installation.....                                                                                                                                                                        | 268 |
| 138.9.4 Environment.....                                                                                                                                                                         | 268 |
| 138.9.5 Electromagnetic emission.....                                                                                                                                                            | 268 |
| 138.9.6 Temperature, humidity, and handling.....                                                                                                                                                 | 268 |
| 138.9.7 PMD labeling requirements.....                                                                                                                                                           | 268 |
| 138.10 Fiber optic cabling model.....                                                                                                                                                            | 268 |
| 138.10.1 Fiber optic cabling model.....                                                                                                                                                          | 269 |
| 138.10.2 Characteristics of the fiber optic cabling (channel).....                                                                                                                               | 270 |
| 138.10.2.1 Optical fiber cable.....                                                                                                                                                              | 270 |
| 138.10.2.2 Optical fiber connection.....                                                                                                                                                         | 270 |
| 138.10.2.2.1 Connection insertion loss.....                                                                                                                                                      | 270 |
| 138.10.2.2.2 Maximum discrete reflectance.....                                                                                                                                                   | 270 |
| 138.10.3 Medium Dependent Interface (MDI).....                                                                                                                                                   | 271 |
| 138.10.3.1 Optical lane assignments for 100GBASE-SR2 and 200GBASE-SR4.....                                                                                                                       | 271 |
| 138.10.3.2 MDI requirements for 50GBASE-SR.....                                                                                                                                                  | 271 |
| 138.10.3.3 MDI requirements for 100GBASE-SR2 and 200GBASE-SR4.....                                                                                                                               | 272 |
| 138.11 Protocol implementation conformance statement (PICS) proforma for Clause 138,<br>Physical Medium Dependent (PMD) sublayer and medium, type 50GBASE-SR,<br>100GBASE-SR2, 200GBASE-SR4..... | 273 |
| 138.11.1 Introduction.....                                                                                                                                                                       | 273 |
| 138.11.2 Identification.....                                                                                                                                                                     | 273 |
| 138.11.2.1 Implementation identification.....                                                                                                                                                    | 273 |
| 138.11.2.2 Protocol summary.....                                                                                                                                                                 | 273 |
| 138.11.3 Major capabilities/options.....                                                                                                                                                         | 274 |
| 138.11.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and<br>medium, type 50GBASE-SR, 100GBASE-SR2, 200GBASE-SR4.....                                                       | 274 |
| 138.11.4.1 PMD functional specifications.....                                                                                                                                                    | 274 |
| 138.11.4.2 Management functions.....                                                                                                                                                             | 275 |
| 138.11.4.3 PMD to MDI optical specifications.....                                                                                                                                                | 276 |
| 138.11.4.4 Optical measurement methods.....                                                                                                                                                      | 276 |

|                                                                                               |     |
|-----------------------------------------------------------------------------------------------|-----|
| 138.11.4.5 Environmental specifications.....                                                  | 277 |
| 138.11.4.6 Characteristics of the fiber optic cabling and MDI.....                            | 277 |
| 139. Physical Medium Dependent (PMD) sublayer and medium, type 50GBASE-FR and 50GBASE-LR..... | 278 |
| 139.1 Overview.....                                                                           | 278 |
| 139.1.1 Bit error ratio .....                                                                 | 279 |
| 139.2 Physical Medium Dependent (PMD) service interface .....                                 | 279 |
| 139.3 Delay and Skew .....                                                                    | 280 |
| 139.3.1 Delay constraints.....                                                                | 280 |
| 139.3.2 Skew constraints .....                                                                | 280 |
| 139.4 PMD MDIO function mapping.....                                                          | 281 |
| 139.5 PMD functional specifications.....                                                      | 281 |
| 139.5.1 PMD block diagram.....                                                                | 281 |
| 139.5.2 PMD transmit function .....                                                           | 282 |
| 139.5.3 PMD receive function.....                                                             | 282 |
| 139.5.4 PMD global signal detect function .....                                               | 282 |
| 139.5.5 PMD reset function.....                                                               | 283 |
| 139.5.6 PMD global transmit disable function (optional) .....                                 | 283 |
| 139.5.7 PMD fault function (optional) .....                                                   | 283 |
| 139.5.8 PMD transmit fault function (optional) .....                                          | 283 |
| 139.5.9 PMD receive fault function (optional).....                                            | 283 |
| 139.6 PMD to MDI optical specifications for 50GBASE-FR and 50GBASE-LR.....                    | 284 |
| 139.6.1 50GBASE-FR and 50GBASE-LR transmitter optical specifications.....                     | 284 |
| 139.6.2 50GBASE-FR and 50GBASE-LR receive optical specifications .....                        | 285 |
| 139.6.3 50GBASE-FR and 50GBASE-LR illustrative link power budgets.....                        | 286 |
| 139.7 Definition of optical parameters and measurement methods.....                           | 286 |
| 139.7.1 Test patterns for optical parameters.....                                             | 286 |
| 139.7.2 Wavelength and side-mode suppression ratio (SMSR) .....                               | 287 |
| 139.7.3 Average optical power .....                                                           | 287 |
| 139.7.4 Outer Optical Modulation Amplitude (OMA <sub>outer</sub> ).....                       | 287 |
| 139.7.5 Transmitter and dispersion eye closure for PAM4 (TDECQ) .....                         | 288 |
| 139.7.5.1 TDECQ conformance test setup .....                                                  | 288 |
| 139.7.5.2 Channel requirements .....                                                          | 289 |
| 139.7.5.3 TDECQ measurement method.....                                                       | 289 |
| 139.7.5.4 TDECQ reference equalizer.....                                                      | 290 |
| 139.7.6 Extinction ratio .....                                                                | 290 |
| 139.7.7 Transmitter transition time.....                                                      | 290 |
| 139.7.8 Relative intensity noise (RIN <sub>17,1</sub> OMA and RIN <sub>15,6</sub> OMA).....   | 290 |
| 139.7.9 Receiver sensitivity.....                                                             | 291 |
| 139.7.10 Stressed receiver sensitivity.....                                                   | 291 |
| 139.7.10.1 Stressed receiver conformance test block diagram.....                              | 292 |
| 139.7.10.2 Stressed receiver conformance test signal characteristics and calibration.....     | 293 |
| 139.7.10.3 Stressed receiver conformance test signal verification.....                        | 293 |
| 139.8 Safety, installation, environment, and labeling.....                                    | 293 |
| 139.8.1 General safety .....                                                                  | 293 |
| 139.8.2 Laser safety .....                                                                    | 293 |
| 139.8.3 Installation .....                                                                    | 294 |
| 139.8.4 Environment.....                                                                      | 294 |
| 139.8.5 Electromagnetic emission .....                                                        | 294 |
| 139.8.6 Temperature, humidity, and handling.....                                              | 294 |
| 139.8.7 PMD labeling requirements .....                                                       | 294 |
| 139.9 Fiber optic cabling model .....                                                         | 295 |

|                                                                                                                                                                                      |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 139.10 Characteristics of the fiber optic cabling (channel) .....                                                                                                                    | 295 |
| 139.10.1 Optical fiber cable .....                                                                                                                                                   | 295 |
| 139.10.2 Optical fiber connection .....                                                                                                                                              | 296 |
| 139.10.2.1 Connection insertion loss .....                                                                                                                                           | 296 |
| 139.10.2.2 Maximum discrete reflectance .....                                                                                                                                        | 296 |
| 139.10.3 Medium Dependent Interface (MDI) requirements .....                                                                                                                         | 297 |
| 139.11 Protocol implementation conformance statement (PICS) proforma for Clause 139,<br>Physical Medium Dependent (PMD) sublayer and medium, type 50GBASE-FR and<br>50GBASE-LR ..... | 298 |
| 139.11.1 Introduction .....                                                                                                                                                          | 298 |
| 139.11.2 Identification .....                                                                                                                                                        | 298 |
| 139.11.2.1 Implementation identification .....                                                                                                                                       | 298 |
| 139.11.2.2 Protocol summary .....                                                                                                                                                    | 298 |
| 139.11.3 Major capabilities/options .....                                                                                                                                            | 299 |
| 139.11.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and<br>medium, type 50GBASE-FR and 50GBASE-LR .....                                                       | 299 |
| 139.11.4.1 PMD functional specifications .....                                                                                                                                       | 299 |
| 139.11.4.2 Management functions .....                                                                                                                                                | 300 |
| 139.11.4.3 PMD to MDI optical specifications for 50GBASE-FR .....                                                                                                                    | 300 |
| 139.11.4.4 PMD to MDI optical specifications for 50GBASE-LR .....                                                                                                                    | 301 |
| 139.11.4.5 Optical measurement methods .....                                                                                                                                         | 301 |
| 139.11.4.6 Environmental specifications .....                                                                                                                                        | 301 |
| 139.11.4.7 Characteristics of the fiber optic cabling and MD .....                                                                                                                   | 302 |
| 140. Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-DR .....                                                                                                     | 303 |
| 140.1 Overview .....                                                                                                                                                                 | 303 |
| 140.1.1 Bit error ratio .....                                                                                                                                                        | 304 |
| 140.2 Physical Medium Dependent (PMD) service interface .....                                                                                                                        | 304 |
| 140.3 Delay and Skew .....                                                                                                                                                           | 305 |
| 140.3.1 Delay constraints .....                                                                                                                                                      | 305 |
| 140.3.2 Skew constraints .....                                                                                                                                                       | 305 |
| 140.4 PMD MDIO function mapping .....                                                                                                                                                | 306 |
| 140.5 PMD functional specifications .....                                                                                                                                            | 306 |
| 140.5.1 PMD block diagram .....                                                                                                                                                      | 306 |
| 140.5.2 PMD transmit function .....                                                                                                                                                  | 307 |
| 140.5.3 PMD receive function .....                                                                                                                                                   | 307 |
| 140.5.4 PMD global signal detect function .....                                                                                                                                      | 307 |
| 140.5.5 PMD reset function .....                                                                                                                                                     | 308 |
| 140.5.6 PMD global transmit disable function (optional) .....                                                                                                                        | 308 |
| 140.5.7 PMD fault function (optional) .....                                                                                                                                          | 308 |
| 140.5.8 PMD transmit fault function (optional) .....                                                                                                                                 | 308 |
| 140.5.9 PMD receive fault function (optional) .....                                                                                                                                  | 308 |
| 140.6 PMD to MDI optical specifications for 100GBASE-DR .....                                                                                                                        | 309 |
| 140.6.1 100GBASE-DR transmitter optical specifications .....                                                                                                                         | 309 |
| 140.6.2 100GBASE-DR receive optical specifications .....                                                                                                                             | 310 |
| 140.6.3 100GBASE-DR illustrative link power budget .....                                                                                                                             | 311 |
| 140.7 Definition of optical parameters and measurement methods .....                                                                                                                 | 311 |
| 140.7.1 Test patterns for optical parameters .....                                                                                                                                   | 311 |
| 140.7.2 Wavelength and side-mode suppression ratio (SMSR) .....                                                                                                                      | 312 |
| 140.7.3 Average optical power .....                                                                                                                                                  | 312 |
| 140.7.4 Outer Optical Modulation Amplitude (OMA <sub>outer</sub> ) .....                                                                                                             | 313 |
| 140.7.5 Transmitter and dispersion eye closure for PAM4 (TDECQ) .....                                                                                                                | 313 |
| 140.7.5.1 TDECQ reference equalizer .....                                                                                                                                            | 313 |

|                                                                                                                                                                     |     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 140.7.6 Extinction ratio .....                                                                                                                                      | 314 |
| 140.7.7 Transmitter transition time.....                                                                                                                            | 314 |
| 140.7.8 Relative intensity noise (RIN15.5OMA) .....                                                                                                                 | 314 |
| 140.7.9 Receiver sensitivity .....                                                                                                                                  | 314 |
| 140.7.10 Stressed receiver sensitivity .....                                                                                                                        | 315 |
| 140.8 Safety, installation, environment, and labeling.....                                                                                                          | 315 |
| 140.8.1 General safety .....                                                                                                                                        | 315 |
| 140.8.2 Laser safety .....                                                                                                                                          | 316 |
| 140.8.3 Installation .....                                                                                                                                          | 316 |
| 140.8.4 Environment.....                                                                                                                                            | 316 |
| 140.8.5 Electromagnetic emission .....                                                                                                                              | 316 |
| 140.8.6 Temperature, humidity, and handling.....                                                                                                                    | 316 |
| 140.8.7 PMD labeling requirements .....                                                                                                                             | 316 |
| 140.9 Fiber optic cabling model .....                                                                                                                               | 317 |
| 140.10 Characteristics of the fiber optic cabling (channel) .....                                                                                                   | 318 |
| 140.10.1 Optical fiber cable.....                                                                                                                                   | 318 |
| 140.10.2 Optical fiber connection.....                                                                                                                              | 319 |
| 140.10.2.1 Connection insertion loss.....                                                                                                                           | 319 |
| 140.10.2.2 Maximum discrete reflectance.....                                                                                                                        | 319 |
| 140.10.3 Medium Dependent Interface (MDI).....                                                                                                                      | 319 |
| 140.11 Protocol implementation conformance statement (PICS) proforma for Clause 140,<br>Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-DR ..... | 320 |
| 140.11.1 Introduction.....                                                                                                                                          | 320 |
| 140.11.2 Identification.....                                                                                                                                        | 320 |
| 140.11.2.1 Implementation identification.....                                                                                                                       | 320 |
| 140.11.2.2 Protocol summary .....                                                                                                                                   | 320 |
| 140.11.3 Major capabilities/options.....                                                                                                                            | 321 |
| 140.11.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and<br>medium, type 100GBASE-DR .....                                                    | 321 |
| 140.11.4.1 PMD functional specifications.....                                                                                                                       | 321 |
| 140.11.4.2 Management functions.....                                                                                                                                | 322 |
| 140.11.4.3 PMD to MDI optical specifications for 100GBASE-DR .....                                                                                                  | 322 |
| 140.11.4.4 Optical measurement methods.....                                                                                                                         | 323 |
| 140.11.4.5 Environmental specifications.....                                                                                                                        | 323 |
| 140.11.4.6 Characteristics of the fiber optic cabling and MD.....                                                                                                   | 323 |
| Annex 4A (normative) Simplified full duplex media access control .....                                                                                              | 324 |
| 4A.4 Specific implementations.....                                                                                                                                  | 324 |
| 4A.4.2 MAC parameters .....                                                                                                                                         | 324 |
| Annex 31B (normative) MAC Control PAUSE operation .....                                                                                                             | 325 |
| 31B.3 Detailed specification of PAUSE operation.....                                                                                                                | 325 |
| 31B.3.7 Timing considerations for PAUSE operation .....                                                                                                             | 325 |
| 31B.4 Protocol implementation conformance statement (PICS) proforma for MAC Control<br>PAUSE operation .....                                                        | 325 |
| 31B.4.3 Major capabilities/options .....                                                                                                                            | 325 |
| 31B.4.6 PAUSE command MAC timing considerations .....                                                                                                               | 325 |
| Annex 93A (normative) Specification methods for electrical channels .....                                                                                           | 326 |
| 93A.1 Channel Operating Margin .....                                                                                                                                | 326 |
| 93A.1.4 Filters .....                                                                                                                                               | 327 |

|                                                                                                                                                                   |     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 93A.1.4.2 Transmitter equalizer .....                                                                                                                             | 327 |
| 93A.1.6 Determination of variable equalizer parameters .....                                                                                                      | 327 |
| 93A.5 Effective Return Loss .....                                                                                                                                 | 328 |
| 93A.5.1 Pulse time-domain reflection signal .....                                                                                                                 | 328 |
| 93A.5.2 Effective reflection waveform .....                                                                                                                       | 329 |
| 93A.5.3 Sampled effective reflection .....                                                                                                                        | 330 |
| 93A.5.4 x-quantile of the reflection distribution .....                                                                                                           | 330 |
| 93A.5.5 ERL .....                                                                                                                                                 | 330 |
| Annex 135A (informative) 50 Gb/s and 100 Gb/s PMA sublayer partitioning examples .....                                                                            | 331 |
| 135A.1 Partitioning examples of 50GBASE-R PHYs .....                                                                                                              | 331 |
| 135A.2 Partitioning examples of 100GBASE-P PHYs .....                                                                                                             | 336 |
| Annex 135B (normative) Chip-to-Chip 50 Gb/s two-lane Attachment Unit Interface (LAUI-2 C2C) .....                                                                 | 337 |
| 135B.1 Overview .....                                                                                                                                             | 337 |
| 135B.2 LAUI-2 C2C compliance point definition .....                                                                                                               | 338 |
| 135B.3 LAUI-2 C2C electrical characteristics .....                                                                                                                | 338 |
| 135B.3.1 LAUI-2 C2C transmitter characteristics .....                                                                                                             | 338 |
| 135B.3.2 LAUI-2 C2C receiver characteristics .....                                                                                                                | 339 |
| 135B.4 LAUI-2 C2C channel characteristics .....                                                                                                                   | 339 |
| 135B.5 Protocol implementation conformance statement (PICS) proforma for Annex 135B, Chip-to-Chip 50 Gb/s two-lane Attachment Unit Interface (LAUI-2 C2C) .....   | 340 |
| 135B.5.1 Introduction .....                                                                                                                                       | 340 |
| 135B.5.2 Identification .....                                                                                                                                     | 340 |
| 135B.5.2.1 Implementation identification .....                                                                                                                    | 340 |
| 135B.5.2.2 Protocol summary .....                                                                                                                                 | 340 |
| 135B.5.3 Major capabilities/options .....                                                                                                                         | 341 |
| 135B.5.4 PICS proforma tables for chip-to-chip 50 Gb/s two-lane Attachment Unit Interface (LAUI-2 C2C) .....                                                      | 341 |
| 135B.5.4.1 Transmitter .....                                                                                                                                      | 341 |
| 135B.5.4.2 Receiver .....                                                                                                                                         | 342 |
| 135B.5.4.3 Channel .....                                                                                                                                          | 342 |
| Annex 135C (normative) Chip-to-module 50 Gb/s two-lane Attachment Unit Interface (LAUI-2 C2M) .....                                                               | 343 |
| 135C.1 Overview .....                                                                                                                                             | 343 |
| 135C.1.1 Bit error ratio .....                                                                                                                                    | 344 |
| 135C.2 LAUI-2 C2M compliance point definitions .....                                                                                                              | 344 |
| 135C.3 LAUI-2 C2M electrical characteristics .....                                                                                                                | 344 |
| 135C.3.1 LAUI-2 C2M host output characteristics .....                                                                                                             | 344 |
| 135C.3.2 LAUI-2 C2M module output characteristics .....                                                                                                           | 344 |
| 135C.3.3 LAUI-2 C2M host input characteristics .....                                                                                                              | 345 |
| 135C.3.4 LAUI-2 C2M module input characteristics .....                                                                                                            | 345 |
| 135C.4 LAUI-2 C2M measurement methodology .....                                                                                                                   | 345 |
| 135C.5 Protocol implementation conformance statement (PICS) proforma for Annex 135C, Chip-to-module 50 Gb/s two-lane Attachment Unit Interface (LAUI-2 C2M) ..... | 346 |
| 135C.5.1 Introduction .....                                                                                                                                       | 346 |
| 135C.5.2 Identification .....                                                                                                                                     | 346 |
| 135C.5.2.1 Implementation identification .....                                                                                                                    | 346 |
| 135C.5.2.2 Protocol summary .....                                                                                                                                 | 346 |
| 135C.5.3 Major capabilities/options .....                                                                                                                         | 347 |

|                                                                                                                                                                                                                                      |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 135C.5.4 PICS proforma tables for chip-to-module 50 Gb/s two-lane Attachment Unit Interface (LAUI-2 C2M) .....                                                                                                                       | 347 |
| 135C.5.4.1 Host output .....                                                                                                                                                                                                         | 347 |
| 135C.5.4.2 Module output .....                                                                                                                                                                                                       | 348 |
| 135C.5.4.3 Host input .....                                                                                                                                                                                                          | 348 |
| 135C.5.4.4 Module input .....                                                                                                                                                                                                        | 348 |
| Annex 135D (normative) Chip-to-chip 50 Gb/s two-lane Attachment Unit Interface (50GAUI-2 C2C) and 100 Gb/s four-lane Attachment Unit Interface (100GAUI-4 C2C) .....                                                                 | 349 |
| 135D.1 Overview .....                                                                                                                                                                                                                | 349 |
| 135D.2 50GAUI-2 C2C and 100GAUI-4 C2C compliance point definition .....                                                                                                                                                              | 351 |
| 135D.3 50GAUI-2 C2C and 100GAUI-4 C2C electrical characteristics .....                                                                                                                                                               | 351 |
| 135D.3.1 50GAUI-2 C2C and 100GAUI-4 C2C transmitter characteristics .....                                                                                                                                                            | 351 |
| 135D.3.2 50GAUI-2 C2C and 100GAUI-4 C2C receiver characteristics .....                                                                                                                                                               | 351 |
| 135D.4 50GAUI-2 C2C and 100GAUI-4 C2C channel characteristics .....                                                                                                                                                                  | 351 |
| 135D.5 Protocol implementation conformance statement (PICS) proforma for Annex 135D, Chip-to-chip 50 Gb/s two-lane Attachment Unit Interface (50GAUI-2 C2C) and 100 Gb/s four-lane Attachment Unit Interface (100GAUI-4 C2C) .....   | 352 |
| 135D.5.1 Introduction .....                                                                                                                                                                                                          | 352 |
| 135D.5.2 Identification .....                                                                                                                                                                                                        | 352 |
| 135D.5.2.1 Implementation identification .....                                                                                                                                                                                       | 352 |
| 135D.5.2.2 Protocol summary .....                                                                                                                                                                                                    | 352 |
| 135D.5.3 Major capabilities/options .....                                                                                                                                                                                            | 353 |
| 135D.5.4 PICS proforma tables for chip-to-chip 50 Gb/s two-lane Attachment Unit Interface (50GAUI-2 C2C) and 100 Gb/s four-lane Attachment Unit Interface (100GAUI-4 C2C) .....                                                      | 353 |
| 135D.5.4.1 Transmitter .....                                                                                                                                                                                                         | 353 |
| 135D.5.4.2 Receiver .....                                                                                                                                                                                                            | 354 |
| 135D.5.4.3 Channel .....                                                                                                                                                                                                             | 354 |
| Annex 135E (normative) Chip-to-module 50 Gb/s two-lane Attachment Unit Interface (50GAUI-2 C2M) and 100 Gb/s four-lane Attachment Unit Interface (100GAUI-4 C2M) .....                                                               | 355 |
| 135E.1 Overview .....                                                                                                                                                                                                                | 355 |
| 135E.1.1 Bit error ratio .....                                                                                                                                                                                                       | 357 |
| 135E.2 50GAUI-2 C2M and 100GAUI-4 C2M compliance point definitions .....                                                                                                                                                             | 357 |
| 135E.3 50GAUI-2 C2M and 100GAUI-4 C2M electrical characteristics .....                                                                                                                                                               | 357 |
| 135E.3.1 50GAUI-2 C2M and 100GAUI-4 C2M host output characteristics .....                                                                                                                                                            | 357 |
| 135E.3.2 50GAUI-2 C2M and 100GAUI-4 C2M module output characteristics .....                                                                                                                                                          | 357 |
| 135E.3.3 50GAUI-2 C2M and 100GAUI-4 C2M host input characteristics .....                                                                                                                                                             | 357 |
| 135E.3.4 50GAUI-2 C2M and 100GAUI-4 C2M module input characteristics .....                                                                                                                                                           | 357 |
| 135E.4 50GAUI-2 C2M and 100GAUI-4 C2M measurement methodology .....                                                                                                                                                                  | 357 |
| 135E.5 Protocol implementation conformance statement (PICS) proforma for Annex 135E, Chip-to-module 50 Gb/s two-lane Attachment Unit Interface (50GAUI-2 C2M) and 100 Gb/s four-lane Attachment Unit Interface (100GAUI-4 C2M) ..... | 358 |
| 135E.5.1 Introduction .....                                                                                                                                                                                                          | 358 |
| 135E.5.2 Identification .....                                                                                                                                                                                                        | 358 |
| 135E.5.2.1 Implementation identification .....                                                                                                                                                                                       | 358 |
| 135E.5.2.2 Protocol summary .....                                                                                                                                                                                                    | 358 |
| 135E.5.3 Major capabilities/options .....                                                                                                                                                                                            | 359 |
| 135E.5.4 PICS proforma tables for chip-to-module 50 Gb/s two-lane Attachment Unit Interface (50GAUI-2 C2M) and 100 Gb/s four-lane Attachment Unit Interface (100GAUI-4 C2M) .....                                                    | 359 |

|                                                                                                                                                                                                                                            |         |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| 135E.5.4.1 Host output .....                                                                                                                                                                                                               | 359     |
| 135E.5.4.2 Module output .....                                                                                                                                                                                                             | 360     |
| 135E.5.4.3 Host input .....                                                                                                                                                                                                                | 361     |
| 135E.5.4.4 Module input .....                                                                                                                                                                                                              | 361     |
| <br>Annex 135F (normative) Chip-to-chip 50 Gb/s one-lane Attachment Unit Interface (50GAUI-1 C2C)<br>and 100 Gb/s two-lane Attachment Unit Interface (100GAUI-2 C2C) .....                                                                 | <br>362 |
| 135F.1 Overview .....                                                                                                                                                                                                                      | 362     |
| 135F.2 50GAUI-1 C2C and 100GAUI-2 C2C compliance point definition .....                                                                                                                                                                    | 364     |
| 135F.3 50GAUI-1 C2C and 100GAUI-2 C2C electrical characteristics .....                                                                                                                                                                     | 364     |
| 135F.3.1 50GAUI-1 C2C and 100GAUI-2 C2C transmitter characteristics .....                                                                                                                                                                  | 364     |
| 135F.3.2 50GAUI-1 C2C and 100GAUI-2 C2C receiver characteristics .....                                                                                                                                                                     | 364     |
| 135F.3.2.1 Transmitter precoder request (optional) .....                                                                                                                                                                                   | 364     |
| 135F.4 50GAUI-1 C2C and 100GAUI-2 C2C channel characteristics .....                                                                                                                                                                        | 365     |
| 135F.5 Example usage of the optional transmitter precoder request .....                                                                                                                                                                    | 365     |
| 135F.5.1 Overview .....                                                                                                                                                                                                                    | 365     |
| 135F.5.2 Configuring precoder setting in the transmit direction .....                                                                                                                                                                      | 365     |
| 135F.5.3 Configuring precoder setting in the receive direction .....                                                                                                                                                                       | 366     |
| 135F.6 Protocol implementation conformance statement (PICS) proforma for Annex 135F, Chip-<br>to-chip 50 Gb/s one-lane Attachment Unit Interface (50GAUI-1 C2C) and 100 Gb/s<br>two-lane Attachment Unit Interface (100GAUI-2 C2C) .....   | <br>367 |
| 135F.6.1 Introduction .....                                                                                                                                                                                                                | 367     |
| 135F.6.2 Identification .....                                                                                                                                                                                                              | 367     |
| 135F.6.2.1 Implementation identification .....                                                                                                                                                                                             | 367     |
| 135F.6.2.2 Protocol summary .....                                                                                                                                                                                                          | 367     |
| 135F.6.3 Major capabilities/options .....                                                                                                                                                                                                  | 368     |
| 135F.6.4 PICS proforma tables for chip-to-chip 50 Gb/s one-lane Attachment Unit Interface<br>(50GAUI-1 C2C) and 100 Gb/s two-lane Attachment Unit Interface<br>(100GAUI-2 C2C) .....                                                       | <br>368 |
| 135F.6.4.1 Transmitter .....                                                                                                                                                                                                               | 368     |
| 135F.6.4.2 Receiver .....                                                                                                                                                                                                                  | 369     |
| 135F.6.4.3 Channel .....                                                                                                                                                                                                                   | 369     |
| <br>Annex 135G (normative) Chip-to-module 50 Gb/s one-lane Attachment Unit Interface<br>(50GAUI-1 C2M) and 100 Gb/s two-lane Attachment Unit Interface (100GAUI-2 C2M) .....                                                               | <br>370 |
| 135G.1 Overview .....                                                                                                                                                                                                                      | 370     |
| 135G.1.1 Bit error ratio .....                                                                                                                                                                                                             | 372     |
| 135G.2 50GAUI-1 C2M and 100GAUI-2 C2M compliance point definitions .....                                                                                                                                                                   | 372     |
| 135G.3 50GAUI-1 C2M and 100GAUI-2 C2M electrical characteristics .....                                                                                                                                                                     | 372     |
| 135G.3.1 50GAUI-1 C2M and 100GAUI-2 C2M host output characteristics .....                                                                                                                                                                  | 372     |
| 135G.3.2 50GAUI-1 C2M and 100GAUI-2 C2M module output characteristics .....                                                                                                                                                                | 372     |
| 135G.3.3 50GAUI-1 C2M and 100GAUI-2 C2M host input characteristics .....                                                                                                                                                                   | 372     |
| 135G.3.4 50GAUI-1 C2M and 100GAUI-2 C2M module input characteristics .....                                                                                                                                                                 | 372     |
| 135G.4 50GAUI-1 C2M and 100GAUI-2 C2M measurement methodology .....                                                                                                                                                                        | 372     |
| 135G.5 Protocol implementation conformance statement (PICS) proforma for Annex 135G, Chip-<br>to-module 50 Gb/s one-lane Attachment Unit Interface (50GAUI-1 C2M) and 100 Gb/s<br>two-lane Attachment Unit Interface (100GAUI-2 C2M) ..... | <br>373 |
| 135G.5.1 Introduction .....                                                                                                                                                                                                                | 373     |
| 135G.5.2 Identification .....                                                                                                                                                                                                              | 373     |
| 135G.5.2.1 Implementation identification .....                                                                                                                                                                                             | 373     |
| 135G.5.2.2 Protocol summary .....                                                                                                                                                                                                          | 373     |
| 135G.5.3 Major capabilities/options .....                                                                                                                                                                                                  | 374     |

|                                                                                                                                                                                      |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 135G.5.4 PICS proforma tables for chip-to-module 50 Gb/s one-lane Attachment Unit Interface (50GAUI-1 C2M) and 100 Gb/s two-lane Attachment Unit Interface (100GAUI-2 C2M) .....     | 374 |
| 135G.5.4.1 Host output.....                                                                                                                                                          | 374 |
| 135G.5.4.2 Module output.....                                                                                                                                                        | 375 |
| 135G.5.4.3 Host input.....                                                                                                                                                           | 376 |
| 135G.5.4.4 Module input.....                                                                                                                                                         | 376 |
| Annex 136A (informative) TP0 and TP5 test point parameters and channel characteristics for 50GBASE-CR, 100GBASE-CR2, and 200GBASE-CR4 .....                                          | 377 |
| 136A.1 Overview .....                                                                                                                                                                | 377 |
| 136A.2 Transmitter characteristics at TP0 .....                                                                                                                                      | 377 |
| 136A.3 Receiver characteristics at TP5 .....                                                                                                                                         | 377 |
| 136A.4 Transmitter and receiver differential printed circuit board trace loss.....                                                                                                   | 377 |
| 136A.5 Channel insertion loss .....                                                                                                                                                  | 377 |
| 136A.6 Channel effective return loss .....                                                                                                                                           | 379 |
| 136A.7 Channel Operating Margin (COM).....                                                                                                                                           | 379 |
| Annex 136B (normative) Test fixtures for 50GBASE-CR, 100GBASE-CR2, 200GBASE-CR4, 50GAUI-1 C2M, and 100GAUI-2 C2M.....                                                                | 380 |
| 136B.1 Test fixtures.....                                                                                                                                                            | 380 |
| 136B.1.1 Mated test fixtures.....                                                                                                                                                    | 380 |
| 136B.1.1.1 Mated test fixtures differential insertion loss.....                                                                                                                      | 380 |
| 136B.1.1.2 Mated test fixtures differential return loss .....                                                                                                                        | 381 |
| 136B.1.1.3 Mated test fixtures common-mode conversion insertion loss.....                                                                                                            | 381 |
| 136B.1.1.4 Mated test fixtures common-mode return loss.....                                                                                                                          | 381 |
| 136B.1.1.5 Mated test fixtures common-mode to differential mode return loss .....                                                                                                    | 381 |
| 136B.1.1.6 Mated test fixtures integrated crosstalk noise .....                                                                                                                      | 381 |
| 136B.2 Protocol implementation conformance statement (PICS) proforma for Annex 136B, Test fixtures for 50GBASE-CR, 100GBASE-CR2, 200GBASE-CR4, 50GAUI-1 C2M, and 100GAUI-2 C2M ..... | 383 |
| 136B.2.1 Introduction .....                                                                                                                                                          | 383 |
| 136B.2.2 Identification .....                                                                                                                                                        | 383 |
| 136B.2.2.1 Implementation identification .....                                                                                                                                       | 383 |
| 136B.2.2.2 Protocol summary .....                                                                                                                                                    | 383 |
| 136B.2.3 Major capabilities/options .....                                                                                                                                            | 384 |
| 136B.2.4 PICS proforma tables for test fixtures for 50GBASE-CR, 100GBASE-CR2, 200GBASE-CR4, 50GAUI-1 C2M, and 100GAUI-2 C2M.....                                                     | 384 |
| Annex 136C (normative) MDIs for 50GBASE-CR, 100GBASE-CR2, and 200GBASE-CR4 .....                                                                                                     | 385 |
| 136C.1 Overview .....                                                                                                                                                                | 385 |
| 136C.2 MDI connector types.....                                                                                                                                                      | 388 |
| 136C.2.1 SFP28 .....                                                                                                                                                                 | 388 |
| 136C.2.2 QSFP28 .....                                                                                                                                                                | 389 |
| 136C.2.3 MicroQSFP .....                                                                                                                                                             | 389 |
| 136C.2.4 QSFP-DD .....                                                                                                                                                               | 390 |
| 136C.2.5 OSFP .....                                                                                                                                                                  | 391 |
| 136C.3 Protocol implementation conformance statement (PICS) proforma for Annex 136C, MDIs for 50GBASE-CR, 100GBASE-CR2, and 200GBASE-CR4.....                                        | 392 |
| 136C.3.1 Introduction .....                                                                                                                                                          | 392 |
| 136C.3.2 Identification .....                                                                                                                                                        | 392 |

|                                                                                                                       |     |
|-----------------------------------------------------------------------------------------------------------------------|-----|
| 136C.3.2.1 Implementation identification .....                                                                        | 392 |
| 136C.3.2.2 Protocol summary .....                                                                                     | 392 |
| 136C.3.3 Major capabilities/options .....                                                                             | 393 |
| 136C.3.4 PICS proforma tables for MDIs for 50GBASE-CR, 100GBASE-CR2, and<br>200GBASE-CR4 .....                        | 393 |
| 136C.3.4.1 Contact Mapping .....                                                                                      | 393 |
| Annex 136D (informative) Host and cable assembly form factors for 50GBASE-CR,<br>100GBASE-CR2, and 200GBASE-CR4 ..... | 394 |
| 136D.1 Overview .....                                                                                                 | 394 |
| 136D.2 Host form factors .....                                                                                        | 394 |
| 136D.2.1 SFP28 host form factor .....                                                                                 | 394 |
| 136D.2.2 QSFP28 host form factor .....                                                                                | 394 |
| 136D.2.3 microQSFP host form factor .....                                                                             | 395 |
| 136D.2.4 QSFP-DD host form factor .....                                                                               | 395 |
| 136D.2.5 OSFP host form factor .....                                                                                  | 395 |
| 136D.3 Cable assembly form factors .....                                                                              | 396 |
| 136D.3.1 One-plug to one-plug cable assembly form factor .....                                                        | 396 |
| 136D.3.2 One-plug to two-plug cable assembly form factor .....                                                        | 397 |
| 136D.3.3 One-plug to four-plug cable assembly form factor .....                                                       | 398 |
| 136D.3.4 One-plug to eight-plug cable assembly form factor .....                                                      | 399 |

# IEEE Standard for Ethernet

## Amendment 3: Media Access Control Parameters for 50 Gb/s and Physical Layers and Management Parameters for 50 Gb/s, 100 Gb/s, and 200 Gb/s Operation

(This amendment is based on IEEE Std 802.3™-2018 as amended by IEEE Std 802.3cb™-2018 and IEEE Std 802.3bt™-2018.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.

Cross references that refer to clauses, tables, equations, or figures not covered by this amendment are highlighted in green.<sup>1</sup>

<sup>1</sup>Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

## 1. Introduction

### 1.1 Overview

#### 1.1.3 Architectural perspectives

##### 1.1.3.2 Compatibility interfaces

*Insert the following new compatibility interfaces into 1.1.3.2 after m) “40 Gb/s Parallel Physical Interface (XLPPi)”:*

- m1) *50 Gb/s Media Independent Interface (50GMII).* The 50GMII is designed to connect a 50 Gb/s capable MAC to a 50 Gb/s PHY. While conformance with implementation of this interface is not necessary to ensure communication, it allows flexibility in intermixing PHYs and DTEs at 50 Gb/s speeds. The 50GMII is a logical interconnection intended for use as an intra-chip interface. No mechanical connector is specified for use with the 50GMII. The 50GMII is optional.
- m2) *50 Gb/s Attachment Unit Interface (LAUI-2/50GAUI-n).* The LAUI-2/50GAUI-n is a physical instantiation of the PMA service interface to extend the connection between 50 Gb/s capable PMAs. While conformance with implementation of this interface is not necessary to ensure communication, it is recommended, since it allows maximum flexibility in intermixing PHYs and DTEs at 50 Gb/s speeds. The LAUI-2/50GAUI-n is intended for use as a chip-to-chip or a chip-to-module interface. Two widths of 50GAUI-n are defined: a two-lane version (50GAUI-2) in Annex 135D and Annex 135E, and a one-lane version (50GAUI-1) in Annex 135F and Annex 135G. No mechanical connector is specified for use with the LAUI-2/50GAUI-n. The LAUI-2/50GAUI-n is optional.

*Change the compatibility interface o) “100 Gb/s Attachment Unit Interface (CAUI-n)” in 1.1.3.2 as follows:*

- o) *100 Gb/s Attachment Unit Interface (CAUI-n/100GAUI-n).* The CAUI-n/100GAUI-n is a physical instantiation of the PMA service interface to extend the connection between 100 Gb/s capable PMAs. While conformance with implementation of this interface is not necessary to ensure communication, it is recommended, since it allows maximum flexibility in intermixing PHYs and DTEs at 100 Gb/s speeds. The CAUI-n is intended for use as a chip-to-chip or a chip-to-module interface. Three ~~Two~~ widths of CAUI-n are defined: a ten-lane version (CAUI-10) in Annex 83A and Annex 83B, ~~and~~ a four-lane version (CAUI-4/100GAUI-4) in Annex 83D, and Annex 83E, Annex 135D, and Annex 135E, ~~and~~ a two-lane version (100GAUI-2) in Annex 135F and Annex 135G. No mechanical connector is specified for use with the CAUI-n/100GAUI-n. The CAUI-n/100GAUI-n is optional.

### 1.3 Normative references

*Change the following reference in 1.3 as shown:*

IEC 61753-022-2:2012, Fibre optic interconnecting devices and passive components—Performance standard—Part 022-2: Fibre optic connectors terminated on multimode fibre for category C—Controlled environment, performance Class M.

## 1.4 Definitions

*Insert the following new definition after 1.4.25 “100GBASE-CR10”:*

**1.4.25a 100GBASE-CR2:** IEEE 802.3 Physical Layer specification for 100 Gb/s using 100GBASE-R encoding over two lanes of shielded balanced copper cabling. (See IEEE Std 802.3, Clause 136.)

*Insert the following new definition after 1.4.26 “100GBASE-CR4”:*

**1.4.26a 100GBASE-DR:** IEEE 802.3 Physical Layer specification for 100 Gb/s serial transmission using 100GBASE-R encoding and 4-level pulse amplitude modulation over one wavelength on single-mode fiber, with reach up to at least 500 m. (See IEEE Std 802.3, Clause 140.)

*Insert the following new definition after 1.4.28 “100GBASE-KP4”:*

**1.4.28a 100GBASE-KR2:** IEEE 802.3 Physical Layer specification for 100 Gb/s using 100GBASE-R encoding over two lanes of an electrical backplane. (See IEEE Std 802.3, Clause 137.)

*Insert the following new definition after 1.4.34 “100GBASE-SR10”:*

**1.4.34a 100GBASE-SR2:** IEEE 802.3 Physical Layer specification for 100 Gb/s using 100GBASE-R encoding over two lanes of multimode fiber. (See IEEE Std 802.3, Clause 138.)

*Change 1.4.36 as follows:*

**1.4.36 100 Gb/s Attachment Unit Interface (CAUI-n, 100GAUI-n):** A physical instantiation of the PMA service interface to extend the connection between 100 Gb/s capable PMAs over n lanes, used for chip-to-chip or chip-to-module interconnections. ThreeTwo widths of CAUI-n are defined: a ten-lane version (CAUI-10), and a two four-lane versions (CAUI-4, 100GAUI-4), and a two-lane version (100GAUI-2). (See IEEE Std 802.3, Annex 83A and Annex 83B for CAUI-10, or Annex 83D and Annex 83E for CAUI-4, Clause 135, Annex 135D, and Annex 135E for 100GAUI-4, or Clause 135, Annex 135F, and Annex 135G for 100GAUI-2.)

*Insert the following new definition after 1.4.82c “2.5GSEI” as inserted by IEEE Std 802.3cb-2018:*

**1.4.82d 200GBASE-CR4:** IEEE 802.3 Physical Layer specification for 200 Gb/s using 200GBASE-R encoding over four lanes of shielded balanced copper cabling. (See IEEE Std 802.3, Clause 136)

*Insert the following new definition after 1.4.84 “200GBASE-FR4”:*

**1.4.84a 200GBASE-KR4:** IEEE 802.3 Physical Layer specification for 200 Gb/s using 200GBASE-R encoding over four lanes of an electrical backplane. (See IEEE Std 802.3, Clause 137.)

*Insert the following new definition after 1.4.86 “200GBASE-R”:*

**1.4.86a 200GBASE-SR4:** IEEE 802.3 Physical Layer specification for 200 Gb/s using 200GBASE-R encoding over four lanes of multimode fiber. (See IEEE Std 802.3, Clause 138.)

*Insert the following new definitions before 1.4.128a “5GBASE-KR” as inserted by IEEE Std 802.3cb-2018:*

**1.4.128aa 50GBASE-CR:** IEEE 802.3 Physical Layer specification for 50 Gb/s using 50GBASE-R encoding over one lane of shielded balanced copper cabling. (See IEEE Std 802.3, Clause 136.)

**1.4.128ab 50GBASE-FR:** IEEE 802.3 Physical Layer specification for 50 Gb/s serial transmission using 50GBASE-R encoding and 4-level pulse amplitude modulation over one wavelength on single-mode fiber, with reach up to at least 2 km. (See IEEE Std 802.3, Clause 139.)

**1.4.128ac 50GBASE-KR:** IEEE 802.3 Physical Layer specification for 50 Gb/s using 50GBASE-R encoding over one lane of an electrical backplane. (See IEEE Std 802.3, Clause 137.)

**1.4.128ad 50GBASE-LR:** IEEE 802.3 Physical Layer specification for 50 Gb/s serial transmission using 50GBASE-R encoding and 4-level pulse amplitude modulation over one wavelength on single-mode fiber, with reach up to at least 10 km. (See IEEE Std 802.3, Clause 139.)

**1.4.128ae 50GBASE-R:** An IEEE 802.3 physical coding sublayer for one-lane 50 Gb/s operation. (See IEEE Std 802.3, Clause 131.)

**1.4.128af 50GBASE-SR:** IEEE 802.3 Physical Layer specification for 50 Gb/s using 50GBASE-R encoding over multimode fiber. (See IEEE Std 802.3, Clause 138.)

**1.4.128ag 50 Gb/s Attachment Unit Interface (50GAUI-n, LAUI-2):** A physical instantiation of the PMA service interface to extend the connection between 50 Gb/s capable PMAs over one lane (50GAUI-1) or two lanes (50GAUI-2, LAUI-2), used for chip-to-chip or chip-to-module interconnections. (See IEEE Std 802.3, Clause 135 and Annex 135B through Annex 135G.)

**1.4.128ah 50 Gb/s Media Independent Interface (50GMII):** The interface between the Reconciliation Sublayer (RS) and the Physical Coding Sublayer (PCS) for 50 Gb/s operation. (See IEEE Std 802.3, Clause 132.)

*Insert the following new definition after 1.4.255 “fast wake”:*

**1.4.255a FEC lane (FECL):** In 50GBASE-R and 100GBASE-R, the FEC distributes encoded data to multiple logical lanes; these logical lanes are called FEC lanes. One or more FEC lanes can be multiplexed and carried on a physical lane together at the PMA service interface. (See IEEE Std 802.3, Clause 135.)

*Change 1.4.386 as follows:*

**1.4.386 PCS lane (PCSL):** In 40GBASE-R, 50GBASE-R, 100GBASE-R, 200GBASE-R, and 400GBASE-R, the PCS distributes encoded data to multiple logical lanes; these logical lanes are called PCS lanes. One or more PCS lanes can be multiplexed and carried on a physical lane together at the PMA service interface. (See IEEE Std 802.3, Clause 83, and ~~Clause 120, and Clause 135.~~)

## 1.5 Abbreviations

*Insert the following new abbreviations into 1.5 in alphanumeric order:*

|         |                                     |
|---------|-------------------------------------|
| 100GAUI | 100 Gb/s Attachment Unit Interface  |
| 50GAUI  | 50 Gb/s Attachment Unit Interface   |
| 50GMII  | 50 Gb/s Media Independent Interface |
| ERL     | effective return loss               |
| FECL    | FEC Lane                            |
| LAUI    | 50 Gb/s Attachment Unit Interface   |

## 4. Media Access Control

### 4.4 Specific implementations

#### 4.4.2 MAC parameters

*Change Table 4–2 as follows:*

**Table 4–2—MAC parameters**

| Parameters                  | MAC data rate                |                      |                                                                                       |                      |
|-----------------------------|------------------------------|----------------------|---------------------------------------------------------------------------------------|----------------------|
|                             | Up to and including 100 Mb/s | 1 Gb/s               | 2.5 Gb/s, 5 Gb/s, 25 Gb/s, 40 Gb/s, <u>50 Gb/s</u> , 100 Gb/s, 200 Gb/s, and 400 Gb/s | 10 Gb/s              |
| slotTime                    | 512 bit times                | 4096 bit times       | not applicable                                                                        | not applicable       |
| interPacketGap <sup>a</sup> | 96 bits                      | 96 bits              | 96 bits                                                                               | 96 bits              |
| attemptLimit                | 16                           | 16                   | not applicable                                                                        | not applicable       |
| backoffLimit                | 10                           | 10                   | not applicable                                                                        | not applicable       |
| jamSize                     | 32 bits                      | 32 bits              | not applicable                                                                        | not applicable       |
| maxBasicFrameSize           | 1518 octets                  | 1518 octets          | 1518 octets                                                                           | 1518 octets          |
| maxEnvelopeFrameSize        | 2000 octets                  | 2000 octets          | 2000 octets                                                                           | 2000 octets          |
| minFrameSize                | 512 bits (64 octets)         | 512 bits (64 octets) | 512 bits (64 octets)                                                                  | 512 bits (64 octets) |
| burstLimit                  | not applicable               | 65 536 bits          | not applicable                                                                        | not applicable       |
| ipgStretchRatio             | not applicable               | not applicable       | not applicable                                                                        | 104 bits             |

<sup>a</sup>References to interFrameGap or interFrameSpacing in other clauses (e.g., 13, 35, and 42) shall be interpreted as interPacketGap.

*Change Note 7 in 4.4.2 as follows:*

NOTE 7—For 40 Gb/s, 50 Gb/s, 100 Gb/s, 200 Gb/s, and 400 Gb/s operation, the received interpacket gap (the spacing between two packets, from the last bit of the FCS field of the first packet to the first bit of the Preamble of the second packet) can have a minimum value of 8 BT (bit times), as measured at the XLGMII, 50GMII, CGMII, 200GMII, or 400GMII receive signals at the DTE due to clock tolerance and lane alignment requirements.

## 30. Management

### 30.3 Layer management for DTEs

#### 30.3.2 PHY device managed object class

##### 30.3.2.1 PHY device attributes

##### 30.3.2.1.2 aPhyType

*Insert the following new entry into “APPROPRIATE SYNTAX” in 30.3.2.1.2 after the entry for 40GBASE-T:*

APPROPRIATE SYNTAX:  
 50GBASE-R                      Clause 133 50 Gb/s multi-PCS lane 64B/66B

##### 30.3.2.1.3 aPhyTypeList

*Insert the following new entry into “APPROPRIATE SYNTAX” in 30.3.2.1.3 after the entry for 40GBASE-T:*

APPROPRIATE SYNTAX:  
 50GBASE-R                      Clause 133 50 Gb/s multi-PCS lane 64B/66B

##### 30.3.2.1.5 aSymbolErrorDuringCarrier

*Change the fourth paragraph of “BEHAVIOUR DEFINED AS” in 30.3.2.1.5 (as modified by IEEE Std 802.3cb-2018) as follows:*

BEHAVIOUR DEFINED AS:  
 For operation at 5 Gb/s, 10 Gb/s, 25 Gb/s, 40 Gb/s, 50 Gb/s, 100 Gb/s, 200 Gb/s, and 400 Gb/s, it is a count of the number of times the receiving media is non-idle (the time between the Start of Packet Delimiter and the End of Packet Delimiter as defined by 46.2.5 and 81.2.5) for a period of time equal to or greater than minFrameSize, and during which there was at least one occurrence of an event that causes the PHY to indicate “Receive Error” on the media independent interface (see Table 46-4 and Table 81-4).

### 30.5 Layer management for medium attachment units (MAUs)

#### 30.5.1 MAU managed object class

##### 30.5.1.1 MAU attributes

##### 30.5.1.1.2 aMAUType

APPROPRIATE SYNTAX:

*Insert the following new entries into “APPROPRIATE SYNTAX” in 30.5.1.1.2 after the entry for 40GBASE-T:*

50GBASE-R                      Multi-lane PCS as specified in Clause 133 with PMA as specified in  
 Clause 135 over undefined PMD

|            |                                                                                      |
|------------|--------------------------------------------------------------------------------------|
| 50GBASE-CR | 50GBASE-R PCS/PMA over shielded copper balanced cable PMD as specified in Clause 136 |
| 50GBASE-KR | 50GBASE-R PCS/PMA over an electrical backplane PMD as specified in Clause 137        |
| 50GBASE-SR | 50GBASE-R PCS/PMA over multimode fiber PMD as specified in Clause 138                |
| 50GBASE-FR | 50GBASE-R PCS/PMA over single mode fiber PMD as specified in Clause 139              |
| 50GBASE-LR | 50GBASE-R PCS/PMA over single mode fiber PMD as specified in Clause 139              |

*Insert the following new entries into “APPROPRIATE SYNTAX” in 30.5.1.1.2 after the entry for 100GBASE-ER4:*

|              |                                                                                              |
|--------------|----------------------------------------------------------------------------------------------|
| 100GBASE-CR2 | 100GBASE-R PCS/PMA over 2 lane shielded copper balanced cable PMD as specified in Clause 136 |
| 100GBASE-KR2 | 100GBASE-R PCS/PMA over an electrical backplane PMD as specified in Clause 137               |
| 100GBASE-SR2 | 100GBASE-R PCS/PMA over 2 lane multimode fiber PMD as specified in Clause 138                |
| 100GBASE-DR  | 100GBASE-R PCS/PMA over single mode fiber PMD as specified in Clause 140                     |

*Insert the following new entries into “APPROPRIATE SYNTAX” in 30.5.1.1.2 after the entry for 200GBASE-LR4:*

|              |                                                                                              |
|--------------|----------------------------------------------------------------------------------------------|
| 200GBASE-CR4 | 200GBASE-R PCS/PMA over 4 lane shielded copper balanced cable PMD as specified in Clause 136 |
| 200GBASE-KR4 | 200GBASE-R PCS/PMA over an electrical backplane PMD as specified in Clause 137               |
| 200GBASE-SR4 | 200GBASE-R PCS/PMA over 4 lane multimode fiber PMD as specified in Clause 138                |

*Change the last paragraph of “BEHAVIOUR DEFINED AS” in 30.5.1.1.2 (as modified by IEEE Std 802.3cb-2018) as follows:*

**BEHAVIOUR DEFINED AS:**

The enumerations 1000BASE-X, 1000BASE-XHD, 1000BASE-XFD, 2.5GBASE-X, 5GBASE-R, 10GBASE-X, 10GBASE-R, 10GBASE-W, 25GBASE-R, 40GBASE-R, 50GBASE-R, 100GBASE-R, 200GBASE-R, and 400GBASE-R shall only be returned if the underlying PMD type is unknown.;

**30.5.1.1.4 aMediaAvailable**

*Change the sixth paragraph of “BEHAVIOUR DEFINED AS” in 30.5.1.1.4 as follows:*

**BEHAVIOUR DEFINED AS:**

For 40 Gb/s, 50 Gb/s, 100 Gb/s, 200 Gb/s, and 400 Gb/s, the enumerations map to value of the link\_fault variable (see 81.3.4) within the Link Fault Signaling state diagram (see 81.3.4.1 and Figure 46–11) as follows: the values OK and Link Interruption map to the enumeration “available”, the value Local Fault maps to the enumeration “not available” and the value Remote Fault maps to the enumeration “remote fault”.

**30.5.1.1.11 aBIPErrorCount**

*Change the text of “APPROPRIATE SYNTAX” and the first sentence of “BEHAVIOUR DEFINED AS” in 30.5.1.1.11 as follows:*

ATTRIBUTE

APPROPRIATE SYNTAX:

A SEQUENCE of generalized nonresettable counters. Each counter has a maximum increment rate of 10 000 counts per second for 40 Gb/s and 50 Gb/s implementations and 5 000 counts per second for 100 Gb/s implementations.

BEHAVIOUR DEFINED AS:

For 40/50/100GBASE-R PHYs and 100GBASE-P PHYs, an array of BIP error counters.

**30.5.1.1.12 aLaneMapping**

*Change the first sentence of “BEHAVIOUR DEFINED AS” in 30.5.1.1.12 as follows:*

BEHAVIOUR DEFINED AS:

For 40/50/100/200/400GBASE-R PHYs and 100GBASE-P PHYs, an array of PCS lane identifiers.

**30.5.1.1.17 aFECCorrectedBlocks**

*Change the text of “APPROPRIATE SYNTAX” in 30.5.1.1.17 as follows:*

APPROPRIATE SYNTAX:

A SEQUENCE of generalized nonresettable counters. Each counter has a maximum increment rate of 1 200 000 counts per second for 1000 Mb/s implementations, 5 000 000 counts per second for 10 Gb/s, 25 Gb/s, and 40 Gb/s implementations, 10 000 000 counts per second for 50 Gb/s implementations, 2 500 000 counts per second for 100 Gb/s implementations, 40 000 000 counts per second for 200 Gb/s implementations, and 80 000 000 counts per second for 400 Gb/s implementations.

*Change the first sentence of “BEHAVIOUR DEFINED AS” in 30.5.1.1.17 as follows:*

BEHAVIOUR DEFINED AS:

For 1000BASE-PX, 10/25/40/50/100/200/400GBASE-R, 100GBASE-P, 10GBASE-PR, or 10/1GBASE-PRX PHYs, an array of corrected FEC block counters.

**30.5.1.1.18 aFECUncorrectableBlocks**

*Change the text of “APPROPRIATE SYNTAX” in 30.5.1.1.18 as follows:*

APPROPRIATE SYNTAX:

A SEQUENCE of generalized nonresettable counters. Each counter has a maximum increment rate of 1 200 000 counts per second for 1000 Mb/s implementations, 5 000 000 counts per second for 10 Gb/s, 25 Gb/s, and 40 Gb/s implementations, 10 000 000 counts per second for 50 Gb/s implementations, 2 500 000 counts per second for 100 Gb/s implementations, 40 000 000 counts per second for 200 Gb/s implementations, and 80 000 000 counts per second for 400 Gb/s implementations.

*Change the first sentence of “BEHAVIOUR DEFINED AS” in 30.5.1.1.18 as follows:*

BEHAVIOUR DEFINED AS:

For 1000BASE-PX, 10/25/40/50/100/200/400GBASE-R, 100GBASE-P, 10GBASE-PR, or 10/1GBASE-PRX PHYs, an array of uncorrectable FEC block counters.

#### 30.5.1.1.26 aRSFECBIPErrorCount

*Change the text of “APPROPRIATE SYNTAX” and the first sentence of “BEHAVIOUR DEFINED AS” in 30.5.1.1.26 as follows:*

ATTRIBUTE

APPROPRIATE SYNTAX:

A SEQUENCE of generalized nonresetable counters. Each counter has a maximum increment rate of 5 000 counts per second for 50 Gb/s and 100 Gb/s implementations.

BEHAVIOUR DEFINED AS:

For 50GBASE-R, 100GBASE-R<sub>x</sub> and 100GBASE-P PHYs, an array of BIP error counters.

#### 30.5.1.1.27 aRSFECLaneMapping

*Change the first sentence of “BEHAVIOUR DEFINED AS” in 30.5.1.1.27 as follows:*

BEHAVIOUR DEFINED AS:

For 50GBASE-R, 100GBASE-R<sub>x</sub> and 100GBASE-P PHYs, an array of PCS lane identifiers.

#### 30.5.1.1.29 aRSFECBypassIndicationAbility

*Change the first sentence of “BEHAVIOUR DEFINED AS” in 30.5.1.1.29 as follows:*

BEHAVIOUR DEFINED AS:

A read-only value that indicates if the PHY supports an optional RS-FEC error indication bypass ability ~~(see 91.5.3.3).~~

#### 30.5.1.1.31 aRSFECBypassIndicationEnable

*Change the first sentence of “BEHAVIOUR DEFINED AS” in 30.5.1.1.31 as follows:*

BEHAVIOUR DEFINED AS:

A read-write value that indicates the mode of operation of the RS-FEC error indication bypass function ~~(see 91.5.3.3).~~

**30.6 Management for link Auto-Negotiation****30.6.1 Auto-Negotiation managed object class****30.6.1.1 Auto-Negotiation attributes****30.6.1.1.5 aAutoNegLocalTechnologyAbility**

APPROPRIATE SYNTAX:

*Insert the following new entry into “APPROPRIATE SYNTAX” in 30.6.1.1.5 after the entry for 40GBASE-T:*

|      |                                                                                |
|------|--------------------------------------------------------------------------------|
| 50GR | 50GBASE-CR as specified in Clause 136 or 50GBASE-KR as specified in Clause 137 |
|------|--------------------------------------------------------------------------------|

*Insert the following new entries into “APPROPRIATE SYNTAX” in 30.6.1.1.5 after the entry for 100GBASE-KP4:*

|        |                                                                                    |
|--------|------------------------------------------------------------------------------------|
| 100GR2 | 100GBASE-CR2 as specified in Clause 136 or 100GBASE-KR2 as specified in Clause 137 |
| 200GR4 | 200GBASE-CR4 as specified in Clause 136 or 200GBASE-KR4 as specified in Clause 137 |

## 45. Management Data Input/Output (MDIO) Interface

### 45.2 MDIO Interface Registers

#### 45.2.1 PMA/PMD registers

Change Table 45–3 as follows (unchanged rows not shown):

Table 45–3—PMA/PMD registers

| Register address                                      | Register name                                                                                                                   | Subclause              |
|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|------------------------|
| ...                                                   |                                                                                                                                 |                        |
| 1.20                                                  | <del>Reserved</del> 50G PMA/PMD extended ability                                                                                | 45.2.1.17a             |
| ...                                                   |                                                                                                                                 |                        |
| 1.25, 1.26                                            | <del>Reserved</del> PMA/PMD extended ability 2                                                                                  | 45.2.1.21a             |
| 1.26                                                  | <del>Reserved</del>                                                                                                             |                        |
| ...                                                   |                                                                                                                                 |                        |
| 1.500 through 1.515                                   | 50GAUI-n, 100GAUI-2, 200GAUI-n, and 400GAUI-n chip-to-chip transmitter equalization, receive direction, lane 0 through lane 15  | 45.2.1.129, 45.2.1.130 |
| 1.516 through 1.531                                   | 50GAUI-n, 100GAUI-2, 200GAUI-n, and 400GAUI-n chip-to-chip transmitter equalization, transmit direction, lane 0 through lane 15 | 45.2.1.131, 45.2.1.132 |
| <del>1.532 through 1.699</del><br>1.532 through 1.599 | <del>Reserved</del>                                                                                                             |                        |
| 1.600                                                 | PMA precoder control Tx output                                                                                                  | 45.2.1.132a            |
| 1.601                                                 | PMA precoder control Rx input                                                                                                   | 45.2.1.132b            |
| 1.602                                                 | PMA precoder control Rx output                                                                                                  | 45.2.1.132c            |
| 1.603                                                 | PMA precoder control Tx input                                                                                                   | 45.2.1.132d            |
| 1.604                                                 | PMA precoder request flag                                                                                                       | 45.2.1.132e            |
| 1.605                                                 | PMA precoder request Rx input status                                                                                            | 45.2.1.132f            |
| 1.606                                                 | PMA precoder request Tx input status                                                                                            | 45.2.1.132g            |
| 1.607 through 1.649                                   | <del>Reserved</del>                                                                                                             |                        |
| 1.650, 1.651                                          | RS-FEC degraded SER activate threshold                                                                                          | 45.2.1.132h            |
| 1.652, 1.653                                          | RS-FEC degraded SER deactivate threshold                                                                                        | 45.2.1.132i            |
| 1.654, 1.655                                          | RS-FEC degraded SER interval                                                                                                    | 45.2.1.132j            |
| 1.656 through 1.699                                   | <del>Reserved</del>                                                                                                             |                        |
| ...                                                   |                                                                                                                                 |                        |

**Table 45–3—PMA/PMD registers (continued)**

| Register address                                                 | Register name                                                     | Subclause          |
|------------------------------------------------------------------|-------------------------------------------------------------------|--------------------|
| <del>1.1110 through 1.1199</del><br><u>1.1110 through 1.1119</u> | Reserved                                                          |                    |
| <u>1.1120 through 1.1123</u>                                     | <u>BASE-R PAM4 PMD training LP control, lane 0 through lane 3</u> | <u>45.2.1.135a</u> |
| <u>1.1124 through 1.1199</u>                                     | <u>Reserved</u>                                                   |                    |
| ...                                                              |                                                                   |                    |
| <del>1.1210 through 1.1299</del><br><u>1.1210 through 1.1219</u> | Reserved                                                          |                    |
| <u>1.1220 through 1.1223</u>                                     | <u>BASE-R PAM4 PMD training LP status, lane 0 through lane 3</u>  | <u>45.2.1.136a</u> |
| <u>1.1224 through 1.1299</u>                                     | <u>Reserved</u>                                                   |                    |
| ...                                                              |                                                                   |                    |
| <del>1.1310 through 1.1399</del><br><u>1.1310 through 1.1319</u> | Reserved                                                          |                    |
| <u>1.1320 through 1.1323</u>                                     | <u>BASE-R PAM4 PMD training LD control, lane 0 through lane 3</u> | <u>45.2.1.137a</u> |
| <u>1.1324 through 1.1399</u>                                     | <u>Reserved</u>                                                   |                    |
| ...                                                              |                                                                   |                    |
| <del>1.1410 through 1.1449</del><br><u>1.1410 through 1.1419</u> | Reserved                                                          |                    |
| <u>1.1420 through 1.1423</u>                                     | <u>BASE-R PAM4 PMD training LD status, lane 0 through lane 3</u>  | <u>45.2.1.138a</u> |
| <u>1.1424 through 1.1449</u>                                     | <u>Reserved</u>                                                   |                    |
| ...                                                              |                                                                   |                    |

**45.2.1.1 PMA/PMD control 1 register (Register 1.0)**

*Change the bits 1.0.5:2 row in Table 45–4 as follows (unchanged rows not shown):*

**Table 45–4—PMA/PMD control 1 register bit definitions**

| Bit(s)  | Name            | Description                                                                                                                                                                                                                                                                                             | R/W <sup>a</sup> |
|---------|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| ...     |                 |                                                                                                                                                                                                                                                                                                         |                  |
| 1.0.5:2 | Speed selection | 5 4 3 2<br>1 1 x x = Reserved<br>1 0 1 x = Reserved<br>1 0 0 1 = 400 Gb/s<br>1 0 0 0 = 200 Gb/s<br>0 1 1 1 = 5 Gb/s<br>0 1 1 0 = 2.5 Gb/s<br>0 1 0 1 = <del>Reserved</del> 50 Gb/s<br>0 1 0 0 = 25 Gb/s<br>0 0 1 1 = 100 Gb/s<br>0 0 1 0 = 40 Gb/s<br>0 0 0 1 = 10PASS-TS/2BASE-TL<br>0 0 0 0 = 10 Gb/s | R/W              |
| ...     |                 |                                                                                                                                                                                                                                                                                                         |                  |

<sup>a</sup>R/W = Read/Write, SC = Self-clearing, RO = Read only

**45.2.1.1.3 Speed selection (1.0.13, 1.0.6, 1.0.5:2)**

*Change the last paragraph of 45.2.1.1.3 as follows:*

When bits 5 through 2 are set to 0010 the use of a 40G PMA/PMD is selected; when set to 0011 the use of a 100G PMA/PMD is selected; when set to 0100 the use of a 25G PMA/PMD is selected; when set to 0101 the use of a 50G PMA/PMD is selected; when set to 0110 the use of a 2.5G PMA/PMD is selected; when set to 0111 the use of a 5G PMA/PMD is selected; when set to 1000 the use of a 200G PMA/PMD is selected; when set to 1001 the use of a 400G PMA/PMD is selected. More specific selection is performed using the PMA/PMD control 2 register (Register 1.7) (see 45.2.1.6.3).

**45.2.1.2 PMA/PMD status 1 register (Register 1.1)****45.2.1.2.3 Fault (1.1.7)**

*Change the fourth sentence of 45.2.1.2.3 as follows:*

For 10/25/40/50/100/200/400 Gb/s operation, bit 1.1.7 is set to a one when either of the fault bits (1.8.11, 1.8.10) located in register 1.8 are set to a one.