

American National Standard for Metric Practice

Co-Sponsors

ASTM Committee E43 on SI Practice

and

IEEE Standards Coordinating Committee 14
(*Quantities, Units, and Letter Symbols*)



IEEE
3 Park Avenue
New York, NY 10016-5997
USA

IEEE/ASTM SI 10™-2016
(Revision of
IEEE/ASTM SI 10-2010)

American National Standard for Metric Practice

Co-Sponsors

ASTM Committee E43 on SI Practice

and

**IEEE Standards Coordinating Committee 14
(Quantities, Units, and Letter Symbols)**

Approved 22 September 2016

IEEE-SA Standards Board

Approved 1 July 2016

ASTM International

Abstract: Guidance for the use of the modern metric system is given. Known as the International System of Units (abbreviated SI), the system is the basis for worldwide standardization of measurement units. Information is included on SI, a list of units recognized for use with SI, and a list of conversion factors, together with general guidance on proper style and usage.

Keywords: conversion factors, International System, International System of Units, metric practice, metric system, rounding, SI, SI 10, Système International d'Unités

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

ASTM International
100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959, USA

Copyright © 2016 by The Institute of Electrical and Electronics Engineers, Inc. and ASTM International.
All rights reserved. Published 10 March 2017. Printed in the United States of America.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

ASTM International is a registered trademark in the U.S. Patent & Trademarks Office, owned by ASTM International.

PDF: ISBN 978-1-5044-3717-2 STD22411
Print: ISBN 978-1-5044-3718-9 STDPD22411

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

ASTM International is a globally recognized leader in the development and delivery of voluntary consensus standards. Today, over 12,500 ASTM standards are used around the world to improve product quality, enhance health and safety, strengthen market access and trade, and build consumer confidence.

Organized in 1898, **ASTM International** is one of the world's largest international standards developing organizations. Our leadership in international standards development is driven by the contributions of our members: more than 30,000 of the world's top technical experts and business professionals representing over 140 countries. Working in an open and transparent process and using ASTM's advanced IT infrastructure, our members create the test methods, specifications, classifications, guides and practices that support industries and governments worldwide.

ASTM standards are the tools of customer satisfaction and competitiveness for companies across a wide range of markets. Through more than 140 technical standards-writing committees, we serve a broad range of industries: metals, construction, petroleum, consumer products and many more. ASTM technical standards can be found on ASTM's website, www.astm.org, and in the 83-volume Annual Book of ASTM Standards (available in print and through online subscription).

Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards at the address shown below.

For more information on this standard and other ASTM publications, contact:

ASTM International
100 Barr Harbor Drive
P.O. Box C700
West Conshohocken, PA 19428-2959
USA
Phone: +1 610 832-9585
Fax: +1 610 832-9555
e-mail: service@astm.org
web: www.astm.org

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE Xplore at <http://ieeexplore.ieee.org/> or contact IEEE at the address listed previously. For more information about the IEEE-SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

This standard was developed by the IEEE/ASTM Committee for Maintaining IEEE/ASTM SI 10, a joint committee established by the sponsoring organizations. The proposed standard generated by this joint committee was then formally adopted by the IEEE and ASTM before transmission to the American National Standards Institute for approval as an American National Standard. At the time this IEEE standard was completed, the joint committee had the following membership. Nonvoting members at the time of publication are marked with an asterisk (*):

Rodney Conn, *Chair*
Terry Bates, *Vice Chair*
James R. Frysinger, *Secretary*

Gordon Aubrecht
Bruce Barrow
Lyle Bowman
Robert Bushnell

Mike Crewdson*
Don Hillger
Stanislav Jakuba
John Nichols
Jim Paschal*

Richard Peppin*
Howard Ressel*
Terry Scott*
Tom Walsh*

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Samuel Aguirre
Robert Aiello
Mihaela Albu
Dwight Alexander
Saleman Alibhay
Roberto Asano
Curtis Ashton
Gordon Aubrecht
Robert Ballard
Peter Balma
Bakul Banerjee
Cleon Barker
Thomas Barnes
Bruce Barrow
Frank Basciano
Earle Bascom III
Ronald Bennell
Jean-Marc Biasse
Thomas Bishop
Thomas Blackburn
William Bloethe
Anne Bosma
Kenneth Bow
Harvey Bowles
Riccardo Brama
Daniel Brosnan
Gustavo Brunello
Paul Cardinal
Yesenia Cevallos
Michael Champagne
Suresh Channarasappa
Arvind Chaudhary
Donald Cherry
Keith Chow
C. Clair Claiborne
Larry Conrad

Stephen Conrad
Charles Cotton
Geoffrey Darnton
Matthew Davis
Ronald Dean
Davide de Luca
Gary Donner
Michael Dood
Neal Dowling
Edgar Dullni
Robert Durham
Sourav Dutta
Douglas J. Edwards
Heiko Ehrenberg
Richard Ellis
Hossam Fahmy
Keith Flowers
Joseph Foldi
Gary Fox
Avraham Freedman
Nancy Frost
James Frysinger
David Fusch
Shawn Galbraith
Michael Garrels
George Gela
John Geldman
Frank Gerleve
Gregg Giesler
James Gilb
Jalal Gohari
Edwin Goodwin
Chris Gorringer
David Gregson
J. Travis Griffith
Randall Groves

Michael Gundlach
Bal Gupta
Ajit Gwal
Donald Hall
J. Harlow
Daryl Harmon
Lee Herron
Guido Hiertz
Lauri Hiivala
Werner Hoelzl
Ronald Hotchkiss
Richard Hulett
Noriyuki Ikeuchi
Magdi Ishac
Atsushi Ito
Richard Jackson
Vincent Jones
Adri Jovin
Laszlo Kadar
Shinkyo Kaku
Innocent Kamwa
Efthymios Karabetsos
Piotr Karocki
John Kay
Stuart Kerry
Vladimir Khalin
Yuri Khersonsky
Jean-Francois Kieffer
Hermann Koch
Richard Kolich
Lawrence Kotewa
Jim Kulchisky
Saumen Kundu
Thomas Kurihara
Chung-Yiu Lam
David Leciston

Wei-Jen Lee
 Yeou Song Lee
 John Lemon
 Arthur H Light
 Paul Lindemulder
 O. Malik
 Jouni Malinen
 Roger Marks
 Jorge Marquez
 Lee Matthews
 Edward McCall
 Thomas McCarthy
 Peter Megna
 Joseph Melanson
 John Merando
 John Miller
 Daniel Mulkey
 Ryan Musgrove
 K. R. M. Nair
 Marie Nemier
 Gary Nissen
 Tim Olson
 Lorraine Padden
 Richard Paes
 Luke Parthemore
 Bansil Patel
 Mark Paulk
 Ronald Petersen
 Branimir Petosic
 Christopher Petrola
 Ghery Pettit
 David R. Phelps

Percy Pool
 Alvaro Portillo
 Iulian Profir
 John Rama
 R. K. Rannow
 Sergio Rapuano
 Carl Reigart
 Annette Reilly
 Maximilian Riegel
 Michael Roberts
 Timothy Robirds
 Charles Rogers
 Ervin Root
 Terence Rout
 Thomas Rozek
 Daniel Sabin
 Bartien Sayogo
 Janek Schumann
 Mike Seavey
 Robert Seitz
 Mark Siira
 Carl Singer
 Jeffrey Sisson
 Jeremy Smith
 Jerry Smith
 Gary Smullin
 Ronald Stahara
 Joseph Stanco
 Thomas Starai
 Donald Steigerwalt
 John Stevens
 Brian Story

Walter Struppler
 K. Stump
 Mark Sturza
 Marcy Stutzman
 Peter Sutherland
 David Tepen
 Phyllis Thomas
 Geoffrey Thompson
 Wayne Timm
 James Tomaseski
 Remi Tremblay
 Richard Tressler
 Thomas Tullia
 Joe Uchiyama
 James Van De Ligt
 John Vergis
 Matthew Wakeham
 David Walker
 Daniel Ward
 Joe Watson
 John Webb
 Hung-Yu Wei
 Kenneth White
 Alan Wilks
 Jan Wittenber
 Terry Woodyard
 Forrest Wright
 Guangning Wu
 Richard Young
 Jian Yu
 Oren Yuen

When the IEEE-SA Standards Board approved this standard on 22 September 2016, it had the following membership:

John D. Kulick, *Chair*
Jon Walter Rosdahl, *Vice Chair*
Richard H. Hulett, *Past Chair*
Konstantinos Karachalios, *Secretary*

Masayuki Ariyoshi
 Ted Burse
 Stephen Dukes
 Jean-Philippe Faure
 J. Travis Griffith
 Gary Hoffman
 Michael Janezic
 Joseph L. Koepfinger*

David J. Law
 Hung Ling
 Andrew Myles
 T. W. Olsen
 Glenn Parsons
 Ronald C. Petersen
 Annette D. Reilly
 Stephen J. Shellhammer

Adrian P. Stephens
 Yatin Trivedi
 Philip Winston
 Don Wright
 Yu Yuan
 Daidi Zhong

*Member Emeritus

Introduction

This introduction is not part of IEEE/ASTM SI 10-2016, American National Standard for Metric Practice.

Any measurable physical quantity can be represented in the International System of Units (SI) with the aid of just seven *base units*—the units for the quantities length, mass, time, electric current, temperature, amount of substance, and luminous intensity—or by combinations (called *derived units*) of these seven. For example, the unit of speed can be expressed by the unit of length divided by the unit of time. This standard shows first the two classes of units (base and derived) that make up the SI, together with the standard symbols that may be used to represent them. Prefixes that allow the formation of decimal multiples and submultiples are explained. Notes on the proper use of the SI units and symbols in many applications follow.

Annex A includes lists of many units from non-SI systems with the appropriate SI units that should be substituted and numerical conversion factors. Other annexes include rules for conversion and rounding (Annex B), a discussion of the advantages of SI units with definitions where appropriate (Annex C), a history of the development of the system (Annex D), a discussion of quantities relating to chemical solutions (Annex E), and a bibliography of source documents (Annex F).

Contents

1. Scope	11
2. SI units and symbols.....	11
2.1 Classes of units	11
2.2 SI prefixes.....	15
3. Use of the SI.....	16
3.1 General	16
3.2 Application of SI prefixes.....	16
3.3 Other units	17
3.4 Some comments concerning quantities and units	22
3.5 Style and usage	27
Annex A (informative) Tables of conversion factors	34
A.1 General.....	34
A.2 Notation	34
A.3 Use.....	34
A.4 Tables.....	35
Annex B (informative) Rules for conversion and rounding	48
B.1 Need for care in conversion and rounding	48
B.2 Definitions	48
B.3 Introduction to conversion	48
B.4 Significant digits	49
B.5 Operations on data	49
B.6 Accuracy and rounding.....	50
B.7 Rounding values.....	52
B.8 Conversion versus substitution	52
Annex C (informative) Comments concerning the application of the International System of Units (SI) ...	54
C.1 Advantages of SI.....	54
C.2 Note concerning the liter.....	55
C.3 Definitions of SI base units	55
C.4 Definitions of SI derived units with special names	56
C.5 Comment on spelling	58
C.6 Comments on mass, force, and weight.....	58
Annex D (informative) Development of the International System of Units (SI).....	59
D.1 History	59
D.2 The International Bureau of Weights and Measures (BIPM)	60
Annex E (informative) The quantities used to characterize the composition of solutions.....	62
E.1 Introduction	62
E.2 Concentration	62
E.3 Dimensionless fractions	63
E.4 Related quantities	64
Annex F (informative) Bibliography	65

American National Standard for Metric Practice

1. Scope

This document is the primary American National Standard on application of the metric system. It emphasizes use of the International System of Units (SI), which is the modern, internationally accepted metric system. It includes information on SI, a limited list of units recognized for use with SI, and a list of conversion factors, together with general guidance on style and usage. It also lists older “metric” units that shall no longer be used. The word *primary* implies that other metric standards in the United States should be consistent with this document.

2. SI units and symbols

2.1 Classes of units

2.1.1 Base units

SI is built upon the seven well-defined base quantities of Table 1, which by convention are regarded as independent, and upon the seven base units for these quantities. The definitions of the base units are given in C.3. Throughout this document, unless otherwise noted, the word *quantity* means a measurable attribute of a phenomenon or of matter.

Table 1—SI base units

Quantity name	Typical quantity symbol ^a	Unit name	Unit symbol
length	l, x, r , etc.	meter	m
mass	m	kilogram	kg
time	t	second	s
electric current	I, i	ampere	A
thermodynamic temperature	T	kelvin	K
amount of substance	n	mole	mol
luminous intensity	I_v	candela	cd

^a The symbols for quantities are suggestions only and alternative symbols may be used, as indicated for length and electric current—see 3.5.1.3 c).

2.1.2 Derived units

Derived units are formed by combining base units according to the algebraic relations linking the corresponding quantities. The symbols for derived units are obtained by means of the mathematical signs for multiplication, division, and use of exponents. Table 2 gives examples of derived units and shows how they are formed from base units.

Table 2—Examples of SI derived units expressed in terms of base units

Quantity name	Typical quantity symbol ^a	Unit name	Unit symbol
area	A	square meter	m ²
volume	V	cubic meter	m ³
speed, velocity	v, v, u	meter per second	m/s
acceleration	a	meter per second squared	m/s ²
wavenumber	σ, k	reciprocal meter	m ⁻¹
density, mass density	ρ	kilogram per cubic meter	kg/m ³
specific volume	v	cubic meter per kilogram	m ³ /kg
current density	j	ampere per square meter	A/m ²
magnetic field strength	H	ampere per meter	A/m
concentration (of amount of substance)	c	mole per cubic meter	mol/m ³
luminance	L_v	candela per square meter	cd/m ²

^a The symbols for quantities are suggestions only and alternative symbols may be used, as indicated for speed and wavenumber—see 3.5.1.3 c).

For convenience, certain derived units have been given special names and symbols. Those that are approved by the General Conference on Weights and Measures (abbreviated CGPM from its name in French; see **Error! Reference source not found.**), and are therefore formally part of the SI, are listed in Table 3. Definitions are provided in C.4.

Table 3—SI derived units with special names and symbols

Quantity name	Unit name	Unit symbol	Expressed in terms of other SI units	Expressed in terms of SI base units
angle, plane	radian	rad	1	$\text{m} \cdot \text{m}^{-1} = 1$ [See NOTE]
angle, solid	steradian	sr	1	$\text{m}^2 \cdot \text{m}^{-2} = 1$ [See NOTE]
frequency (of a periodic phenomenon)	hertz	Hz		s^{-1}
force	newton	N		$\text{kg} \cdot \text{m} \cdot \text{s}^{-2}$
pressure, stress	pascal	Pa	N/m^2	$\text{kg} \cdot \text{m}^{-1} \cdot \text{s}^{-2}$
energy, work, quantity of heat	joule	J	$\text{N} \cdot \text{m}$	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2}$
power, radiant flux	watt	W	J/s	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-3}$
electric charge, quantity of electricity	coulomb	C		$\text{s} \cdot \text{A}$
electric potential difference, electromotive force	volt	V	W/A	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-3} \cdot \text{A}^{-1}$
capacitance	farad	F	C/V	$\text{kg}^{-1} \cdot \text{m}^{-2} \cdot \text{s}^4 \cdot \text{A}^2$
electric resistance	ohm	Ω	V/A	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-3} \cdot \text{A}^{-2}$
electric conductance	siemens	S	A/V	$\text{kg}^{-1} \cdot \text{m}^{-2} \cdot \text{s}^3 \cdot \text{A}^2$
magnetic flux	weber	Wb	$\text{V} \cdot \text{s}$	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2} \cdot \text{A}^{-1}$
magnetic flux density	tesla	T	Wb/m^2 ; $\text{N}/(\text{A} \cdot \text{m})$	$\text{kg} \cdot \text{s}^{-2} \cdot \text{A}^{-1}$
inductance	henry	H	Wb/A	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2} \cdot \text{A}^{-2}$
luminous flux	lumen	lm	$\text{cd} \cdot \text{sr}$	$\text{m}^2 \cdot \text{m}^{-2} \cdot \text{cd} = \text{cd}$
illuminance	lux	lx	lm/m^2	$\text{m}^2 \cdot \text{m}^{-4} \cdot \text{cd} = \text{m}^{-2} \cdot \text{cd}$
activity (referred to a radionuclide)	becquerel	Bq		s^{-1}
absorbed dose, specific energy imparted, kerma	gray	Gy	J/kg	$\text{m}^2 \cdot \text{s}^{-2}$
dose equivalent, ambient dose equivalent, directional dose equivalent, personal dose equivalent, organ equivalent dose	sievert	Sv	J/kg	$\text{m}^2 \cdot \text{s}^{-2}$
catalytic activity	katal	kat		$\text{s}^{-1} \cdot \text{mol}$
NOTE—If the SI units are considered as a mathematical group, group theory requires that the number 1 be included with the base units. The CGPM has not yet adopted this position. ¹				

It is sometimes convenient to express derived units in terms of other derived units with special names. Some examples appear in Table 3 and additional examples are given in Table 4. Note that although the expression of a derived unit in terms of the SI base units is unique, there are frequently alternative ways to express a derived unit using other derived units.

¹ Notes in text, tables, and figures of a standard are given for information only and do not contain requirements needed to implement this standard.

Table 4—Examples of SI derived units whose names include coherent SI derived units with special names and symbols

Quantity name	Unit name	Unit symbol	Expressed in terms of SI base units
absorbed dose rate	gray per second	Gy/s	$\text{m}^2 \cdot \text{s}^{-3}$
angular acceleration	radian per second squared	rad/s^2	$\text{m} \cdot \text{m}^{-1} \cdot \text{s}^{-2} = \text{s}^{-2}$
angular velocity	radian per second	rad/s	$\text{m} \cdot \text{m}^{-1} \cdot \text{s}^{-1} = \text{s}^{-1}$
electric charge density	coulomb per cubic meter	C/m^3	$\text{m}^{-3} \cdot \text{s} \cdot \text{A}$
electric field strength	volt per meter	V/m	$\text{kg} \cdot \text{m} \cdot \text{s}^{-3} \cdot \text{A}^{-1}$
electric field strength	newton per coulomb	N/C	$\text{kg} \cdot \text{m} \cdot \text{s}^{-3} \cdot \text{A}^{-1}$
electric flux density	coulomb per square meter	C/m^2	$\text{m}^{-2} \cdot \text{s} \cdot \text{A}$
energy density	joule per cubic meter	J/m^3	$\text{kg} \cdot \text{m}^{-1} \cdot \text{s}^{-2}$
entropy	joule per kelvin	J/K	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2} \cdot \text{K}^{-1}$
exposure (X-rays and gamma rays)	coulomb per kilogram	C/kg	$\text{kg}^{-1} \cdot \text{s} \cdot \text{A}$
heat capacity	joule per kelvin	J/K	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2} \cdot \text{K}^{-1}$
heat flux density, irradiance	watt per square meter	W/m^2	$\text{kg} \cdot \text{s}^{-3}$
molar energy	joule per mole	J/mol	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2} \cdot \text{mol}^{-1}$
molar entropy, molar heat capacity	joule per mole kelvin	$\text{J}/(\text{mol} \cdot \text{K})$	$\text{m}^2 \cdot \text{kg} \cdot \text{s}^{-2} \cdot \text{K}^{-1} \cdot \text{mol}^{-1}$
moment of force	newton meter	$\text{N} \cdot \text{m}$	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2}$
permeability (magnetic)	henry per meter	H/m	$\text{kg} \cdot \text{m} \cdot \text{s}^{-2} \cdot \text{A}^{-2}$
permittivity	farad per meter	F/m	$\text{kg}^{-1} \cdot \text{m}^{-3} \cdot \text{s}^4 \cdot \text{A}^2$
power density	watt per square meter	W/m^2	$\text{kg} \cdot \text{s}^{-3}$
radiance	watt per square meter steradian	$\text{W}/(\text{m}^2 \cdot \text{sr})$	$\text{kg} \cdot \text{s}^{-3}$
radiant intensity	watt per steradian	W/sr	$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-3}$
specific heat capacity	joule per kilogram kelvin	$\text{J}/(\text{kg} \cdot \text{K})$	$\text{m}^2 \cdot \text{s}^{-2} \cdot \text{K}^{-1}$
specific energy	joule per kilogram	J/kg	$\text{m}^2 \cdot \text{s}^{-2}$
specific entropy	joule per kilogram kelvin	$\text{J}/(\text{kg} \cdot \text{K})$	$\text{m}^2 \cdot \text{s}^{-2} \cdot \text{K}^{-1}$
surface tension	newton per meter	N/m	$\text{kg} \cdot \text{s}^{-2}$
thermal conductivity	watt per meter kelvin	$\text{W}/(\text{m} \cdot \text{K})$	$\text{kg} \cdot \text{m} \cdot \text{s}^{-3} \cdot \text{K}^{-1}$
viscosity, dynamic	pascal second	$\text{Pa} \cdot \text{s}$	$\text{kg} \cdot \text{m}^{-1} \cdot \text{s}^{-1}$
viscosity, kinematic	square meter per second	m^2/s	$\text{m}^2 \cdot \text{s}^{-1}$

2.1.3 Coherence

The SI base units and SI derived units form a coherent set, *the set of coherent SI units*, where *coherent* is used in the specialist sense of a system whose units are mutually related by rules of multiplication and division with no numerical factor other than 1.

2.2 SI prefixes

The prefixes listed in Table 5 are used to form decimal multiples and submultiples of the SI base and derived units. The term *SI units* includes the SI base units, the SI derived units, and all units formed from them using the SI prefixes. See 3.2.5 for non-SI prefixes for binary multiples.

Table 5—SI prefixes

Name	Symbol	Multiplication factor
yotta	Y	10^{24}
zetta	Z	10^{21}
exa	E	10^{18}
peta	P	10^{15}
tera	T	10^{12}
giga	G	10^9
mega	M	10^6
kilo	k	$10^3 = 1000$
hecto	h	$10^2 = 100$
deka	da	$10^1 = 10$
deci	d	$10^{-1} = 0.1$
centi	c	$10^{-2} = 0.01$
milli	m	$10^{-3} = 0.001$
micro	μ	10^{-6}
nano	n	10^{-9}
pico	p	10^{-12}
femto	f	10^{-15}
atto	a	10^{-18}
zepto	z	10^{-21}
yocto	y	10^{-24}

2.2.1 Unit of mass

Among the base and derived units of SI, the unit of mass (kilogram) is the only one whose name, for historical reasons, contains a prefix. Names or symbols of decimal multiples and submultiples of the unit of mass are formed by attaching prefixes to the word gram or prefix symbols to the symbol g.

2.2.2 Limited character sets

When the metric system developed in the 19th century, all educated persons were familiar with the Greek alphabet, and the Greek letters lowercase mu (for micro) and uppercase omega (for ohm) were standardized and have been included in the official SI Brochure. This presents a problem now with limited character sets, especially in embedded and applied computer operating systems used in manufacturing and labware. IEEE Std 260.1™-2004 [B9]² addresses this problem and prescribes lowercase u as a substitute prefix symbol for micro and Ohm (note the uppercase O) as a substitute unit symbol for ohm when Greek letters are not available. It also gives recommendations where only uppercase or only lowercase letters are available.

3. Use of the SI

3.1 General

SI is the form of the metric system that shall be used for all applications. It is important that this modern form of the metric system be thoroughly understood and properly applied. The remainder of this standard gives guidance concerning the use of the system, including the limited number of cases in which units outside SI are appropriately used, and makes recommendations concerning usage and style.

3.2 Application of SI prefixes

3.2.1 General

In general, use the SI prefixes (see 2.2) to indicate orders of magnitude. Thus, one can eliminate nonsignificant digits (for example, 12 300 m becomes 12.3 km, or 12.30 km, or 12.300 km depending on the appropriate number of significant digits) and leading zeros in decimal fractions (for example, 0.001 23 μm becomes 1.23 nm). SI prefixes provide a convenient alternative to the powers-of-ten notation (for example, $12.3 \times 10^3 \text{ m}$ becomes 12.3 km). Never use a prefix alone.

3.2.2 Selection

When expressing a quantity by a numerical value and a unit, give preference to a prefix that yields a numerical value between 0.1 and 1000. For simplicity, give preference to prefixes representing 1000 raised to a positive or negative integral power. However, the following factors may justify deviation from these prefixes:

- a) In expressing area and volume, the prefixes hecto, deka, deci, and centi may be convenient, for example, cubic decimeter, square hectometer, or cubic centimeter.
- b) In tables of values of the same quantity, or in a discussion of such values within a given context, it is preferable to use the same unit multiple or submultiple throughout.
- c) For certain quantities in particular applications, one particular multiple or submultiple is often used. For example, the millimeter is used for linear dimensions in engineering drawings even when the values lie far outside the range of 0.1 mm to 1000 mm; the centimeter is usually used for body measurements, clothing sizes, household products, and other everyday purposes for which millimeters are inconveniently precise.

² The numbers in brackets correspond to those of the bibliography in Annex F.

3.2.3 Compound prefixes

Do not use prefixes formed by the juxtaposition of two or more SI prefixes. For example, use

1.3 nm, *not* 1.3 mμm

2.4 pF, *not* 2.4 μμF

3.2.4 Powers of units

An exponent attached to a unit symbol containing a prefix indicates that the multiple or submultiple of the unit (the unit with its prefix) is raised to the power expressed by the exponent.

Examples:

$$\begin{aligned} 1 \text{ cm}^3 &= (10^{-2} \text{ m})^3 &= 10^{-6} \text{ m}^3 \\ 2.5 \text{ ns}^{-1} &= 2.5(10^{-9} \text{ s})^{-1} &= 2.5 \times 10^9 \text{ s}^{-1} \\ 7 \text{ mm}^2/\text{s} &= 7(10^{-3} \text{ m})^2/\text{s} &= 7 \times 10^{-6} \text{ m}^2/\text{s} \end{aligned}$$

3.2.5 Prefixes for binary multiples

In the computer field the SI prefixes kilo, mega, giga, etc. have sometimes been defined as powers of two. That is, kilo has been used to mean 1024 (i.e., 2^{10}), mega has been used to mean 1 048 576 (i.e., 2^{20}), etc. The SI prefixes shall not be used as prefixes for binary multiples.

The International Electrotechnical Commission (IEC) and IEEE have adopted standard prefixes for binary multiples. These include kibi (Ki) for 2^{10} , mebi (Mi) for 2^{20} , and gibi (Gi) for 2^{30} . See NIST Special Publication 811 [B29], NIST Technical Note 1265 [B31], and IEEE Std 1541TM-2002 (reaff. 2008) [B10].

3.3 Other units

3.3.1 Units from other systems

To preserve the advantages of SI, minimize the use of non-SI units. Such use should be limited to units listed in Table 6 and Table 7.

Table 6—Non-SI Units in use with SI

Quantity	Unit name	Unit symbol	Exact value in SI units
time	minute	min	min = 60 s
	hour	h	h = 60 min = 3600 s
	day	d	d = 24 h = 86 400 s
	month	mo	
	year	a	
plane angle	degree ^a	°	1° = (π/180) rad
	minute ^a	'	1' = (1/60)° = (π/10 800) rad
	second ^a	"	1" = (1/60)' = (π/648 000) rad
	revolution, turn	r	r = 2π rad
	nautical mile	nmi	nmi = 1852 m
speed	knot	kn	kn = nmi/h
area	hectare	ha	ha = 1 hm ² = 10 ⁴ m ²
volume	liter ^b	L	L = 1 dm ³ = 10 ⁻³ m ³
mass	metric ton	t	t = 1 Mg = 10 ³ kg
logarithmic ratio quantities	neper	Np	See 3.4.9
	bel	B	
	decibel	dB	

^a Decimal degrees should be used for division of degrees, except for fields such as astronomy and cartography.

^b See 3.3.2.5.

Table 7—Units whose values are obtained experimentally

Quantity	Unit name	Unit symbol	Value in SI units ^a
energy	electronvolt ^b	eV	eV = 1.602 176 6208(98) × 10 ⁻¹⁹ J
mass	dalton, unified atomic mass unit ^c	Da u	Da = 1.660 539 040(20) × 10 ⁻²⁷ kg u = Da

^a The numerical values are taken from the 2014 CODATA set of recommended values of the fundamental physical constants, Mohr, Taylor, and Newell (2015) [B27]. The values are given with their combined standard uncertainties, which apply to the last two digits, shown in parentheses. The next CODATA will be issued in 2018 and will use the new SI definitions expected to be issued in 2018. The values given in the CODATA might change as a result and significant changes in uncertainties are expected due to the definitions of all base units in terms of exact quantities.

^b The electronvolt is the kinetic energy acquired by an electron in passing through a potential difference of 1 V in vacuum. The electronvolt is often combined with the SI prefixes.

^c The dalton (Da) and the unified atomic mass unit (u) are equivalent names for the same unit, equal to 1/12 of the mass of an unbound atom of the nuclide ¹²C at rest and in its ground state. The dalton (Da) is often combined with the SI prefixes to express masses of large molecules (e.g., kDa, MDa) or small mass differences of atoms or molecules (e.g., nDa, pDa).

3.3.2 Units in use with SI

3.3.2.1 General

Compliance with this standard includes the use, as needed and convenient, of certain non-SI units listed in Table 6 and Table 7, as well as all the SI units, including the multiples and submultiples.

3.3.2.2 Time

The SI unit of time is the second (s), which should be used in technical calculations. However, where time relates to life customs or calendar cycles, the minute (min), hour (h), day (d), and other calendar units may be used. For example, vehicle speed is often expressed in the non-SI unit kilometer per hour (km/h) instead of the SI unit meter per second (m/s). There are no values or symbols given in the SI for week, month, and year. The latter two especially have varying values depending on the actuarial or astronomical unit intended. However, industry often uses the units month and year for statistical and financial purposes and so Table 6 of this standard includes those two units and their symbols.

3.3.2.3 Plane angle

The SI unit of plane angle is the number one (1), which is also called by its special name radian (rad). Use of the degree of plane angle is permissible when the radian is not convenient.

3.3.2.4 Area

The SI unit of area is the square meter (m²). The hectare (ha) is a special name for the square hectometer (hm²). Large land or water areas are generally expressed in hectares or in square kilometers (km²). Because hectare, for historical reasons, already involves an SI prefix, additional SI prefixes may not be used with this unit.

3.3.2.5 Volume

The SI unit of volume is the cubic meter (m³). Use this unit, or a multiple or submultiple of it, such as cubic kilometer (km³), cubic hectometer (hm³), cubic centimeter (cm³), etc. The liter is a special name for the cubic decimeter (dm³). SI prefixes are often used with liter for convenience.

In 1979, the CGPM approved the letters l and L as alternative symbols for the liter. Because the letter symbol l can easily be confused with the numeral 1, the symbol L is recommended for use in the United States. The script “ell” (ℓ) shall not be used as a symbol for liter. See C.2 for information concerning the history of this unit.

3.3.2.6 Mass

The SI unit of mass is the kilogram (kg). This unit, or a multiple or submultiple formed by attaching an SI prefix to gram (g), is preferred in all applications.

The name *ton* has been given to several large mass units that are widely used in commerce and technology: the long ton of 2240 lb, the short ton of 2000 lb, and the metric ton of 1000 kg or 1 Mg, which is almost 2205 lb. *Tonne* is a name for metric ton that is used in many countries. Only the megagram is SI.

3.3.2.7 Units whose values are obtained experimentally

Table 7 lists two non-SI units that are also accepted for use with SI, whose values expressed in SI units must be obtained by experiment and are therefore not known exactly. These units are in common use in certain specialized fields. The values given in this document are taken from the latest CODATA [B27] existing at the time of publication. Consult the CODATA for the latest value where utmost precision is important.

3.3.3 Units and names that shall not be used

Table 8 lists units and names that shall not be used and gives SI equivalents that shall be used in their place. These are examples of several metric and related units other than those of SI that have been defined over the years. Some are used only in special fields; others have found broad application outside the United States. Do not use units that are not part of SI (or non-SI names for multiples or submultiples of SI units, such as micron for micrometer). Some units that shall not be used are discussed in more detail in 3.3.3.1 and 3.3.3.2. Note that these subclauses and Table 8 are not complete but only indicate prominent examples.

3.3.3.1 Pressure and stress

The SI unit of pressure and stress is the pascal (newton per square meter), and with appropriate SI prefixes it should be used in all applications (see also 3.4.7). The kilopascal is useful in many practical applications—normal atmospheric pressure is approximately 100 kPa (or 1000 hPa), and automobile manufacturers are specifying tire pressure in kPa. Do not use old metric units for pressure and stress such as kilogram-force per square centimeter (kgf/cm^2) or other non-SI units—such as torr, millimeter of mercury, or meter of water—for pressure.

3.3.3.2 Centimeter-gram-second (CGS) units

Prior to the introduction of the SI, many units were defined in measurement systems based upon the centimeter, gram, and second (CGS units) and given special names. Do not use any of these units.

A few examples of CGS units with special names that are not to be used are:

- In mechanics and fluid mechanics: erg, dyne, gal, poise, stokes
- In photometry: stilb, phot, lambert

In electricity and magnetism, the so-called electrostatic units (esu) and electromagnetic units (emu) are further examples of CGS units. Do not use any of the units in these systems, including those with special names such as gauss, maxwell, oersted, gilbert, biot, and franklin. This prohibition extends also to those units with names formed with the prefixes *ab* and *stat*, such as the abampere and the statvolt.

These and other examples of units not to be used can be found in Table 8.