



**International
Standard**

ISO 13118

**Textile — Biaxial tensile properties
of woven fabric — Determination
of elasticity properties using a
cruciform test piece**

*Textiles — Propriétés biaxiales des tissus — Détermination des
propriétés d'élasticité au moyen d'éprouvette cruciforme*

**First edition
2024-09**

Reference number
ISO 13118:2024(en)

Full document details: [ISO 13118-2024](#)

© ISO 2024  **Documents**
Document Sharing Hub



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	3
5 Sampling	3
6 Apparatus	3
6.1 CRE biaxial tensile testing machine	3
7 Atmosphere for conditioning and testing	4
8 Preparation of test specimens	4
8.1 General	4
8.2 Test specimen preparation	4
9 Procedure	5
9.1 Gauge length	5
9.2 Rate of extension	5
9.3 Mounting of test specimen	5
9.4 Loading	5
9.5 Operation	5
10 Recording	5
11 Calculation and expression of test results	5
12 Test report	6
Annex A (informative) Example of a typical cycling graph	8
Annex B (informative) Example of a pattern for cutting test specimens from a laboratory sample	9
Annex C (normative) Preparation of test specimen	10
Bibliography	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 38, *Textiles*, Subcommittee SC 24, *Conditioning atmospheres and physical tests for textile fabrics*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Textile — Biaxial tensile properties of woven fabric — Determination of elasticity properties using a cruciform test piece

1 Scope

This document specifies a test method for determination of the elasticity and related properties of woven textile fabrics, using biaxial stress states, which exhibit stretch characteristics imparted by the presence of an elastomeric fibre, mechanical, or chemical treatment.

This biaxial elasticity test is restricted to the use of constant rate of extension (CRE) testing machine.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 139, *Textiles — Standard atmospheres for conditioning and testing*

ISO 7500-1, *Metallic materials — Calibration and verification of static uniaxial testing machines — Part 1: Tension/compression testing machines — Calibration and verification of the force-measuring system*

3 Terms and definitions

For the purposes of this document, the terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

biaxial elasticity test

method for measuring the stress-strain curves of test specimens subject to biaxial tension using a cruciform test piece

3.2

CRE biaxial tensile testing machine

testing machine for applying biaxial tensile stress with a constant speed to a test specimen in the orthogonal directions parallel to the arms of the cruciform test piece

3.3

grip separation length

distance between the two gripping points of the testing device

3.4

gauge length

distance between the two effective gauge mark points of the test specimen in each direction