INTERNATIONAL STANDARD

ISO 16460

First edition
2021-04

Intelligent transport systems — Localized communications — Communication protocol messages for global usage

Systèmes de transport intelligents — Communications localisées — Messages de protocole de communication pour une utilisation globale

Reference number
ISO 16460:2021(E)

Documents
Document Sharing Hub
© ISO 2021

Full document details: ISO 16460-2021

COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO 2021 – All rights reserved

Documents
Document Sharing Hub

Full document details: ISO 16460-2021

Contents

Page

Foreword ... **iv**
Introduction ... **v**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 Symbols and abbreviated terms ... **1**
5 Localized communications messages ... **3**
5.1 Purpose ... 3
5.2 Localized message protocol ... 3
5.3 Message formats ... 3
5.4 Networking features ... 4
5.4.1 Subtype values ... 4
5.4.2 Networking feature 0 ... 5
5.4.3 Networking feature 1 ... 5
5.4.4 Networking feature 2 ... 6
5.4.5 N-Extensions ... 7
5.4.6 TPID values ... 7
5.5 Transport features ... 8
5.5.1 Transport feature 0 ... 8
5.5.2 Transport feature 1 ... 9
5.5.3 Transport feature 2 ... 10
5.5.4 T-Extensions ... 11
5.5.5 ITS port numbers ... 11
5.6 Procedures ... 11
6 Service advertisement messages ... **12**
6.1 Purpose ... 12
6.2 Unique identifiers ... 12
6.2.1 ITS-AID/PSID ... 12
6.2.2 ITS port numbers (ITS-PNs) ... 13
6.3 Service advertisement protocol ... 13
6.4 Service advertisement message (SAM) ... 13
6.4.1 Messages ... 13
6.4.2 Message structure ... 13
6.4.3 Message header ... 14
6.4.4 Message body ... 16
6.5 Service Response Message (SRM) ... 22
6.5.1 Message structure ... 22
6.5.2 Message header ... 23
6.5.3 Message body ... 23
6.6 Count N ... 27
6.7 Procedures ... 27
6.7.1 General ... 27
6.7.2 Privately allocated channels ... 27
6.8 Secured messages ... 28
7 Structure of extension elements ... **29**
Annex A (normative) **ASN.1 modules** ... **31**
Bibliography ... **45**

© ISO 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO 16460-2021

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www. iso. org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www. iso. org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www. iso. org/iso/foreword. html.

This document was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*.

This first edition cancels and replaces the first edition (ISO/TS 16460:2016), which has been technically revised.

The main changes compared to the previous edition are as follows:

— editorial improvements;

— editorial corrections.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2021 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO 16460-2021

Introduction

This document belongs to a set of International Standards for Intelligent Transport Systems (ITS) and Cooperative ITS (C-ITS). An introduction to this set of International Standards is provided in ISO 21217.

Localized communications, i.e. communications without networking through nodes, and service advertisement are essential protocol functionalities in C-ITS. ISO and IEEE developed protocols with similar functionality, i.e. the

— ISO Fast Networking & Transport Protocol (FNTP) standardized in ISO 29281-1;

— IEEE WAVE Short Message Protocol (WSMP) standardized in IEEE 1609.3[15],

— ISO Fast Service Advertisement Protocol (FSAP) standardized in ISO 24102-5,

— IEEE WAVE Service Advertisement (WSA) standardized in IEEE 1609.3[15],

where ISO considered the architectural context of an ITS station specified in ISO 21217:2014, and IEEE considered the architectural context of a WAVE device specified in IEEE 1609.0[13].

Although initial versions of these protocols from ISO and IEEE are very similar, there are differences in details of the message formats and the functionality. These differences were identified by the EU/US task force HTG 3, from which a recommendation resulted to harmonize the protocols[20].

The result of harmonization of FNTP with WSMP, and of FSAP with WSA is presented in this document, distinguishing interoperability modes, and enhanced features specified in this document.

With reference to this document, the initial editions of ISO 29281-1 and IEEE 1609.3 were revised, and ISO 24102-5 was converted into EN ISO 22418, enabling global interoperability of equipment designed for different architectures. Finally, ETSI developed EN 302 890-1 (a further service announcement protocol profile) with reference to the previous edition of this document, i.e. ISO/TS 16460:2016.

© ISO 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO 16460-2021

Documents
Document Sharing Hub

Full document details: ISO 16460-2021

Intelligent transport systems — Localized communications — Communication protocol messages for global usage

1 Scope

This document specifies:

— the Localized Message (LM) format: an NPDU of a networking & transport layer protocol that does not support routing of a packet through a network;

— the Service Advertisement Message (SAM): an APDU to be transported in an LM, for example;

— the Service Response Message (SRM): an APDU acknowledging a SAM that offered a service based on an ITS application class[2] to be transported in an LM, for example;

— related basic requirements for procedures.

Specifications are partly made by normative references to IEEE 1609.3(TM)-2016.

NOTE These message format specifications and basic procedures need to be complemented by complete procedures and SAP specifications according to the context of usage, i.e. an ITS station specified in ISO 21217, or a WAVE device specified in IEEE 1609.0[13] or any other context.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 8824-1, *Information technology — Abstract Syntax Notation One (ASN.1): Specification of basic notation*

IEEE 1609.3(TM)-2016: *Standard for Wireless Access in Vehicular Environments (WAVE) — Networking Services*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

4 Symbols and abbreviated terms

CIP	communication interface parameter
C-ITS	cooperative ITS
DNS	domain name server
EIRP	effective isotropic radiated power

© ISO 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO 16460-2021

ESAP	ETSI Service Announcement Protocol
FNTP	Fast Networking & Transport Protocol
FSAP	Fast Service Advertisement Protocol
HTG	Harmonization Task Group
IPv6	Internet Protocol version 6
ITS	Intelligent Transport Systems
ITS-AID	ITS application identifier
ITS-PN	ITS port number
LM	localized message
LPP	Local Port Protocol
MAC	medium access control
NPDU	network protocol data unit
OER	octet encoding rules
OSI	open system interconnection
PSID	provider service identifier
RX CIP	receiver CIP
SAM	service advertisement message
SAM-ID	SAM identifier
SAM-Count	SAM change of content identifier
SAP	service access point
SRM	service response message
TCP	transmission control protocol
TPID	transport protocol identifier
TX CIP	transmitter CIP
UPER	unaligned packet encoding rules
VANET	vehicular ad-hoc network
WAVE	wireless access in vehicular environment
WSA	WAVE service advertisement
WSMP	WAVE short message protocol

© ISO 2021 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO 16460-2021

5 Localized communications messages

5.1 Purpose

Localized communication is used to communicate with nearby peer stations, e.g. ITS station units or WAVE devices. These stations are uniquely identified with an OSI data link layer address, typically by the MAC address. Networking in the sense of IP networking, where stations route packets to other nodes through a network (cloud), is not supported. Nevertheless, multi-hopping can be performed in different ways, e.g.:

— N-hop broadcast or N-hop multicast, which requires careful means to avoid flooding of the communication channel;

— dedicated forwarding performed at higher layers, e.g. at the ITS-S facilities layer of an ITS station[4]; this is a feature useful for geo-dissemination of information,

which create so-called "Vehicular Ad-hoc NETworks" (VANETs). Routing of packets through a network in ITS will use the Internet protocol version 6 (IPv6).

5.2 Localized message protocol

As this document does not specify a specific localized communications protocol but just the structure of messages of such protocols and related basic requirements, a hypothetical localized communications protocol with the name "Localized Message Protocol" is used to simplify reading of the document.

5.3 Message formats

Figure 1 illustrates the basic format of the LM. Unaligned packet encoding rules UPER applied to the ASN.1 type `LMnpdu` defined in A.2.1 result in the intended binary presentation of this LM format.

<table>
<tr><td colspan="11">LM NPDU</td></tr>
<tr><td colspan="6">N-Header</td><td colspan="4">T-Header</td><td>Body</td></tr>
<tr><td>4 bits</td><td>1 bit</td><td>3 bits</td><td>Variable</td><td>Variable</td><td>7 bits</td><td>1 bit</td><td>Variable</td><td>Variable</td><td>1 .. 2 octets</td><td>Variable</td></tr>
<tr><td rowspan="2">Subtype</td><td rowspan="2">N-Extensions flag</td><td rowspan="2">Version</td><td rowspan="2">Depends on Subtype</td><td rowspan="2">N-Extensions</td><td colspan="2">TPID</td><td rowspan="2">Depends on TPID</td><td rowspan="2">T-Extensions</td><td rowspan="2">Length of User Data</td><td rowspan="2">User Data</td></tr>
<tr><td>Feature selector</td><td>T-Extensions flag</td></tr>
</table>

NOTE In Figure 1 the "TPID" field (specified in IEEE 1609.3(TM)-2016 as a 1-octet unsigned Integer field completely allocated in the WSMP-N-Header) is split into a "Feature selector" field of the "N-Header" and a "T-Extensions flag" field of the "T-Header" (according to the general rules of the OSI model). However, the two presentations result in identical binary presentations.

Figure 1 — General format of the LM NPDU

The LM consists of three parts:

— "N-Header"

  — A 4-bit unsigned Integer "Subtype" number in the range of 0 to 15 indicating a networking related feature.

  — A 1-bit "N-Extensions flag".

  — A 3-bit unsigned Integer "Version" number in the range of 0 to 7 indicating the version of the localized message protocol. In case a receiver does not support the version, the received packet cannot be processed. The first version number used is three in accordance with IEEE 1609.3(TM):2016.

© ISO 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO 16460-2021

NOTE 1 The format presented in Figure 1 is such that WAVE devices implementing version 2 of WSMP[15] can identify LMs as WSMP messages with version number 3 or higher.

  — A networking related feature specified in 5.4 and selected by the value contained in the field "Subtype".

  — "N-Extensions" being present if the "N-Extensions flag" is set to '1'b.

  — A 7-bit unsigned Integer in the range of 0 to 127, the " TPID - Feature selector", indicating content in the "T-Header".

— "T-Header".

  — A 1-bit "TPID - T-Extensions flag".

  — A transport related feature specified in 5.5 and selected by the TPID - Feature selector value contained in the "N-Header".

  — "T-Extensions" being present if the "T-Extension flag" is set to '1'b.

  — A one or two octet field indicating the number of octets contained in "User data".

— Body.

  — The "User data".

The distinction of "N-Header" (networking related features) and "T-Header" (transport related features) is in line with the OSI layers 3 and 4; these two OSI layers constitute the ITS-S networking & transport layer as illustrated in ISO 21217.

The field "Length of User data" has a length of one or two octets dependent on the value contained in it:

— One octet size: Values from 0 through 127. The most significant bit is always set to zero. Presentation as 0x00 (=0) through 0xEF (=127), i.e. the remaining 7 bits contain an unsigned integer number.

— Two octet size: Values from 128 through 16383. The most significant bit of the first octet is always set to one, and the second most significant bit of the first octet is always set to zero. Presentation as 0x8080 (=128) through 0xBFFF (=16383), i.e. the remaining 14 bits contain an unsigned integer number.

NOTE 2 This presentation results from the unaligned packed encoding rules applied to ASN.1 types of unconstraint variable length.

5.4 Networking features

5.4.1 Subtype values

Networking features are identified by a Subtype value. Subtype values are presented in Table 1.

Table 1 — Subtype values

Subtype	N-Extensions flag	N-Extensions	Networking related features	Remark
0	'0'b	Not present	Null-Networking	Mandatory feature specified in IEEE 1609.3(TM)-2016. Format specified in 5.4.2.
	'1'b	Present		
1	'0'b	Not present	ITS station-internal forwarding	Format specified in 5.4.3.
	'1'b	Present		
2	'0'b	Not present	N-hop forwarding	Format specified in 5.4.4.
	'1'b	Present		

© ISO 2021 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO 16460-2021

Table 1 *(continued)*

Subtype	N-Extensions flag	N-Extensions	Networking related features	Remark
3	'0'b	Not present	Geo-forwarding	Reserved. Not specified in this version of the Document.
	'1'b	Present		
4 - 7	'0'b	Not present	Reserved for ISO	Allows for further four networking features.
	'1'b	Present		
8 - 15	'0'b	Not present	Reserved for IEEE	Allows for further eight networking features.
	'1'b	Present		

N-Extensions and related basic procedures shall be as specified in 5.4.5.

New networking features can be specified and linked to so far reserved Subtype values at a later stage without breaking backward compatibility.

5.4.2 Networking feature 0

Subtype 0 selects the "Null-Networking" feature introduced in 5.4.1.

NOTE Procedures on how to use this feature in the context of an ITS station unit, or a WAVE device, or any other context are outside the scope of this document.

The "Null-Networking" feature with Subtype 0 is the uppermost simple feature, as it requires only processing of the TPID - Feature selector field specified in 5.6. Figure 2 presents the N-Header format for Subtype 0 with N-Extensions being absent.

N-Header			
4 bits	*1 bit*	*3 bits*	*7 bits*
Subtype = 0	N-Extensions flag = '0'b	Version	TPID - Feature Selector

Figure 2 — N-Header for Subtype 0 without N-Extensions

Figure 3 presents the N-Header format for Subtype 0 with N-Extensions being present.

N-Header				
4 bits	*1 bit*	*3 bits*	*Variable*	*7 bits*
Subtype = 0	N-Extensions flag = '1'b	Version	N-Extensions	TPID - Feature Selector

Figure 3 — N-Header for Subtype 0 with N-Extensions

N-Extensions and related basic procedures shall be as specified in 5.4.5.

5.4.3 Networking feature 1

Subtype 1 selects the "ITS Station-Internal Forwarding" feature introduced in 5.4.1.

NOTE Procedures on how to use this feature in the context of an ITS station unit, or a WAVE device, or any other context are outside the scope of this document.

ITS station-internal forwarding is a feature applicable in ITS stations conformant with ISO 21218 (Link-ID) and ISO 24102-4 (ITS-SCU-ID). It is used to forward packets between router units and host units that are part of the same station/device. The field "Direction" contains an unsigned integer number with the

© ISO 2021 – All rights reserved

AVA Documents Document Sharing Hub
Full document details: ISO 16460-2021

two possible values "0" ("from host to router") and "255" ("from router to host"). The field "Counter" contains a 1-octet unsigned integer cyclic packet counter being unique in the unit that forwards a packet. Figure 4 presents the N-Header format for Subtype 1 with N-Extensions being absent.

N-Header								
4 bits	*1 bit*	*3 bits*	*1 octet*	*2 octets*	*8 octets*	*1 octet*	*variable*	*7 bits*
Subtype = 1	N-Extensions flag = '0'b	Version	Direction	ITS-SCU-ID ITS-S host	Link-ID VCI in ITS-S router	Counter	Original N-Header	TPID - Feature Selector

Figure 4 — N-Header for Subtype 1 without N-Extensions

Figure 5 presents the N-Header format for Subtype 1 with N-Extensions being present.

N-Header									
4 bits	*1 bit*	*3 bits*	*1 octet*	*2 octets*	*8 octets*	*1 octet*	*Variable*	*variable*	*7 bits*
Subtype = 1	N-Extensions flag = '1'b	Version	Direction	ITS-SCU-ID ITS-S host	Link-ID VCI in ITS-S router	Counter	N-Extensions	Original N-Header	TPID - Feature Selector

Figure 5 — N-Header for Subtype 1 with N-Extensions

NOTE In Figure 5, unlike in the presentation in Figure 1, subtype-specific elements (i.e. "Original N-Header") are allocated between "N-Extensions" and "TPID - Feature Selector". This is to simplify processing at the receiver side.

N-Extensions and related basic procedures shall be as specified in 5.4.5.

5.4.4 Networking feature 2

Subtype 2 select the "N-hop Forwarding" feature introduced in 5.4.1.

NOTE Procedures on how to use this feature in the context of an ITS station unit, or a WAVE device, or any other context are outside the scope of this document.

N-hop forwarding is a feature that allows extending the communication range for information dissemination (MAC broadcast or multicast mode) beyond the next directly reachable neighbour stations. It uses parameters that allow flooding of the communication channel to be avoided. Figure 6 presents the N-Header format for Subtype 2 with N-Extensions being absent.

N-Header					
4 bits	*1 bit*	*3 bits*	*22 bit*	*2 bit*	*7 bits*
Subtype = 2	N-Extensions flag = '0'b	Version	Message ID	Hop Count	TPID - Feature Selector

Figure 6 — N-Header for Subtype 2 without N-Extensions

The 22-bit Message ID is generated from a random number generator and is unique within the N-hop communication range with a "high" likelihood. In case of duplicate Message ID values, forwarding might not be performed correctly in a station.

The 2-bit unsigned Integer Hop Count indicates to a receiver whether a forwarding shall be performed or not. If the Hop Count equals zero, forwarding is prohibited. Prior to forwarding of a packet, the Hop Count shall be decremented by one. Consequently, a maximum of four hops is possible.

© ISO 2021 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO 16460-2021

Forwarding shall be performed also if the TPID value contained in the received message is not supported or is reserved.

Figure 7 presents the N-Header format for Subtype 2 with N-Extensions being present.

N-Header						
4 bits	*1 bit*	*3 bits*	*22 bit*	*2 bit*	*Variable*	*7 bits*
Subtype = 2	N-Extensions flag = '1'b	Version	Message ID	Hop Count	N-Extensions	TPID - Feature Selector

Figure 7 — N-Header for Subtype 2 with N-Extensions

N-Extensions and related procedures shall be as specified in 5.4.5.

5.4.5 N-Extensions

The structure of the N-Extensions is specified in Clause 7. Extension elements presented in Table 2 may be used in the "N-Extensions" field.

Table 2 — N-Extensions elements

Element ID	Element type (ASN.1)	Element name
`c-TxPowerUsed80211`= 4	`TXpower80211`	Transmit Power Used (specified in IEEE 1609.3(TM)-2016).
`c-ChannelNumber80211` = 15	`ChannelNumber80211`	802.11 Channel Number used (specified in IEEE 1609.3(TM)-2016).
`c-DataRate80211` = 16	`DataRate80211`	802.11 Data Rate used (specified in IEEE 1609.3(TM)-2016).
`c-LMtxCip` = 80	`TXcip`	Communication Interface transmit parameters.
`c-LMrxCip` = 81	`RXcip`	Communication Interface receive parameters (RX-CIP).
`c-LMchannelBusyRatio` = 82	`LMchannelBusyRatio`	Channel Busy Ratio.

The "Transmit Power Used" element is optionally included in the LM N-Header for use by the LM recipient; see also IEEE Std 802.11[12].

The "Channel Number" element is optionally included in the LM N-Header for use by the LM recipient; see also IEEE Std 802.11[12].

The "Data Rate" element is optionally included in the LM N-Header for use by the LM recipient; see also IEEE Std 802.11[12].

The "TX CIP" element is optionally included in the LM N-Header indicating CIP settings used by the transmitter of the LM.

The "RX CIP" element is optionally included in the LM N-Header used with Subtype 1 indicating CIP settings of the ITS-SCU that received the LM from a peer station.

The "Channel Busy Ratio" element is a one octet unsigned integer optionally included in the LM N-Header reporting the observed channel busy ratio in percent (0 % up to 100 % in steps of 0,5 %). The integer values 201 through 255 indicate "unknown ratio".

5.4.6 TPID values

Table 3 provides a summary of TPID values.

© ISO 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO 16460-2021

Table 3 — TPID values

TPID		T-Extensions	Transport related feature	Remark
Feature selector	T-Extensions flag			
0	'0'b	Not present	Information dissemination	Mandatory feature specified in IEEE 1609.3(TM)-2016. Format specified in 5.5.1.
	'1'b	Present		
1	'0'b	Not present	General session mode	Format specified in 5.5.2,
	'1'b	Present		
2	'0'b	Not present	LPP mode	Format specified in 5.5.3.
	'1'b	Present		
3 - 10	'0'b	Not present	Reserved for ISO	Allows for further 8 transport features.
	'1'b	Present		
11 - 127	'0'b	Not present	Reserved for IEEE	Allows for further 117 transport features.
	'1'b	Present		

New transport features can be specified and linked to so far reserved TPID - Feature selector values at a later stage without breaking backward compatibility.

5.5 Transport features

5.5.1 Transport feature 0

The TPID feature selector 0 selects the "Information Dissemination" feature specified in 5.4.6.

Figure 8 presents the T-Header for TPID = 1, i.e. with T-Extensions being present.

T-Header (TPID = 1)			
1 bit	*Variable*	*Variable*	*Variable*
TPID T-Extensions flag = '1'b	Destination Address *ITS-AID*	T-Extensions	Length of User data

Figure 8 — TPID 1 — Information dissemination with T-Extensions

The T-header consists of four parts:

— a 1-bit "T-Extensions flag" (LSB of TPID) set to '1'b;

— a variable length "Destination Address" field containing an ITS-AID specified in ISO 17419 identifying the upper layer entity (referred to as ITS-S application process in ISO 21217) in the receiver for which the message is intended;

— a variable length "T-Extensions" field with the structure specified in Clause 7 and content details specified in 5.5.4;

— a variable length field indicating the length of the User data.

NOTE PSID specified in IEEE 1609.3(TM)-2016 and ITS-AID share a common number space; see 6.2.1. In the given context, PSID and ITS-AID are presented with the same ASN.1 type.

If no T-Extensions are needed, the T-Extensions flag is set to '0'b. The corresponding T-Header is presented in Figure 9.

© ISO 2021 – All rights reserved
Documents Document Sharing Hub
Full document details: ISO 16460-2021

T-Header (TPID = 0)		
1 bit	*Variable*	*Variable*
TPID T-Extensions flag = '0'b	Destination Address *ITS-AID*	Length of User data

Figure 9 — TPID 0 — Information dissemination without T-Extensions

Feature 0 is designed for information dissemination (typically combined with MAC broadcast or MAC multicast).

A receiver shall first check the T-Extensions and shall perform related procedures, if supported. Then the receiver shall forward the data contained in the message (optionally together with information contained in T-Extensions) to the recipient(s) identified by the Destination Address.

NOTE 1 If the Destination Address is not identifying a known upper layer entity, the receiver cannot further process the message.

NOTE 2 Procedures on how to use this feature in the context of an ITS station unit, or a WAVE device, or any other context are outside the scope of this document.

5.5.2 Transport feature 1

The TPID feature selector 1 selects the "General Session Mode" feature specified in 5.4.6.

Figure 10 presents the T-Header for TPID = 3, i.e. with T-Extensions being present.

T-Header (TPID = 3)				
1 bit	*2 octets*	*2 octets*	*Variable*	*Variable*
TPID T-Extensions flag = '1'b	Source Address *ITS port number*	Destination Address *ITS port number*	T-Extensions	Length of User data

Figure 10 — TPID 3 — general purpose session support transport feature with T-Extensions

The T-Header consists of five parts:

— a 1-bit "T-Extensions flag" (LSB of TPID) set to '1'b;

— a 2-octet ITS port number in the "Source Address" field identifying the address of the upper layer entity in the transmitter;

— a 2-octet ITS port number in the "Destination Address" field identifying the address of the upper layer entity in the receiver;

— a variable length "T-Extensions" field with the structure specified in Clause 7 and content details specified in 5.5.4;

— a variable length field indicating the length of the User data.

If no T-Extensions are needed, the T-Extensions flag is set to '0'b. The corresponding T-Header is presented in Figure 11.

© ISO 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO 16460-2021

T-Header (TPID = 2)			
1 bit	*2 octets*	*2 octets*	*Variable*
TPID T-Extensions flag = '0'b	Source Address *ITS port number*	Destination Address *ITS port number*	Length of User data

Figure 11 — TPID 2 — General purpose session support transport feature without T-Extensions

Feature 1 is designed for sessions when a reply is expected, for example. Note that groupcast transmissions with no expected reply can also use this TPID.

A receiver shall first check the T-Extensions and shall perform related procedures, if supported. Then the receiver shall forward the data contained in the message (optionally together with information contained in T-Extensions) to the recipient(s) identified by the ITS port number contained in the Destination Address field.

NOTE 1 If the Destination Address ITS port number is not identifying a known upper layer entity, the receiver cannot further process the message.

The ITS port number contained in the Source Address field is typically used in the Destination Address field of replies to the transmitter.

NOTE 2 Procedures on how to use this feature in the context of an ITS station unit, or a WAVE device, or any other context are outside the scope of this document.

5.5.3 Transport feature 2

The TPID feature selector 2 selects the "LPP" feature specified in 5.4.6. LPP is the "Local Port Protocol" standardized in ARIB STD-T88[18].

Figure 12 presents the T-Header for TPID = 5, i.e. with T-Extensions being present.

T-Header (TPID = 5)					
1 bit	*2 octets*	*2 octets*	*variable*	*Variable*	*Variable*
TPID T-Extensions flag = '1'b	Source Address *ITS port number*	Destination Address *ITS port number*	LPP Header ARIB STD-T88:2004, *DSRC application sub-layer*	T-Extensions	Length of User data

Figure 12 — TPID 5 — LPP feature with T-Extensions

The T-Header consists of six parts:

— a one bit "T-Extensions flag" (LSB of TPID) set to '1'b;

— a 2-octet ITS port number in the "Source Address" field identifying the address of the upper layer entity in the transmitter;

— a 2-octet ITS port number in the "Destination Address" field identifying the address of the upper layer entity in the receiver;

— the "LPP Header" specified in ARIB STD-T88[18];

— a variable length "T-Extensions" field with the structure specified in Clause 7 and content details specified in 5.5.4;

— a variable length field indicating the length of the User data.

© ISO 2021 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO 16460-2021

If no T-Extensions are needed, the T-Extensions flag is set to '0'b. The corresponding T-Header is presented in Figure 13.

T-Header (TPID = 4)				
1 bit	*2 octets*	*2 octets*	*variable*	*Variable*
TPID T-Extensions flag = '0'b	Source Address *ITS port number*	Destination Address *ITS port number*	LPP Header ARIB STD-T88:2004, *DSRC application sub-layer*	Length of User data

Figure 13 — TPID 4 — LPP feature without T-Extensions

NOTE 1 If the Destination Address ITS port number is not identifying a known upper layer entity, the receiver cannot further process the message.

NOTE 2 Procedures on how to use this feature in the context of an ITS station unit, or a WAVE device, or any other context are outside the scope of this document.

5.5.4 T-Extensions

The structure of the T-Extensions is specified in Clause 7. Extension elements presented in Table 4 may be used in the "T-Extensions" field.

Table 4 — T-Extensions elements

Element ID	Element type	Element name
`c-LMpacketID` = 83	`LMpacketID`	Packet Identifier. Composed of — TPmessageID, — TPfragmentID, — TPnoFragments.

The "Packet Identifier" element is optionally included in the LM T-Header to identify uniquely a specific packet in a sequence of packets from a specific transmitter. TPmessageID is used to uniquely distinguish different messages. TPfragmentID (1 ≤ TPfragmentID ≤ TPnoFragments) identifies the number of the given fragment out of the total number TPnoFragments of the message.

5.5.5 ITS port numbers

ITS port numbers are unsigned integer numbers of ASN.1 type `PortNumber` in the range 0 to 65535, i.e. contained in two octets. Details of ITS port numbers usage and management are presented in ISO 17419.

5.6 Procedures

A receiver shall first inspect the Version field specified in 5.2. If the presented version is supported by the implementation, then the receiver shall inspect the Subtype field specified in 5.2 and in 5.4.1.

NOTE 1 If the presented version is not supported in a given implementation, the message cannot be processed.

If the presented subtype is supported by the implementation, then the related procedure shall be performed as specified in 5.4.2 to 5.4.4.

NOTE 2 If a received subtype value is pointing to `NoSubtypeProcessing`, i.e. not supported in a given implementation, the message cannot be processed.

Upon successful processing of the subtype procedure, the receiver shall inspect the TPID - Feature selector field specified in 5.2 and in 5.4.6.

© ISO 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO 16460-2021