
**Respiratory protective devices —
Human factors —**

**Part 4:
Work of breathing and breathing
resistance: physiologically based
limits**

Appareils de protection respiratoire — Facteurs humains —

*Partie 4: Travail de respiration et résistance respiratoire : limites
physiologiques*





COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
5 Pressure and volume changes during breathing	3
5.1 Pressure and volume changes in the absence of an RPD	3
5.2 The effect of RPD flow resistance on pressure and volume changes while using an RPD	6
5.3 The effect of RPD with static pressure on pressure and volume changes while using an RPD	6
5.4 The effect of RPD flow resistance and static pressure on pressure and volume changes while using an RPD	7
5.5 Effects of high static pressure	7
6 Work of breathing (WoB)	8
6.1 Physiological work versus physical work	8
6.1.1 General	8
6.1.2 Static work	8
6.1.3 Elastic work	8
6.1.4 Positive and negative physical work	9
6.2 Calculations of inspiratory WoB	9
6.3 Calculations of expiratory WoB	9
6.4 Calculations of total WoB	10
6.4.1 Calculations of the wearer's WoB while using an RPD	10
6.4.2 Calculations of WoB for an RPD only	10
6.5 Breathing resistance	11
6.6 Physiologically acceptable WoB	11
7 Other respiratory loads	13
7.1 Static load	13
7.2 Elastic loads	13
7.3 Other loads	13
7.4 How respiratory loads add up	13
8 Summary	14
Bibliography	15

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 94, *Personal safety — Personal protective equipment*, Subcommittee SC 15, *Respiratory protective devices*.

This first edition of ISO 16976-4 cancels and replaces the second edition of the Technical Specification ISO/TS 16976-4:2019, which has been technically revised.

The main changes are as follows:

— the document has been editorially revised.

A list of all parts in the ISO 16976 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

A respiratory protective device (RPD) is designed to offer protection from the inhalation of hazardous substances. However, this protection requires extra effort by the respiratory muscles as they need to generate higher pressures to overcome the associated respiratory loads imposed by the RPD.

Respiratory protective devices — Human factors —

Part 4:

Work of breathing and breathing resistance: physiologically based limits

1 Scope

This document describes how to calculate the work performed by a person's respiratory muscles with and without the external respiratory impediments that are imposed by RPD of all kinds, except diving equipment. This document describes how much additional impediment people can tolerate and contains values that can be used to judge the acceptability of an RPD.

NOTE These calculations are explained in some textbooks on respiratory physiology (in the absence of an RPD), but most omit them or are incomplete in their explanations.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 16972, *Respiratory protective devices — Vocabulary and graphical symbols*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16972 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

body temperature pressure saturated

BTPS

standard condition for the expression of ventilation parameters

EXAMPLE Body temperature (37 °C), atmospheric pressure (1 013,25 hPa) and water vapour pressure (6,27 kPa) in saturated air.

Note 1 to entry: It is the atmospheric pressure at the test location that should be used whenever BTPS conditions are specified.

3.2

compliance

change in volume of the human lung that results from a change in pressure

Note 1 to entry: The compliance is measured in l/kPa.

Note 2 to entry: This term is the typical term for the elastic behaviour of the lungs and chest. Compliance is the inverse of elastance.

3.3
elastance

change in pressure that results from a given volume change of the human lung

Note 1 to entry: The elastance is measured in kPa/l.

Note 2 to entry: This term is the typical term for the elastic behaviour of an RPD. Elastance is the inverse of compliance.

3.4
relaxation volume

lung volume when respiratory muscles are relaxed, i.e. the volume at the beginning of an inspiration, also known as functional residual capacity (FRC) and expiratory reserve volume (ERV)

3.5
tidal volume

V_T
volume of a breath

Note 1 to entry: The tidal volume is measured in litres BTPS.

3.6
vital capacity

VC
volume of the largest breath a person can take, i.e. the volume difference between a maximum inspiration and a maximum expiration

Note 1 to entry: The vital capacity is measured in litres BTPS.

3.7
work of breathing

WoB
work required for an entire breathing cycle

Note 1 to entry: The work in breathing is measured in Joules.

3.8
work of breathing per tidal volume

WoB/V_T
normalized *WoB* (3.7) (equivalent to volume-averaged pressure)

Note 1 to entry: The work in breathing per tidal volume is measured in Joules per litre = kPa.

4 Symbols and abbreviated terms

BTPS	body temperature pressure saturated
ERV	expiratory reserve volume
FRC	functional residual capacity
RPD	respiratory protective device
VC	vital capacity
WoB	work of breathing
p_{el}	pressure required to overcome the elastance
p_{aw}	pressure required to overcome the flow resistance of the airways