



International
Standard

ISO 7447

**Underwater acoustics —
Measurement of radiated
underwater sound from percussive
pile driving — In situ determination
of the insertion loss of barrier
control measures underwater**

*Acoustique sous-marine — Mesurage de l'émission sonore sous-marine lors de l'enfoncement de pieux marins par percussion
— Détermination in situ de la perte par insertion de barrières sous-marines*

**First edition
2024-09**

Reference number
ISO 7447:2024(en)

Full document details: [ISO 7447-2024](#)

© ISO 2024  **Documents**
Document Sharing Hub



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Instrumentation	2
4.1 General information	2
4.2 Hydrophones and analysers	2
4.3 Analysis software	2
4.4 Calibration	3
5 Methods	3
5.1 General remarks	3
5.2 Comparability of measurements	3
5.3 Background noise	4
5.4 Measurements on one single pile (direct method)	5
5.5 Measurements on two different piles (indirect method)	5
6 Measurement procedure	5
6.1 General remarks	5
6.2 Chronological order of the measurements	6
6.3 Measuring positions	6
6.3.1 General	6
6.3.2 Number of hydrophones/measuring positions	6
6.3.3 Measuring distance	6
6.3.4 Measuring direction	6
6.3.5 Measuring depths	6
6.4 Examples of measuring setups	7
6.4.1 General	7
6.4.2 Measuring setup 1 — Checking for a radially-symmetric effect	8
6.4.3 Measuring setup 2 — Checking for dependence on depth	9
6.4.4 Measuring setup 3 — Measurement with radially-symmetric effect, independent of the respective depth	9
6.5 Functional test and measuring conditions	10
6.6 Measuring quantities and accompanying parameters	10
6.7 Data recording	11
7 Data processing and calculation of acoustic metrics	11
7.1 Data processing steps	11
7.2 Background noise correction	11
7.3 Determination of the insertion loss	12
7.3.1 General	12
7.3.2 Case 1 — Measurement on one pile	12
7.3.3 Case 2 — Measurement on two different piles	12
7.4 Uncertainties	13
7.4.1 General	13
7.4.2 Measurement uncertainty	13
7.4.3 Characterization of noise abatement systems	13
7.5 Sound insulation for broadband level quantities	13
8 Test report	14
8.1 Formal information in the reports	14
8.1.1 Front page	14
8.1.2 Recurring information on the following pages	14
8.1.3 Signatures	14
8.2 Contents of the reports	14

8.2.1 Structuring of contents 14

8.2.2 Description of the measurements..... 15

8.2.3 Presentation of the results..... 16

Annex A (informative) Considerations for near shore piling applications..... 17

Annex B (informative) Sound particle motion and seabed vibration 19

Bibliography 23

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 3, *Underwater acoustics*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Within the scope of approval and licensing procedures for offshore wind energy farms worldwide an assessment is required of whether sound caused by the construction, operation and demolition of wind energy farms represents a possible hazard for the marine environment. To reduce the noise output effective noise abatement systems (noise control measures underwater) can be used to protect the marine environment, see References [12] to [25].

Examples of noise-generating activities are pile driving (e.g. by impact hammer) or pile extraction. Examples for noise abatement systems are bubble curtains and cofferdams whose acoustic efficiency can be demonstrated by applying the methodology described in this document.

This document describes measuring methods for the in situ characterization of the effectiveness of noise abatement systems underwater. The acoustic effectiveness of a system can be derived from measurements carried out with and without the considered noise abatement system, e.g. References [10] and [11]. This acoustic effectiveness of the system is given as insertion loss.

The principles of the method can also be applied in other cases such as construction of docks, piers, wharfs, bridge supports, etc., a procedure is described in [Annex A](#). Sound particle motion and seabed vibration are of increasing interest in ocean acoustics and are dealt with in [Annex B](#).

In general, in acoustic underwater measurements, the influences of the noise source and the noise propagation cannot be completely separated. For example, the soil properties have a direct influence on the noise source. Another influence is the sound propagation and sound radiation via the sea bottom.

Results acquired in accordance with this specification are necessary and useful for

- comparison with acoustical specifications, e.g. within the scope of approval procedures,
- comparison with different noise abatement systems, and
- further development and improvement of noise abatement systems.

Underwater acoustics — Measurement of radiated underwater sound from percussive pile driving — In situ determination of the insertion loss of barrier control measures underwater

1 Scope

This document specifies two procedures for the in situ determination of the insertion loss of underwater noise abatement measures (noise abatement systems). The impulsive sound of pile driving is used as the sound source for the investigation of noise abatement systems. This document does not apply to artificial sound sources and investigations under laboratory conditions.

Apart from the correct application of the respective noise abatement system, the achieved sound attenuation also depends on the installation conditions (e.g. type of hammer, driving energy, pile dimensioning) as well as on the environmental conditions (e.g. water depth, seafloor classification and bathymetry, current and wind conditions) and the flanking transmission via the seafloor.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 18405, *Underwater acoustics — Terminology*

ISO 18406:2017, *Underwater acoustics — Measurement of radiated underwater sound from percussive pile driving*

3 Terms and definitions

For the purpose of this document, the terms and definitions given in ISO 18405, ISO 18406 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

insertion loss of barriers

$D_p(f)$

difference, in sound pressure levels at a specified receiver position before and after the installation of a barrier

Note 1 to entry: $D_p(f)$ is the sound pressure level without barrier minus the sound pressure level with barrier, in one-third octave (base 10) bands. According to ISO 18405, an alternative name for one-third octave (base 10) is decidecade.

Note 2 to entry: The sound pressure level is determined over multiple pulses.

Note 3 to entry: The insertion loss can also be calculated with sound exposure level. The results are identical to the calculations with sound pressure level using the same integration time T .

Note 4 to entry: For calculation of insertion loss, see [7.3](#).

Note 5 to entry: Insertion loss is expressed in decibels.

[SOURCE: ISO 10847:1997, 3.5, modified — Abbreviation modified and Notes 1 to 4 to entry added.]

3.2

noise abatement system

mitigation measure that attenuates the sound output from the sound source

Note 1 to entry: There are near-pile noise abatement systems, such as cofferdams, where a pipe is built into the water enclosing the pile and the water is pumped out between the pile and the pipe. Applications away from the pile are mostly bubble curtains, see References [12] to [25].

3.3

flanking transmission

transmission of sound from a source (pile) to receiver point but not via the *noise abatement system* (3.2)

[SOURCE: IEC 60050-801-31-40:1994, modified — Term from building acoustics, changed for underwater applications.]

4 Instrumentation

4.1 General information

[Clause 4](#) describes relevant information on instrumentation for underwater measurements. ISO 18406 provides further considerable details on the type of measurements and instrumentation.

4.2 Hydrophones and analysers

The measurement chain for hydroacoustic measurements consists of the following components:

- omnidirectional hydrophone (with preamplifier) with a constant sensitivity that deviates by less than 2 dB over the analysed frequency range;
- analogue high-pass filter (which may be integrated in the measuring amplifier) to limit the low-frequency dynamics of the measuring data;
- measuring device, including the possibility to record time raw data, consisting of low-pass filters (anti-aliasing filters), amplifiers, and A/D converters;
- cables, connecting components, etc.

Furthermore, the following test equipment, devices and recording equipment are required:

- pistonphone for checking the calibration of the hydrophone measuring chain before and after each measurement;
- distance meter (e.g. laser, GPS based);
- equipment to record the data required to determine the sound speed profile (sound speed as a function of depth). For example, CTD sensors are used to determine the temperature, conductivity and the depth below the water surface at the CTD probe. With the measured quantities the sound speed profile can be determined.

4.3 Analysis software

For data post-processing and evaluation, an analysis software is required which comprises the following methods:

- one-third octave (base 10) bands analysis, with the filters corresponding to the requirements in IEC 61260-1;

- narrow-band analysis;
- time averaging.

Filtering may be accomplished using analogue electronic filters, but is more commonly undertaken using digital processing. The digital methods can either utilise implementations of digital filters, or may be achieved by aggregating levels in the frequency domain over the requisite bands (subsequent to a Fourier transform of the time-domain waveform).

Data processing can also be carried out within the measuring device.

4.4 Calibration

The organization performing the measurements shall make sure that the devices of the acoustic measuring chain (including hydrophones) are calibrated traceable to appropriate standards using a suitable method (IEC 60565-1 and IEC 60565-2).

The calibration interval shall be 24 months at maximum. The required calibration certificates shall be kept available for at least 10 years.

5 Methods

5.1 General remarks

Two methods are common for the in situ characterization of noise abatement systems underwater: the direct method (see [5.4](#)) and the indirect method (see [5.5](#)).

5.2 Comparability of measurements

Two methods are described in this document. Both have the objective to determine the in situ insertion loss of an underwater noise abatement system. The descriptions for both approaches are to ensure that excitation and conditions of the sound source as well as transmission properties to the hydrophone positions are comparable for the situation with and without noise mitigation system.

In the following, parameters are listed that could have an influence on the direct and indirect measurements:

- a) configuration and pile characteristics relating to
 - pile geometry (e.g. diameter, length, wall thickness distribution),
 - material,
 - pile head design (e.g. flange), and
 - slant angle to the seabed;
- b) environmental conditions:
 - water depth at pile and hydrophone location and in between pile and hydrophone (bathymetry);
 - distance between pile and noise mitigation system;
 - distance between hydrophone and noise mitigation system;
 - hydrophone depth;
 - properties and layering of the seabed, cpt (cone penetration test) values at site;
 - ocean current[\[27\]](#);
 - wind conditions[\[27\]](#);

- significant wave height^[27] and direction;
- swell height^[27] and direction;

c) operating conditions:

- type of pile driver (e.g. manufacturer, driving/rotational mass, maximum blow energy/operating frequency);
- type of force-conducting connecting elements between pile driver and pile (e.g. anvil);
- hammer energy;
- pulse repetition rate;
- penetration depth;
- number of blows in the noise measurement period.

Any changes in the above conditions that occur between measurements with and without the noise attenuation in place shall be determined and documented.

To ensure comparability of measurements between the unmitigated and mitigated situation, these parameters should all be sufficiently equal.

Ideal equal conditions cannot always be achieved, so quantitative minimum requirements are listed below:

- pile material should be equal, and pile and pile head geometry should not differ more than 10 %;
- flat bathymetry is required: the variation in water depth should not exceed 10 % between source and measurement site;
- measurement geometry (distance between noise mitigation measure and hydrophones to pile and hydrophone depths should not differ more than 10 %);
- hammer energy and pulse repetition rate should not differ more than 10 %.

The combined standard uncertainty should remain <20 %, so that the error in the determination of the insertion loss is <1 dB, see also [7.4](#) on the uncertainty of measurement according to ISO/IEC Guide 98-3.

NOTE 1 Experience shows that the background noise which includes self-noise of the hydrophone measurement device including mooring concept and measurement device can limit the validity of the determination of the in situ insertion loss. In concrete terms, this means that the noise abatement system used can have a higher insertion loss than can be verified by measurement. However, this case would be excluded if requirement [5.3](#) is considered.

NOTE 2 The measurements describe an in situ "insertion loss". The in situ determined insertion loss is therefore dependent on the environmental parameters and the selected measurement configuration. Thus, for each measurement report, the validity range is documented by representations of the above-mentioned parameters, see also [Clause 8](#).

NOTE 3 The parameters water depth, wind, significant wave height and current are important for the documentation of acoustic measures such as the bubble curtain, as the properties can be/are influenced by these parameters. Up to a significant wave height (Hs) of 2 m, no relevant effects on the performance of the noise abatement systems are known from experience. For currents above ~0,75 m/s (and water depths up to ~40 m), experience has shown that the noise reduction in the direction of flow decreases significantly due to drift effects, see Reference [\[24\]](#).

NOTE 4 The parameter soil or soil layering is fundamentally important to document for all noise abatement systems, as this parameter can influence the properties of the insertion loss determined in situ.

5.3 Background noise

According to ISO 18406, the background noise is all sound recorded by the hydrophone in the absence of the pile driving signal for a specified pile driving signal being measured. The sound pressure level of the sound source shall be high enough to create a sound pressure level at the measuring location which exceeds – with and without the respective noise abatement system – the background noise level in the frequency bands