
International Standard



7545

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Shipbuilding and marine structures — Inland navigation — Single-lock automatic couplings for push tows

Construction navale et structures maritimes — Navigation intérieure — Dispositifs d'accouplement automatique à un seul verrou pour convois poussés

First edition — 1983-09-15

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been authorized has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 7545 was developed by Technical Committee ISO/TC 8, *Shipbuilding and marine structures*, and was circulated to the member bodies in February 1982.

It has been approved by the member bodies of the following countries:

Austria	Egypt, Arab Rep. of	Romania
Belgium	India	Spain
Brazil	Japan	United Kingdom
China	Korea, Dem. P. Rep. of	USSR
Czechoslovakia	Korea, Rep. of	Yugoslavia

The member bodies of the following countries expressed disapproval of the document on technical grounds:

France
Germany, F.R.
Netherlands

Shipbuilding and marine structures — Inland navigation — Single-lock automatic couplings for push tows

1 Scope and field of application

This International Standard specifies types and main dimensions of single-lock automatic couplings intended for a bow-to-stern connection of vessels in push tows, navigating in waters with a wave height of not more than 2 m. It also lays down basic technical requirements for the couplings.

This International Standard does not cover side couplings.

2 Definitions

2.1 automatic coupling: A coupling mechanism together with rest elements, ensuring:

- a) a quick connection of vessels;
- b) a reliable and safe bow-to-stern connection of vessels in a push tow travelling and manoeuvring in navigation conditions as stated in this International Standard;
- c) a quick disconnection of the vessels.

2.2 bow-to-stern connection: Connection of the vessels of a push tow in one of the following ways:

- a) the bow of the pushboat to the stern of the non-powered vessel;
- b) the bow of the non-powered vessel to the stern of another non-powered vessel.

2.3 For the purpose of this International Standard, the following designations are applicable:

- a) the automatic single-lock coupling: "coupling";
- b) the system of the coupling mechanism with gripping elements: "coupling lock".

3 Arrangement of coupling

3.1 The bow coupling of pushboat/non-powered vessel shall consist of a coupling lock and rest elements. The coupling lock

shall be set in the centre plane of the vessel, and the rest elements located symmetrically to the coupling lock on either side (see figure 1).

3.2 The stern coupling of a non-powered vessel shall consist of a coupling beam and rest elements. The coupling beam shall be set in the centre plane of the vessel, and the rest elements located symmetrically to the coupling beam on either side (see figure 2).

3.3 The width location of the rest elements shall ensure the possibility of coupling either a pushboat to a non-powered vessel or non-powered vessels to one another.

4 Classification

Two types of couplings are specified:

— **Type A:** for pushboats of up to 220 kW inclusive and for non-powered vessels with a carrying capacity of up to 1 000 t inclusive, operating in waterways with a wave height up to 1,2 m and a maximum wind speed of 12 m/s.

The design stress on the coupling lock shall be not more than 200 kN. The maximum carrying capacity of a push tow shall be not more than 2 000 t.

— **Type B:** for pushboats of over 220 kW up to 1 500 kW inclusive and for non-powered vessels with a carrying capacity of up to 4 000 t inclusive, operating in waterways with a wave height up to 2 m and a maximum wind speed of 19 m/s.

The design stress on the coupling lock shall be not more than 2 000 kN. The maximum carrying capacity of a push tow shall be not more than 19 000 t.

5 Dimensions

The main dimensions, in millimetres, of the couplings shall correspond to figures 3 to 8 and the table.