
**Road vehicles — Spin-on fuel filters for
diesel engines — Mounting and connecting
dimensions**

*Véhicules routiers — Filtres à combustible vissés pour moteurs diesels —
Dimensions de montage et de raccordement*



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 7654 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 7, *Injection equipment and filters for use on road vehicles*.

This third edition cancels and replaces the second edition (ISO 7654:1991), which has been technically revised.

Annex A forms an integral part of this International Standard. Annex B is for information only.

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

Road vehicles — Spin-on fuel filters for diesel engines — Mounting and connecting dimensions

1 Scope

This international Standard specifies the mounting and connecting dimensions for spin-on fuel filters, with and without an inner sealing, to be used with diesel (compression-ignition) engines.

The preferred design of spin-on fuel filters are those without an inner sealing, and they are specified in clause 2. The alternative filter design is specified in annex A and should be used if an inner sealing is required.

The corresponding filter heads are specified in ISO 7310, ISO 7311 and ISO 7577 (see annex B).

2 Dimensions and tolerances

Details not specified in this International Standard are left to the manufacturer's choice.

2.1 The dimensions and tolerances of the filter shall be in accordance with figure 1.

The shape of the sealing ring shown in X shall be such that effective sealing is ensured. The dimensions of the compressed sealing ring shall be within the sealing surface shown in figure 2.

The dimension 0,5 mm min. shown in X shall be measured after tightening the filter in accordance with the filter manufacturer's recommendations. In cases where moulded sealing rings are used, this dimension may be 0; i.e., metal contact between the sealing surface to which the filter is attached and the face of the spin-on filter is allowed. This special design shall be identified on the filter with necessary fitting instructions.

2.2 The dimensions and tolerances of the sealing surface and connecting thread shall be in accordance with figure 2.

3 Marking

Spin-on fuel filters may optionally be marked as follows:

- a) designation of filter type: diesel fuel filter;
- b) size of connecting thread, for example, M16 × 1,5;
- c) instructions for installation.

The appearance and position of this marking on the filter body are left to the discretion of the manufacturer.