

INTERNATIONAL STANDARD

ISO
8128-2

First edition
1993-07-01

Apple juice, apple juice concentrates and drinks containing apple juice — Determination of patulin content —

Part 2:

Method using thin-layer chromatography

*Jus de pommes, concentrés de jus de pommes et boissons à base de jus
de pommes — Détermination de la teneur en patuline —*

Partie 2: Méthode par chromatographie sur couche mince



Reference number
ISO 8128-2:1993(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 8128-2 was prepared by Technical Committee ISO/TC 34, *Agricultural food products*, Sub-Committee SC 3, *Fruit and vegetable products*.

ISO 8128 consists of the following parts, under the general title *Apple juice, apple juice concentrates and drinks containing apple juice — Determination of patulin content*:

- Part 1: *Method using high-performance liquid chromatography*
- Part 2: *Method using thin-layer chromatography*

Annex A of this part of ISO 8128 is for information only.

© ISO 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland
Printed in Switzerland

Apple juice, apple juice concentrates and drinks containing apple juice — Determination of patulin content —

Part 2:

Method using thin-layer chromatography

1 Scope

This part of ISO 8128 specifies a method using thin-layer chromatography for the determination of the patulin content of apple juice, apple juice concentrates and drinks containing apple juice.

The limit of detection of the method is 25 µg/l, based on 50 ml of ready-to-drink apple juice.

NOTE 1 For more precise analyses or in case of a dispute, the HPLC method specified in ISO 8128-1 should be used.

2 Principle

Extraction of patulin in a mixture of ethyl acetate and chloroform (3:2 by volume). Filtration of the extract on a silica-gel column and qualitative and semi-quantitative determination by means of two-directional thin-layer chromatography (TLC). The spots are developed using a 3-méthyl-2-benzothiazoline hydrozone (MBTH) hydrochloride solution.

3 Reagents

Use only reagents of recognized analytical grade and water of the purity required for chromatography.

WARNING — Special attention should be paid when using benzene or chloroform, which are toxic and may cause explosions.

3.1 Solvents, ethyl acetate, chloroform and toluene.

3.2 Developing solvents, for two-directional TLC:)

benzene/methanol/acetic acid (80 % by mass) mixture (19:2:1 by volume);

toluene/ethyl acetate/formic acid (90 % by mass) mixture (5:4:1 by volume).

3.3 Silica gel, for column chromatography, of 0,063 mm to 0,2 mm particle size.

3.4 Eluting solution, toluene/ethyl acetate mixture (75:25 by volume).

3.5 Patulin standard solution (C₇H₆O₄).

3.5.1 Preparation

Weigh, to the nearest 0,1 mg, 10,0 mg of patulin in a 100 ml one-mark volumetric flask and dissolve it in ethyl acetate (3.1). Make up to the mark with ethyl acetate.

Pipette 10,0 ml of this solution into another 100 ml one-mark volumetric flask and make up to the mark with ethyl acetate.

The patulin content of this standard solution is 10 µg/ml approximately.

Measure the absorbance at 276 nm of this standard solution on an appropriate spectrometer using quartz cells of optical path length 10 mm.

NOTE 2 The preparation of the standard solution and the control of its purity are based on reference [3].