

INTERNATIONAL STANDARD

ISO
9614-2

First edition
1996-08-01

Acoustics — Determination of sound power levels of noise sources using sound intensity —

Part 2: Measurement by scanning

*Acoustique — Détermination par intensimétrie des niveaux de puissance
acoustique émis par les sources de bruit —*

Partie 2: Mesurage par balayage

This material is reproduced from ISO documents under International Organization for Standardization (ISO) Copyright License number IHS/ICC/1996. Not for resale. No part of these ISO documents may be reproduced in any form, electronic retrieval system or otherwise, except as allowed in the copyright law of the country of use, or with the prior written consent of ISO (Case postale 56, 1211 Geneva 20, Switzerland, Fax +41 22 734 10 79), IHS or the ISO Licensor's members.



Reference number
ISO 9614-2:1996(E)



Documents
Document Sharing Hub

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 9614-2 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

ISO 9614 consists of the following parts, under the general title *Acoustics — Determination of sound power levels of noise sources using sound intensity*:

- *Part 1: Measurement at discrete points*
- *Part 2: Measurement by scanning*
- *Part 3: Precision method for measurement by scanning*

Annexes A and B form an integral part of this part of ISO 9614. Annexes C, D, E and F are for information only.

© ISO 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Introduction

0.1 The sound power radiated by a source is equal in value to the integral of the scalar product of the sound intensity vector and the associated elemental area vector over any surface totally enclosing the source. Previous International Standards which describe methods of determination of sound power levels of noise sources, principally ISO 3740 to ISO 3747, without exception specify sound pressure level as the primary acoustic quantity to be measured. The relationship between sound intensity level and sound pressure level at any point depends on the characteristics of the source, the characteristics of the measurement environment, and the disposition of the measurement positions with respect to the source. Therefore ISO 3740 to ISO 3747 necessarily specify the source characteristics, the test environment characteristics and qualification procedures, together with measurement methods which are expected to restrict the uncertainty of the sound power level determination to within acceptable limits.

The procedures specified ISO 3740 to ISO 3747 are not always appropriate, for the following reasons.

- a) Costly facilities are necessary if high precision is required. It is frequently not possible to install and operate large pieces of equipment in such facilities.
- b) They cannot be used in the presence of high levels of extraneous noise generated by sources other than that under investigation.

0.2 This part of ISO 9614 specifies methods of determining the sound power levels of sources, within specific ranges of uncertainty, under test conditions which are less restricted than those required by ISO 3740 to ISO 3747. The sound power level is the *in situ* sound power level as determined by the procedure of this part of ISO 9614; it is physically a function of the environment, and may in some cases differ from the sound power level of the same source determined under other conditions.

It is recommended that personnel performing sound intensity measurements according to this part of ISO 9614 are appropriately trained and experienced.

0.3 This part of ISO 9614 complements ISO 9614-1 and the series ISO 3740 to ISO 3747 which specify various methods for the determination of sound power levels of machines and equipment. It differs from the ISO 3740 to ISO 3747 series principally in three aspects:

- a) measurements are made of sound intensity as well as of sound pressure;
- b) the uncertainty of the sound power level determined by the method specified in this part of ISO 9614 is classified according to the results of specified ancillary tests and calculations performed in association with the test measurements;
- c) current limitations of intensity measurement equipment which conforms to IEC 1043 restricts measurements to the one-third-octave range 50 Hz to 6,3 kHz; band-limited A-weighted values are determined from the constituent one-octave or one-third-octave band values and not by direct A-weighted measurement.

0.4 The integral over any surface totally enclosing the source of the scalar product of the sound intensity vector and the associated elemental area vector provides a measure of the sound power radiated directly into the air by all sources located within the enclosing surface and excludes sound radiated by sources located outside this surface. In practice, this exclusion is effective only if the source under test and other sources of extraneous intensity on the measurement surface are stationary in time. In the presence of sound sources operating outside the measurement surface, any system lying within the surface may absorb a proportion of energy incident upon it. The total sound power absorbed within the measurement surface will appear as a negative contribution to source power, and may produce an error in the sound power determination. In order to minimize the associated error, it is therefore necessary to remove any sound-absorbing material lying within the measurement surface which is not normally present during the operation of the source under test.

This method is based on sampling of the intensity field normal to the measurement surface by moving an intensity probe continuously along one or more specified paths. The resulting sampling error is a function of the spatial variation of the normal intensity component over the measurement surface, which depends upon the directivity of the source, the chosen sampling surface, the pattern and speed of the probe scanning, and the proximity of extraneous sources outside the measurement surface.

The accuracy of measurement of the normal component of sound intensity at a position is sensitive to the difference between the local sound pressure level and the local normal sound intensity level. A large difference may occur when the intensity vector at a measurement position is directed at a large angle (approaching 90°) to the local normal to the measurement surface. Alternatively, the local sound pressure level may contain strong contributions from sources outside the measurement surface, but may be associated with little net sound energy flow, as in a reverberant field in an enclosure; or the field may be strongly reactive because of the presence of the near field and/or standing waves.

The accuracy of determination of sound power level is adversely affected by a flow of sound energy into the volume enclosed by the measurement surface through a portion of that surface, even though it is, in principle, compensated by increased flow out of the volume through the remaining portion of the surface. This condition is caused by the presence of a strong extraneous source close to, but outside, the measurement surface.

Acoustics — Determination of sound power levels of noise sources using sound intensity —

Part 2: Measurement by scanning

1 Scope

1.1 This part of ISO 9614 specifies a method for measuring the component of sound intensity normal to a measurement surface which is chosen so as to enclose the noise source(s) of which the sound power level is to be determined.

Surface integration of the intensity component normal to the measurement surface is approximated by subdividing the measurement surface into contiguous segments, and scanning the intensity probe over each segment along a continuous path which covers the extent of the segment. The measurement instrument determines the average normal intensity component and averaged squared sound pressure over the duration of each scan. The scanning operation may be performed either manually or by means of a mechanical system.

Band-limited weighted sound power level is calculated from the measured octave or one-third-octave band values. The method is applicable to any source for which a physically stationary measurement surface can be defined, and on which the noises generated by the source under test and by other significant extraneous sources are stationary in time, as defined in 3.13. The source is defined by the choice of measurement surface. The method is applicable *in situ*, or in special-purpose test environments.

This part of ISO 9614 specifies certain ancillary procedures, described in annex B, to be followed in conjunction with the sound power determination. The results are used to indicate the quality of the determination, and hence the grade of accuracy. If the in-

dicated quality of the determination does not meet the requirements of this part of ISO 9614, the test procedure is to be modified in the manner indicated.

This part of ISO 9614 does not apply in any frequency band in which the sound power of the source is found to be negative on measurement.

1.2 This part of ISO 9614 is applicable to sources situated in any environment which is neither so variable in time as to reduce the accuracy of the measurement of sound intensity to an unacceptable degree, nor subjects the intensity measurement probe to gas flows of unacceptable speed or unsteadiness (see 5.2.2, 5.3 and 5.4).

In some cases it will be found that the test conditions are too adverse to allow the requirements of this part of ISO 9614 to be met. Extraneous noise levels may exceed the dynamic capability of the measuring instrument or may vary to an excessive degree during the test. In such cases the method given in this part of ISO 9614 is not suitable for the determination of the sound power level of the source.

NOTE 1 Other methods (e.g. determination of sound power levels from surface vibration levels as described in ISO/TR 7849) may be more suitable.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 9614. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this

part of ISO 9614 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 942:1988, *Sound calibrators*.

IEC 1043:1993, *Electroacoustics — Instruments for the measurement of sound intensity — Measurements with pairs of pressure sensing microphones*.

3 Definitions

For the purposes of this part of ISO 9614, the following definitions apply.

3.1 Sound pressure levels

3.1.1 sound pressure level, L_p : Ten times the logarithm to the base 10 of the ratio of the mean-square sound pressure to the square of the reference sound pressure. The reference sound pressure is 20 μPa .

Sound pressure level is expressed in decibels.

3.1.2 segment-average sound pressure level, L_{pi} : Ten times the logarithm to the base 10 of the ratio of the spatial-average mean-square pressure on segment i to the square of the reference sound pressure.

It is expressed in decibels.

3.2 instantaneous sound intensity, $\vec{I}(t)$: Instantaneous rate of flow of sound energy per unit of surface area in the direction of the local instantaneous acoustic particle velocity.

This is a vectorial quantity which is equal to the product of the instantaneous sound pressure at a point and the associated particle velocity:

$$\vec{I}(t) = p(t) \cdot \vec{u}(t) \quad \dots (1)$$

where

$p(t)$ is the instantaneous sound pressure at a point;

$\vec{u}(t)$ is the associated instantaneous particle velocity at the same point;

t is the time.

3.3 sound intensity, $\vec{I}$: Time-average value of $\vec{I}(t)$ in a temporally stationary sound field:

$$\vec{I} = \lim_{T \rightarrow \infty} \frac{1}{T} \int_0^T \vec{I}(t) dt \quad \dots (2)$$

where T is the integration period.

Also

I is the signed magnitude of $\vec{I}$; the sign is an indication of directional sense, and is dictated by the choice of positive direction of energy flow;

$|I|$ is the unsigned magnitude of $\vec{I}$.

3.4 normal sound intensity, I_n : Component of the sound intensity in the direction normal to a measurement surface defined by the unit normal vector $\vec{n}$:

$$I_n = \vec{I} \cdot \vec{n} \quad \dots (3)$$

where $\vec{n}$ is the unit normal vector directed out of the volume enclosed by the measurement surface.

3.5 normal sound intensity level, L_{In} : Logarithmic measure of the unsigned value of the normal sound intensity, $|I_n|$, given by:

$$L_{In} = 10 \lg[|I_n|/I_0] \text{ dB} \quad \dots (4)$$

where I_0 is the reference sound intensity ($= 10^{-12} \text{ Wm}^{-2}$).

It is expressed in decibels.

When I_n is negative, the level is expressed as $(-)\text{XX dB}$, except when used in the evaluation of δ_{pt} (see 3.11).

3.6 Sound powers

3.6.1 partial sound power, P_i : Time-averaged rate of flow of sound energy through an element (segment) of a measurement surface, given by:

$$P_i = \langle I_{ni} \rangle S_i \quad \dots (5)$$

where

$\langle I_{ni} \rangle$ is the signed magnitude of the segment-average normal sound intensity measured on the segment i of the measurement surface;

S_i is the area of the segment i .

Also $|P_i|$ is the magnitude of P_i .

3.6.2 sound power, P : Total sound power generated by a source, as determined using the method given in this part of ISO 9614, given by:

$$P = \sum_{i=1}^N P_i \quad \dots (6)$$

and

$$|P| = \left| \sum_{i=1}^N P_i \right| \quad \dots (7)$$

where N is the total number of segments of the measurement surface.

3.6.3 partial sound power level, L_{wi} : Logarithmic measure of the sound power passing through segment i of the measurement surface, given by:

$$L_{wi} = 10 \lg[|P_i|/P_0] \text{ dB} \quad \dots (8)$$

where P_0 is the reference sound power ($= 10^{-12}$ W).

It is expressed in decibels.

When P_i is negative, it is expressed as (–) XX dB.

3.6.4 sound power level, L_w : Logarithmic measure of the sound power generated by a source, as determined using the method given in this part of ISO 9614, given by:

$$L_w = 10 \lg[|P|/P_0] \text{ dB} \quad \dots (9)$$

It is expressed in decibels.

When P is negative, the level is expressed as (–) XX dB for record purposes only.

3.7 measurement surface: Hypothetical surface on which intensity measurements are made, and which either completely encloses the noise source under test or, in conjunction with an acoustically rigid, continuous surface, encloses the noise source under test. In cases where the hypothetical surface is penetrated by bodies possessing solid surfaces, the measurement surface terminates at the lines of intersection between the bodies and the surface.

3.8 segment: One of a set of smaller surfaces into which a measurement surface is divided.

3.9 extraneous intensity: Contribution to the sound intensity which arises from the operation of sources external to the measurement surface (source mechanisms operating outside the volume enclosed by the measurement surface).

3.10 probe: That part of the intensity measurement system which incorporates the sensors.

3.11 pressure-residual intensity index, δ_{pl_0} : The difference between the indicated L_p and indicated L_l when the intensity probe is placed and oriented in a sound field such that the sound intensity is zero. It is expressed in decibels.

Details for determining δ_{pl_0} are given in IEC 1043.

$$\delta_{pl_0} = (L_p - L_l) \quad \dots (10)$$

3.12 dynamic capability index, L_d : Given by:

$$L_d = \delta_{pl_0} - K \quad \dots (11)$$

It is expressed in decibels.

The value of K is selected according to the grade of accuracy required (see table 1).

Table 1 — Bias error factor, K

Grade of accuracy ¹⁾	Bias error factor dB
Engineering (grade 2)	10
Survey (grade 3)	7
1) Defined in ISO 12001.	

3.13 stationary signal: A signal of which the time-averaged properties during a measurement on one segment of the measurement surface are equal to those obtained on the same segment when the averaging period is extended over the total time taken to measure on all segments.

NOTE 2 Cyclic signals are, by this definition, stationary, if on each segment the measurement period extends over at least ten cycles.

3.14 field indicators F_{pl} and $F_{+/-}$: See annex A.

3.15 scan: A continuous movement of an intensity probe along a specified path on a segment of a measurement surface.

3.16 scan-line density: Inverse of the average separation of adjacent scan lines.

4 General requirements

4.1 Size of noise source

The size of the noise source is unrestricted. The extent of the source is defined by the choice of the measurement surface.

4.2 Character of noise radiated by the source

The signal shall be stationary in time, as defined in 3.13. If a source operates according to a duty cycle, within which there are distinct continuous periods of steady operation, for the purposes of application of this part of ISO 9614, an individual sound power level is determined and reported for each distinct period. Action should be taken to avoid measurement during times of operation of non-stationary extraneous noise sources of which the occurrences are predictable (see table B.1 in annex B).

4.3 Measurement uncertainty

The value of the sound power of a noise source determined by a single application of the procedures of this part of ISO 9614 is likely to differ from the true value. The actual difference cannot be evaluated, but the confidence that the value determined lies within a certain range about the true value can be stated, on the reasonable assumption that the values determined by numerous applications of the procedure are normally distributed about the true value. Where repeated applications are made to a source located at a given test site under nominally identical test conditions, using the same test procedures and instrumentation, the values so determined constitute the data set which statistically describes the repeatability of the determination. Where the values are determined from tests conforming to this part of ISO 9614 made on the given source at different test sites using physically different instruments, the data set so obtained statistically describes the reproducibility of the determination. Reproducibility is affected by variations of environmental conditions at the test sites and of experimental technique. The standard deviations do not account for variations of sound power output caused by changes in operating conditions of a source (e.g. rotational speed, line voltage) or mounting conditions. For the procedures specified in this part of ISO 9614, the highest standard deviations of reproducibility are stated in table 2.

NOTES

3 If certain operatives use similar facilities and instrumentation, the results of sound power determinations on a given source at a given site are likely to exhibit smaller standard deviations than those indicated in table 2.

4 For a particular family of sound sources of similar size with similar sound power spectra operating in similar environmental conditions, and measured according to a specific test code, the standard deviations of reproducibility are

likely to be less than those indicated in table 2. Statistical methods for the characterization of batches of machines are described in ISO 7574-4.

5 The procedures of this part of ISO 9614 and the standard deviations stated in table 2 are applicable to measurements on a given source. Characterization of the sound power levels of a batch of sources of the same family or type involves the use of random sampling techniques in which confidence intervals are specified, and the results are expressed in terms of statistical upper limits. In applying these techniques, the total standard deviation is either known or estimated, including the standard deviation of production, which is a measure of the variation in sound power output between individual machines within the batch, as defined in ISO 7574-1.

For the purposes of application of this part of ISO 9614, two grades of accuracy are defined in table 2. The stated uncertainties allow for random errors associated with the measurement procedure, together with the maximum measurement bias error which is limited by the selection of the bias error factor K appropriate to the required grade of accuracy (see table 1). They do not account for tolerances in nominal instrument performance which are specified in IEC 1043. Nor do they account for the effects of variation in source installation, mounting and operating conditions.

NOTE 6 Below 50 Hz there are insufficient data on which to base uncertainty values. For the purposes of this part of ISO 9614, the normal range for A-weighted data is covered by octave bands from 63 Hz to 4 kHz, and one-third-octave bands from 50 Hz to 6,3 kHz. The A-weighted value which is computed from octave band levels in the range 63 Hz to 4 kHz, and one-third-octave band levels in the range 50 Hz to 6,3 kHz, is correct if there are no significantly high levels in the bands for 31 Hz to 40 Hz and 8 kHz to 10 kHz. For the purpose of this assessment, significant levels are band levels which after A-weighting are no more than 6 dB below the A-weighted value computed. If A-weighted measurements and associated sound power level determinations are made in a more restricted frequency range, this range shall be stated in accordance with 10.6 b).

The uncertainty of determination of the sound power level of a noise source is related to the nature of the sound field of the source, to the nature of the extraneous sound field, to the absorption of the source under test, and to the form of the intensity field sampling and measurement procedure employed. For this reason this part of ISO 9614 specifies initial procedures for the evaluation of indicators of the nature of the sound field which exists in the region of the proposed measurement surface (see annex A). The results of this initial test are used to select an appropriate course of action according to table B.1.