



**International
Standard**

ISO 9795

**Lignins — Determination of
inorganics content in kraft lignin,
soda lignin and hydrolysis lignin**

*Lignines — Détermination de la teneur en matières inorganiques
dans la lignine kraft, la lignine soude et la lignine d'hydrolyse*

**First edition
2023-12**

Reference number
ISO 9795:2023(en)

Full document details: [ISO 9795-2023](#)

© ISO 2023  **Documents**
Document Sharing Hub



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO 2023 – All rights reserved

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Reagents	2
6 Apparatus	3
7 Sampling	4
8 Procedure	4
8.1 Overview	4
8.2 General	4
8.3 Measurement of dry matter content	4
8.4 Incineration	4
9 Determination of inorganics content	5
9.1 General	5
9.2 Dissolution of the residue	5
9.3 Preparation of calibration solutions	6
9.4 Blank solution	6
9.5 Determination	6
10 Expression of results	7
10.1 Inorganics content of kraft lignin (acid form), soda lignin, and hydrolysis lignin	7
10.2 Inorganics content of kraft lignin in the base form	7
11 Precision	8
12 Test report	8
Annex A (informative) Precision	9
Bibliography	12

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 6, *Paper, board and pulps*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document describes methods for the determination of the total inorganics content of kraft lignin, soda lignin and lignin obtained from hydrolysis of biomass.

The inorganics content of lignins is of high significance in several applications of lignin as a replacement of fossil-based raw materials, in products such as solid fuels, phenolic resins, polyurethane foams, thermoplastics, carbon fibre and many others. For example, when lignin is used as a fuel in the lime kiln, the ash content must be very low since it can cause bridging and ringing problems in the lime kiln^[5]. Similarly, when lignin is used as a feedstock to make carbon fibres, it is recommended that the ash content be less than a mass fraction of 0,1 %^[6]. In the case of resole-type phenolic resins, the lignin should be in the base form (i.e. have a high inorganics content) since the process of making such resins is conducted at an alkaline pH^[7].

For kraft lignin in the acid form, soda lignin, and hydrolysis lignin, the ash content determined at 525 °C is a good approximation of the total inorganics content of the samples. However, for kraft lignin in the base form, the ash content significantly overestimates - by a factor of 2 to 3 - the inorganics content of lignin. This is largely due to the fact that, upon combustion, sodium and other metals associated with the phenolic and carboxylic acid groups in lignin are converted to sodium/metal sulfate, nitrate and especially carbonate, depending on the relative ratio of sulfur, nitrogen, and carbon in the lignin. In other words, the ashing process leads to the formation of chemical species (e.g. sulfate, nitrate, carbonate) that were not present in the lignin itself, thereby contributing to an overestimation of the inorganics content of the lignin since essentially all organic matter is destroyed at that temperature.

This phenomenon was demonstrated by establishing a sodium mass balance for kraft lignin in the base form. The amount of sodium ions needed to balance the phenolic and carboxylic acid groups was calculated, based on their respective pKa values^[8]. Good agreement was found between the total sodium and the sodium needed to balance the phenolic and carboxylic acid groups. This shows that most of the sodium in kraft lignin in the base form is present as the salt of the phenolic and carboxylic acid groups.

Thus, for kraft lignin in the base form, the total inorganics content is best determined from an analysis of sodium, along with other major inorganic elements, including calcium, potassium, magnesium, iron, manganese, and copper. The level of trace elements such as zinc, cadmium, and chromium is considered to be too low to have a significant impact on the total inorganics content.

For kraft lignin in the acid form, soda lignin, and hydrolysis lignin, the method used for determining ash content is largely based on ISO 1762^[1]. For kraft lignin in the base form, the method used for determining major inorganic elements is based on ISO 12830^[2].

