

INTERNATIONAL STANDARD

ISO/IEC 10149

First edition
1989-09-01

Information technology — Data interchange on read-only 120 mm optical data disks (CD-ROM)

*Technologies de l'information — Échange de données sur des disques optiques de
diamètre 120 mm à lecture unique (CD-ROM)*



Reference number
ISO/IEC 10149 : 1989 (E)

AVA Documents
Document Sharing Hub

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Definitions	2
4.1 Audio Track	2
4.2 concentricity	2
4.3 Control byte	2
4.4 Digital Data Track	2
4.5 F ₁ -Frame	2
4.6 F ₂ -Frame	2
4.7 F ₃ -Frame	2
4.8 Information Area	2
4.9 Information Track	2
4.10 Physical Track	2
4.11 radial acceleration	2
4.12 radial runout	2
4.13 Section	2
4.14 Sector	2
4.15 User Data Area	2
5 Environments	3
5.1 Testing environments	3
5.1.1 Optical stylus	3
5.1.2 Clamping	3
5.1.3 Normal testing environment	3
5.1.4 Restricted testing environment	3
5.2 Operating environment	3
5.3 Storage environment	4
6 Flammability	4
7 Material	4
8 Mechanical, physical and dimensional characteristics	4
8.1 Reference planes	5
8.2 Centre hole (figures 1 and 2)	5
8.3 First transition area (figure 1)	5
8.4 Clamping area (figure 1)	6

8.5	Second transition area (figure 1)	6
8.6	Information Area (figures 1 and 3)	6
8.7	Rim area (figures 1 and 4)	8
8.8	General remarks	8
9	Mechanical deflection of the entrance surface	9
10	Deflection of the reflective layer	9
11	Physical Track geometry	9
11.1	Physical Track shape	9
11.2	Direction of rotation	9
11.3	Physical Track pitch	9
11.4	Scanning velocity	10
11.5	Radial runout of tracks	10
12	Optical read system	10
12.1	HF signal	10
12.2	Modulation amplitude	11
12.3	Symmetry	11
12.4	Cross talk	11
12.5	Quality of the HF signal	11
12.5.1	Position jitter of the Channel bits	11
12.5.2	Specification of random errors	11
12.5.3	Specification of burst errors	11
12.6	Radial track-following signal	11
12.6.1	Magnitude	12
12.6.1	Defects	12
13	General	17
13.1	Information Tracks	17
13.2	Coded representation of user data	17
13.2.1	Standards	17
13.2.2	Coding methods	17
14	Sectors of a Digital Data Track	18
14.1	Sync field	19
14.2	Header field	19
14.3	EDC field	20
14.4	Intermediate field	20
14.5	P-Parity field	20
14.6	Q-Parity field	20
15	Scrambling	20
16	F ₁ -Frames	20
17	CIRC encoding — F ₂ -Frames	20
18	Control Bytes — F ₃ -Frames and Sections	21
19	Recording of the F ₃ -Frames on the disk	21
19.1	8-to-14 Encoding	21

19.2 Sync Header 21

19.3 Merging Channel bits 22

19.4 Channel Frame 22

20 Track structure of the information area 22

20.1 Lead-in Area 23

20.2 User Data Area 23

20.3 Lead-out Area 23

21 Addressing system in the Information Area 23

22 Specification of the Control bytes of Digital Data Tracks 24

22.1 Setting of r-channel to w-channel 24

22.2 Setting of the p-channel 24

22.3 Setting of the q-channel 25

22.3.1 Control field 25

22.3.2 q-Mode field 26

22.3.3 q-Mode 1 — q-Data Field in the User Data Area and in the Lead-out Area . 26

22.3.4 q-Mode 1 — q-Data field in the Lead-in Area 27

22.3.5 q-Mode 2 — q-Data field in the Information Area 28

22.3.6 CRC field 29

Annexes

A Error correction encoding by RSPC 30

B Scrambler 33

C Error correction encoding by CIRC 34

D 8-bit to 14-Channel bit conversion 40

E Merging bits 42

F Storage tests 43

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) together form a system for worldwide standardization as a whole. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for approval before their acceptance as International Standards. They are approved in accordance with procedures requiring at least 75 % approval by the national bodies voting.

International Standard ISO/IEC 10149 was prepared by the European Computer Manufacturers Association (as ECMA-130) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A to E form an integral part of this International Standard. Annex F is for information only.

Introduction

In this International Standard

- clauses 1 to 3 identify and introduce the contents of the standard;
- clause 4 gives definitions and clauses 5, 6 and 7 specify requirements for environments, flammability and material respectively;
- clauses 8 to 12 specify the characteristics of the disk;
- clause 12 deals with optical signals;
- clauses 13 to 19 describes recording;
- clauses 20 to 22 specify the format of the information area.

Information technology — Data interchange on read-only 120 mm optical data disks (CD-ROM)

1 Scope

This International Standard specifies the characteristics of 120 mm optical disks for information interchange between information processing systems and for information storage, called CD-ROM.

The optical disk specified by this International Standard is of the type in which the information is recorded before delivery to the user and can only be read from the disk. This International Standard specifies

- some definitions, the environments in which the characteristics of the disk shall be tested and the environments in which it shall be used and stored;
- the mechanical, physical, and dimensional characteristics of the disk;
- the recording characteristics, the format of the tracks, the error-detecting and the error-correcting characters, and the coding of the information;
- the optical characteristics for reading the information.

The characteristics are specified for tracks recorded with digital data. According to this International Standard, a disk may also contain one or more tracks recorded with digital audio data. Such tracks shall be recorded according to IEC 908.

2 Conformance

An optical disk is in conformance with this International Standard if it conforms to all its mandatory requirements.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 9660 : 1988, *Information processing — Volume and file structure of CD-ROM for information interchange*.

IEC 908 : 1987, *Compact disc digital audio system*.

4 Definitions

For the purposes of this International Standard, the following definitions apply.

- 4.1 Audio Track:** An Information Track containing digitally encoded audio information.
- 4.2 concentricity:** The diameter of a circular tolerance zone within which the centres of two circular features must lie.
- 4.3 Control byte:** An 8-bit byte from a table of 98 bytes, added to an F_2 -Frame and containing addressing information.
- 4.4 Digital Data Track:** An Information Track organized in sectors and containing digital user data.
- 4.5 F_1 -Frame:** A group of 24 8-bit bytes, being the output of the scrambler and input of the CIRC encoder.
- 4.6 F_2 -Frame:** A group of 32 8-bit bytes, being the output of the CIRC encoder.
- 4.7 F_3 -Frame:** A group of 33 8-bit bytes, being an F_2 -Frame with a control byte, and input of the 8-to-14 encoder.
- 4.8 Information Area:** An area on the disk with physical tracks, consisting of a Lead-in area, User Data area and a Lead-out area.
- 4.9 Information Track:** An area on the disk containing a collection of user information.
- 4.10 Physical Track:** A 360° turn of a continuous spiral line on the disk, followed by the optical stylus.
- 4.11 radial acceleration:** The radial acceleration of any physical track in the direction perpendicular to the axis of rotation of the disk, at a specified rotational speed.
- 4.12 radial runout:** The difference between the maximum and the minimum distance of a physical track to the axis of rotation measured over one revolution.
- 4.13 Section:** A group of 98 F_3 -Frames containing one complete table of Control bytes.
- 4.14 Sector:** The smallest addressable part of a Digital Data Track in the information area that can be accessed independently of other addressable parts of the area.
- 4.15 User Data Area:** A part of the information area containing User Data.

5 Environments

5.1 Testing environments

5.1.1 Optical stylus

The optical stylus used for testing measurements shall have the following characteristics:

wavelength λ : 780 nm $\pm$ 10 nm

polarization: circular

numerical aperture: 0,45 $\pm$ 0,01

intensity at the rim of the pupil of the objective lens: larger than 50 % of the maximum intensity value

The rms wave front error of the beam near the information layer shall be less than 0,07 λ . The contribution of the disk to this error shall be less than 0,05 λ .

5.1.2 Clamping

Where applicable, the disk shall be held between two concentric rings having an inner diameter of at least 29 mm and an outer diameter of at most 31 mm holding the disk with a force in the range 1 N to 2 N.

5.1.3 Normal testing environment

Unless otherwise stated, tests and measurements made on the disk to check the requirements of this International Standard shall be carried out under the following conditions:

temperature: 25 °C $\pm$ 10 °C

relative humidity: 45 % to 75 %

atmospheric pressure: 96 kPa $\pm$ 10 kPa

conditioning before testing: 24 h min.

No condensation on the disk shall be permitted to occur.

5.1.4 Restricted testing environment

Where specifically stated, tests and measurements shall be carried out under the following conditions:

temperature: 23 °C $\pm$ 2 °C

relative humidity: 45 % to 55 %

atmospheric pressure: 96 kPa $\pm$ 10 kPa

conditioning before testing: 24 h min.

No condensation on the disk shall be permitted to occur.

5.2 Operating environment

Disks used for data interchange shall be operated under the following conditions, when mounted in the drive supplied with voltage and measured on the outside surface of the disk.

The disk exposed to storage conditions must be conditioned in the operating environment for at least 2 h before operating.

temperature:	- 25 °C to + 70 °C
relative humidity:	10 % to 95 %
absolute humidity:	0,5 g · m ⁻³ to 60 g · m ⁻³
sudden change of temperature:	50 °C max.
sudden change of relative humidity:	30 % max.

There shall be no condensation of moisture on the disk.

5.3 Storage environment

Storage environment is the ambient condition to which the disk is exposed when stored. No condensation of moisture on the disk is permitted (see annex F).

temperature:	- 20 °C to + 50 °C
relative humidity:	5 % to 90 %
wet bulb temperature:	29 °C max.
atmospheric pressure:	75 kPa to 105 kPa

6 Flammability

The disk shall be made from materials which, if ignited from a match flame, do not continue to burn in a still carbon dioxide atmosphere.

7 Material

This International Standard specifies the material of the disk only in the information area (see 8.6). The remainder of the disk can be made of any material as long as all mandatory requirements of this International Standard are met.

The weight of the disk shall be between 14 g and 33 g.

8 Mechanical, physical, and dimensional characteristics

Dimensional characteristics are specified for those parameters deemed mandatory for interchange and compatible use of the disk. Where there is freedom of design, only the functional characteristics of the elements described are indicated. The enclosed drawings show the dimensional requirements in summarized form. The different parts of the disk are described from the centre hole to the outside rim.

All diameters are referred to the centre of the centre hole.

Other dimensions are referred to two Reference Planes P and Q.

Figure 1 shows a cross-section of a part of the disk.

Figure 2 shows at a larger scale the edges of the centre hole.

Figure 3 shows at a larger scale a cross-section of the disk in the information area.

Figure 4 shows at a larger scale a cross-section of the rim area.

8.1 Reference Planes

Reference Plane P is the primary Reference Plane. It is the plane on which the bottom surface of the clamping area rests (see 8.5).

Reference Plane Q is the plane parallel to Reference Plane P at the height of the top surface of the clamping area.

8.2 Centre hole (figures 1 and 2)

The centre hole shall have a cylindrical shape. Its diameter shall be

$$d_1 = 15,0 \text{ mm} \begin{matrix} + 0,1 \text{ mm} \\ 0,0 \text{ mm} \end{matrix}$$

Diameter d_1 shall be measured in the restricted testing environment.

The bottom edge of the centre hole may have a chamfer up to a height

$$h_1 = 0,1 \text{ mm max.}$$

above the bottom surface of the first transition area (see 8.3) at an angle

$$\alpha = 45^\circ$$

Alternatively this edge may be rounded with a radius of not greater than 0,1 mm.

The top edge of the centre hole may present burrs which are permitted to extend by

$$h_2 = 0,2 \text{ mm max.}$$

above the top surface of the first transition area.

8.3 First transition area (figure 1)

The first transition area shall extend between diameter d_1 and diameter d_2 .

$$d_2 = 20 \text{ mm} \begin{matrix} + 6 \text{ mm} \\ 0 \text{ mm} \end{matrix}$$

In this whole area the top surface of the disk is permitted to be below Reference Plane Q by

$$h_3 = 0,2 \text{ mm max.}$$

and the bottom surface of the disk is permitted to be above Reference Plane P by

$$h_4 = 0,2 \text{ mm max.}$$

In addition, in the part of the area defined by

$$20 \text{ mm} < d_2 < 26 \text{ mm}$$

the top surface of the disk is permitted to be below Reference Plane Q by

$$h_5 = 0,4 \text{ mm max.}$$

and the bottom surface of the disk is permitted to be above Reference Plane P by

$$h_6 = 0,4 \text{ mm max.}$$

8.4 Clamping area (figure 1)

The clamping area shall extend between the maximum value of diameter d_2 and diameter d_3 .

$$d_2 (\text{max.}) = 26 \text{ mm}$$

$$d_3 = 33 \text{ mm min.}$$

The bottom surface of the clamping area shall be flat within 0,1 mm and shall lie on Reference Plane P.

The top surface of the clamping area shall be parallel to Reference Plane P within 0,2 mm; it defines Reference Plane Q.

The height of the top surface above Reference Plane P shall be

$$h_7 = 1,2 \text{ mm} \begin{matrix} + 0,3 \text{ mm} \\ 0,1 \text{ mm} \end{matrix}$$

8.5 Second transition area (figure 1)

The second transition area shall extend between diameters d_3 and d_4 .

$$d_4 = 44 \text{ mm max.}$$

In this area the bottom surface of the disk is permitted to be either above Reference Plane P by

$$h_8 = 0,4 \text{ mm max.}$$

or below Reference Plane P by

$$h_9 = 0,4 \text{ mm max.}$$

and the top surface of the disk is permitted to be either above Reference Plane Q by

$$h_{10} = 0,4 \text{ mm max.}$$

or below Reference Plane Q by

$$h_1 = 0,4 \text{ mm max.}$$

8.6 Information Area (figures 1 and 3)

The Information Area shall extend between diameters d_4 and d_5 .

$$d_5 = 118 \text{ mm max.}$$

The information Area comprises the following zones:

- An inner buffer zone that extends between diameters d_4 and d_6 .

$$d_4 + 1 \text{ mm} \leq d_6 \leq 46 \text{ mm max.}$$

This diameter shall be measured in the restricted testing environment.

- A lead-in zone that extends between diameters d_6 and d_7 .

$$d_7 = 50,0 \text{ mm} \begin{matrix} + 0,0 \text{ mm} \\ - 0,4 \text{ mm} \end{matrix}$$

This diameter shall be measured in the restricted testing environment.

- A user data zone that extends between diameter d_7 and d_8 .

$$d_8 = 116 \text{ mm max.}$$

This diameter shall be measured in the restricted testing environment.

- A lead-out zone that extends between diameters d_8 and d_9 .

$$d_9 = (d_8 + 1 \text{ mm}) \text{ min.}$$

- An outer buffer zone that extends between diameters d_9 and d_5 , where

$$d_9 + 1 \text{ mm} \leq d_5 \leq 118 \text{ mm}$$

Between diameters d_4 and d_5 the disk shall consist of (figure 3):

- a transparent substrate;
- a reflective layer;
- a protective layer;
- an optional label.

The label may extend beyond the so-defined zone.

The height of the label above Reference Plane P shall be

$$h_{12} = 1,2 \text{ mm} \begin{matrix} + 0,3 \text{ mm} \\ - 0,1 \text{ mm} \end{matrix}$$

The thickness e of the transparent substrate shall be

$$e = 1,2 \text{ mm} \pm 0,1 \text{ mm}$$

The bottom surface of the transparent substrate shall lie on Reference Plane P.

The index of refraction of the transparent substrate shall be

$$1,55 \pm 0,10$$

The birefringence of the transparent substrate expressed as a retardation (parallel beam, circularly polarized, normal incidence, double-pass) shall be

$$100 \text{ nm max.}$$

The reflectance of the transparent substrate and reflective layer measured under normal incidence and parallel beam in an unrecorded part of the information area shall be

70 % min.

The relative variation of this reflectance for frequencies below 100 Hz shall be less than 3 % for a disk rotating at scanning velocity.

These parameters shall be measured at the wavelength specified in 5.1.1.

8.7 Rim area (figures 1 and 4)

The rim area shall extend between diameters d_5 and d_{10} .

$$d_{10} = 120,0 \text{ mm} \pm 0,3 \text{ mm}$$

This diameter shall be measured in the restricted testing environment.

Its concentricity relative to the largest circle inscribed in the centre hole shall be within

0,2 mm.

In the zone extending between diameters d_5 and d_{11} , where d_{11} shall satisfy both of the following conditions:

$$d_{11} \geq d_5$$

$$117,7 \text{ mm} \leq d_{11} \leq 118,3 \text{ mm}$$

the bottom surface of the disk shall lie on the Reference Plane P and the height of the top surface above Reference Plane P shall be equal to h_{12} .

In the zone extending between diameters d_{11} and d_{10} the bottom surface of the disk is permitted to be below Reference Plane P by

$$h_{13} = 0,1 \text{ mm max.}$$

and the top surface of the disk is permitted to be higher than h_{12} by

$$h_{14} = 0,1 \text{ mm max.}$$

The values of h_{13} and h_{14} shall satisfy the condition

$$(h_{12} + h_{13} + h_{14}) \leq 1,5 \text{ mm}$$

In this zone the thickness of the disk is also permitted to decrease so that

$$h_{16} - h_{15} = 0,6 \text{ mm min.}$$

as shown in figure 4.

8.8 General remarks

All heights specified in the preceding clauses and indicated by h_i are independent from each other. This means, for example, that if the top surface of the first transition area is below Reference Plane Q by up to h_3 there is no implication that the bottom surface of this area has to be above Reference Plane P by up to h_4 . Moreover, whilst the height and tolerances for the top surfaces of the clamping area and the information area (i.e. h_7 and h_{12}) have the same numerical values, this does not imply that the actual values have to be identical.

9 Mechanical deflection of the entrance surface

The following requirements apply to both a static disk and a disk clamped according to 5.1.2 and rotating at the scanning velocity.

The bottom surface of the information area (i.e. the entrance surface of the read beam) shall not deviate from Reference Plane P by more than $\pm 0,4$ mm between d_6 and d_{11} . The rms value over one revolution shall not exceed 0,3 mm.

The angle which the normal to this entrance surface, averaged over an area of 2 mm diameter, makes with the normal to Reference Plane P shall not exceed $0^\circ 36'$. If a beam of light enters the disk along a normal to the Reference Plane P, then the angular deviation of the reflected beam in radial direction from the normal to Reference Plane P shall not exceed $\pm 1^\circ 36'$. This figure includes the tolerance on the parallelism of the information layer and the entrance surface.

10 Deflection of the reflective layer

With the disk clamped according to 5.1.2, and rotating at the scanning velocity, the deflection of the reflective layer is its axial deviation from its nominal position related to Reference Plane P (see 8.6) as seen by the optical stylus. Thus, it comprises the tolerances on the thickness, on the index of refraction and the deflection of the entrance surface. This deflection shall be measured between diameters d_4 and d_5 .

a) Frequencies below 500 Hz

The deflection on either side of the nominal position of the reflective layer shall not exceed 0,5 mm. The rms value shall not exceed 0,4 mm. The acceleration of the reflective layer along a fixed line normal to the Reference Plane P shall not exceed 10 m/s^2 .

b) Frequencies above 500 Hz

The deflection on either side of the nominal position shall not exceed $1 \mu\text{m}$.

11 Physical Track geometry

11.1 Physical Track shape

There shall be Physical Tracks between diameters d_6 and d_9 each of which forms a 360° turn of a continuous spiral line.

Each Physical Track shall consist of a succession of depressions as seen by the optical stylus, called pits, in the otherwise flat reflective layer. The encoded information is represented by variations of the pit length and by variation of the distance between pits. The depth of the pits shall be such that the requirements of 12.2 are met.

11.2 Direction of rotation

The Physical Tracks shall spiral outward when the disk rotates counter-clockwise as seen by the optical stylus.

11.3 Physical Track pitch

The spiral shall have a pitch of $1,6 \mu\text{m} \pm 0,1 \mu\text{m}$.

11.4 Scanning velocity

The scanning velocity during recording shall be between 1,20 m/s and 1,40 m/s with a Channel bit rate of 4,321 8 Mbit/s (see clause 20). The velocity variation for a disk when recorded shall be within $\pm 0,01$ m/s.

11.5 Radial runout of tracks

The following requirements shall be met with the disk rotating at scanning velocity:

a) Frequencies below 500 Hz

The radial runout of any Physical Track, i.e. the distance between the Physical Track and the centre hole, shall not exceed 140 μm , peak-to-peak.

The acceleration shall not exceed 0,4 m/s^2 .

b) Frequencies above 500 Hz

The noise in the radial tracking signal is measured in the closed loop situation of the radial servo in a frequency band from 500 Hz to 10 kHz (zero decibel point of the open-loop transfer function of the servo: 200 Hz; cross-over points of the lead network: 65 Hz and 650 Hz; see figure 5).

The rms value of the noise in the residual error signal shall correspond to a tracking error of less than 0,03 μm , integration time 20 ms.

In addition, to avoid strong single frequency noise contributions, this rms value shall be less than 0,01 μm when measured with a scanning filter with a width of 100 Hz over a range from 500 Hz to 10 kHz.

12 Optical read system

For testing the requirements of 12.1 to 12.6 the information in the reflective layer shall be read by the optical beam from an optical stylus according to 5.1.1 and focused on this layer through the transparent substrate. During reading the scanning light spot is diffracted by the pits of the reflective information layer. The optical power that is diffracted back into the objective lens of the optical system is modulated according to the encoded digital information. The modulated photo current is called the high frequency (HF) signal.

12.1 HF signal

The HF signal is measured before alternating current (a.c.) coupling (see figure 6). The highest and lowest fundamental frequencies that occur are 720 kHz and 196 kHz. The peak-to-peak values of the detector current of the highest and lowest fundamental frequencies are denoted by I_3 and I_{11} respectively. The top level of HF signal, which is given by the lowest fundamental frequency, is denoted by I_{top} .

The information contained in the HF signal is extracted in the form of the positions of the crossings of the HF signal with a decision level I_D . This decision level I_D is the level in the middle of the extreme values of I_3 . There are three lozenges of the eye pattern between successive crossings of I_3 and I_D .