

INTERNATIONAL STANDARD

ISO/IEC 10166-1

First edition
1991-12-15

AMENDMENT 1
1995-12-15

Information technology — Text and office systems — Document Filing and Retrieval (DFR) —

Part 1:

Abstract service definition and procedures

AMENDMENT 1: Minor enhancements

Technologies de l'information — Bureautique — Classement et récupération de documents —

Partie 1: Procédures et définition de service abstrait

AMENDEMENT 1: Améliorations mineures



Reference number
ISO/IEC 10166-1:1991/Amd.1:1995(E)



Documents

Document Sharing Hub

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Amendment 1 to International Standard ISO/IEC 10166-1:1991 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee 18, *Document processing and related communication*.

© ISO/IEC 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Information technology — Text and office systems — Document Filing and Retrieval (DFR) —

Part 1:

Abstract service definition and procedures

AMENDMENT 1: Minor enhancements

Page 3

Clause 2

Add the following text to the end of clause 2:

ITU-T T.435(1994), *Document Transfer and Manipulation (DTAM) - Services and Protocols - Abstract Service Definitions and Procedures for Document Manipulation.*

Page 25

Subclause 7.1.1

Change the ASN.1 definition of "DfrBindArgument" as follows:

```

DfrBindArgument ::= SEQUENCE {
    initiator-name           [0]    DistinguishedName,
    credentials              [1]    Credentials,
    retrieve-restrictions    [2]    Restrictions OPTIONAL,
                                -- default is none --
    dfr-configuration-request [3]    BOOLEAN DEFAULT FALSE,
    bind-security            [4]    BindSecurity OPTIONAL,
    priority                 [5]    Priority DEFAULT medium,
    dor-for-produce-operations [6]    BOOLEAN DEFAULT TRUE,
    dor-for-consume-operations [7]    BOOLEAN DEFAULT TRUE,
    protocol-version         [8]    INTEGER {
        version-1      (1),
        version-2      (2) } DEFAULT {1},
    bilateralInformation     [9]    SEQUENCE OF
                                BilateralInformationEntry OPTIONAL }

```

Add the following new paragraph after paragraph **h**):

i) **protocol-version (O)**: This parameter indicates the DFR protocol version which the DFR-User requests. If the DFR-Server can honor this request, DFR Abstract-Bind continues normally. Otherwise, the DFR-Server will issue error.

1) **version-1** is defined by ISO/IEC 10166-1:1991.

2) **version-2** is defined by ISO/IEC 10166-1:1991 together with ISO/IEC 10166-1:1991/Amd 1:1995.

Note - Since a server that knows only the DFR protocol version 1 will not understand a version request, such a request will lead to an (implementation dependent) error. A server that knows the DFR protocol version 2 may accept the bind from a version 1 client, or may return an appropriate error which DFR protocol version 1 client understands. One example of such error code is the **unclassified-server-error**.

Add the following new paragraph and ASN.1 definition of "**BilateralInformationEntry**" and "**ServerName**" after the (new) paragraph **i**):

j) **bilateralInformation (O)**: This parameter includes bilateral information between the DFR-Server and the DFR-User. Format of this bilateral information is as follows.

```
BilateralInformationEntry ::= SEQUENCE {
    serverName  [0]    ServerName,
    information  [1]    EXTERNAL }
```

```
ServerName ::= DistinguishedName
```

Change the ASN.1 definition of "**DfrBindResult**" as follows:

```
DfrBindResult ::= SET {
    authentication-attributes  [0]    SET OF AuthenticationAttribute,
    constraints-supported       [1]    SET OF ConstraintsType
                                     OPTIONAL,
    dfr-document-types-supported [2]    SET OF TypeAndAttribute
                                     OPTIONAL,
    function-set-supported     [3]    FunctionSetType OPTIONAL,
    maximum-length-supported   [4]    INTEGER OPTIONAL,
    dor-for-produce-operations [5]    BOOLEAN DEFAULT TRUE,
    dor-for-consume-operations [6]    BOOLEAN DEFAULT TRUE,
    rOA-protocols-accessee     [7]    ROAProtocols OPTIONAL,
```

rOA-protocols-accessor	[8]	ROAProtocols OPTIONAL,
bilateralInformation	[9]	SEQUENCE OF
		BilateralInformationEntry OPTIONAL,
server-selected-protocol-version	[10]	INTEGER {
version-1	(1),	
version-2	(2) }	OPTIONAL }

Change the ASN.1 definition of "ConstraintsType" in paragraph b) as follows:

```

ConstraintsType ::= SEQUENCE {
    name-constraint      [0]  NameConstraint,
    version-constraint   [1]  VersionConstraint,
    profile-supported     [2]  SEQUENCE OF OBJECT IDENTIFIER
                               OPTIONAL }

```

Page 28

Change the ASN.1 definition of "VersionConstraint" as follows:

```

VersionConstraint ::= ENUMERATED {
    no-version-constraint      (0),
    version-unambiguity        (1),
    version-not-supported      (2) }

```

Add the following paragraph at the end of the description of 2) Version-constraint in paragraph b):

iii) Version not supported (conceptual document is not supported).

Add the following paragraph to the bottom of paragraph b):

3) **profile-supported** specifies the function subsets (for example, function profiles) which are supported by the DFR-Server.

Page 29

Add the following two paragraphs after paragraph i):

j) **bilateralInformation (O)**: This parameter includes bilateral information between the DFR-Server and the DFR-User.

k) **server-selected-protocol-version (O)**: This parameter indicates the DFR protocol version which the DFR-Server selected. This parameter is only present if **protocol-version** is specified in the bind argument. If the DFR-Server supports the DFR protocol version specified by the DFR-User, the DFR-Server includes the value corresponding to the specified DFR protocol version in this parameter. If the DFR-Server does not support

the DFR protocol version specified by the DFR-User, the DFR-Server includes the value corresponding to one of the DFR protocol versions supported by the DFR-Server.

Page 32

Subclause 8.1.3.2

Change the ASN.1 definition of "Reservation" as follows:

```
Reservation ::= SEQUENCE {
    reservation-duration [0] GeneralizedTime OPTIONAL,
    reservation-level     [1] ReservationLevel,
    reservation-status    [2] ReservationStatus DEFAULT uncommitted,
    reservation-referent  [3] BOOLEAN DEFAULT FALSE }
```

Page 39

Subclause 8.1.5.6

Change the ASN.1 definition of "EntryInformationSelection" as follows:

```
EntryInformationSelection ::= SEQUENCE {
    read-selector      [0] ENUMERATED {
        attributes-only           (0),
        attributes-and-content    (1),
        content-only              (2),
        dor-to-attr-only          (3),
        attr-and-dor-to-content   (4),
        dor-to-content-only       (5),
        dor-to-entire-object      (6),
        attr-and-dor-to-entire-object (7),
        attributes-and-part-of-content (8),
        part-of-content-only      (9) },
        DEFAULT attributes-only,
    attribute-selection [1] AttributeSelection OPTIONAL,
    content-selection   [2] SEQUENCE {
        content-server-id      DistinguishedName,
        content-selection-parameter EXTERNAL } OPTIONAL }
```

Page 40

Subclause 8.1.5.6

Change the ASN.1 definition of "EntryInformation" as follows:

```
EntryInformation ::= CHOICE {
    attributes-only           [0] DfrEntryAttributes,
    attributes-and-content    [1] DfrObject,
    ... }
```