



Information technology — Text and office systems — Document Printing Application (DPA) —

Part 1: Abstract service definition and procedures

TECHNICAL CORRIGENDUM 1

Technologies de l'information — Bureautique — Application impression de documents (DPA) —

Partie 1: Définition de service abstrait et procédures

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to International Standard ISO/IEC 10175-1:1996 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 33, *Distributed application services*.

Page 74

Subclause 8.4.7

In the syntax definition of **ServiceProblem**, change:

unsupported-operation (15) },

to:

unsupported-operation (15),
clean-logical-printer-unsupported (16) },

Page 75

At the end of 8.4.7, add the following item:

- p) **clean-logical-printer-unsupported**: A client made a request to clean a logical-printer that the server considers to be a gateway rather than a container.

Page 75

Subclause 8.4.8

In the syntax definition of **UpdateProblem**, change:

cancellation-not-possible (5) },

to:

cancellation-not-possible (5) ,
resubmit-job-not-possible (6) , -- *new problem*
deletion-not-possible (7)}, -- *new problem*

At the end of 8.4.8, add the following items:

- e) **resubmit-job-not-possible**: A client made a request to resubmit a job that is currently printing.
- f) **deletion-not-possible**: A client made a request to delete a server or physical-printer that contains jobs.

Page 78

Subclause 8.5.4

At the end of 8.5.4, add the following items:

- j) **id-val-event-report-job-cancelled**: The server has completed cancelling the print-job.
- k) **id-val-event-report-printer-cleaned**: The clean operation has been completed on the printer.
- l) **id-val-event-report-server-cleaned**: The clean operation has been completed on the server.
- m) **id-val-event-report-job-resubmitted**: The job has been resubmitted and accepted by the new server (which may be the same as, or different from, the original server).

Page 284

At the end of the list headed:

-- **Operation Attributes**
id-att-priority ID ::= { id-oc-operation 0 }

add the following attribute-identifier values:

id-att-reset ID ::= { id-oc-operation 4 }
id-att-trace-enable ID ::= { id-oc-operation 5 }
id-att-backup ID ::= { id-oc-operation 7 }

Page 294

Change the lines:

-- **DPA Attribute Value Classes** --

to:

-- **DPA Attribute and Operation Value Classes** --

 -- **Operation value classes** --
id-vc-when ID ::= { id-vc 109 }
id-vc-reset ID ::= { id-vc 116 }