
Cards and security devices for personal identification — Test methods —

Part 6: Contactless proximity objects

AMENDMENT 1: Dynamic power level management

*Cartes et dispositifs de sécurité pour l'identification personnelle —
Méthodes d'essai —*

Partie 6: Objets sans contact de proximité

AMENDEMENT 1: Gestion dynamique de niveau de puissance



Reference number
ISO/IEC 10373-6:2020/Amd.1:2021(E)

Documents
Document Sharing Hub
© ISO/IEC 2021



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier; Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and security devices for personal identification*.

A list of all parts in the ISO/IEC 10373 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Cards and security devices for personal identification — Test methods —

Part 6: Contactless proximity objects

AMENDMENT 1: Dynamic power level management

Page 3, 3.2

Add the following symbols:

" H_0 PCD field strength during power level management test procedures"

Page 7, 4.7, Table 3

Add the following two rows after the row for "Optional PICC classes":

"

Parameter	Description	Unit
Support of PLI_{ATQ} handling	Ability to change power level (and therefore field strength) after receiving PLI_{ATQ} from a PICC	
Support of PLI_{CID} handling	Ability to change power level (and therefore field strength) after receiving PLI_{CID} from a PICC	

"

Page 8, 4.8, Table 6

Replace Table 6 with the following table:

"

Table 6 — PICC manufacturer information

Parameter	Description	Unit
Location, center and size of the antenna	Drawing with dimensions of the PICC outside shape and the position of the external rectangle/circle of the claimed PICC class.	
PICC class (optional) ^a	Claimed PICC class	
Resonance frequency range (optional)	Minimum and maximum resonance frequency	MHz
Communication signal interface	Supported communication signal interface(s): — Type A — Type B — Type A and Type B	
^a If not provided, test methods for Class 1 shall be used		