
**Information technology — Generic coding
of moving pictures and associated audio
information —**

**Part 1:
Systems**

**AMENDMENT 3: Transport of HEVC video
over MPEG-2 systems**

*Technologies de l'information — Codage générique des images
animées et du son associé —*

*Partie 1:
Systèmes*

AMENDEMENT 3: Transport de vidéo HEVC sur les systèmes MPEG-2



Reference number
ISO/IEC 13818-1:2013/Amd.3:2014(E)

Documents
Document Sharing Hub
© ISO/IEC 2014



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 3 to ISO/IEC 13818-1:2013 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in collaboration with ITU-T. The identical text is published as Rec. ITU-T H.222.0 (2012)/Amd.3 (01/2014).

INTERNATIONAL STANDARD
RECOMMENDATION ITU-TInformation technology – Generic coding of moving pictures
and associated audio information: Systems

Amendment 3

Transport of HEVC video over MPEG-2 systems

1) Clause 1.2.2

Add the following references:

- Recommendation ITU-T H.265 (2013), *High efficiency video coding*.
ISO/IEC 23008-2:2013, *Information technology – High efficiency coding and media delivery in heterogeneous environments – Part 2: High efficiency video coding*.

2) Clauses 2.1.95 to 2.1.109

Add the following definitions after clause 2.1.94:

2.1.95 HEVC video stream: A byte stream as specified in Rec. ITU-T H. 265 | ISO/IEC 23008-2 Annex B.

2.1.96 HEVC access unit: An access unit as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2 with the constraints specified in 2.17.1.

2.1.97 HEVC 24-hour picture (system): An *HEVC access unit* with a presentation time that is more than 24 hours in the future. For the purpose of this definition, *HEVC access unit* n has a presentation time that is more than 24 hours in the future if the difference between the initial arrival time $t_{ai}(n)$ and the DPB output time $t_{o,dpb}(n)$ is more than 24 hours.

2.1.98 HEVC slice: An *HEVC independent slice segment* and zero or more subsequent *HEVC dependent slice segments* preceding the next *HEVC independent slice segment* (if any) within the same *HEVC access unit*.

2.1.99 HEVC slice segment: A *byte_stream_nal_unit* with *nal_unit_type* in the range of 0 to 9 and 16 to 23, as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2.

2.1.100 HEVC dependent slice segment: An *HEVC slice segment* with the syntax element *dependent_slice_segment_flag* in the slice header set to a value equal to 1, as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2.

2.1.101 HEVC independent slice segment: An *HEVC slice segment* with the syntax element *dependent_slice_segment_flag* in the slice header set to a value 0 or inferred to be equal to 0, as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2.

2.1.102 HEVC tile of slices: One or more consecutive *HEVC slices* which form the coded representation of a tile, as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2.

2.1.103 HEVC still picture (system): An HEVC still picture consists of an *HEVC access unit* containing an IDR picture preceded by VPS, SPS and PPS NAL units, as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2, that carry sufficient information to correctly decode this IDR picture. Preceding an HEVC still picture, there shall be another HEVC still picture or an end of sequence NAL unit terminating a preceding coded video sequence, as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2.

2.1.104 HEVC video sequence (system): A coded video sequence as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2.

2.1.105 HEVC video sub-bitstream: A subset of the NAL units of an HEVC video stream in their original order.

2.1.106 HEVC temporal video sub-bitstream: An *HEVC video sub-bitstream* that contains all VCL NAL units and associated non-VCL NAL units of the temporal sub-layer, as specified in Rec. ITU-T H.265 | ISO/IEC 23008-2, associated with TemporalId equal to 0 and which may additionally contain all VCL NAL units and associated non-VCL NAL units of all temporal sub-layers associated with a contiguous range of TemporalId from 1 to a value equal to or smaller than $\text{sps_max_sub_layers_minus1}$ included in the active sequence parameter set, as specified in Rec. ITU-T H.265 | ISO/IEC 23008-2.

2.1.107 HEVC temporal video subset: An *HEVC video sub-bitstream* that contains all VCL NAL units and the associated non-VCL NAL units of one or more temporal sub-layers, as specified in Rec. ITU-T H.265 | ISO/IEC 23008-2, with each temporal sub-layer not being present in the corresponding *HEVC temporal video sub-bitstream* and TemporalId associated with each temporal sub-layer forming a contiguous range of values.

NOTE – According to the constraints for the transport of HEVC specified in 2.17.1, each temporal sub-layer of an *HEVC video stream* is present either in the *HEVC temporal video sub-bitstream* or in exactly one *HEVC temporal video subset* which is carried in a set of elementary streams that are associated by hierarchy descriptors. This prevents the multiple inclusion of the same temporal sub-layer and allows aggregation of the *HEVC temporal video sub-bitstream* with associated *HEVC temporal video subsets* according to the hierarchy descriptors, as specified in 2.17.3.

2.1.108 HEVC highest temporal sub-layer representation: The sub-layer representation of the temporal sub-layer with the highest value of TemporalId, as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2, in the associated *HEVC temporal video sub-bitstream* or *HEVC temporal video subset*.

2.1.109 HEVC complete temporal representation: A sub-layer representation as defined in Rec. ITU-T H.265 | ISO/IEC 23008-2 that contains all temporal sub-layers up to the temporal sub-layer with TemporalId equal to $\text{sps_max_sub_layers_minus1}+1$ as included in the active sequence parameter set, as specified in Rec. ITU-T H.265 | ISO/IEC 23008-2.

3) Clause 2.4.2.6

Replace the following two paragraphs:

Replace:

The delay of any data through the system target decoder buffers shall be less than or equal to one second except for still picture video data and ISO/IEC 14496 streams. Specifically: $\text{td}_n(j) - t(i) \leq 1$ second for all j , and all bytes i in access unit $A_n(j)$.

with:

The delay of any data through the system target decoder buffers shall be less than or equal to one second except for still picture video data, ISO/IEC 14496 and ISO/IEC 23008-2 streams. Specifically: $\text{td}_n(j) - t(i) \leq 1$ second for all j , and all bytes i in access unit $A_n(j)$.

Replace:

For ISO/IEC 14496 streams, the delay is constrained by $\text{td}_n(j) - t(i) \leq 10$ seconds for all j , and all bytes i in access unit $A_n(j)$.

with:

For ISO/IEC 14496 and ISO/IEC 23008-2 streams, the delay is constrained by $\text{td}_n(j) - t(i) \leq 10$ seconds for all j , and all bytes i in access unit $A_n(j)$.

4) Clause 2.4.2.11

Add the following new clause immediately after clause 2.4.2.10:

2.4.2.11 T-STD extensions for carriage of HEVC

T-STD extensions and T-STD parameters for the decoding of HEVC video streams are defined in 2.17.2 and 2.17.3. Program stream support including P-STD extensions and P-STD parameters are not specified for HEVC video streams.