



INTERNATIONAL STANDARD ISO/IEC 14443-2:2001/Amd.1:2005
TECHNICAL CORRIGENDUM 1

Published 2007-11-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Identification cards — Contactless integrated circuit(s) cards — Proximity cards —

Part 2: Radio frequency power and signal interface

AMENDMENT 1: Bit rates of $f_c/64$, $f_c/32$ and $f_c/16$

TECHNICAL CORRIGENDUM 1

Cartes d'identification — Cartes à circuit(s) intégré(s) sans contact — Cartes de proximité —

Partie 2: Interface radiofréquence et des signaux de communication

AMENDEMENT 1: Débit binaires de $f_c/64$, $f_c/32$ et $f_c/16$

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO/IEC 14443-2:2001/Amd.1:2005 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.

Page 4, Subclause 8.1.2.2

Replace the sentence:

“The parameter *a* in figure Amd. 1-2 shall be between 0 and 0,6 for bit rates of *fc/64*, *fc/32* and *fc/16*.”

with the following:

“The parameter *a* in figure Amd. 1-2 is specified in table C1 for bit rates of *fc/64*, *fc/32* and *fc/16*.”

Table C1 — Parameter *a*

Parameter	Bit rate					
	<i>fc/64</i>		<i>fc/32</i>		<i>fc/16</i>	
	Min	Max	Min	Max	Min	Max
<i>a</i>	0	0,2	0	0,35	0	0,6

”