INTERNATIONAL STANDARD ISO/IEC 14496-1:2004
TECHNICAL CORRIGENDUM 1

Published 2006-09-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Coding of audio-visual objects —

Part 1: Systems

TECHNICAL CORRIGENDUM 1

Technologies de l'information — Codage des objets audiovisuels —

Partie 1: Systèmes

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO/IEC 14496-1:2004 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information.*

In subclause 7.1.3.5, "Composition Time Stamp (CTS)," replace:

7.1.3.5 Composition Time Stamp (CTS)

Each composition unit has an associated nominal composition time, the time at which it must be available in the composition memory for composition. The CU is not guaranteed to be available in the composition memory *for composition* before this time. Since the SDM assumes an instantaneous decoding process, the CU is available to the *decoder*, at that instant in time corresponding to the DTS of the corresponding AU, for further use (e.g. in prediction processes).

This instant in time is implicitly known, if the (constant) temporal distance between successive composition units is indicated in the setup of the elementary stream. Otherwise a composition time stamp (CTS) whose syntax is defined in 10.2.4 conveys this instant in time.

ICS 35.040 **Ref. No. ISO/IEC 14496-1:2004/Cor.1:2006(E)**

© ISO/IEC 2006 – All rights reserved

Published in Switzerland

Documents
Document Sharing Hub

Full document details: ISO_IEC 14496-1_2004_COR1_2006

The current CU is instantaneously accessible by the compositor anytime between its composition time and the composition time of the subsequent CU. If a subsequent CU does not exist, the current CU becomes unavailable at the end of the lifetime of its elementary stream (i.e., when its elementary stream descriptor is removed).

with:

7.1.3.5 Composition Time Stamp (CTS)

Each composition unit has an associated nominal composition time, the time at which it must be available in the composition memory for composition. The CU is not guaranteed to be available in the composition memory *for composition* before this time. Since the SDM assumes an instantaneous decoding process, the CU is available to the *decoder*, at that instant in time corresponding to the DTS of the corresponding AU, for further use (e.g. in prediction processes).

This instant in time is implicitly known, if the (constant) temporal distance between successive composition units is indicated in the setup of the elementary stream. Otherwise a composition time stamp (CTS) whose syntax is defined in 10.2.4 conveys this instant in time.

The current CU is instantaneously accessible by the compositor anytime between its composition time and the composition time of the subsequent CU. If a subsequent CU does not exist, the current CU becomes unavailable at the end of the lifetime of its elementary stream (i.e., when its elementary stream descriptor is removed).

In case of audio decoders, the following additionally applies to the audio samples within a composition unit: the composition time applies to the *n*-th audio sample within the composition unit. The value of *n* is 1 unless explicitly specified in ISO/IEC 14496-3 subclause 1.6.6 *Interface between Audio and Systems*.

In subclause 7.2.2.2.2, replace:
ExtDescrTagStartRange = 0x60

with:

ExtDescrTagStartRange = 0x6A

In subclause 7.2.6.16.1, replace:

```
abstract class ExtensionDescriptor extends BaseDescriptor
: bit(8) tag = ExtDescrTagStartRange .. ExtDescrTagEndRange {
   // empty. To be filled by classes extending this class.
}
```

with:

```
abstract class ExtensionDescriptor extends BaseDescriptor
: bit(8) tag = ExtensionProfileLevelDescrTag, ExtDescrTagStartRange .. ExtDescrTagEndRange
{
   // empty. To be filled by classes extending this class.
}
```


© ISO/IEC 2006 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO_IEC 14496-1_2004_COR1_2006