



Information technology — Coding of audio-visual objects — Part 10: Advanced Video Coding

TECHNICAL CORRIGENDUM 1

Technologies de l'information — Codage des objets audiovisuels —

Partie 10: Codage visuel avancé

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO/IEC 14496-10:2012 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

In G.7.4.3.4, replace the following:

"When `quality_id` is equal to 0, the NAL units with `DQId` equal to `ref_layer_dq_id` shall have `discardable_flag` equal to 0.

The variable `MaxRefLayerDQId` is set equal to the maximum value of `ref_layer_dq_id` for the slices of the current layer representation."

with

"When `quality_id` is equal to 0, the NAL units with `DQId` equal to `ref_layer_dq_id` shall have `discardable_flag` equal to 0.

When `ref_layer_dq_id` is greater than or equal to 0, it is a requirement of bitstream conformance that the layer representation with `DQId` equal to `ref_layer_dq_id` is present in the bitstream.

The variable MaxRefLayerDQId is set equal to the maximum value of ref_layer_dq_id for the slices of the current layer representation."

Replace H.8.5.1 with the following text:

H.8.5.1 Derivation process for required anchor view components

This process is recursively invoked to derive the set of required anchor view components for a specified view.

Input to this process is a variable viewId, representing a view with view_id equal to viewId, with its corresponding view order index denoted by vOldx.

Outputs of this process are a possibly updated VOIdxList, and additional invocations of the derivation process based on the inter-view dependency for anchor view components in the view with view_id equal to viewId as specified in the sequence parameter set MVC extension.

The following ordered steps are specified:

1. Add vOldx to VOIdxList if the same value is not already included in VOIdxList.
2. Depending on num_anchor_refs_I0[vOldx] and num_anchor_refs_I1[vOldx], the following applies.
 - If both num_anchor_refs_I0[vOldx] and num_anchor_refs_I1[vOldx] are equal to 0, terminate this process.
 - Otherwise (num_anchor_refs_I0[vOldx] or num_anchor_refs_I1[vOldx] is not equal to 0), the following ordered steps are specified:
 - a. When num_anchor_refs_I0[vOldx] is not equal to 0, invoke the process specified in subclause H.8.5.1 for each viewId equal to anchor_ref_I0[vOldx][i] for all i in the range of 0 to num_anchor_refs_I0[vOldx] – 1, inclusive, in ascending order of i.
 - b. When num_anchor_refs_I1[vOldx] is not equal to 0, invoke the process specified in subclause H.8.5.1 for each viewId equal to anchor_ref_I1[vOldx][i] for all i in the range of 0 to num_anchor_refs_I1[vOldx] – 1, inclusive, in ascending order of i.

Replace H.8.5.2 with the following text:

H.8.5.2 Derivation process for required non-anchor view components

This process is recursively invoked to derive the set of required non-anchor view components for a specified view.

Input to this process is a variable viewId, representing a view with view_id equal to viewId, with its corresponding view order index denoted by vOldx.

Outputs of this process are a possibly updated VOIdxList and additional invocations of the derivation process based on the inter-view dependency for non-anchor view components in the view with view_id equal to viewId as specified in the sequence parameter set MVC extension.

The following ordered steps are specified:

1. Add vOldx to VOIdxList if the same value is not already included in VOIdxList.
2. Depending on num_non_anchor_refs_I0[vOldx] and num_non_anchor_refs_I1[vOldx], the following applies.
 - If both num_non_anchor_refs_I0[vOldx] and num_non_anchor_refs_I1[vOldx] are equal to 0, terminate this process.
 - Otherwise (num_non_anchor_refs_I0[vOldx] or num_non_anchor_refs_I1[vOldx] is not equal to 0), the following ordered steps are specified: