



Information technology — Coding of audio-visual objects — Part 16: Animation Framework eXtension (AFX)

TECHNICAL CORRIGENDUM 1

*Technologies de l'information — Codage des objets audiovisuels —
Partie 16: Extension du cadre d'animation (AFX)*

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO/IEC 14496-16:2011 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information Technology*, Subcommittee SC 29, *Coding of Audio, Picture, Multimedia and Hypermedia Information*.

Replace section 5.2.5.3.5.1 Syntax

```
"Class IntArrayDecoder (numberOfdata, dim)
{
    ....
}"
with
```

```
Class IntArrayDecoder(numberOfdata, dim)
{
    Bit(4) predictionMode;
    Bit(4) binarizationMode;
    If ((binarizationMode == 0) && (predictionMode == 0)) // FL
    {
```

```

    unsigned int (32) streamSizeFL;
    Bit(8) QP;
    for(i=0;i< numberOfdata *dim;i++)
        bit (QP) nData; // simple QBCR
}
else if (binarizationMode == 1)        // BPC
{
    unsigned int (32) streamSizeBPC;
    If (predictionMode==3)    bit(1-7) predictor;
    bit (5) prefixSize;
    for(i=0;i< numberOfdata *dim;i++)
    {BPPDecoder(prefixSize) nDifData;
        If ((predictionMode==1,4,5)&&(nDifData != 0))    bit(1) nSign;
    }
}
else if (binarizationMode == 2)        // 4C
{
    unsigned int (32) streamSize4C;
    for(i=0;i< numberOfdata *dim;i++)
    {
        If (predictionMode==3)
        {
            bit(3) predictor;
            bit (1) terminationBit;
            while (terminationBit)
            {
                bit(3)    threeBitsFL;
                bit(1)    terminationBit;
            }
        }
        else
        {
            Do
            {
                bit(3)    threeBitsFL;
                bit(1)    terminationBit;
            }
            while (terminationBit)
        }
        If((predictionMode==1,4,5)&&(difValue!=0))    bit(1) signBit;
    }
}
else if (binarizationMode == 3)        // AC
{
    unsigned int (32) streamSizeAC;
    for(i=0;i< numberOfdata *dim;i++)
    {
        If (predictionMode==3)    ACDDecoder(8) predictor
        ACDDecoder(1<<QP) nValue
        ACDDecoder(2) hasnext
        If (nValue!= 0)    ACDDecoder(1) nSign
    }
}
else if (binarizationMode == 4)        // AC/EGk
{
    unsigned int (32) streamSizeACEGk;
    unsigned int (8) K
    unsigned int (8) M
    for(i=0;i< numberOfdata *dim;i++)
    {

```