
Information technology — Coding of audio-visual objects —

Part 3: Audio

AMENDMENT 7: SBR enhancements

Technologies de l'information — Codage des objets audiovisuels —

Partie 3: Codage audio

AMENDEMENT 7



Reference number
ISO/IEC 14496-3:2009/Amd.7:2018(E)

AVA Documents
Document Sharing Hub
© ISO/IEC 2018



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

A list of all parts in the ISO/IEC 14496 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Information technology — Coding of audio-visual objects —

Part 3: Audio

AMENDMENT 7: SBR enhancements

1.5.1.2.6

Replace the first sentence with:

The SBR Object contains the SBR-Tool and the MPEG-4 SBR Enhancements as signalled in the SBR extension element (bs_extension_id== EXTENSION_ID_ESBR) of Annex 8.A and can be combined with the audio object types indicated in Table 1.2. If a decoder detects and supports this SBR extension element, the decoder shall process the MPEG-4 SBR Enhancements.

1.5.2.2

In Table 1.4, update the row for Object Type SBR as follows:

SBR	fs = 24/48 kHz (in/out) (SBR tool)	3	2.5	1)
	fs = 24/48 kHz (in/out) (eSBR tool)	4.5	3	1)
	fs = 24/48 kHz (in/out) (Low Power SBR tool)	2	1.5	1)
	fs = 48/48 kHz (in/out) (Down Sampled SBR tool)	4.5	2.5	1)
	fs = 48/48 kHz (in/out) (Low Power Down Sampled SBR tool)	3	1.5	1)