



INTERNATIONAL STANDARD ISO/IEC 14496-4:2004/Amd.11:2006
TECHNICAL CORRIGENDUM 2

Published 2007-02-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Coding of audio-visual objects —
Part 4:
Conformance testing

AMENDMENT 11: Parametric stereo conformance

TECHNICAL CORRIGENDUM 2

Technologies de l'information — Codage des objets audiovisuels —

Partie 4: Essai de conformité

AMENDEMENT 11: Conformité stéréo paramétrique

RECTIFICATIF TECHNIQUE 2

Technical Corrigendum 2 to ISO/IEC 14496-4:2004/Amd.11:2006 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

ICS 35.040

Ref. No. ISO/IEC 14496-4:2004/Amd.11:2006/Cor.2:2007(E)

© ISO/IEC 2007 — All rights reserved

AVA Documents
Document Sharing Hub

Copyright International Organization for Standardization
Provided by IHS under license with ISO

No reproduction or networking permitted without license from IHS

Not for Resale

Full document details: ISO IEC 14496-4-2004 amd11-2006 cor2-2007

In subclause 6.6.18.2.4, replace Table AMD11.1:

file base name	content	bitrate (kbit/s)	iid_data	icc_data	ipd_data	opd_data	mixing procedure	iid-/icc-mode	Diff max	RMS max (linear)	test procedure
al_sbr_ps_00	sweep	32	-	-	-	-	-	-	8	1.7	RMS
al_sbr_ps_01	sweep	32	y	-	-	-	-	-	12	1.8	RMS
al_sbr_ps_02	sweep	32	-	y	-	-	Ra	-	-	-	-
al_sbr_ps_03	sweep	32	y	y	-	-	Rb	-	-	-	-
al_sbr_ps_04	sweep	32	y	-	y	y	-	-	-	-	-
al_sbr_ps_05	sweep	32	y	y	-	-	Ra	-	-	-	-
al_sbr_ps_06	sweep	32	y	y	-	-	Ra	y	-	-	-

with the following (changes highlighted):

file base name	content	bitrate (kbit/s)	iid_data	icc_data	ipd_data	opd_data	mixing procedure	iid-/icc-mode switching	Diff max baseline decoding	RMS max (linear value) baseline decoding	Diff max unrestricted decoding	RMS max (linear value) unrestricted decoding	test procedure
al_sbr_ps_00	sweep	32	-	-	-	-	-	-	8	1.7	8	1.7	RMS
al_sbr_ps_01	sweep	32	y	-	-	-	-	-	12	1.8	12	1.8	RMS
al_sbr_ps_02	sweep	32	-	y	-	-	R _a	-	30	3.6	30	3.6	RMS
al_sbr_ps_03	sweep	32	y	y	-	-	R _b	-	45	3.7	-	-	RMS
al_sbr_ps_04	sweep	32	y	-	y	y	-	-	12	1.8	-	-	RMS
al_sbr_ps_05	sweep	32	y	y	-	-	R _a	-	40	3.6	-	-	RMS
al_sbr_ps_06	sweep	32	y	y	-	-	R _a	y	40	3.7	-	-	RMS