
**Information technology — JPEG 2000
image coding system: Core coding
system**

**AMENDMENT 4: Guidelines for digital
cinema applications**

*Technologies de l'information — Système de codage d'images
JPEG 2000: Système de codage de noyau*

*AMENDEMENT 4: Lignes directrices pour les applications de cinéma
numérique*



Reference number
ISO/IEC 15444-1:2004/Amd.4:2013(E)

AVA Documents
Document Sharing Hub
© ISO/IEC 2013



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 15444-1:2004/Amd.4 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*, in collaboration with ITU-T. The identical text is published as Rec. ITU-T T.800 (2002)/Amd.4(05/2011).

CONTENTS

	<i>Page</i>
1) Modification to Annex J	1
2) Annex K	16
3) Clause 2.2, Additional references	17
4) Clause 4.1, Abbreviations	17

**INTERNATIONAL STANDARD
RECOMMENDATION ITU-T**

Information technology – JPEG 2000 image coding system: Core coding system

Amendment 4

Guidelines for digital cinema applications

1) Modification to Annex J

Add the following new clause J.16 at the end of Annex J (i.e., immediately following J.15.3):

J.16 Guidelines for digital cinema applications

This clause is intended as guidelines for the usage of JPEG 2000 in the framework of digital cinema applications. It is split in four parts: the first is dedicated to multicast transmission; the second presents the recommended visual frequency weightings for digital cinema environment; the third deals with the use of JPEG 2000 for film archive applications, and finally the fourth gives guidelines for digital cinema distribution.

J.16.1 Reliable multicast transmission of JPEG 2000 codestreams

J.16.1.1 Introduction

Digital Cinema (D-Cinema) content may be delivered to the theatres by using several communication channels, and many of them can be wireless, such as, for example, DVB-T [50], DVB-S [51], and WiMAX [52]. The destination of the video contents, in this case, can also (at reduced resolution/quality) be a mobile user, such as, for instance, an audience located on a train or bus.

In addition to the file transfer approach, already used for digital cinema transfer to the theatres, the use of streaming would allow for applications such as live events exhibition and (Near) movie on demand (in this case, however, additional methods for the reduction of the bit rate must be adopted).

The delivery of JPEG 2000 compressed video is a well-known challenge for wireless IP networks. In the case of TCP, the variable delay is unacceptable for many types of real-time applications. D-Cinema will introduce even more stringent conditions, in terms of both the required bandwidth and the high quality demand.

As concerns the distribution, the requirements can be specified in the following terms:

- low required bandwidth occupancy, not only of the JPEG 2000 compressed content itself, but also considering some signalling overhead;
- reliable transmission of the contents, by use of forward error correction techniques (FEC) and/or selective retransmission of lost data (selective ARQ).

A possible solution can be that of adopting a multicast protocol, which can be adapted to the high bit rate and low packet loss rate necessary for the distribution of D-Cinema content. If using multicast transmission, a reliable protocol could be used, which guarantees the sender that every receiver has a copy equal to the original. NORM protocol [56] can be a viable solution for such needs: it uses a NACK-oriented reliable multicast, achieving reliability by means of negative ACKs that are sent back from the receivers to the sender. In addition, it is possible to specify even a small FEC layer, which reduces the retransmission rate at the expense of some added overhead.

Moreover, in case of multicast transmission of JPEG 2000 codestreams, there are some constraints in limited network bandwidth or capabilities of mobile devices.

New mechanisms are required to distribute D-cinema contents to local theatres, high-end mobile users via wireless networks under the constrained conditions.

In forwarding packets to a mobile user, an intermediate distributor may have such functions such as adjusting the image quality or resolution for network bandwidth, network convergence, or capability of mobile device purposes.

J.16.1.2 Distribution model

Figure J.17 shows a possible scenario for content distribution. Different users, with different quality requirements/capabilities may be foreseen. In this scenario, an intermediate distributor is required with the role of adaptation of resolution/quality for forwarding capabilities.

In Figure J.17, cinema contents are transmitted from the production site (for example, studio post-production house) to regional theatres through satellite links. After that, some resolution or quality level is extracted from the original content and is distributed to local theatres, high-end mobile users, home and low-end mobile users by wireless network such as DVB-T, WiMAX and WLAN (IEEE 802.11n) [54].




Figure J.17 – Distribution scenario for D-Cinema and live event

There are mainly three main problems in network delivery:

- 1) limited bandwidth;
- 2) convergence;
- 3) packet loss.

In forwarding a digital cinema stream to mobile users, an intermediate distributor such as a regional theatre might have functions of adjusting the image quality or resolution for network bandwidth, network convergence, or the capability of mobile device purposes.

J.16.1.3 Multicast protocol overview

NORM (NACK oriented reliable multicast) is a multicast protocol designed to provide end-to-end reliable multicast transfer. This protocol uses generic IP multicast capabilities, and on top of that tries to achieve reliable transfer using NACKs (negative acknowledgments). It can work both on reciprocal multicast network (i.e., wireless or wired LAN) or unidirectional link (such as a unidirectional satellite); in this way, it can satisfy all of the transmission needs for digital cinema distribution [53].

NORM repair capabilities are based on the use of negative acknowledgments (NACKs), sent from the receivers to the sender upon detection of an erroneous or missing packet. The sender transmits packets of data, segmented according to a precise strategy, each of which is identified by symbol numbers. As a receiver detects a missing packet, it initiates a repair request with a NACK message. Upon reception of NACKs, the sender prepares the appropriate repair messages, using FEC (forward error correction) blocks. Each receiver can reinitiate a repair procedure if it does not receive repair blocks.

Feedback suppression is applied, using a random back-off algorithm; each receiver, before sending a NACK for a certain packet, waits for a random-duration interval, during which it senses the medium and checks if other receivers requested a repair for the same packet: if so, it discards the NACK; otherwise, it sends it and waits for repair bits. When the sender receives the NACK, it enqueues repair bits (or the entire lost packet). Feedback suppression works efficiently in this protocol, and can achieve good results.

NACK packets can be sent both in multicast or unicast mode, using the sender's address. In the second case, feedback suppression can be achieved using multicast advertising messages, sent from each sender, which allow the receivers to know which packets have a pending repair request.

A NORM sender can even autonomously add FEC parity bits to each packet, thus enabling the receiver to correct errors and recover losses without starting a NACK procedure.




Figure J.18 – Sender and receiver sequence of operations

Figure J.18 shows a sequence of operations performed by a NORM sender and receiver during the normal transmission session. The sender node enqueues data packets, segmented according to parameters that can be changed by the user to accommodate for particular needs: in this case, JPEG 2000 codestreams are encapsulated and an additional header is included at the end of the NORM packet header. It also periodically enqueues control messages, such as round-trip collection and rate congestion control feedback.

Each receiver controls if the packet is in order and error-free: in this case, it accepts the packet and passes it to the destination application. Otherwise, it enters the NACK procedure: this consists in picking a random back-off delay, based on some parameters such as the greatest round-trip delay, usually supplied by the sender, and delaying NACK transmission until this interval is passed. In the meantime, if it receives a repair request for the same packet or the repair bits, the NACK is dropped; otherwise, it sends the NACK in multicast mode. Sending the NACK in multicast is useful for feedback suppression, as described previously.