



INTERNATIONAL STANDARD ISO/IEC 15444-12:2012
TECHNICAL CORRIGENDUM 2

Published 2014-07-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — JPEG 2000 image coding system —

Part 12:

ISO base media file format

TECHNICAL CORRIGENDUM 2

Technologies de l'information — Système de codage d'images JPEG 2000 —

Partie 12: Format ISO de base pour les fichiers médias

RECTIFICATIF TECHNIQUE 2

Technical Corrigendum 2 to ISO/IEC 15444-12:2012 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

In 8.5.2.1 replace

A TextSubtitleSampleEntry, TextMetadataSampleEntry, or SimpleTextSampleEntry, all of which contain a MIME type, may be used to identify the format of streams for which a MIME type applies. A MIME type applies if the contents of a set of samples, starting with a sync sample and ending at the sample immediately preceding a sync sample, are concatenated in their entirety, and the result meets the decoding requirements for documents of that MIME type. Non-sync samples should be used only if that format specifies the behaviour of 'progressive decoding', and then the sample times indicate when the results of such progressive decoding should be presented (according to the media type).

NOTE the samples in a track that is all sync samples are therefore each a valid document for that MIME type.

ICS 35.040

Ref. No. ISO/IEC 15444-12:2012/Cor.2:2014(E)

© ISO/IEC 2014 – All rights reserved

Published in Switzerland

AVA Documents
Document Sharing Hub

with

A TextSubtitleSampleEntry, TextMetaDataSampleEntry, or SimpleTextSampleEntry, all of which contain a MIME type, may be used to identify the format of streams for which a MIME type applies. A MIME type applies if the contents of the string in the optional configuration box (without its null termination), followed by the contents of a set of samples, starting with a sync sample and ending at the sample immediately preceding a sync sample, are concatenated in their entirety, and the result meets the decoding requirements for documents of that MIME type. Non-sync samples should be used only if that format specifies the behaviour of 'progressive decoding', and then the sample times indicate when the results of such progressive decoding should be presented (according to the media type).

NOTE the samples in a track that is all sync samples are therefore each a valid document for that MIME type.

In 8.5.2.2, replace:

```
class TextMetaDataSampleEntry() extends MetaDataSampleEntry ('mett') {
    string    content_encoding; // optional
    string    mime_format;
    BitRateBox (); // optional
}
```

with

```
class TextConfigBox() extends Fullbox ('txtC', 0, 0) {
    string    text_config;
}

class TextMetaDataSampleEntry() extends MetaDataSampleEntry ('mett') {
    string    content_encoding; // optional
    string    mime_format;
    BitRateBox (); // optional
    TextConfigBox (); // optional
}
```

and replace

```
class SimpleTextSampleEntry(codingname) extends PlainTextSampleEntry (codingname)
{
    string    content_encoding; // optional
    string    mime_format;
    BitRateBox (); // optional
}
```

with

```
class SimpleTextSampleEntry(codingname) extends PlainTextSampleEntry ('stxt') {
    string    content_encoding; // optional
    string    mime_format;
    BitRateBox (); // optional
    TextConfigBox (); // optional
}
```

and replace

```
class TextSubtitleSampleEntry() extends SubtitleSampleEntry ('sbtt') {
    string    content_encoding; // optional
    string    mime_format;
    BitRateBox (); // optional
}
```