
Information technology — Virtualization Management Specification —

*Technologies de l'information — Spécifications pour la gestion de la
virtualisation*



Reference number
ISO/IEC 19099:2014(E)

AVA Documents
Document Sharing Hub
© ISO/IEC 2014



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 19099 was prepared by SVPC Work Group of the DTMF (as INCITS 483-2012) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by the national bodies of ISO and IEC.

American National Standard

*for Information Technology –
Virtualization Management Specification*

Developed by



Where IT all begins



American National Standard
for Information Technology –
Virtualization Management Specification

Secretariat
Information Technology Industry Council

Approved May 29, 2012
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires review by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made towards their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

CAUTION: The developers of this standard have requested that holders of patents that may be required for the implementation of the standard disclose such patents to the publisher. However, neither the developers nor the publisher have undertaken a patent search in order to identify which, if any, patents may apply to this standard. As of the date of publication of this standard and following calls for the identification of patents that may be required for the implementation of the standard, no such claims have been made. No further patent search is conducted by the developer or publisher in respect to any standard it processes. No representation is made or implied that licenses are not required to avoid infringement in the use of this standard.

Published by

**American National Standards Institute, Inc.
25 West 43rd Street, New York, NY 10036**

Copyright © 2012 by Information Technology Industry Council (ITI)
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of ITI, 1101 K Street NW, Suite 610, Washington, DC 20005.

Printed in the United States of America

CONTENTS

Foreword	ix
Introduction	1
1 Scope	3
1.1 Resource Allocation Profile	3
1.2 System Virtualization Profile	3
1.3 Allocation Capabilities Profile	3
1.4 Processor Resource Virtualization Profile	3
1.5 Memory Resource Virtualization Profile	3
1.6 Storage Resource Virtualization Profile	3
1.7 Ethernet Port Resource Virtualization Profile	3
1.8 Virtual System Profile	3
1.9 Generic Device Resource Virtualization Profile	3
1.10 Virtual Ethernet Switch Profile	4
2 Normative references	4
3 Terms and definitions	5
4 Symbols and abbreviated terms	12
5 Resource Allocation Profile	14
5.1 Description	14
5.2 Implementation	18
5.3 Methods	27
5.4 Use cases	35
5.5 CIM elements	40
6 System Virtualization Profile	52
6.1 Description	52
6.2 Implementation	59
6.3 Methods	67
6.4 Use cases	84
6.5 CIM elements	110
7 Allocation Capabilities Profile	126
7.1 Description	126
7.2 Implementation	129
7.3 Methods	130
7.4 Use cases	134
7.5 CIM elements	139
8 Processor Resource Virtualization Profile	144
8.1 Description	144
8.2 Implementation	149
8.3 Methods	157
8.4 Use cases	158
8.5 CIM elements	168
9 Memory Resource Virtualization Profile	178
9.1 Description (informative)	178
9.2 Implementation	186
9.3 Methods	198
9.4 Use cases (informative)	198
9.5 CIM elements	207
10 Storage Resource Virtualization Profile	221
10.1 Description	222
10.2 Implementation	234
10.3 Methods	251
10.4 Use cases	253
10.5 CIM Elements	270
11 Ethernet Port Resource Virtualization Profile	282
11.1 Description	282
11.2 Implementation	291
11.3 Methods	303

11.4	Use cases	304
11.5	CIM elements	318
12	Virtual System Profile	341
12.1	Description	341
12.2	Implementation.....	350
12.3	Methods	360
12.4	Use-cases	363
12.5	CIM elements	374
13	Generic Device Resource Virtualization Profile	381
13.1	Description	381
13.2	Implementation.....	383
13.3	Methods	383
13.4	Use cases	383
13.5	CIM elements	388
14	Virtual Ethernet Switch Profile	390
14.1	Description	390
14.2	Implementation.....	394
14.3	Methods	395
14.4	Use cases	397
14.5	CIM elements	400
Annex A (Informative)	Virtual system modeling — background information.....	407
A.1	Concepts: Model, view, controller	407
A.2	Aspect-oriented modeling approach.....	407
A.3	Presence of model information.....	408
A.4	Model extension through settings.....	409
Annex B (Informative)	Implementation details.....	410
B.1	Dual-configuration implementation approach	410
B.2	Single-configuration implementation approach	413

Figures

Figure 1 – Resource Allocation Profile: Class Diagram	15
Figure 2 – Abstract instance diagram: Concrete resource pool	35
Figure 3 – Abstract instance diagram: Primordial pool with backed resources	36
Figure 4 – Abstract instance diagram: Primordial pool without backed resources.....	36
Figure 5 – Resource pool hierarchy instance diagram	37
Figure 6 – Simple resource allocation	38
Figure 7 – Profiles related to system virtualization	54
Figure 8 – System Virtualization Profile: Class diagram.....	56
Figure 9 – System Virtualization Profile instance diagram: Discovery, localization, and inspection	86
Figure 10 – Virtual system configuration based on input virtual system configurations and implementation defaults ..	98
Figure 11 – Virtual system resource modification	102
Figure 12 – System Virtualization Profile: Snapshot example	105
Figure 13 – Allocation Capabilities Profile: Class diagram	127
Figure 14 – Allocation capabilities associated to CIM_ComputerSystem and CIM_ResourcePool.....	135
Figure 15 – Allocation capabilities associated to CIM_ResourceAllocationSettingData	136
Figure 16 – Multiple CIM_AllocationCapabilities instances	137
Figure 17 – Processor Resource Virtualization Profile: Class Diagram.....	145
Figure 18 – Processor Resource Virtualization Profile: Instance diagram.....	159
Figure 19 – Defined state	160
Figure 20 – Active state	161
Figure 21 – CIM_ModifyResourceSettings – Before	163
Figure 22 – RASD to Modify Resources	164

Figure 23 – CIM_ModifyResourceSettings – After	165
Figure 24 – CIM_AddResourceSettings – Before	166
Figure 25 – RASD to add processor	167
Figure 26 – CIM_AddResourceSettings – After	168
Figure 27 – Memory Resource Virtualization Profile: Profile class diagram	179
Figure 28 – Instance Diagram: Concept of memory resource pool hierarchies	181
Figure 29 – Instance Diagram: Concept of memory resource allocation	183
Figure 30 – Instance Diagram: Memory composition	185
Figure 31 – Instance Diagram: Example CIM representation of memory resource virtualization	200
Figure 32 – Storage Resource Virtualization Profile: Profile class diagram	223
Figure 33 – Instance diagram: Concept of storage resource pool hierarchies	227
Figure 34 – Instance diagram: Concept of storage resource allocation	230
Figure 35 – Cooperation of DMTF SVPC and SNIA SMI-S profiles	233
Figure 36 – Instance diagram: Example CIM representation of storage resource virtualization	254
Figure 37 – Create virtual disk with implicit file creation	263
Figure 38 – Create virtual disk with pre-existing file	265
Figure 39 – Create dedicated virtual disk	267
Figure 40 – Create virtual delta disk and file	269
Figure 41 – Ethernet Port Resource Virtualization: Profile class diagram	283
Figure 42 – Virtual ethernet switch port allocation	287
Figure 43 – Instance Diagram: Ethernet adapter and Ethernet connection resource allocations	289
Figure 44 – Ethernet switch port and Ethernet connection resource pools	306
Figure 45 – Static Ethernet switch port allocation to a virtual Ethernet switch	308
Figure 46 – Ethernet adapter connection to static switch port	310
Figure 47 – Dynamic Ethernet switch port connection capabilities	313
Figure 48 – Dynamic Ethernet switch port allocation	314
Figure 49 – Allocation capabilities for simple Ethernet connection	315
Figure 50 – Simple connection of virtual machine to Ethernet switch	316
Figure 51 – Profiles related to system virtualization	343
Figure 52 – Virtual System Profile: Class diagram	344
Figure 53 – Virtual system states	349
Figure 54 – Virtual system representation and virtual system configuration	354
Figure 55 – Sample virtual system configuration	365
Figure 56 – Sample virtual system in "active" state	367
Figure 57 – Instance diagram: Profile conformance of scoped resources	368
Figure 58 – Generic Device Resource Virtualization: Class diagram	382
Figure 59 – Simple virtual device allocation	384
Figure 60 – Profile registration using central class	385
Figure 61 – Profile registration using scoping class	386
Figure 62 – Determining resource capabilities	387
Figure 63 – DMTF Management profiles related to the virtual Ethernet switch	392
Figure 64 – Virtual Ethernet Switch Profile: Class Diagram	393
Figure 65 – Basic example of virtual Ethernet switch	398
Figure A-1 – State-dependent presence of model elements	408
Figure B-2 – Sample virtual system in a state other than "defined" (Dual-configuration approach)	412
Figure B-3 – Sample virtual system in the "defined" state (Single-configuration approach)	414
Figure B-4 – Sample virtual system in a state other than "defined" (Single-configuration approach)	415

Tables

Table 1 – Component documents	2
Table 2 – Related profiles for the Resource Allocation Profile	14
Table 3 – CIM_ResourcePoolConfigurationService.CreateChildResourcePool() method: Return code values	27
Table 4 – CIM_ResourcePoolConfigurationService.CreateChildResourcePool() method: Parameters	28
Table 5 – CIM_ResourcePoolConfigurationService.DeleteResourcePool() method: Return code values	28
Table 6 – CIM_ResourcePoolConfigurationService.DeleteResourcePool() method: Parameters	29
Table 7 – CIM_ResourcePoolConfigurationService.AddResourcesToResourcePool() method: Return code values	29
Table 8 – CIM_ResourcePoolConfigurationService.AddResourcesToResourcePool() method: Parameters	30
Table 9 – CIM_ResourcePoolConfigurationService.RemoveResourcesFromResourcePool() method: Return code values	31
Table 10 – CIM_ResourcePoolConfigurationService.RemoveResourcesFromResourcePool() method: Parameters	31
Table 11 – CIM_ResourcePoolConfigurationService.ChangeParentResourcePool() method: Return code values	32
Table 12 – CIM_ResourcePoolConfigurationService.ChangeParentResourcePool() method: Parameters	32
Table 13 – CIM elements: Resource Allocation Profile	40
Table 14 – Class: CIM_AffectedJobElement	41
Table 15 – Class: CIM_BaseMetricDefinition	41
Table 16 – Class: CIM_BaseMetricDefinition — Instantaneous consumption	42
Table 17 – Class: CIM_BaseMetricDefinition — Interval metrics	42
Table 18 – Class: CIM_BaseMetricDefinition — Aggregate consumption	42
Table 19 – Class: CIM_BaseMetricValue	43
Table 20 – Class: CIM_BaseMetricValue — Instantaneous consumption	43
Table 21 – Class: CIM_BaseMetricValue — Interval metrics	43
Table 22 – Class: CIM_BaseMetricValue — Aggregate consumption	44
Table 23 – Class: CIM_Component	44
Table 24 – Class: CIM_ConcreteJob	44
Table 25 – Class: CIM_ElementAllocatedFromPool	45
Table 26 – Class: CIM_ElementCapabilities	45
Table 27 – Class: CIM_ElementSettingData	45
Table 28 – Class: CIM_HostedDependency	46
Table 29 – Class: CIM_HostedResourcePool	46
Table 30 – Class: CIM_HostedService	46
Table 31 – Class: CIM_LogicalDevice	47
Table 32 – Class: CIM_MetricDefForME	47
Table 33 – Class: CIM_MetricForME	47
Table 34 – Class: CIM_ResourceAllocationFromPool	48
Table 35 – Class: CIM_ResourceAllocationSettingData (current settings)	48
Table 36 – Class: CIM_ResourceAllocationSettingData (defined settings)	49
Table 37 – Class: CIM_ResourcePool	49
Table 38 – Class: CIM_ResourcePoolConfigurationCapabilities	50
Table 39 – Class: CIM_ResourcePoolConfigurationService	50
Table 40 – Class: CIM_SettingsDefineState	51
Table 41 – Class: CIM_ServiceAffectsElement	51
Table 42 – Class: CIM_SystemDevice	51
Table 43 – Related profiles for the System Virtualization Profile	52
Table 44 – DefineSystem() method: Parameters	70
Table 45 – DefineSystem() method: Return code values	72
Table 46 – DestroySystem() method: Parameters	72
Table 47 – DestroySystem() method: Return code values	73

Table 48 – AddResourceSettings() method: Parameters	73
Table 49 – AddResourceSettings() method: Return code values	74
Table 50 – ModifyResourceSettings() method: Parameters	75
Table 51 – ModifyResourceSettings() Method: Return code values	76
Table 52 – ModifySystemSettings() Method: Parameters	76
Table 53 – ModifySystemSettings() Method: Return code values	77
Table 54 – RemoveResourceSettings() Method: Parameters	78
Table 55 – RemoveResourceSettings() Method: Return code values	78
Table 56 – CreateSnapshot() method: Parameters	79
Table 57 – CreateSnapshot() method: Return code values	80
Table 58 – DestroySnapshot() method: Parameters	80
Table 59 – DestroySnapshot() method: Return code values	81
Table 60 – ApplySnapshot() method: Parameters	81
Table 61 – ApplySnapshot() method: Return code values	82
Table 62 – CIM Elements: System Virtualization Profile	110
Table 63 – Association: CIM_AffectedJobElement	111
Table 64 – Class: CIM_ConcreteJob	112
Table 65 – Class: CIM_Dependency Class	112
Table 66 – Association: CIM_ElementCapabilities (host system)	113
Table 67 – Association: CIM_ElementCapabilities (virtual system management)	113
Table 68 – Association: CIM_ElementCapabilities (snapshot service)	114
Table 69 – Association: CIM_ElementCapabilities (snapshots of virtual systems)	114
Table 70 – Association: CIM_ElementConformsToProfile	115
Table 71 – Association: CIM_HostedDependency	115
Table 72 – Association: CIM_HostedService (virtual system management service)	116
Table 73 – Association: CIM_HostedService (virtual system snapshot service)	116
Table 74 – Association: CIM_LastAppliedSnapshot	117
Table 75 – Association: CIM_MostCurrentSnapshotInBranch	117
Table 76 – Association: CIM_ReferencedProfile	118
Table 77 – Class: CIM_RegisteredProfile	118
Table 78 – Association: CIM_ServiceAffectsElement (virtual system management service)	119
Table 79 – Association: CIM_ServiceAffectsElement	120
Table 80 – Association: CIM_SnapshotOfVirtualSystem	120
Table 81 – Class: CIM_VirtualSystemManagementCapabilities	121
Table 82 – Class: CIM_VirtualSystemManagementCapabilities	121
Table 83 – Class: CIM_VirtualSystemManagementService	121
Table 84 – Class: CIM_VirtualSystemSettingData (input)	122
Table 85 – Class: CIM_VirtualSystemSettingData (Snapshot)	123
Table 86 – Class: CIM_VirtualSystemSnapshotCapabilities	124
Table 87 – Class: CIM_VirtualSystemSnapshotService	124
Table 88 – Class: CIM_VirtualSystemSnapshotServiceCapabilities	125
Table 89 – Related profiles for the Allocation Capabilities Profile	126
Table 90 – Operations: CIM_SettingsDefineCapabilities	131
Table 91 – Operations: CIM_ElementCapabilities	134
Table 92 – CIM elements: Allocation Capabilities Profile	139
Table 93 – Class: CIM_AllocationCapabilities	139
Table 94 – Class: CIM_ElementCapabilities	140
Table 95 – Class: CIM_ElementCapabilities (default)	140
Table 96 – Class: CIM_SettingsDefineCapabilities	141
Table 97 – Class: CIM_SettingsDefineCapabilities (Default)	141
Table 98 – Class: CIM_SettingsDefineCapabilities (minimums)	142
Table 99 – Class: CIM_SettingsDefineCapabilities (maximums)	142

Table 100 – Class: CIM_SettingsDefineCapabilities (Increments)	143
Table 101 – Class: CIM_SettingsDefineCapabilities (Independent Supported Point)	143
Table 102 – Related profiles for the Processor Resource Virtualization Profile	144
Table 103 – Acronyms for RASD adapted for the representation of various flavors of allocation data	153
Table 104 – CIM Elements: Processor Resource Virtualization Profile	169
Table 105 – Association: CIM_Component for resource pool	170
Table 106 – Association: CIM_ElementAllocatedFromPool	171
Table 107 – Association: CIM_ElementSettingData	171
Table 108 – Association: CIM_ElementSettingData for processor resource allocation	172
Table 109 – Association: CIM_ElementSettingData (Processor Resource Pool)	172
Table 110 – Association: CIM_HostedDependency	173
Table 111 – Class: CIM_Processor (host processor)	173
Table 112 – Class: CIM_Processor (virtual system)	173
Table 113 – Class: CIM_RegisteredProfile	174
Table 114 – Association: CIM_ResourceAllocationFromPool	174
Table 115 – Class: CIM_ResourceAllocationSettingData	175
Table 116 – Class: CIM_ResourcePool	175
Table 117 – Association: CIM_SettingsDefineState	176
Table 118 – Association: CIM_SystemDevice (Host Processor)	176
Table 119 – Association: CIM_SystemDevice (Virtual Processor)	177
Table 120 – Related profiles for the Memory Resource Virtualization Profile	178
Table 121 – CIM Elements: Memory Resource Virtualization Profile	208
Table 122 – Association: CIM_AffectedJobElement	209
Table 123 – Class: CIM_AllocationCapabilities (memory allocation capabilities)	209
Table 124 – Class: CIM_AllocationCapabilities (memory allocation mutability)	210
Table 125 – Association: CIM_Component (memory resource)	211
Table 126 – Association: CIM_Component (resource pool)	211
Table 127 – Class: CIM_ConcreteJob	212
Table 128 – Association: CIM_ElementAllocatedFromPool	212
Table 129 – Association: CIM_ElementCapabilities (capabilities)	213
Table 130 – Association: CIM_ElementCapabilities (mutability)	213
Table 131 – Association: CIM_ElementSettingData (memory resource pool)	214
Table 132 – Association: CIM_ElementSettingData (memory resource)	214
Table 133 – Association: CIM_HostedDependency	215
Table 134 – Class: CIM_Memory (host system)	215
Table 135 – Class: CIM_Memory (virtual system)	216
Table 136 – Class: CIM_RegisteredProfile	216
Table 137 – Association: CIM_ResourceAllocationFromPool	216
Table 138 – Class: CIM_ResourceAllocationSettingData	217
Table 139 – Class: CIM_ResourcePool	218
Table 140 – Class: CIM_ResourcePoolConfigurationCapabilities	218
Table 141 – Association: CIM_SettingsDefineState	218
Table 142 – Association: CIM_ServiceAffectsElement	219
Table 143 – Association: CIM_SystemDevice (virtual memory)	219
Table 144 – Association: CIM_SystemDevice (host memory)	220
Table 145 – Related profiles for the Storage Resource Virtualization Profile	221
Table 146 – Optional Features	222
Table 147 – Predefined ResourceSubType values (EXPERIMENTAL)	237
Table 148 – Acronyms for RASD adapted for the representation of various flavors of allocation data	241
Table 149 – CIM Elements: Storage Resource Virtualization Profile	270
Table 150 – Association: CIM_Component for resource pool	272
Table 151 – Class: CIM_DiskDrive (Host)	272

Table 152 – Class: CIM_DiskDrive (Virtual System)	272
Table 153 – Association: CIM_ElementSettingData	273
Table 154 – Association: CIM_ElementSettingData	273
Table 155 – Association: CIM_ElementSettingData	274
Table 156 – Association: CIM_ElementSettingData	274
Table 157 – Association: CIM_HostedDependency	275
Table 158 – Class: CIM_LogicalDisk (Virtual System)	275
Table 159 – Association: CIM_ReferencedProfile	277
Table 160 – Class: CIM_RegisteredProfile	277
Table 161 – Class: CIM_ResourceAllocationSettingData	277
Table 162 – Class: CIM_ResourcePool	278
Table 163 – Association: CIM_SettingsDefineState	279
Table 164 – Class: CIM_StorageAllocationSettingData	279
Table 165 – Class: CIM_StorageVolume for host storage volume	280
Table 166 – Class: CIM_StorageExtent for virtual disks	281
Table 167 – Association: CIM_SystemDevice for host storage volumes	281
Table 168 – Association: CIM_SystemDevice for virtual resources	281
Table 169 – Related profiles for the Ethernet Port Resource Virtualization Profile	282
Table 170 – Acronyms for EASD adapted for the representation of various flavors of allocation data	295
Table 171 – CIM Elements: Ethernet Port Resource Virtualization Profile	318
Table 172 – Association: CIM_ActiveConnection	320
Table 173 – Association: CIM_Component for resource pool	321
Table 174 – Association: CIM_ElementAllocatedFromPool	321
Table 175 – Association: CIM_ElementSettingData for connection resources	322
Table 176 – Association: CIM_ElementSettingData for CIM_EthernetPort resource allocation	322
Table 177 – Association: CIM_ElementSettingData for CIM_EthernetPort resource allocation	323
Table 178 – Class: CIM_EthernetPort (host system)	323
Table 179 – Class: CIM_EthernetPort (virtual system)	323
Table 180 – Class: CIM_EthernetPortAllocationSettingData for Ethernet adapter (Q_EASD)	324
Table 181 – Class: CIM_EthernetPortAllocationSettingData for Ethernet adapter (R_EASD)	324
Table 182 – Class: CIM_EthernetPortAllocationSettingData for Ethernet adapter (C_EASD)	325
Table 183 – Class: CIM_EthernetPortAllocationSettingData for Ethernet adapter (D_EASD)	326
Table 184 – Class: CIM_EthernetPortAllocationSettingData for Ethernet adapter (M_EASD)	327
Table 185 – Class: CIM_EthernetPortAllocationSettingData for Ethernet connection (Q_EASD)	328
Table 186 – Class: CIM_EthernetPortAllocationSettingData for Ethernet connection (R_EASD)	329
Table 187 – Class: CIM_EthernetPortAllocationSettingData for Ethernet connection (C_EASD)	329
Table 188 – Class: CIM_EthernetPortAllocationSettingData for Ethernet connection (D_EASD)	330
Table 189 – Class: CIM_EthernetPortAllocationSettingData for Ethernet connection (M_EASD)	331
Table 190 – Class: CIM_EthernetPortAllocationSettingData for Ethernet switch port (Q_EASD)	332
Table 191 – Class: CIM_EthernetPortAllocationSettingData for Ethernet switch port (R_EASD)	332
Table 192 – Class: CIM_EthernetPortAllocationSettingData for Ethernet switch port (C_EASD)	333
Table 193 – Class: CIM_EthernetPortAllocationSettingData for Ethernet switch port (D_EASD)	334
Table 194 – Class: CIM_EthernetPortAllocationSettingData for Ethernet switch port (M_EASD)	335
Table 195 – Class: CIM_RegisteredProfile	335
Table 196 – Class: CIM_ResourcePool (Ethernet adapter)	336
Table 197 – Class: CIM_ResourcePool	336
Table 198 – Class: CIM_ResourcePool (Ethernet switch port)	337
Table 199 – Association: CIM_SettingsDefineState	339
Table 200 – Association: CIM_SystemDevice (Virtual EthernetPort)	339
Table 201 – Association: CIM_SystemDevice (host Ethernet adapter)	339
Table 202 – Related profiles for the Virtual System Profile	341
Table 203 – Observation of virtual system states	350

Table 204 – Observation of virtual system state transitions	352
Table 205 – CIM_ComputerSystem.RequestStateChange() method: Parameters	361
Table 206 – CIM_PowerManagementService.RequestPowerStateChange() method: Parameters	361
Table 207 – CIM elements: Virtual System Profile	374
Table 208 – Association: CIM_AffectedJobElement	375
Table 209 – Class: CIM_ComputerSystem	375
Table 210 – Class: CIM_ConcreteJob	375
Table 211 – Association: CIM_ElementConformsToProfile	376
Table 212 – Association: CIM_ElementSettingData	377
Table 213 – Class: CIM_EnabledLogicalElementCapabilities	377
Table 214 – Association: CIM_ReferencedProfile	378
Table 215 – Class: CIM_RegisteredProfile	378
Table 216 – Association: CIM_SettingsDefineState	379
Table 217 – Class: CIM_VirtualSystemSettingData	379
Table 218 – Association: CIM_VirtualSystemSettingDataComponent	380
Table 219 – Related profiles for the Generic Device Resource Virtualization Profile	381
Table 220 – CIM Elements: Generic Device Resource Virtualization Profile	388
Table 221 – Class: CIM_AllocationCapabilities	388
Table 222 – Class: CIM_ElementCapabilities	389
Table 223 – Class: CIM_RegisteredProfile	389
Table 224 – Related profiles for the Virtual Ethernet Switch Profile	390
Table 225 – CIM Elements: Virtual System Profile	400
Table 226 – Class: CIM_ComputerSystem	401
Table 227 – Association: CIM_ElementSettingData	401
Table 228 – Association: CIM_HostedCollection	402
Table 229 – Association: CIM_MemberOfCollection	402
Table 230 – Class: CIM_NetworkVLAN	403
Table 231 – Class: CIM_RegisteredProfile	403
Table 232 – Association: CIM_SettingsDefineState	405
Table 233 – Association: CIM_SystemComponent	405
Table 234 – Class: CIM_VirtualEthernetSwitchSettingData	406
Table 235 – Association: CIM_VirtualSystemSettingDataComponent	406

Foreword (This foreword is not part of American National Standard INCITS 483-2012.)

Virtualization Management was prepared by the System Virtualization, Partitioning, and Clustering Working Group of the DTMF.

DMTF is a not-for-profit association of industry members dedicated to promoting enterprise and systems management and interoperability. For information about the DMTF, see <http://www.dmtf.org>.

Requests for interpretation, suggestions for improvement or addenda, or defect reports are welcome. They should be sent to InterNational Committee for Information Technology Standards (INCITS), ITI, 1101 K Street, NW, Suite 610, Washington, DC 20005.

This standard was processed and approved for submittal to ANSI by INCITS. Committee approval of this standard does not necessarily imply that all committee members voted for its approval. At the time it approved this standard, INCITS had the following members:

Don Wright, Chair
Jennifer Garner, Secretary

<i>Organization Represented</i>	<i>Name of Representative</i>
Adobe Systems Inc.....	Scott Foshee Steve Zilles (Alt.)
AIM Global, Inc.	Steve Halliday
Apple	Helene Workman David Singer (Alt.)
Distributed Management Task Force	John Crandall Jeff Hilland (Alt.)
EMC Corporation	Gary Robinson Stephen Diamond (Alt.)
Farance, Inc.....	Frank Farance Timothy Schoechle (Alt.)
GS1 US	Frank Sharkey Charles Biss (Alt.)
Hewlett-Packard Company	Karen Higginbottom Paul Jeran (Alt.)
IBM Corporation	Alexander Tarpinian Robert Weir (Alt.) Arnaud Le Hors (Alt.) Debra Boland (Alt.) Steve Holbrook (Alt.) Gerald Lane (Alt.)
IEEE	Jodie Haasz Terry deCourcelle (Alt.) Bob Labelle (Alt.)
Intel	Philip Wennblom Grace Wei (Alt.) Stephen Balogh (Alt.)
Lexmark International	Don Wright Dwight Lewis (Alt.) Paul Menard (Alt.) Jerry Thrasher (Alt.)
Microsoft Corporation	Jim Hughes Dick Brackney (Alt.) John Calhoon (Alt.)
National Institute of Standards & Technology	Michael Hogan Sal Francomacaro (Alt.) Dan Benigni (Alt.) Fernando Podio (Alt.) Teresa Schwarzhoff (Alt.) Wo Chang (Alt.) Elaine Newton (Alt.)

<i>Organization Represented</i>	<i>Name of Representative</i>
Oracle Corporation	Donald R. Deutsch Jim Melton (Alt.) Michael Kavanaugh (Alt.) Toshihiro Suzuki (Alt.) Jeff Mischkinsky (Alt.) Tony DiCenzo (Alt.) Patrick Curran (Alt.)
Purdue University	Stephen Elliott Kevin O'Connor (Alt.)
Telecommunications Industry Association (TIA)	Herb Congdon, II Cheryl Blum (Alt.)
US Department of Defense	Jerry Smith Dennis Devera (Alt.) Dave Brown (Alt.) Leonard Levine (Alt.) Matthew Young (Alt.) Thomas D'Agostino (Alt.)
US Department of Homeland Security	Peter Shebell Gregg Piermarini (Alt.) Juan Gonzalez (Alt.)
VMware	Lawrence Lamers Winston Bumpus (Alt.)

The System Virtualization, Partitioning, and Clustering Working Group of the DTMF, which developed this standard, had the following contributors:

Michael Johanssen, IBM, Editor

Contributors:

Gareth Bestor - IBM
Chris Brown - HP
Mike Dutch - Symantec
Jim Fehlig - Novell
Kevin Fox - Sun Microsystems, Inc.
Ron Goering - IBM
Daniel Hiltgen - EMC/VMware
Michael Johanssen - IBM
Larry Lamers - EMC/VMware
Andreas Maier - IBM
Aaron Merkin - IBM
John Parchem - Microsoft
Nihar Shah - Microsoft
David Simpson - IBM
Carl Waldspurger - EMC/VMware

Acknowledgments

The authors wish to acknowledge the following people.

Contributors:

- Kamesh Aiyer – EMC
- Tatyana Bagerman – Oracle
- Dave Barrett – Emulex
- Oliver Benke – IBM
- Gareth Bestor – IBM
- Chris Brown -- Hewlett-Packard
- Ron Doyle – IBM
- Mike Dutch – Symantec
- George Ericson – EMC
- James Fehlig – Novell
- Kevin Fox – Sun Microsystems, Inc.
- Michael Gering – IBM
- Ron Goering – IBM
- Steffen Grarup – VMware Inc.
- Steve Hand – Symantec
- Mark Hapner – Sun Microsystems, Inc.
- Daniel Hiltgen – VMware Inc.
- Michael Johanssen – IBM
- Mark Johnson – IBM
- Lawrence Lamers – VMware Inc.
- Richard Landau – Dell
- John Leung – Intel Corporation
- John Linn – EMC
- Fred Maciel – Hitachi Ltd.
- Andreas Maier – IBM
- Srinivas Maturi – Oracle
- Aaron Merkin – IBM
- John Parchem – Microsoft Corporation
- Shishir Pardikar – Citrix Systems Inc.
- Murali Rajagopal -- QLogic
- Rene Schmidt – VMware Inc.
- Stephen Schmidt – IBM
- Hemal Shah – Broadcom

- Nihar Shah – Microsoft Corporation
- David Simpson – IBM
- John Suit – Fortisphere
- Carl Waldsburger -- VMware Inc.
- Mike Walker – IBM
- Jeff Wheeler – Cisco

American National Standard for Information Technology –

Virtualization Management Specification

Introduction

The information in this standard should be sufficient for a provider or consumer of this data to unambiguously identify the classes, properties, methods, and values that shall be instantiated to subscribe, advertise, produce, or consume an indication using the DMTF Common Information Model (CIM) Schema.

The target audience for this standard is implementers who are writing CIM-based providers or consumers of management interfaces that represent the components described in this document.

Document conventions

Typographical conventions

The following typographical conventions are used in this document:

- Document titles are marked in *italics*.
- Important terms that are used for the first time are marked in italics.
- ABNF rules are in monospaced font.

The following conventions are followed for defining formats of entries such as URIs:

- Literal characters within a format definition are surrounded by single quotes.
- Names of variables within a format are in standard text and are explicitly defined by means of a "Where: variable-name is ..." section that follows the format definition.
- A specific value of a variable within a generalized example of a formatted entry is displayed in *italics*.
- Definitions of formats are case sensitive.
- Whitespace, if any, in formats is explicitly indicated.

In XML and MOF examples, an ellipsis (" . . . ") indicates omitted or optional entries that would typically occupy the position of the ellipsis.

ABNF usage conventions

Format definitions in this document are specified using ABNF (see [RFC 5234](#)), with the following deviations:

- Literal strings are to be interpreted as case-sensitive Unicode characters, as opposed to the definition in [RFC 5234](#) that interprets literal strings as case-insensitive US-ASCII characters.

Experimental material

Experimental material has yet to receive sufficient review to satisfy the adoption requirements set forth by the DMTF. Experimental material is included in this document as an aid to implementers who are interested in likely future developments. Experimental material may change as implementation experience is gained. It is likely that experimental material will be included in an upcoming revision of the document. Until that time, experimental material is purely informational.

Experimental content is indicated by an Experimental Note.

In places where the Experimental Note cannot be used (for example, tables or figures), the "EXPERIMENTAL" label is used alone.

DMTF component documents

Table 1 lists the DMTF component documents that were combined to create this standard.

Table 1 – Component documents

Document Number	Document Title	Version
DSP1041	<i>Resource Allocation Profile</i>	1.1.0
DSP1042	<i>System Virtualization Profile</i>	1.0.0
DSP1043	<i>Allocation Capabilities Profile</i>	1.0.0
DSP1044	<i>Processor Resource Virtualization Profile</i>	1.0.0
DSP1045	<i>Memory Resource Virtualization Profile</i>	1.0.0
DSP1047	<i>Storage Resource Virtualization Profile</i>	1.0.0
DSP1050	<i>Ethernet Port Resource Virtualization Profile</i>	1.0.0
DSP1057	<i>Virtual System Profile</i>	1.0.0
DSP1059	<i>Generic Device Resource Virtualization Profile</i>	1.0.0
DSP1097	<i>Virtual Ethernet Switch Profile</i>	1.0.0

1 Scope

1.1 Resource Allocation Profile

Clause 5 sets the basic resource allocation pattern for resource pools, allocations, and setting data. It also defines the resource-pool-lifecycle management and relationships.

1.2 System Virtualization Profile

Clause 6 is an autonomous profile that specifies the minimum top-level object model needed for the representation of host systems and the discovery of hosted virtual computer systems. In addition, it specifies a service for the manipulation of virtual computer systems and their resources, including operations for the creation, deletion, and modification of virtual computer systems and operations for the addition or removal of virtual resources to or from virtual computer systems.

1.3 Allocation Capabilities Profile

Clause 7 extends the management capability of referencing profiles by adding the ability to represent the default, supported and range of property values for resource allocation requests for a given resource, and the mutability of properties in a Resource Allocation Setting Data instance.

1.4 Processor Resource Virtualization Profile

Clause 8 is a component profile that extends the management capabilities of the specialized profiles by adding the support to represent and manage the allocation of processor resources to virtual systems.

1.5 Memory Resource Virtualization Profile

Clause 9 is a component DMTF management profile that extends the management capabilities of the referencing profile by adding the support to represent and manage the allocation of memory to virtual systems.

1.6 Storage Resource Virtualization Profile

Clause 10 is a component profile that extends the management capabilities of the referencing profile by adding the support to represent and manage the allocation of storage to virtual systems.

1.7 Ethernet Port Resource Virtualization Profile

Clause 11 is a component DMTF management profile that extends the management capabilities of the referencing profile by adding the support to represent and manage the allocation of Ethernet ports to virtual systems.

1.8 Virtual System Profile

Clause 12 is an autonomous profile that defines the minimum object model needed to provide for the inspection of a virtual system and its components. In addition, it defines optional basic control operations for activating, deactivating, pausing, or suspending a virtual system.

1.9 Generic Device Resource Virtualization Profile

Clause 13 is a concrete component profile that specializes the abstract Resource Allocation Profile described in clause 5 and the abstract [Allocation Capabilities Profile](#) described in clause 7.

Clause 13 is intended for use when a more specific resource allocation profile (for example, the [Processor Resource Virtualization Profile](#) described in clause 8, the [Memory Resource Virtualization Profile](#) described in clause 9, and so on) for common resource types has not yet been defined or approved, or when the device in question is an unusual device type for which no more specific profile exists.

1.10 Virtual Ethernet Switch Profile

Clause 14 is an autonomous DMTF management profile that defines the minimum object model needed to provide for the inspection of a virtualization system's internal Ethernet switch and its components.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated or versioned references, only the edition cited (including any corrigenda or DMTF update versions) applies. For references without a date or version, the latest published edition of the referenced document (including any corrigenda or DMTF update versions) applies.

DMTF, *CIM Schema 2.27*,
<http://dmtof.org/standards/cim/schemas>

DMTF DSP0004, *CIM Infrastructure Specification 2.6*,
http://www.dmtf.org/standards/published_documents/DSP0004_2.6.pdf

DMTF DSP0200, *CIM Operations over HTTP 1.3*,
http://www.dmtf.org/standards/published_documents/DSP0200_1.3.pdf

DMTF DSP0201, *Specification for the Representation of CIM in XML 2.3.1*,
http://www.dmtf.org/standards/published_documents/DSP201.pdf

DMTF DSP0207, *WBEM URI Mapping Specification 1.0*,
http://www.dmtf.org/standards/published_documents/DSP0207_1.0.pdf

DMTF DSP1001, *Management Profile Specification Usage Guide 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1001_1.0.pdf

DMTF DSP1012, *Boot Control Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1012_1.0.pdf

DMTF DSP1014, *Ethernet Port Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1014_1.0.pdf

DMTF DSP1022, *CPU Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1022_1.0.pdf

DMTF DSP1026, *System Memory Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1026_1.0.pdf

DMTF DSP1027, *Power State Management Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1027_1.0.pdf

DMTF DSP1033, *Profile Registration Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1033_1.0.pdf

DMTF DSP1035, *Host LAN Network Port Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1035_1.0.pdf

DMTF DSP1052, *Computer System Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1052_1.0.pdf

DMTF DSP1053, *Base Metrics Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1053_1.0.pdf

DMTF DSP1054, *Indications Profile 1.0*,
http://www.dmtf.org/standards/published_documents/DSP1054_1.0.pdf

IETF RFC1738, *Uniform Resource Locators (URL)*, December 1994,
<http://www.ietf.org/rfc/rfc1738.txt>

IETF RFC3986, *Uniform Resource Identifier (URI): Generic Syntax*,
<http://tools.ietf.org/html/rfc3986>

IETF RFC5234, *ABNF: Augmented BNF for Syntax Specifications*, January 2008,
<http://tools.ietf.org/html/rfc5234>

ISO/IEC Directives, Part 2, *Rules for the structure and drafting of International Standards*,
<http://isotc.iso.org/livelink/livelink.exe?func=ll&objId=4230456&objAction=browse&sort=subtype>

SNIA SMI-S, *Storage Management Technical Specification 1.3*,
http://www.snia.org/tech_activities/standards/curr_standards/smi/SMI-S_Technical_Position_v1.3.0r5.zip

NOTE This standard refers to the following clauses of SNIA SMI-S: 1.3, Part 2 *Common Profiles*:

Clause 6: *Generic Target Ports* profile 1.0

Clause 14: *Generic Initiator Ports* profile 1.0

This standard refers to the following clauses of SNIA SMI-S: 1.3, Part 3 *Block Devices*:

Clause 5: *Block Services* package 1.3

Clause 15: *Extent Composition* subprofile 1.2

This standard refers to the following clauses of SNIA SMI-S: 1.3, Part 6 *Host Elements*:

Clause 6: *Storage HBA* profile 1.3

Clause 7: *Host Discovered Resources* profile 1.2

NOTE All parts of the SNIA SMI-S Storage Management Technical Specification have been approved as American National Standards, under the designation INCITS 388-2011. All parts of the specification are available at the ANSI Electronic Standards Store (ESS) on the ANSI website, www.ansi.org.

3 Terms and definitions

In this document, some terms have a specific meaning beyond the normal English meaning. Those terms are defined in this clause.

The terms "shall" ("required"), "shall not," "should" ("recommended"), "should not" ("not recommended"), "may," "need not" ("not required"), "can" and "cannot" in this document are to be interpreted as described in [ISO/IEC Directives, Part 2](#), Annex H. The terms in parenthesis are alternatives for the preceding term, for use in exceptional cases when the preceding term cannot be used for linguistic reasons. Note that [ISO/IEC Directives, Part 2](#), Annex H specifies additional alternatives. Occurrences of such additional alternatives shall be interpreted in their normal English meaning.

The terms "clause," "subclause," "paragraph," and "annex" in this document are to be interpreted as described in [ISO/IEC Directives, Part 2](#), Clause 5.

The terms "normative" and "informative" in this document are to be interpreted as described in [ISO/IEC Directives, Part 2](#), Clause 3. In this document, clauses, subclauses, or annexes labeled "(informative)" do not contain normative content. Notes and examples are always informative elements.

The terms defined in [DSP0004](#), [DSP0200](#), and [DSP1001](#) apply to this document. The following additional terms are used in this document.

3.1

allocated resource

the result of a resource allocation request — the assigned, separated, reserved, or shared part of the resource or emulated resource allocated to the consumer based on the resource allocation request

3.2

capability set

a set of instances of class CIM_SettingData associated with the association CIM_SettingsDefineCapabilities to a CIM_Capabilities instance, and the associated CIM_Capabilities instance.

3.3

child pool

pool whose resources are backed by other resource pools; consumer of resources from its parent resource pools; contains no host resources, instead draws resources from parent pools through resource allocations

3.4

client

an application that exploits facilities specified by the profiles in this standard

3.5

concrete memory resource pool

a resource pool that subdivides the capacity of its (primordial or concrete) parent resource pool

3.6

concrete storage resource pool

a storage resource pool that subdivides the capacity of its (primordial or concrete) parent resource pool

3.7

consumer

entity using allocated resources (for example, a virtual system)

3.8

current resource allocation setting data

resource allocation setting data that describes an allocated resource; differs from defined resource allocation setting data if the host system supports the dynamic modification of a resource allocation

3.9

current setting data

the virtual setting data associated with the current allocation state of a virtual resource or system.

3.10

dedicated virtual resource

virtual resource that has been given exclusive use of one or more host resources (the host resources are not shared with any other consumer)

3.11

defined resource allocation setting data

resource allocation setting data that describes a resource allocation request

3.12**dynamic ethernet connection allocation**

an Ethernet connection in which a default Ethernet switch port is instantiated as part of an Ethernet connection allocation

3.13**ethernet adapter**

an EthernetPort, its associated LAN Endpoint(s) and, optionally, a VLAN Endpoint that models the Ethernet device on a virtual or host system

3.14**ethernet adapter allocation request**

a request for an Ethernet adapter resource allocation to a virtual machine; represented as instance of CIM_EthernetPortAllocationSettingData.

3.15**ethernet adapter resource allocation**

the allocation of an Ethernet port to a virtual system

3.16**ethernet adapter resource pool**

a resource pool that represents Ethernet adapters available as resources for a virtual computer system resource allocation

3.17**ethernet connection**

the connection of two LAN endpoints where one LAN endpoint is implemented by an Ethernet adapter, and the other LAN endpoint is implemented by an Ethernet switch port, resulting in the connection of a virtual or host system Ethernet adapter to an Ethernet switch port

3.18**ethernet connection allocation request**

an allocation request for a connection between a LAN Endpoint on an Ethernet adapter and a LAN Endpoint on an Ethernet switch port. An Ethernet connection allocation request may cause the implicit allocation of the entities that it connects, such as virtual Ethernet adapters and virtual switch ports. Ethernet connection allocation request is represented as instance of CIM_EthernetPortAllocationSettingData.

3.19**ethernet connection allocation**

the allocation of an Ethernet connection between the LAN Endpoints of an Ethernet adapter and an Ethernet switch port

3.20**ethernet connection resource pool**

a resource pool that represents available Ethernet connections on a virtual Ethernet switch for a virtual computer system

3.21**ethernet switch port**

an EthernetPort, its associated LAN Endpoint(s) and, optionally, a VLAN Endpoint that models the Ethernet port on an Ethernet switch

3.22

ethernet switch port allocation request

a request for an Ethernet switch port resource allocation; represented as instance of CIM_EthernetPortAllocationSettingData.

3.23

ethernet switch port resource allocation

the allocation of an Ethernet port to a virtual Ethernet switch

3.24

ethernet switch port resource pool

a resource pool that represents Ethernet switch ports available as resources for a virtual Ethernet switch port resource allocation

3.25

host memory

a contiguous extent of memory contained by the host system that may be allocated with either exclusive or shared access to a memory resource pool

3.26

host processor resource

host processor resources are processor devices or computing resource contained by the host system that may be allocated with either exclusive or shared access to provide processing resources to a processor resource pool or a virtual system.

3.27

host resource

a device or computing resource contained by the host system that may be allocated with either exclusive or shared access through the host system to provide resources to a resource pool or consumer

3.28

host storage resource

a storage resource that exists in scope of or is accessible by a host system. A host system may contain or have access to one or more storage resources that may be as a whole or partially allocated to virtual systems

3.29

host system

the system that contains the host resources that are subject to resource allocation

3.30

implementation

a set of CIM providers that realize the classes specified by the profiles described in this standard

3.31

initiator port

a port that acts as the source for a data exchange operation

3.32

logical disk

the instantiation of allocated host resources that is exposed to a virtual system through a storage device; the result of a storage resource allocation based on a storage resource allocation request

3.33**memory composition**

the aggregation of memory extents into an encompassing memory extent

3.34**memory resource allocation**

the allocation of memory from a memory resource pool to a virtual system

3.35**memory resource allocation request**

a request for a memory resource allocation

3.36**memory resource pool**

a resource pool that represents memory available for memory resource allocation

3.37**memory resource pool configuration service**

a configuration service that supports the addition or removal of host memory to or from a memory resource pool, and the creation or deletion of concrete subpools of a memory resource pool

3.38**port**

communication endpoint for systems or storage devices. A port enables the exchange of data according to one or more protocols

3.39**primordial resource pool**

a resource pool with no parent that may aggregate host resources

3.40**primordial storage resource pool**

a storage resource pool that aggregates storage resources available for or used by storage resource allocations

3.41**processor resource**

a processor device or computing resource as seen by a consumer

3.42**processor resource allocation**

the allocation of a processor resource from a processor resource pool to a virtual system

3.43**processor resource allocation request**

a request for a processor resource allocation

3.44**processor resource pool**

a resource pool that represents processor resources available for processor resource allocation

3.45

processor resource pool configuration service

a configuration service that supports the addition or removal of host storage processor resources to or from a processor resource pool, and the creation or deletion of concrete subpools of a processor resource pool

3.46

resource allocation

process of assigning, separating, reserving, granting share of, or emulating resources for use by a consumer

3.47

resource allocation request

request for resources to be allocated

3.48

resource allocation setting data

RASD

CIM_ResourceAllocationSettingData - settings describing resource allocation; used by a host system to manage the allocation of resources and their relationship to host resources, resource pools used for the allocation, or both

3.49

resource pool

an abstract entity exposed by the virtualization platform for the purpose of allocation of allocated resources to consumers

3.50

resource type

generic type categorizing classes of resources (for example, processor, memory, network adapter)

3.51

shared virtual resource

virtual resource that has been given the use of host resources that may also be shared with other consumers

3.52

simple ethernet connection

an Ethernet connection in which a default Ethernet switch port and a default Ethernet adapter are instantiated as part of an Ethernet connection allocation

3.53

simple resource allocation

resource allocation with no logical device representing the allocated resources

3.54

static ethernet connection allocation

an Ethernet connection allocation where a specific pre-existing Ethernet switch port is requested as part of the allocation request

3.55

storage resource

a logical disk, a storage volume or a storage extent

3.56**storage resource allocation**

the allocation of a storage resource from a storage resource pool to a virtual system

3.57**storage resource allocation request**

a request for a storage resource allocation

3.58**storage resource pool**

a resource pool that represents storage resources available for storage resource allocation

3.59**storage resource pool configuration service**

a configuration service that supports the addition or removal of host storage resources to or from a storage resource pool, and the creation or deletion of concrete subpools of a storage resource pool

3.60**storage volume**

the instantiation of allocated host resources that is exposed to a virtual system through a storage device that is published for use outside of the scoping system. Like a logical disk, a storage volume is the result of a storage resource allocation based on a storage resource allocation request

3.61**target port**

a port that acts as a target of a data exchange operation

3.62**virtual computer system**

virtual system as applied to a computer system

Other common industry terms for such a system include *virtual machine*, *hosted computer*, *child partition*, *logical partition*, *domain*, *guest*, and *container*.

3.63**virtual Ethernet switch**

the concept of a virtual system as applied to a virtual Ethernet switch

A virtual Ethernet switch is a specialized virtual system.

3.64**virtual memory**

the instantiation of allocated host memory that is exposed to a virtual system through a logical memory device; the result of a memory resource allocation based on a memory resource allocation request

NOTE The definition of the term “virtual memory” is specialized from the term “virtual resource” defined in clause 5 and deviates from common computer industry parlance.

3.65**virtualization platform**

virtualizing infrastructure provided by a host system that enables the deployment of virtual systems

3.66**virtual processor**

the instantiation of the allocated host processor resources that is exposed to a virtual system via a logical processor device.

3.67

virtual resource

an allocated resource that is represented as a logical device and assigned to a virtual system

3.68

virtual resource allocation

resource allocation with a logical device representing the allocated resources

3.69

virtual system

a computer system that is composed of virtual resources. Other common industry terms for such a system include *virtual machine*, *hosted computer*, *child partition*, *logical partition*, *domain*, *guest virtual machine*, and *container*.

3.70

virtualization platform

infrastructure that supports virtual systems. Other common industry terms for this infrastructure are *hypervisor* and *virtual machine monitor*.

4 Symbols and abbreviated terms

The abbreviations defined in [DSP0004](#), [DSP0200](#), and [DSP1001](#) apply to this document. The following additional abbreviations are used in this document.

4.1

CIM

common information model

4.2

CIMOM

CIM object manager

4.3

CPU

central processing unit

4.4

EASD

ethernet port allocation setting data

4.5

ESD

element setting data

4.6

HBA

host bus adapter

4.7

MCA

capabilities settings of systems and of memory resource pools

4.8

MMS

mutability settings of memory resource allocation requests or memory resource allocations

4.9

MRA

memory resource allocation

4.10

MRQ

memory resource allocation request

4.11

RASD

resource allocation setting data

4.12

SASD

storage allocation setting data

4.13

SAN

storage area network

4.14

SDC

settings define capabilities

4.15

SDS

settings define state

4.16

SLP

service location protocol

4.17

SMI-S

Storage Management Initiative Specification

4.18

SNIA

Storage Networking Industry Association

4.19

VESSD

virtual ethernet switch setting data

4.20

VS

virtual system

4.21**VSSD**

virtual system setting data

4.22**VSSDC**

virtual system setting data component

5 Resource Allocation Profile

Profile Name: Resource Allocation**Version:** 1.1.0**Organization:** DMTF**CIM schema version:** 2.22**Central Class:** CIM_ResourcePool**Scoping Class:** CIM_System

The Resource Allocation Profile is an abstract profile that extends the management capability of referencing profiles by adding the capability to represent the allocation of resources to consumers. This includes allocation of underlying supporting resources, such as power and cooling, and the allocation of computing resources, such as processors and memory. The resources may be virtualized. A general model is defined by the Resource Allocation Profile. Requirements and constraints specific to a resource type are defined in a referencing profile dedicated to the resource type. This profile defines a resource pool, allocated resources, allocation settings, and host resources.

The Resource Allocation Profile shall not be directly implemented. Implementation shall be based on a profile that specializes the requirements of this profile.

Table 2 identifies the profile on which the Resource Allocation Profile has a dependency.

Table 2 – Related profiles for the Resource Allocation Profile

Profile Name	Organization	Version	Requirement	Description
Allocation Capabilities	DMTF	1.0	Optional	Profile that describes allocation capabilities (see clause 7)

5.1 Description

This subclause provides an informative description of the management domain addressed by the profile described in this clause and describes how the CIM elements defined in the profile apply to the management domain.

Figure 1 is the class diagram for the Resource Allocation Profile. Cardinalities shown in the diagram reflect the constraints relative to implementations of this profile. For simplicity, the prefix *CIM_* has been removed from the names of the classes.




Figure 1 – Resource Allocation Profile: Class Diagram

5.1.1 General resource allocation concepts

The Resource Allocation Profile captures the general concept of defining the availability of a given resource type for allocation to consumers. The amount of resource available and the amount of resource allocated are modeled and managed. The aggregation of the underlying components that provide the resource (host resources) may be represented.

5.1.1.1 Host resources

Host resources are those that compose or enable a computer system. Examples include processors, memory, I/O, power supplied to the system, cooling allocated to the system, and so on.

5.1.1.2 Resource pool

The profile described in this clause uses a resource pool as the focal point for resource allocations. Consumers receive resource allocations from resource pools based on resource allocation requests. A resource pool results from aggregation of host resources of a specific type into a resource pool.

For example, when modeling virtualized computer systems, host processors are aggregated into a pool, giving it a known computing capacity, from which virtual processors are allocated. When modeling virtualized storage, the pool may map to a RAID volume or other storage-aggregating construct. Using power as an example, the host power supplies may be aggregated into a pool, thus establishing the total power available for allocation. Power is then allocated to dependent resource consumers from the pool.

5.1.1.3 Resource allocation

A resource allocation is a resource that is allocated from a resource pool. A resource allocation request is a request for a resource allocation. A resource allocation is obtained based on a corresponding resource allocation request. Both resource allocation and resource allocation request are represented through instances of the `CIM_ResourceAllocationSettingData` class.

5.1.1.4 Hierarchies of resource pools

A hierarchy of resource pools may be supported. A hierarchy may be used to provide administrative controls over the set of resources or to partition resources into disjoint sets.

For example, the aggregate processor capability of the computer system may be divided into child pools for individual departments or users.

A hierarchy of resource pools represents the same type of resource and is acyclic. Hierarchies of resource pools consisting of different types of resources are not defined by the profile described in this clause.

5.1.1.5 Pool and resource management

The creation, deletion, and management of resource pools and assignment of the host resources that they contain are covered by the profile described in this clause. The allocation of resources to a consumer is covered in derived profiles. The `CIM_ResourcePoolConfigurationService` class provides extrinsic methods for the management of resource pools.

5.1.2 Simple resource allocation

Simple resource allocation is the allocation of resources (for example, power, cooling, and so on) to a consumer where no logical device represents the resource allocated.

5.1.3 Virtual resource allocation

Virtual resource allocation is the allocation of resources (for example, processor, memory, and so on) to a consumer using an allocated resource. Virtual resource allocation extends the concept of resource allocation with the addition of semantics specific to virtualization. The virtual resources represent the consumer's view of the allocated resource, which enables management of the allocated resource in the context of management of the consumer. Additional functionality, such as the management of resource allocation definition or state, is introduced.

Multiple virtual resource allocations or virtual resource allocation requests may affect a single resource. For example, a virtual disk may be affected by the allocation of a storage extent and of bandwidth. A resource allocation or resource allocation request may affect one resource or a comprehensive set of resources. For example, a set of virtual processors may be modeled by one resource allocation request.

5.1.3.1 Virtual resource

A virtual resource represents the consumer's view of the allocated resource. In a processor example, the virtual processor represents the virtual resource and may be consumed by a virtual computer system. In a storage example, a storage volume represents the virtual resource and may be consumed by a physical or a virtual computer system.

The same CIM class is used to model both the host resource and the virtual resource. In many systems, virtualization-specific details are hidden from the consumer, and the consumer is presented with a virtual resource that looks no different than a host resource (that is, a resource that is not virtualized). The property values contained in the instance of a virtual resource reflect what the consumer of that resource is presented, not the virtualization-specific details of the allocation.

Information specific to resource allocation is modeled using resource allocations and resource allocation requests. These are represented by instances of the CIM_ResourceAllocationSettingData class. This approach ensures that general-purpose management applications may consume information about the virtual resources without having to know details of the underlying virtualization. This approach also prevents proliferation of virtualization-specific properties throughout the CIM schema, or mandatory subclassing of every possible device that may be virtualized. For example, the virtualized processor in the virtual computer system uses the same properties as a physical processor in a physical computer system.

Resource allocation CIM management profiles that specialize the profile described in this clause may allow or require different CIM classes to be used to represent the virtual and host resources. For example, a consumable storage device may be modeled using CIM_StorageVolume or CIM_LogicalDisk, while the hosting resource may be modeled using CIM_StorageExtent.

5.1.3.2 Dedicated virtual resources

Dedicated virtual resources are allocated to a consumer and are not available to other consumers. The host resource backs the virtual resource through a one-to-one mapping that is identified by the MappingBehavior property of CIM_ResourceAllocationSettingData set to a value of 2 (Dedicated).

5.1.3.3 Shared virtual resources

Shared resources may be used by multiple consumers. The host resource may map to multiple virtual resources that may be allocated to the same resource consumer. One host resource is shared by many consumers (for example, a quorum drive in a cluster environment).

A virtual resource may map to different host resources over time. One virtual resource may be mapped to many backing host resources (for example, a virtual processor scheduled to run on different host processors during the course of execution).

5.1.3.4 Relationship between host resource and virtual resource

If the virtual resource always maps to the same host resource, the CIM_HostedDependency association may be used to reflect this relationship for a current allocation. Implementations that support scheduling across the pool of host resources transparent to the consumer may not expose the CIM_HostedDependency association because this relationship may change frequently.

5.1.3.5 Resource allocation definition and resource allocation state

For each resource that may be allocated, a resource allocation request represents the resource allocation definition. Once one or more elements requested by the resource allocation definition are allocated, a corresponding set of resource allocations represents the resource allocation state. Details of a resource allocation request or a resource allocation are represented by an instance of the CIM_ResourceAllocationSettingData class. Elements of resource allocation definition and resource allocation state may be changed independently.

For example:

- A system may support changing the processor resource allocation for the next boot or reset of the virtual system while the system is running without changing the current state of the system. This behavior is reflected by updates to the defined settings.
- An implementation for virtual memory may support changing the resource allocation definition only. A change such as an increase in virtual memory becomes effective the next time the virtual system is activated.
- An implementation may support changing the settings for the currently running virtual system only where the values revert to the prior settings on the next boot or reset. This behavior is reflected by updates in the current settings only.
- An implementation may support changing the resource allocation definition and state of virtual processors simultaneously. A change such as an increase in the relative share of processing power that a group of processors scoped by a virtual system receive becomes effective immediately without a need for a re-activation, and remains effective beyond the next re-activation.

The kind of changes that are supported are defined in resource allocation CIM management profiles that specialize the profile described in this clause.

5.2 Implementation

This subclause provides normative requirements related to the arrangement of instances and properties of instances for implementations of the profile described in this clause. The CIM Schema definitions and requirements apply.

5.2.1 Common requirements

This subclause details requirements that shall be met regardless of whether simple resource allocation or virtual resource allocation is implemented. In addition to these common requirements, either the requirements in 5.2.2 or the requirements in 5.2.3 shall also be implemented.

5.2.1.1 Representation of a resource pool

Each resource pool managed using the profile described in this clause shall be represented by an instance of the CIM_ResourcePool class. It shall be associated with the instance of CIM_System that represents the scoping system through one instance of the CIM_HostedResourcePool association. Each resource pool shall represent resources of the same type.

5.2.1.2 Primordial and concrete resource pools

A resource pool may be primordial or concrete.

Primordial pools aggregate capacity; they represent the known manageable capacity for the host system. Capacity is drawn from the primordial pool to create concrete resource pools or to allocate resources to consumers. There shall be at least one primordial pool for each resource type managed through the profile described in this clause. The instance of the CIM_ResourcePool class that represents a primordial resource pool shall have the Primordial property set to a value of TRUE.

Concrete resource pools subdivide the resource capacity available at a system. A single concrete pool may represent all the capacity of a primordial pool. The instance of the CIM_ResourcePool class that represents a concrete resource pool shall have the Primordial property set to a value of FALSE.

If a one-to-one correspondence exists between the host resource and the virtual resource, the CIM_HostedDependency association may be used to indicate the correspondence.

5.2.2 Modeling virtual resource allocation

Virtual resource allocation may be modeled. If virtual resource allocation is modeled, the requirements specified in this subclause shall be met.

5.2.2.1 Host resources

Host resources are modeled as a subclass of the CIM_LogicalDevice class. Host resources may be aggregated into one or more primordial resource pools and allocated to resource pools or resource consumers.

If aggregation of host resources is supported, at least one instance of the CIM_LogicalDevice class shall be associated with the instance of the CIM_ResourcePool class through an instance of the CIM_Component association. If aggregation of host resources is supported, the CIM_ResourceAllocationSettingData.Capacity property shall be supported.

If a resource pool is used for dedicated or shared resources, aggregation of host resources should be supported.

5.2.2.2 Virtual resources

Each virtual resource that is fully or partially allocated shall be represented by an instance of the CIM_LogicalDevice class. That instance shall be associated with the instance of the CIM_System class that represents the scoping virtual system through an instance of the CIM_SystemDevice association.

5.2.2.3 Resource allocation definition

Each resource shall have a resource allocation definition. Each element of a resource allocation definition shall be represented by one instance of the CIM_ResourceAllocationSettingData class.

5.2.2.4 Resource allocations

An instance of the CIM_LogicalDevice class that represents a virtual resource shall be associated to zero or more instances of the CIM_ResourceAllocationSettingData class that represents the resource allocation state through an instance of the CIM_SettingsDefineState association.

One instance of the CIM_ResourceAllocationSettingData class may be associated with more than one instance of the CIM_LogicalDevice class that represents a set of virtual resources.

An instance of the CIM_ResourceAllocationSettingData class that represents the current allocation state shall be associated with a virtual resource through an instance of the CIM_SettingsDefineState association.

An instance of the CIM_ResourceAllocationSettingData class that represents the defined allocation state shall be associated with the instance of the CIM_ResourceAllocationSettingData class that represents the current allocation state through an instance of the CIM_ElementSettingData association with the IsDefault property set to 1 (Is Default).

The non-key properties of the two instances of the CIM_ResourceAllocationSettingData class may match if both the current and defined settings are the same.

An instance of the CIM_ResourceAllocationSettingData class that represents a current resource allocation shall be associated with one instance of the CIM_ResourcePool class through an instance of the CIM_ResourceAllocationFromPool association.

An instance of CIM_ResourceAllocationSettingData that represents a defined resource allocation shall not be associated with instances of CIM_ResourcePool through the CIM_ResourceAllocationFromPool association.

5.2.2.5 Dedicated allocations

If the value of the MappingBehavior property is set to 2 (Dedicated) in the instance of the CIM_ResourceAllocationSettingData class that represents the defined allocation state, and if no values are specified for the HostResource[] array property or the HostResource[] array property is not specified (NULL), the system shall select the host resources if the virtual resource is allocated.

If the value of the MappingBehavior property is set to 2 (Dedicated) in the instance of the CIM_ResourceAllocationSettingData class that represents the current allocation state, the HostResource[] array property shall contain the identities of host resources that are dedicated to the virtual resource. For dedicated resources, an instance of the CIM_HostedDependency association may be present between the instance of the CIM_LogicalDevice class that represents a dedicated host resource allocation and the instance of the CIM_LogicalDevice class that represents the virtual resource.

5.2.2.6 Allocations with affinity

Virtual resources may be allocated with affinity to host resources using values of the MappingBehavior property.

If the MappingBehavior property is set to 4 (Hard Affinity), only the resources specified in the HostResource[] array property shall be used. If no values are specified for the HostResource[] array property or the HostResource[] array property is not specified (NULL), the system shall select the host resources if the virtual resource is allocated and maintain the allocation of those resources to the virtual device.

If the MappingBehavior property is set to 3 (Soft Affinity), the resources specified in the HostResource[] array property are preferred, but alternative host resources may be used. If no values are specified for the HostResource[] array property or the HostResource[] array property is not specified (NULL), the system shall select the host resources if the virtual resource is allocated.

If the MappingBehavior property is set to 3 (Soft Affinity) or 4 (Hard Affinity), an instance of the CIM_HostedDependency association shall not be used between the instance of the CIM_LogicalDevice class that represents a dedicated host resource allocation and the instance of the CIM_LogicalDevice class that represents the virtual resource.

If values are specified for the HostResource[] array property, the number of resources listed in the HostResource[] array property shall be adequate to satisfy the allocation request but may include additional resources.

The HostResource[] array property that represents the defined allocation state shall be set to the user's request. The HostResource[] array property that represents the current allocation state shall be set to the current active behavior.

5.2.3 Modeling simple resource allocation

Simple resource allocation may be modeled. If simple resource allocation is modeled, the requirements in this subclause shall be met.

5.2.3.1 General requirements

Each instance of the CIM_ResourceAllocationSettingData class that represents a current allocation state or alternate allocation state shall be associated with one instance of the CIM_ResourcePool class through an instance of the CIM_ResourceAllocationFromPool association.

A logical device shall not be instantiated.

5.2.3.2 Current allocation

An instance of the CIM_ResourceAllocationSettingData class that represents the current state shall be associated with one instance of the CIM_ResourceAllocationSettingData class through an instance of the CIM_ElementSettingData association with the IsCurrent property set to 1 (Is Current). If the CIM_ResourceAllocationSettingData class that represents the current state is modified, the IsCurrent property shall be set to a value other than 1 (Is Current).

5.2.3.3 Alternate allocations

Alternate allocations of the resource for the consumer may be supported. Each alternate allocation state shall be represented by an instance of the CIM_ResourceAllocationSettingData class that is associated with an instance of the CIM_ResourceAllocationSettingData class that represents the alternate allocation state through an instance of the CIM_ElementSettingData association with the IsCurrent property set to 2 (Is Not Current).

5.2.4 Resource pool management

Resource pool management may be modeled. If resource pool management is modeled, the requirements of this subclause shall be met. Implementations may support active management of instances of the CIM_ResourcePool class, or they may expose a read-only view of existing instances of the CIM_ResourcePool class.

An instance of the CIM_ResourcePoolConfigurationService class shall be implemented; however, the methods of the service are optional. The instance of the CIM_ResourcePoolConfigurationService class shall be associated with the host system through an instance of the CIM_HostedService association. One instance of CIM_ResourcePoolConfigurationCapabilities shall be associated with the CIM_ResourcePoolConfigurationService instance through the CIM_ElementCapabilities association. This instance of CIM_ResourcePoolConfigurationCapabilities shall reflect the methods supported. If active management is not supported by an implementation, all properties of the associated CIM_ResourcePoolConfigurationCapabilities instance shall be set to NULL.

5.2.5 Metrics

If metrics are implemented, the [DSP1053](#) shall be implemented. If the instance of the CIM_BaseMetricDefinition class defines a metric that applies across the entire resource pool, the instance of CIM_BaseMetricDefinition class shall be associated with an instance of the CIM_ResourcePool class through the CIM_MetricDefForME association, and the instance of the CIM_BaseMetricDefinition class shall not be associated with any other instances of the CIM_ManagedElement class. An example of this type of metric is a metric that reports the total instantaneous resource consumption from the pool.

If the instance of the CIM_BaseMetricDefinition class defines a metric related to an individual virtual device's utilization of resources from the resource pool, the instance of the CIM_BaseMetricDefinition class shall be associated with the instance of the CIM_ResourcePool class through the CIM_MetricDefForME association, and the instance of the CIM_BaseMetricDefinition class shall be associated with the instance of the CIM_LogicalDevice class that represents the virtual device through an instance of the CIM_MetricDefForME association.

If the instance of the CIM_BaseMetricDefinition class defines a metric for the virtual device that is not related to the consumption by the device of resources from the resource pool, the instance of the CIM_BaseMetricDefinition class shall not be associated with the instance of the CIM_ResourcePool class.

If the instance of the CIM_BaseMetricDefinition class defines a metric related to the resource pool and a host resource, the instance of the CIM_BaseMetricDefinition class shall be associated with the instance of the CIM_ResourcePool class through an instance of the CIM_MetricDefForME association, and the

instance of the CIM_BaseMetricDefinition class shall be associated with the instance of the CIM_ManagedElement class that represents the host resource through an instance of the CIM_MetricDefForME association.

5.2.6 Resource pool hierarchies

Hierarchies of resource pools may be modeled. A hierarchy of resource pools represents the same type of resource and shall be acyclic.

Child pools may be allocated from the parent pool using the CIM_ResourcePoolConfigurationService class.

Parent and child pools shall be scoped to the same system.

A pool may have virtual resources and child pools allocated from it simultaneously.

5.2.7 Virtual resource definition and modification

The CIM_ResourceAllocationSettingData class is used as an input for virtual system definition. The client and implementation considerations are defined. The Resource Allocation Profile specifies how to define and modify virtual resources using methods of the virtual system management service. In these method specifications, the CIM_ResourceAllocationSettingData class is used for parameterization of resource-allocation-specific properties. The capabilities model may be used to convey information about limitations for and default values of properties of the CIM_ResourceAllocationSettingData class; see 7.4.

5.2.7.1 CIM_ResourceAllocationSettingData.InstanceID property

A client shall set the InstanceID property to NULL if the instance of the CIM_ResourceAllocationSettingData class is created locally. A client shall not modify the InstanceID property in an instance of the CIM_ResourceAllocationSettingData class that was received from an implementation and is sent back to the implementation as a parameter of a modification method.

An implementation shall ignore any non-NULL value in a definition request.

In a modification request, an implementation shall use a non-NULL value to identify an existing instance of the CIM_ResourceAllocationSettingData class. If a value is specified that does not identify an instance of the CIM_ResourceAllocationSettingData class, an implementation shall return a return code that indicates an invalid parameter; see 5.3.

5.2.7.2 CIM_ResourceAllocationSettingData.ResourceType property

A client shall set the value of the ResourceType property to designate the type of the virtual resource allocation request.

The implementation shall use the value of the ResourceType property, as well as the value of the OtherResourceType property if the value of the ResourceType property is 1 (Other), to determine the type of the virtual resource allocation request. If the implementation does not support the requested resource type, it shall fail the method execution.

5.2.7.3 CIM_ResourceAllocationSettingData.OtherResourceType property (conditional)

If a client sets the value of the ResourceType property to a value other than 1 (Other), it shall set the value of OtherResourceType property to NULL. If a client sets the value of the ResourceType property to 1 (Other), it shall set the value of the OtherResourceType property to identify the type of the virtual resource allocation request in an implementation-dependent way.

The implementation shall use the value of the OtherResourceType property if the value of the ResourceType property is 1 (Other) to determine the type of the virtual resource allocation request. If the implementation does not support the requested resource type, it shall fail the method execution.

5.2.7.4 CIM_ResourceAllocationSettingData.ResourceSubType property

A client may set the value of the ResourceSubType property to designate the subtype of the virtual resource allocation request. A client may set the value of the ResourceSubType property to NULL, requesting default behavior.

The implementation shall use the value of the ResourceSubType property to determine the subtype of the virtual resource allocation request. If the implementation does not support the requested virtual resource subtype, it shall return a return code that indicates an invalid parameter; see 5.3.

5.2.7.5 CIM_ResourceAllocationSettingData.PoolID property

A client may set the value of the PoolID property to designate a resource pool that shall be used for resource allocation. In this case, the values of the PoolID and ResourceType properties shall be equal to the values of respective properties in an instance of the CIM_ResourcePool class that represents the designated resource pool. A client may set the value of the PoolID property to NULL, requesting default behavior.

An implementation shall use the value of the PoolID and ResourceType properties to assign the resource pool that shall be used for the resource allocation. If the value of the PoolID property is NULL, the implementation may assign a default resource pool. If no resource pool exists with matching values of the PoolID and ResourceType properties, the implementation may either assign a default resource pool or fail the method execution. An implementation may defer the selection of a default resource pool until resource allocation actually occurs.

5.2.7.6 CIM_ResourceAllocationSettingData.ConsumerVisibility property

A client may set the value of the ConsumerVisibility property to specify whether the virtual resource or comprehensive set of virtual resources that is requested by the virtual resource allocation request shall be virtualized or shall be one or more passed-through host resources. A client may specify a value of NULL for the ConsumerVisibility property, requesting a default behavior.

If the property is set to a value other than NULL, the client shall perform one of the following actions:

- set a value of 0 (Unknown) to request default behavior (with the same effect as a value of NULL)
- set a value of 2 (Passed-Through) to specify that one or more passed-through host devices shall be allocated to the virtual resource requested by this virtual resource allocation request, and shall provide one or more elements in the HostResource[] array property that identify the host resources that shall be passed through
- set a value of 3 (Virtualized) to specify that the virtual resource that results from this virtual resource allocation request shall be virtualized

The client shall not use a value of 4 (Not Represented).

An implementation shall use the value of the ConsumerVisibility property to determine whether the virtual resource or comprehensive set of virtual resources requested by this virtual resource allocation request shall be virtualized or shall be a passed-through host resource.

- If the value of the ConsumerVisibility property is NULL or 0 (Unknown), the implementation may exhibit an implementation-specific default behavior that may also depend on the resource type, the selected resource pool, or both.

- If the value of the ConsumerVisibility property is 2 (Passed-Through), the implementation shall establish a virtual resource allocation request or virtual resource allocation for host resources as specified by elements of the HostResource[] array property as passed-through devices in the resulting virtual resource allocation. If no values are specified by the HostResource[] array property, the implementation may exhibit an implementation-specific default behavior.
- If the value of the ConsumerVisibility property is 3 (Virtualized), the implementation shall establish a virtual resource allocation request or virtual resource allocation for a virtualized virtual device or a comprehensive set of virtualized virtual devices.
- If the value of the ConsumerVisibility property is 4 (Not Represented), the implementation shall fail the method execution.

5.2.7.7 CIM_ResourceAllocationSettingData.HostResource[] Array property

A client may set the value of the HostResource[] array property to indicate that the requested virtual resource allocation shall be based on host resources that are identified by element values. The kind of dependency is specified through the ConsumerVisibility property (see 5.2.7.6) and the MappingBehavior property (see 5.2.7.18). A client may set the value of the HostResource[] array property to NULL or may specify an empty array in order to request the implementation to decide whether the requested resource allocation shall be directly based on host resources.

An implementation shall use the value of the HostResource[] array property to determine whether and how the requested virtual resource allocation shall be based on host resources. Respective host resources are identified by element values of the HostResource[] array property. The implementation shall use the value of other properties such as ConsumerVisibility (see 5.2.7.6) and MappingBehavior (see 5.2.7.18) to determine the kind of dependency. If no value or an empty array is provided as the value of the HostResource[] array property, the implementation may provide a pure virtual resource for the request or may select host resources at its own discretion.

5.2.7.8 CIM_ResourceAllocationSettingData.AllocationUnits property

A client should set the value of the AllocationUnits property to specify a unit of measurement for the virtual resource allocation request. The unit of measurement shall be compatible with the requested resource type. A client may set the value of the AllocationUnits property to NULL, requesting the implementation to assume a resource-type-specific default value for the unit of measurement.

An implementation shall use the value of the AllocationUnits property to determine the unit of measurement for the virtual resource allocation request. If the provided value is not compatible with the resource type, the implementation shall fail the method execution. If a value is not provided (NULL), the implementation shall assume a resource-type-specific default value for the unit of measurement. A resource-type-specific resource allocation DMTF management profile may specify rules for the determination of the default value.

5.2.7.9 CIM_ResourceAllocationSettingData.VirtualQuantity property

A client should set the value of the VirtualQuantity property to specify the quantity of virtual resources that shall result from the virtual resource allocation request. A client may set the value of the VirtualQuantity property to NULL, requesting a default behavior. A resource-type-specific resource allocation DMTF management profile may specify rules for the determination of a default value.

5.2.7.10 CIM_ResourceAllocationSettingData.Reservation property

A client may set the value of the Reservation property to specify the amount of host resource that is requested by the virtual resource allocation request. The unit of measurement established by the value of the AllocationUnits property applies. A client may set the value of the Reservation property to NULL, requesting a default behavior.

An implementation shall use the value of the Reservation property to determine the amount of host resource that is requested by the virtual resource allocation request. If a value is not provided (NULL), the implementation may exhibit an implementation-specific default behavior. A resource-type-specific resource allocation DMTF management profile may specify rules for the determination of a default value.

5.2.7.11 CIM_ResourceAllocationSettingData.Limit property

A client may set the value of the Limit property to specify the maximum amount of host resource that is requested by the virtual resource allocation request. The unit of measurement established by the value of the AllocationUnits property applies. A client may set the value of the Limit property to NULL, requesting a default behavior.

An implementation shall use the value of the Limit property to determine the maximum amount of host resource that is requested by the virtual resource allocation request. If a value is not provided (NULL), the implementation may exhibit an implementation-specific default behavior. A resource-type-specific resource allocation DMTF management profile may specify rules for the determination of a default value.

5.2.7.12 CIM_ResourceAllocationSettingData.Weight property

A client may set the value of the Weight property to specify a relative weight that is requested by the virtual resource allocation request with respect to other virtual resource allocation requests from the same resource pool. A client may set the value of the Weight property to NULL, requesting a default behavior.

An implementation shall use the value of the Weight property to determine a relative weight that is requested by the virtual resource allocation request with respect to other virtual resource allocation requests from the same resource pool. If a value is not provided (NULL), the implementation may exhibit an implementation-specific default behavior. A resource-type-specific resource allocation DMTF management profile may specify rules for the determination of a default value.

5.2.7.13 CIM_ResourceAllocationSettingDataAutomaticAllocation property

A client may set the value of the AutomaticAllocation property to specify that the requested resource allocation is obtained automatically when the virtual system is activated. A client may set the value of the AutomaticAllocation property to NULL, requesting a default value of TRUE.

An implementation shall use the value of the AutomaticAllocation property to determine whether the requested resource allocation is obtained automatically when the virtual system is activated. The default value shall be TRUE, requesting automatic resource allocation. Resource-type-specific resource allocation DMTF management profiles may specify a different default behavior.

5.2.7.14 CIM_ResourceAllocationSettingDataAutomaticDeallocation property

A client may set the value of the AutomaticDeallocation property to specify that the requested resource allocation is released automatically when the virtual system is deactivated. A client may set the value of the AutomaticDeallocation property to NULL, requesting a default value of TRUE.

An implementation shall use the value of the AutomaticDeallocation property to determine whether the resource allocation is automatically released when the virtual system is de-activated. The default value shall be TRUE, requesting automatic resource deallocation. Resource-type-specific resource allocation DMTF management profiles may specify a different default behavior.

5.2.7.15 CIM_ResourceAllocationSettingData.Parent property

A client may set the value of the Parent property to specify a parent resource required to establish the resource allocation. An example of such a parent resource would be a controller. A client may set the value of the Parent property to NULL, requesting a default behavior.

An implementation shall use the value of the Parent property to determine if and which parent resource is required for the requested resource allocation. If no value is specified (NULL), the implementation may decide whether a parent resource is needed and eventually select one itself. If a value is specified, the implementation shall base the resource allocation request on the requested parent resource. If the requested parent resource is not capable to support the requested resource allocation, the implementation shall fail the request.

5.2.7.16 CIM_ResourceAllocationSettingData.Connection[] array property

A client may set the value of the Connection[] array property to specify connection information for the requested resource allocation. An example of connection information is the target network for a network adaptor or the target switch port for storage adaptors. Connection information is highly dependent on resource type and implementation; for details, refer to the resource-type-specific resource allocation DMTF management profile.

An implementation shall use the values within the Connection[] array property to determine connection information for the requested resource allocation. If no value is specified (NULL), the implementation may decide whether the requested resource allocation requires connection information and establish a default connection.

5.2.7.17 CIM_ResourceAllocationSettingData.Address property

A client may set the value of the Address property to specify an address for the new virtual device. In general, the requirement for the value of the Address property will depend on the resource type. For a particular resource type, restrictions on the potential value set may exist.

An implementation shall interpret the value of the Address property such that the new virtual resource adopts that address value while it is instantiated. If no value is specified (NULL), the implementation may assign a value for the Address that is specific to the implementation and resource type.

5.2.7.18 CIM_ResourceAllocationSettingData.MappingBehavior property

A client may set the value of the MappingBehavior property to specify whether the requested resource allocation has an affinity to or is directly based on host resources that are specified in the optional HostResource[] array property (see 5.2.7.7). A client may set the value of the MappingBehavior property to NULL or to 0 (Unknown) to request that the implementation shall decide on the mapping behavior. A client shall not specify a value of 1 (Not Supported).

An implementation shall use the value of the MappingBehavior property to determine how the requested resource allocation depends on host resources that are specified in the HostResource[] array property.

- If the value is 1 (Not Supported), the implementation shall return a return code that indicates an invalid parameter; see 5.3.
- If the value is not provided (NULL), is 0 (Unknown), or is 1 (Not Supported), the implementation shall establish an implementation-specific default behavior. The resource request may or may not be mapped to or based on host resources depending on the implementation's decision.
- If the value is 2 (Dedicated), the implementation shall establish a direct mapping of the virtual resource onto the resources specified through the HostResource[] array property. The implementation may establish a mapping in the resource allocation request resulting from this instance of the CIM_ResourceAllocationSettingData class; however, it is possible that the requested resources are not available at resource allocation time, resulting in an error condition at that time.

5.3 Methods

This subclause details the requirements for supporting intrinsic operations and extrinsic methods for the CIM elements defined by the profile described in this clause.

5.3.1 CIM_ResourcePoolConfigurationService.CreateChildResourcePool()

The CIM Schema description of this method applies. This optional method creates (or starts a job to create) a nested resource pool. Refer to the MOF for a detailed description.

If the SupportedSyncMethods property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 3 (CreateChildResourcePool Is Supported), the CreateChildResourcePool() method shall be implemented and shall not return a value of 1 or 4096.

If the SupportedAsyncMethods property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 3 (CreateChildResourcePool Is Supported), the CreateChildResourcePool() method shall be implemented and shall not return a value of 1.

If neither the SupportedSyncMethods nor the SupportedAsyncMethods property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 3 (CreateChildResourcePool Is Supported), the CreateChildResourcePool() method shall not be implemented, or if the method is implemented, it shall return the value 1.

If an implementation supports the resource pool hierarchy device model, it uses this method to create child pools.

Detailed requirements of the CreateChildResourcePool() method are specified in Table 3 and Table 4.

No standard messages are defined.

Table 3 – CIM_ResourcePoolConfigurationService.CreateChildResourcePool() method: Return code values

Value	Description
0	Job completed with no error
1	Not supported
2	Unknown
3	Timeout
4	Failed
5	Invalid parameter
6	In use
7	Incorrect ResourceType for the pool
8	Insufficient resources
4096	Method parameters checked – job started

Table 4 – CIM_ResourcePoolConfigurationService.CreateChildResourcePool() method: Parameters

Qualifiers	Name	Type	Description/Values
IN	ElementName	String	The desired name of the resource pool
IN	Settings	String	A string representation of a CIM_ResourceAllocationSettingData instance that represents the allocation assigned to this child pool
IN	ParentPool	CIM_ResourcePool REF	The parent pool from which to create this pool
OUT	Pool	CIM_ResourcePool REF	The resulting resource pool
OUT	Job	CIM_ConcreteJob REF	Returned job if started
OUT	Error	String	Encoded error instance if the operation failed and did not return a job

5.3.2 CIM_ResourcePoolConfigurationService.DeleteResourcePool()

The CIM Schema description of this method applies. This optional method deletes (or starts a job to delete) a resource pool. Refer to the MOF for a detailed description.

If the SupportedSyncMethods property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 4 (DeleteResourcePool Is Supported), the DeleteResourcePool() method shall be implemented and shall not return a value of 1 or 4096.

If the SupportedAsyncMethods property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 4 (DeleteResourcePool Is Supported), the DeleteResourcePool() method shall be implemented and shall not return a value of 1.

If neither the SupportedSyncMethods nor the SupportedAsyncMethods property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 4 (DeleteResourcePool Is Supported), the DeleteResourcePool() method shall not be implemented, or if the method is implemented, it shall return the value 1.

Detailed requirements of the DeleteResourcePool() method are specified in Table 5 and Table 6.

No standard messages are defined.

Table 5 – CIM_ResourcePoolConfigurationService.DeleteResourcePool() method: Return code values

Value	Description
0	Job completed with no error
1	Not supported
2	Unknown
3	Timeout
4	Failed
5	Invalid parameter
6	In use
7	Incorrect ResourceType for the pool
4096	Method parameters checked – job started

Table 6 – CIM_ResourcePoolConfigurationService.DeleteResourcePool() method: Parameters

Qualifiers	Name	Type	Description/Values
IN	Pool	CIM_ResourcePool REF	The resource pool to delete
OUT	Job	CIM_ConcreteJob REF	Returned job if started
OUT	Error	String	Encoded error instance if the operation failed and did not return a job

5.3.3 CIM_ResourcePoolConfigurationService.AddResourcesToResourcePool()

The CIM Schema description of this method applies. This optional method adds (or starts a job to add) resources to a resource pool. Refer to the MOF for a detailed description.

If the SupportedSyncMethods property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 5 (AddResourcesToResourcePool Is Supported), the AddResourcesToResourcePool() method shall be implemented and shall not return a value of 1 or 4096.

If the SupportedAsyncMethods property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 5 (AddResourcesToResourcePool Is Supported), the AddResourcesToResourcePool() method shall be implemented and shall not return a value of 1.

If neither the SupportedSyncMethods nor the SupportedAsyncMethods property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 5 (AddResourcesToResourcePool Is Supported), the AddResourcesToResourcePool() method shall not be implemented, or if the method is implemented, it shall return the value 1.

Detailed requirements of the AddResourcesToResourcePool() method are specified in Table 7 and Table 8.

No standard messages are defined.

**Table 7 – CIM_ResourcePoolConfigurationService.AddResourcesToResourcePool() method:
Return code values**

Value	Description
0	Job completed with no error
1	Not supported
2	Unknown
3	Timeout
4	Failed
5	Invalid parameter
6	In use
7	Incorrect ResourceType for the pool
4096	Method parameters checked – job started

**Table 8 – CIM_ResourcePoolConfigurationService.AddResourcesToResourcePool() method:
Parameters**

Qualifiers	Name	Type	Description/Values
IN	HostResource[]	CIM_LogicalDevice REF[]	The host resources to assign to the pool
IN	Pool	CIM_ResourcePool REF	The primordial ResourcePool to add resources to
OUT	Job	CIM_ConcreteJob REF	Returned job if started
OUT	Error	String	Encoded error instance if the operation failed and did not return a job

5.3.4 CIM_ResourcePoolConfigurationService.RemoveResourcesFromResourcePool()

The CIM Schema description of this method applies. This optional method removes (or starts a job to remove) resources from a resource pool. Refer to the MOF for a detailed description.

If the SynchronousMethodsSupported property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 6 (RemoveResourcesFromResourcePool Is Supported), the RemoveResourcesFromResourcePool() method shall be implemented and shall not return a value of 1 or 4096.

If the AsynchronousMethodsSupported property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 6 (RemoveResourcesFromResourcePool Is Supported), the RemoveResourcesFromResourcePool() method shall be implemented and shall not return a value of 1.

If neither the SynchronousMethodsSupported nor the AsynchronousMethodsSupported property of the associated instance of CIM_ResourcePoolConfigurationCapabilities is set to 6 (RemoveResourcesFromResourcePool Is Supported), the RemoveResourcesFromResourcePool() method shall not be implemented, or if the method is implemented, it shall return the value 1.

Detailed requirements of the RemoveResourcesFromResourcePool() method are specified in Table 9 and Table 10.

No standard messages are defined.